

Wharton Fire Department

Heavy Rescue Specification

SVI

SCOPE AND GENERAL INFORMATION	10
GENERAL CONSTRUCTION AND DESIGN	10
ACCESSIBILITY	11
MATERIALS	11
QUALITY AND WORKMANSHIP	12
INTERNET IN-PROCESS SITE.....	12
VEHICLE STABILITY SUPPLIED WITH CAB/CHASSIS	12
ROADABILITY	13
SERVICEABILITY	13
CONSTRUCTION DOCUMENTATION	14
OPERATIONS AND SERVICE DOCUMENTATION	15
NFPA REQUIRED DOCUMENTATION FORMAT - CD-ROM	16
STATEMENT OF EXCEPTIONS	16
CARRYING CAPACITY	17
TESTING	18
ROAD TEST	18
LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST	18
TEST SEQUENCE	18
(1) RESERVE CAPACITY TEST	19
(2) ALTERNATOR PERFORMANCE TEST	19
TEST AT IDLE	19
TEST AT FULL LOAD	19
(3) LOW VOLTAGE ALARM TEST	19
DOCUMENTATION	20
UL 120/240 VAC CERTIFICATION	20
DIELECTRIC VOLTAGE WITHSTAND TEST	21
GENERAL WARRANTY - ONE (1) YEAR	22
LOW VOLTAGE ELECTRICAL SYSTEM - FIVE (5) YEARS	22
STRUCTURAL WARRANTY - TEN (10) YEARS	23
PAINT WARRANTY - SEVEN (7) YEARS	23
CONSTRUCTION PERIOD	23
OVERALL HEIGHT	23
OVERALL LENGTH	24
PRE-CONSTRUCTION AND FINAL INSPECTION TRIPS	24
DELIVERY AND DEMONSTRATION	24
SPARTAN METRO STAR ELFD, 4-DOOR CHASSIS WITH 20" RAISED ROOF	24
MODEL YEAR	24
COUNTRY OF SERVICE	24
APPARATUS TYPE	24
TRUCK TYPE	25
AXLE CONFIGURATION	25
GROSS AXLE WEIGHT RATINGS FRONT	25
GROSS AXLE WEIGHT RATINGS REAR	25
CAB STYLE	25
CAB FRONT FASCIA	27
FRONT GRILLE	27
CAB ENGINE TUNNEL	27
CAB ENTRY DOORS	28
CAB ENTRY DOOR TYPE	28
LH EXTERIOR REAR COMPARTMENT	28
LH EXTERIOR REAR COMPARTMENT LIGHTING	28
RH EXTERIOR REAR COMPARTMENT	29
RH EXTERIOR REAR COMPARTMENT LIGHTING	29

Wharton Fire Department

Heavy Rescue Specification

SVI

CAB STRUCTURAL WARRANTY.....	29
CAB TEST INFORMATION.....	29
CAB PAINT EXTERIOR.....	30
CAB PAINT MANUFACTURER.....	30
CAB PAINT PRIMARY/ LOWER COLOR.....	30
CAB PAINT SECONDARY/UPPER CAB COLOR.....	30
CAB PAINT EXTERIOR BREAK LINE.....	30
CAB PAINT PINSTRIPE.....	31
CAB PAINT WARRANTY.....	31
ELECTRICAL SYSTEM.....	31
APPARATUS WIRING PROVISION.....	31
MULTIPLEX DISPLAY.....	31
VEHICLE DATA RECORDER.....	32
POWER & GROUND STUD.....	32
AUXILIARY POWER & GROUND STUD.....	32
EXTERIOR ELECTRICAL TERMINAL COATING.....	32
ENGINE.....	33
DIESEL PARTICULATE FILTER CONTROLS.....	33
ENGINE PROGRAMMING HIGH IDLE SPEED.....	33
ENGINE HIGH IDLE CONTROL.....	33
ENGINE PROGRAMMING ROAD SPEED GOVERNOR.....	34
AUXILIARY ENGINE BRAKE.....	34
AUXILIARY ENGINE BRAKE CONTROL.....	34
FLUID FILLS.....	34
ELECTRONIC ENGINE OIL LEVEL INDICATOR.....	34
ENGINE WARRANTY.....	34
ENGINE PROGRAMMING REMOTE THROTTLE.....	34
ENGINE PROGRAMMING IDLE SPEED.....	35
ENGINE FAN DRIVE.....	35
ENGINE COOLING SYSTEM.....	35
ENGINE COOLANT.....	36
ELECTRONIC COOLANT LEVEL INDICATOR.....	36
COOLANT HOSES.....	36
ENGINE AIR INTAKE.....	36
AIR INTAKE SKIDPLATE.....	37
ENGINE EXHAUST SYSTEM.....	37
ENGINE EXHAUST ACCESSORIES.....	37
TRANSMISSION.....	37
TRANSMISSION MODE PROGRAMMING.....	37
TRANSMISSION FEATURE PROGRAMMING.....	38
ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR.....	38
TRANSMISSION SHIFT SELECTOR.....	38
TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE.....	38
TRANSMISSION WARRANTY.....	38
TRANSMISSION COOLING SYSTEM.....	39
LH PTO.....	39
LH PTO MODEL.....	39
PTO LOCATION.....	39
PTO CONTROL.....	39
DRIVELINE.....	39
FUEL FILTER/WATER SEPARATOR.....	40
FUEL LINES.....	40
FUEL SHUTOFF VALVE.....	40

Wharton Fire Department

Heavy Rescue Specification

SVI

FUEL TANK	40
FUEL TANK FILL PORT	41
FRONT AXLE	41
FRONT WHEEL BEARING LUBRICATION	41
FRONT SHOCK ABSORBERS	41
FRONT SUSPENSION	41
STEERING COLUMN/ WHEEL	41
POWER STEERING PUMP	42
ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR	42
FRONT AXLE CRAMP ANGLE	42
POWER STEERING GEAR.....	42
CHASSIS ALIGNMENT	42
REAR AXLE.....	42
REAR WHEEL BEARING LUBRICATION.....	43
REAR AXLE DIFFERENTIAL LUBRICATION	43
VEHICLE TOP SPEED	43
REAR SUSPENSION	43
REAR SHOCK ABSORBERS.....	43
FRONT TIRE	43
REAR TIRE.....	44
TIRE PRESSURE EQUALIZATION SYSTEM.....	44
TIRE PRESSURE INDICATOR	44
FRONT WHEEL.....	44
REAR WHEEL	44
BALANCE WHEELS AND TIRES.....	44
WHEEL TRIM	45
BRAKE SYSTEM.....	45
FRONT BRAKES	46
REAR BRAKES	46
PARK BRAKE	46
PARK BRAKE CONTROL	46
AIR DRYER	46
FRONT BRAKE CHAMBERS.....	46
REAR BRAKE CHAMBERS	47
AIR COMPRESSOR.....	47
AIR GOVERNOR.....	47
MOISTURE EJECTORS.....	47
AIR SUPPLY LINES	47
AIR HORN SHUTOFF VALVE.....	47
WHEELBASE	48
REAR OVERHANG	48
FRAME	48
FRAME WARRANTY.....	49
REAR TOW DEVICE	49
FRAME CLEAR AREA	49
FRAME PAINT.....	49
FRONT BUMPER	50
FRONT BUMPER EXTENSION LENGTH.....	50
FRONT BUMPER EXTENSION WIDTH.....	50
FRONT BUMPER PAINT.....	50
AIR HORN	50
AIR HORN LOCATION	50
AIR HORN RESERVOIR	50

Wharton Fire Department

Heavy Rescue Specification

SVI

ELECTRONIC SIREN SPEAKER.....	51
ELECTRONIC SIREN SPEAKER LOCATION	51
FRONT BUMPER TOW HOOKS.....	51
CAB TILT SYSTEM	51
CAB TILT AUXILIARY PUMP.....	51
CAB TILT CONTROL RECEPTACLE	53
CAB WINDSHIELD.....	53
GLASS FRONT DOOR.....	53
GLASS TINT FRONT DOOR.....	53
GLASS REAR DOOR RH.....	53
GLASS TINT REAR DOOR RH.....	54
GLASS REAR DOOR LH	54
GLASS TINT REAR DOOR LH	54
GLASS SIDE MID RH.....	54
GLASS TINT SIDE MID RH.....	54
GLASS SIDE MID LH	54
GLASS TINT SIDE MID LH	55
GLASS UPPER SIDE FRONT.....	55
GLASS TINT UPPER SIDE FRONT.....	55
GLASS UPPER SIDE MID	55
GLASS TINT UPPER SIDE MID	55
GLASS UPPER SIDE REAR DOOR.....	55
GLASS TINT UPPER SIDE REAR DOOR	56
CLIMATE CONTROL.....	56
CLIMATE CONTROL ACTIVATION	56
A/C CONDENSER LOCATION.....	56
A/C COMPRESSOR.....	56
CAB CIRCULATION FANS FRONT	57
CAB CIRCULATION FANS REAR.....	57
CAB INSULATION.....	57
UNDER CAB INSULATION.....	57
INTERIOR TRIM FLOOR MAT.....	57
INTERIOR TRIM VINYL.....	58
HEADER TRIM	58
INTERIOR TRIM SUN VISOR.....	58
TRIM LH DASH	58
TRIM CENTER DASH	58
TRIM RH DASH.....	59
ENGINE TUNNEL TRIM.....	59
POWER POINT DASH MOUNT	59
STEP TRIM.....	59
INTERIOR DOOR TRIM	59
DOOR TRIM CUSTOMER NAMEPLATE	59
CAB DOOR TRIM REFLECTIVE.....	60
INTERIOR GRAB HANDLE "A" PILLAR.....	60
INTERIOR GRAB HANDLE FRONT DOOR.....	60
INTERIOR GRAB HANDLE REAR DOOR.....	60
INTERIOR FLOOR MAT COLOR.....	60
INTERIOR TRIM VINYL COLOR.....	60
INTERIOR ABS TRIM COLOR.....	60
CAB PAINT INTERIOR.....	60
CAB PAINT INTERIOR DOOR TRIM	61
DASH PANEL GROUP	61

Wharton Fire Department

Heavy Rescue Specification

SVI

SWITCHES CENTER PANEL	61
SWITCHES LEFT PANEL	61
SWITCHES RIGHT PANEL	61
SWITCH PANEL IGNITION	61
SEAT BELT WARNING	61
SEAT MATERIAL	62
SEAT COLOR	62
WHARTON VOLUNTEER FIRE DEPARTMENT'S SEAT BACK LOGO	62
SEAT DRIVER	62
SEAT BACK DRIVER	62
SEAT OFFICER	64
SEAT BACK OFFICER	64
POWER SEAT WIRING	64
SEAT REAR FACING OUTER LOCATION	64
SEAT CREW REAR FACING OUTER	65
SEAT BACK REAR FACING OUTER	65
SEAT MOUNTING REAR FACING OUTER	65
SEAT BELT ORIENTATION CREW	65
SEAT FORWARD FACING CENTER LOCATION	65
SEAT CREW FORWARD FACING CENTER	66
SEAT BACK FORWARD FACING CENTER	66
SEAT MOUNTING FORWARD FACING CENTER	66
SEAT FRAME FORWARD FACING	66
SEAT FRAME FORWARD FACING STORAGE ACCESS	67
CAB FRONT UNDERSEAT STORAGE ACCESS	67
WINDSHIELD WIPER SYSTEM	67
ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR	67
CAB DOOR HARDWARE	67
DOOR LOCKS	67
DOOR LOCK LH REAR CAB COMPARTMENT	68
DOOR LOCK RH REAR CAB COMPARTMENT	68
GRAB HANDLES	68
REARVIEW MIRROR	68
REARVIEW MIRROR HEAT SWITCH	68
TRIM LOWER SIDE	68
TRIM LOWER SIDE FRONT	69
CAB FENDER	69
MUD FLAPS FRONT	69
CAB EXTERIOR MODEL NAMEPLATE	69
CAB EXTERIOR FRONT & SIDE EMBLEMS	69
IGNITION	69
BATTERY	69
BATTERY BOX	70
BATTERY CABLE	70
BATTERY JUMPER STUD	70
ALTERNATOR	70
BATTERY CONDITIONER	70
BATTERY CONDITIONER DISPLAY	70
AUXILIARY AIR COMPRESSOR	70
ELECTRICAL INLET	71
ELECTRICAL INLET COLOR	71
HEADLIGHTS	71
FRONT TURN SIGNALS	71

Wharton Fire Department

Heavy Rescue Specification

SVI

HEADLIGHT LOCATION	71
SIDE MARKER/TURN SIGNALS	72
MARKER AND ICC LIGHTS	72
GROUND LIGHTS	72
STEP LIGHTS	72
ENGINE COMPARTMENT LIGHTS	72
FRONT SCENE LIGHTS	72
FRONT SCENE LIGHT LOCATION	73
FRONT SCENE LIGHTS ACTIVATION	73
SIDE SCENE LIGHT MODEL	73
SIDE SCENE LIGHT LOCATION	73
SIDE SCENE ACTIVATION	73
INTERIOR OVERHEAD LIGHTING	73
AUXILIARY DOME LIGHT RH	74
AUXILIARY DOME LIGHT MID CREW	74
MAP LIGHTS	74
HANDHELD SPOTLIGHTS	74
DO NOT MOVE APPARATUS LIGHT	74
MASTER WARNING SWITCH	74
HEADLIGHT FLASHER	75
ALTERNATING HEADLIGHT SWITCH	75
INBOARD FRONT WARNING LIGHTS	75
INBOARD FRONT WARNING LIGHTS COLOR	75
OUTBOARD FRONT WARNING LIGHTS	75
OUTBOARD FRONT WARNING LIGHTS COLOR	75
FRONT WARNING SWITCH	75
INTERSECTION WARNING LIGHTS	76
INTERSECTION WARNING LIGHTS COLOR	76
INTERSECTION WARNING LIGHTS LOCATION	76
SIDE WARNING LIGHTS	76
SIDE WARNING LIGHTS COLOR	76
SIDE WARNING LIGHTS LOCATION	76
SIDE AND INTERSECTION WARNING SWITCH	76
HORN RING SELECTOR SWITCH	76
AIR HORN ACTIVATION	77
BACK-UP ALARM	77
INSTRUMENTATION	77
RED LAMPS	78
YELLOW LAMPS	78
GREEN LAMPS	78
BLUE LAMPS	78
RADIO	80
RADIO ANTENNA	80
CAMERA SYSTEMS	80
CAB EXTERIOR PROTECTION	80
FIRE EXTINGUISHER	80
ROAD SAFETY KIT	80
DOOR KEYS	81
AS BUILT WIRING DIAGRAMS	81
WARRANTY - CAB AND CHASSIS	81
OPERATORS AND PARTS LIST MANUAL	81
ENGINE AND TRANSMISSION OPERATION MANUALS	81
ENGINE SERVICE MANUALS	81

Wharton Fire Department

Heavy Rescue Specification

SVI

TRANSMISSION SERVICE MANUALS	82
CHASSIS MODIFICATIONS.....	82
LUBRICATION AND TIRE DATA PLATE	82
VEHICLE DATA PLATE	83
OVERALL HEIGHT, LENGTH DATA PLATE	83
ACCIDENT PREVENTION	83
PERSONNEL CAPACITY.....	83
ACCIDENT PREVENTION	83
WEARING HELMET WARNING.....	84
BUMPER GRAVEL SHIELD.....	84
RESCUE BUMPER COMPARTMENT	84
AIR HORN(S).....	86
FRONT TOW PROVISIONS.....	86
EXHAUST.....	86
MUDFLAPS	86
REAR CAB AREA LAYOUT	86
CAB INTERIOR CABINET - CURBSIDE ON REAR WALL.....	86
CAB INTERIOR CABINET - STREETSIDE ON REAR WALL.....	87
CENTER REAR FACING CABINET/DESK TOP.....	87
CAB INTERIOR CABINET - OVERHEAD	87
CAB COMMAND 120V INTERIOR LIGHT(S)	88
FUEL FILL	88
BODY DESIGN.....	88
EXTERIOR ALUMINUM BODY	89
ROOF CONSTRUCTION.....	89
BODY SUBFRAME.....	90
BODY MOUNTING	90
10" REAR STEP BUMPER.....	90
REAR TOW EYES.....	90
TRAILER HITCH.....	91
GROUND LIGHTS.....	91
WHEEL WELL EXTERIOR PANEL.....	91
DIEFORMED BEADED EDGE BODY FENDERS.....	91
WHEEL WELL LINERS	91
SCBA BOTTLE COMPARTMENTS	92
ALUMINUM BODY PAINT SPECIFICATIONS.....	92
PAINT FINISH - SINGLE COLOR	92
PAINT WARRANTY.....	92
BODY UNDERCOATING.....	93
UNDERCOAT WARRANTY.....	93
COMPARTMENT INTERIOR FINISH.....	93
ROOF COMPARTMENT INTERIOR FINISH	93
REFLECTIVE STRIPE AND LETTERING	93
EXTERIOR COMPARTMENT DOORS	94
ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM)	94
EXTERIOR ROLL-UP DOOR FINISH - SATIN.....	94
BODY HEIGHT MEASUREMENTS.....	95
UPPER BODY COMPARTMENTS.....	96
UPPER BODY WALKWAY	96
WALKWAY LIGHTS	96
ROOF ACCESS STAIRWAY	97
STAIRWAY HANDRAILS	97
WALKWAY LIGHTS	97

Wharton Fire Department

Heavy Rescue Specification

SVI

STEP COMPARTMENT(S) - LOWER	97
FOLD-DOWN STEP	97
REAR BODY HANDRAILS	97
BODY WIDTH DIMENSIONS	98
STREETSIDE COMPARTMENT - FRONT (S1).....	99
STREETSIDE COMPARTMENT - AHEAD OF REAR WHEELS (S2).....	101
STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S3)	103
STREETSIDE COMPARTMENT - REAR (S4).....	104
CURBSIDE COMPARTMENT - FRONT (C1).....	106
CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C3).....	110
CURBSIDE COMPARTMENT - REAR (C4).....	111
ROOF ACCESS STAIRWAY	113
PLASTIC FLOOR AND SHELF TILE.....	113
ROPE TIE-OFF OR PORTABLE WINCH RECEIVERS	113
STRAIGHT PULL.....	113
SAFETY FACTOR.....	113
SIDE BODY PROTECTION - RUB RAIL	114
COMPARTMENT COMPONENTS DESCRIPTIONS.....	115
ADJUSTABLE SHELVING HARDWARE	115
ADJUSTABLE SHELF/SHELVES	115
SLIDE-OUT EQUIPMENT TRAY - (400 LB CAPACITY).....	115
HEAVY DUTY 100% EXTENSION EQUIPMENT SLIDE - (1,000 LB. CAPACITY).....	116
HEAVY DUTY 100% EXTENSION EQUIPMENT SLIDE - (750 LB. CAPACITY).....	116
HEAVY DUTY 70% EXTENSION EQUIPMENT SLIDE TRANSVERSE (1,000 LBS. CAPACITY)	116
HEAVY DUTY EQUIPMENT TRAYS - SLIDE OUT AND DOWN (250 LBS. CAPACITY).....	117
HEAVY DUTY EQUIPMENT TRAYS - SLIDE OUT AND DOWN (150 LBS. CAPACITY).....	117
SLIDE-OUT TOOL BOARD (SMOOTH ALUMINUM).....	117
COMPARTMENT PARTITIONS	118
TRANSVERSE STORAGE MODULE	118
SCBA CYLINDER RACK.....	118
LISTA DRAWER CABINET	118
COMPARTMENT LIGHTING.....	118
ELECTRIC CORD REEL	119
POWER DISTRIBUTION BOX	120
LOW PRESSURE AIR HOSE REEL	120
UTILITY AIR SYSTEM.....	121
AIR COMPRESSOR.....	121
BREATHING AIR STORAGE SYSTEM	121
FILL STATION	122
"CONTAINMENT TYPE" FILL STATION.....	122
CONTROL AND FILLING PANEL	124
TESTING AND PREPARATION OF FILL STATION	124
STEP / GROUND LIGHTS.....	125
LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC.....	126
12 VOLT MULTIPLEX CONTROL CENTER	129
BATTERY SYSTEM	130
BATTERY SWITCH.....	130
BATTERY SOLENOID.....	130
BATTERY CONDITIONER.....	131
ENGINE COMPARTMENT LIGHT	131
CAB HAZARD WARNING LIGHT.....	131
BACK-UP ALARM	131
REAR VIEW CAMERA	131

Wharton Fire Department

Heavy Rescue Specification

SVI

TAIL LIGHTS	131
MIDSHIP MARKER/TURN SIGNAL	132
MARKER LIGHTS	132
LICENSE PLATE MOUNTING BRACKET	132
ELECTRONIC SIREN	132
SIREN SPEAKER	132
SIDE SCENE LIGHTS	132
REAR SCENE LIGHTS	132
TRAFFIC DIRECTIONAL LIGHT	133
WARNING LIGHT PACKAGE	133
UPPER LEVEL OPTICAL WARNING DEVICES	134
SECTION	134
INTERNAL COMPONENTS	134
LENS COLOR	134
LOWER LEVEL OPTICAL WARNING DEVICES	136
ONAN PTO GENERATOR	137
GENERATOR ENGAGEMENT	138
WARRANTY PERIOD	138
GENERATOR SPLASH GUARD	138
GENERATOR MOUNTING	138
MANUALS AND SCHEMATICS	138
POWER-TAKE-OFF GENERATOR DRIVE	139
ENGINE SPEED CONTROL	139
GENERATOR MONITORING PANEL	139
LOADCENTER	140
OUTLETS AND CIRCUITS	140
GENERAL REQUIREMENTS	140
120/240 VAC SCENE LIGHTING	147
REAR TRIPOD SCENE LIGHTS	147
COMMAND LIGHT TOWER WITH METAL HALIDE BULB OPTION AND LOWER BANK BACKLIGHT	148
COMMAND LIGHT - KNIGHT TOWER w/ BACKLIGHT	149
EQUIPMENT	150

Wharton Fire Department

Heavy Rescue Specification

SVI

SCOPE AND GENERAL INFORMATION

It is the intent of the WHARTON VOLUNTEER FIRE DEPARTMENT to secure an emergency apparatus to withstand the continuous use encountered in the emergency service. The apparatus shall be of the latest type, symmetrically proportioned and constructed with due consideration of the load to be sustained.

All parts not specifically mentioned herein, but which are necessary in order to furnish a complete emergency apparatus, shall be furnished and shall conform to the best practices known to the emergency industry.

The apparatus and all major components shall be manufactured in North America. Where the following detailed specifications require specific brand names, model number, dimension or capacities of components such as: axles, brakes, spring suspension, frame, steering gear, drive line, universal joints, engine transmission, alternator, batteries, air brake system, they have been specified for the service because of their reliability/availability of replacement parts on a local basis.

All specifications herein contained are considered as minimum. No exceptions to these minimum standards shall be allowed relating to gauge, alloy, and type of metal, size of compartments, and overall design.

The apparatus shall comply with all applicable State and Federal requirements pertaining to vehicles used for fire fighting and emergency vehicles at time of contract signing. The apparatus must also comply with all requirements as specified in the NFPA 1901 standards that are applicable on date of contract signing.

The delivered apparatus shall have a certified G.V.W.R. weight sticker applied to vehicle on delivery to assure the apparatus meets all laws pertaining to the weight carrying capacity of the vehicle.

GENERAL CONSTRUCTION AND DESIGN

The design of the equipment shall be in accordance with the best engineering practices. The equipment design and accessory installation shall permit accessibility for use, maintenance and service. All components and assemblies shall be free of hazardous protrusions, sharp edges, cracks or other elements which might cause injury to personnel or equipment. All components shall be designed and protected so that heavy rains or other adverse weather conditions will not interfere with normal servicing or operation.

All oil, hydraulic and air tubing lines, and electrical wiring shall be located in protective positions properly attached to the frame or body structure and shall have protective loom or grommets at each point where they pass through structural members, except where a through frame connector is necessary.

The apparatus shall be designed and the equipment mounted with due consideration to distribution of load between the front and rear axles, so that all specified equipment including personnel will be carried without injury to the apparatus. All dimensions are approximate and subject to a plus or minus 1/4" tolerance.

The following specifications describe minimum requirements for an emergency services vehicle designed for severe duty applications.

The materials specified are considered absolute minimum. Exceptions will not be accepted or permitted since all raw materials of the specified type are available to all Manufacturers. Since all custom Manufacturers have the ability to shear, break, and weld as these specifications require, all basic design requirements shall be complied with.

Subletting any part of the fabrication, painting, or finishing of the apparatus will not be acceptable.

Wharton Fire Department

Heavy Rescue Specification

SVI

ACCESSIBILITY

Parts and components shall be located or positioned for rapid and simple inspection and recognition of excessive wear or potential failure. Whenever functional layout of operating components determines that physical or visual interference between items cannot be avoided, the item predicted to require the most maintenance shall be located for best accessibility.

Cover plates which must be removed for component adjustment or part removal should be equipped with quick disconnect fasteners or hinged panels.

Drains, filler plugs, grease fittings, hydraulic lines, bleeders, and check points for all components should be located so that they are readily accessible and do not require special tools for proper servicing. Design practices should minimize the number of tools required for maintenance.

MATERIALS

The materials specifications are considered absolute minimum. Exceptions will not be accepted or permitted since all raw materials of specified type are available to all manufacturers. Since all manufacturers have the ability to shear, break and weld as these specifications require, all basic design requirements shall be complied with.

Materials shall conform to the specifications listed herein. When not specifically listed, materials shall be of the best quality for purpose of commercial practice. Materials shall be free of all defects and imperfections that might affect the serviceability of finished product.

Wharton Fire Department

Heavy Rescue Specification

SVI

QUALITY AND WORKMANSHIP

The manufacturing process, including quality control, shall be consistent with present industry standards. All equipment, material, and articles required under these specifications are to be new or fabricated from new materials produced from recovered materials. The term "Recovered Materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this document. The term "Heavy Duty", as used to describe an item, shall mean in excess of the standard, quantity, quality, or capacity and represents the best, most durable, strongest, etc., part, component, WHARTON VOLUNTEER FIRE DEPARTMENT system, etc., that is available. The WHARTON VOLUNTEER FIRE DEPARTMENT or their designate shall be the sole judge of quality, construction and stability of the apparatus and equipment being offered.

Welding shall not be employed in the assembly of the apparatus in a manner that will prevent the ready removal of any component part for service or repair. All steel and stainless steel welding shall be done to American Welding Society D1.1-83 recommendations for structural steel welding. All aluminum welding shall be done to American Welding Society and ANSI D1.2-83 requirements for structural welding of aluminum.

Defective components shall not be furnished. Parts, equipment, and assemblies, which have been repaired or modified to overcome deficiencies, shall not be furnished without the approval of the WHARTON VOLUNTEER FIRE DEPARTMENT. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry. Component parts and units shall be manufactured to definite standard dimensions with proper fits, clearances, and uniformity. General appearance of the vehicle shall not show any evidence of poor quality of work.

INTERNET IN-PROCESS SITE

The Body Manufacturer shall post and maintain a website where the WHARTON VOLUNTEER FIRE DEPARTMENT will be able to view digital images of their apparatus as its being manufactured. The digital images shall be posted once a week starting when the body begins production or when the cab/chassis arrives and shall continue until the final completion of the apparatus.

VEHICLE STABILITY SUPPLIED WITH CAB/CHASSIS

The cab/chassis shall be equipped with a stability control system. The system shall have, at a minimum, a steering wheel position sensor, a vehicle yaw sensor, a lateral accelerometer, and individual wheel brake controls.

Wharton Fire Department

Heavy Rescue Specification

SVI

ROADABILITY

The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

- (1) From a standing start, the apparatus shall be able to attain a speed of 35 mph (55 km/hr) within 25 seconds on a level road.
- (2) The apparatus shall be able to attain a minimum top speed of 50 mph (80 km/hr) on a level road.
- (3) The apparatus shall be able to maintain a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent.

The maximum top speed of fire apparatus with a GVWR over 26,000 lb (11,800 kg) shall not exceed either 68 mph (105 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gal (4732 L), or the GVWR of the vehicle is over 50,000 lb (22,680 kg), the maximum top speed of the apparatus shall not exceed either 60 mph (85 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

SERVICEABILITY

The fire apparatus shall be designed so that all the manufacturer's recommended routine maintenance checks of lubricant and fluid levels can be performed by the operator without lifting the cab of a tilt-cab apparatus or without the need for hand tools.

Where special tools are required for routine service on any component of the apparatus, such tools shall be provided with the apparatus.

Apparatus components that interfere with repair or removal of other major components shall be attached with fasteners, such as cap screws and nuts, so that the components can be removed and installed with ordinary hand tools. These components shall not be welded or otherwise permanently secured into place.

Wharton Fire Department

Heavy Rescue Specification

SVI

CONSTRUCTION DOCUMENTATION

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

- (1) The manufacturer's record of apparatus construction details, including the following information:
 - (a) Owner's name and address
 - (b) Apparatus manufacturer, model, and serial number
 - (c) Chassis make, model, and serial number
 - (d) GAWR of front and rear axles and GVWR
 - (e) Front tire size and total rated capacity in pounds (kilograms)
 - (f) Rear tire size and total rated capacity in pounds (kilograms)
 - (g) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)
 - (h) Engine make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
 - (i) Type of fuel and fuel tank capacity
 - (j) Electrical system voltage and alternator output in amps
 - (k) Battery make, model, and capacity in cold cranking amps (CCA)
 - (l) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
 - (m) Ratios of all driving axles
 - (n) Maximum governed road speed
 - (o) Pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
 - (p) Pump transmission make, model, serial number, and gear ratio
 - (q) Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
 - (r) Water and Foam tank certified capacity in gallons or liters
 - (s) Paint manufacturer and paint number(s)
 - (t) Company name and signature of responsible company representative
 - (u) Weight documents from a certified scale showing actual loading on the front axle, rear axle(s), and overall fire apparatus (with the water tank full but without personnel, equipment, and hose)
- (2) Certification of compliance of the optical warning system
- (3) Siren manufacturer's certification of the siren
- (4) Written load analysis and results of the electrical system performance tests
- (5) Certification of slip resistance of all stepping, standing, and walking surfaces
- (6) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability
- (7) If the apparatus is equipped with a fire pump and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions
- (8) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications
- (9) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed
- (10) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test
- (11) If the apparatus has a fire pump, the certification of inspection and test for the fire pump
- (12) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test

Wharton Fire Department

Heavy Rescue Specification

SVI

- (13) When the apparatus is equipped with a water tank, the certification of water tank capacity
- (14) If the apparatus has an aerial device, the certification of inspection and test for the aerial device
- (15) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy and the final installer's certification the foam proportioning system meets this standard
- (16) If the system has a CAFS, the documentation of the manufacturer's pre delivery tests
- (17) If the apparatus has a line voltage power source, the certification of the test for the power source
- (18) If the apparatus is equipped with an air system, air tank certificates, the SCBA fill station certification (see 24.9.7), and the results of the testing of the air system installation
- (19) Any other required manufacturer test data or reports

OPERATIONS AND SERVICE DOCUMENTATION

The contractor shall deliver with the fire apparatus at least two (2) sets of complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service, and operations of the fire apparatus and all major components thereof.

The contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- (1) Manufacturer's name and address
- (2) Country of manufacture
- (3) Source for service and technical information
- (4) Parts replacement information
- (5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- (6) Wiring diagrams for low voltage and line voltage systems to include the following information:
 - (a) Pictorial representations of circuit logic for all electrical components and wiring
 - (b) Circuit identification
 - (c) Connector pin identification
 - (d) Zone location of electrical components
 - (e) Safety interlocks
 - (f) Alternator–battery power distribution circuits
 - (g) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- (7) Lubrication charts
- (8) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- (9) Precautions related to multiple configurations of aerial devices, if applicable
- (10) Instructions regarding the frequency and procedure for recommended maintenance
- (11) Overall apparatus operating instructions
- (12) Safety considerations
- (13) Limitations of use
- (14) Inspection procedures
- (15) Recommended service procedures
- (16) Troubleshooting guide
- (17) Apparatus body, chassis, and other component manufacturer's warranties

Wharton Fire Department

Heavy Rescue Specification

SVI

(18) Special data required by this standard

(19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus

The contractor shall deliver with the apparatus all manufacturers' operations and service documents supplied with components and equipment that are installed or supplied by the contractor.

NFPA REQUIRED DOCUMENTATION FORMAT - CD-ROM

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a CD-ROM. These manuals shall be divided into sections for ease of reference. There shall be two (2) copies of the CD-ROM provided with the completed vehicle.

STATEMENT OF EXCEPTIONS

The contractor shall deliver with the fire apparatus either a certification that the apparatus fully complies with all requirements of this standard or, alternatively, a Statement of Exceptions specifically describing each aspect of the completed apparatus that is not fully compliant with the requirements of this standard at the time of delivery.

The Statement of Exceptions shall contain, for each noncompliant aspect of the apparatus or missing required item, the following information:

- (1) A separate specification of the section of the applicable standard for which compliance is lacking
- (2) A description of the particular aspect of the apparatus that is not in compliance therewith or required equipment that is missing
- (3) A description of the further changes or modifications to the delivered apparatus that must be completed to achieve full compliance
- (4) Identification of the entity that will be responsible for making the necessary post delivery changes or modifications or for supplying and installing any missing required equipment to the apparatus to achieve full compliance with this standard

Prior to, or at the time of, delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

An apparatus that is delivered subject to a Statement of Exceptions other than a certification of full compliance shall not be placed in emergency service until the apparatus has been modified as necessary to accomplish full compliance with this standard.

Wharton Fire Department

Heavy Rescue Specification

SVI

CARRYING CAPACITY

The GAWR and the GCWR or GVWR of the chassis shall be adequate to carry the weight of the completed vehicle when loaded to its estimated in-service weight. The manufacturer shall establish the estimated in service weight during the design of the vehicle

The estimated in-service weight shall include the following:

- (1) The chassis, body, and tank(s)
- (2) Full fuel, lubricant, and other chassis or component fluid tanks or reservoirs
- (3) Full water and other agent tanks
- (4) *250 lb (114 kg) in each seating position
- (5) Fixed equipment such as pumps, aerial devices, generators, reels, and air systems as installed
- (6) Ground ladders, suction hose, designed hose load in their hose beds and on their reels
- (7) An allowance for miscellaneous equipment that is the greatest of the values for type of vehicle per NFPA 1901, a purchaser provided list of equipment to be carried with weights, or a purchaser specified miscellaneous equipment allowance.

The manufacturer shall engineer and design the vehicle such that the completed unit, when loaded to its estimated in-service weight, with all movable weights distributed as close as is practical to their intended in-service configuration, does not exceed the GVWR.

A final manufacturer's certification of the GVWR or GCWR, along with a certification of each GAWR, shall be supplied on a label affixed to the vehicle.

Apparatus Type	Equipt. Storage Area	Apparatus Size	Equipment Allowance	
			lb.	kg.
Special Service Fire Apparatus	Minimum of 120 cu ft (3.4 cu mt) of enclosed compartmentation.	10,000 lb to 15,000 lb (4,500 kg to 7,000 kg) GVWR	2,000	910
		15,001 lb to 20,000 lb (7,001 kg to 9,000 kg) GVWR	2,500	1,135
		20,001 lb to 30,000 lb (9,001 kg to 14,000 kg) GVWR	3,000	1,350
		30,001 lb to 40,000 lb (14,001 kg to 18,000 kg) GVWR	4,000	1,800
		40,001 lb to 50,000 lb (18,001 kg to 23,000 kg) GVWR	6,000	2,700
		50,001 lb to 60,000 lb (23,001 kg to 27,000 kg) GVWR	8,000	3,600
		60,001 lb and up (27,001 kg)	10,000	4,500

Wharton Fire Department

Heavy Rescue Specification

SVI

		GVWR		
--	--	------	--	--

TESTING

ROAD TEST

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial, or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition.

The apparatus shall be loaded to its estimated in service weight.

The engine shall not operate in excess of the maximum governed speed.

Acceleration tests shall consist of two runs in opposite directions over the same route.

The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds.

The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil, or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil, or grease.

LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (–18°C and 43°C).

TEST SEQUENCE

Wharton Fire Department

Heavy Rescue Specification

SVI

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for 10 minutes. Failure of any of these tests shall require a repeat of the sequence.

(1) RESERVE CAPACITY TEST

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off, and the minimum continuous electrical load shall be activated for 10 minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

(2) ALTERNATOR PERFORMANCE TEST

TEST AT IDLE

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

TEST AT FULL LOAD

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of 2 hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

(3) LOW VOLTAGE ALARM TEST

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system, or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

Wharton Fire Department

Heavy Rescue Specification

SVI

DOCUMENTATION

The manufacturer shall deliver the following with the fire apparatus:

- (1) Documentation of the electrical system performance tests
- (2) A written electrical load analysis, including the following:
 - (a) The nameplate rating of the alternator
 - (b) The alternator rating
 - (c) Each of the component loads specified that make up the minimum continuous electrical load
 - (d) Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load
 - (e) Each individual intermittent electrical load.

UL 120/240 VAC CERTIFICATION

The 120/240 volt electrical system shall be tested and certified by Underwriters Laboratories, to perform as listed below;

The prime mover shall be started from a cold start condition, and the unloaded voltage and frequency shall be recorded.

The line voltage electrical system shall be loaded to at least 100 percent of the continuous rated wattage stated on the power source specification label. Testing with a resistive load bank shall be permitted.

The power source shall be operated in the manner specified by the apparatus manufacturer as documented on instruction plates or in operation manuals. The power source shall be operated at a minimum of 100 percent of the continuous rated wattage as stated on the power source specification label for a minimum of 2 hours.

The load shall be adjusted to maintain the output wattage at or above the continuous rated wattage during the entire 2-hour test.

The following conditions shall be recorded at least every 1.2 hour during the test:

- (1) The power source output voltage, frequency, and amperes
- (2) The prime mover's oil pressure, water temperature, and transmission temperature, if applicable
- (3) The power source hydraulic fluid temperature, if applicable
- (4) The ambient temperature and power source air inlet temperature

The following conditions shall be recorded once during the test for power sources driven by dedicated auxiliary internal combustion engines:

- (1) Altitude
- (2) Barometric pressure
- (3) Relative humidity

If the generator is driven by the chassis engine and the generator allows for operation at variable speeds, the chassis engine speed shall be reduced to the lowest rpm allowed for generator operation and the voltage and frequency shall be recorded.

The load shall be removed, and the unloaded voltage and frequency shall be recorded.

Wharton Fire Department

Heavy Rescue Specification

SVI

Voltage shall be maintained within ± 10 percent of the voltage stated on the power source specification label during the entire test. Frequency shall be maintained within ± 3 Hz of the frequency stated on the power source specification label during the entire test.

The total continuous electrical loads, excluding those loads associated with the equipment defined in 22.15.7.3.11.2, shall be applied during the testing unless an auxiliary engine drives the power source.

If the apparatus is equipped with a fire pump, the 2-hour certification test of the power source shall be completed with the fire pump pumping at 100 percent capacity at 150 psi (1000 kPa) net pump pressure. The test shall be permitted to be run concurrently with the pump certification test.

The results of each test shall be recorded on an appropriate form and provided with the delivery of the fire apparatus.

DIELECTRIC VOLTAGE WITHSTAND TEST

The line voltage wiring and permanently connected devices and equipment shall be subjected to a dielectric voltage withstand test of 900 volts for 1 minute. The testing shall be performed after all body work has been completed.

The test shall be conducted as follows:

- (1) Isolate the power source from the panel board and disconnect any solid state low voltage components.
- (2) Connect one lead of the dielectric tester to all the hot and neutral buses tied together.
- (3) Connect the other lead to the fire apparatus frame or body.
- (4) Close any switches and circuit breakers in the circuit(s).
- (5) Apply the dielectric voltage for 1 minute in accordance with the testing equipment manufacturer's instructions.

The electrical polarity of all permanently wired equipment, cord reels, and receptacles shall be tested to verify that wiring connections have been properly made.

Electrical continuity shall be verified from the chassis or body to all line voltage electrical enclosures, light housings, motor housings, light poles, switch boxes, and receptacle ground connections that are accessible to fire fighters in normal operations.

If the apparatus is equipped with a transfer switch, it shall be tested to verify operation and that all non grounded conductors are switched.

Electrical light towers, floodlights, motors, fixed appliances, and portable generators shall be operated at their full rating or capacity for 30 minutes to ensure proper operation.

Wharton Fire Department

Heavy Rescue Specification

SVI

GENERAL WARRANTY - ONE (1) YEAR

The entire body and all contractor installed components shall be warranted, including parts and labor for a period of at least **one (1) year** commencing upon the placing of the unit in-service by the WHARTON VOLUNTEER FIRE DEPARTMENT (except that warranty on the tires and tubes, batteries, electrical lamps, and other devices subject to deterioration is limited to the warranty of the manufacturer thereof and adjustments for same are to be made directly with the manufacturer). Extended warranties on the engine, transmission, or other major components shall be detailed by contractor in their proposal.

This warranty shall not apply to those items which are usually considered normal maintenance and repair; including but not limited to normal lubrication or proper adjustment of main functional operating components. All manufacturers' warranties (apparatus & equipment) shall be furnished and indicated in the manufacturer's bid. Any standard warranties, including, but not limited to engine, transmission, tires and axles furnished by the original equipment manufacturer (OEM) or the prime contractor will be passed on to the WHARTON VOLUNTEER FIRE DEPARTMENT. Also include any available extended warranties that will start after the initial warranty period. Goods or property shall be as represented by these specifications as well as additional agreements as a result of discussions regarding these specifications and shall be as promised with implied liability on the manufacturer.

The contractor must be the "single source" coordinator of all warranties on the vehicle.

LOW VOLTAGE ELECTRICAL SYSTEM - FIVE (5) YEARS

Contractor shall warrant the integrity of the electrical system on this emergency vehicle for a period of **five (5) years, or 60,000 miles** from date of delivery. To be free from defects in materials and workmanship under normal use and service. The obligation of contractor under this warranty is limited to repairing or replacing, at its option, any part or parts thereof which shall, after delivery of such vehicle to the original purchaser, be returned with transportation charges pre-paid to contractor or an authorized distributor or dealer, and which examination shall disclose to have been defective, except as herein after provided.

Items specifically covered are:

- Electrical harness and harness installation
- Printed circuit boards
- Load management system
- Warning light control panel switches that are provided and installed by bidder.

Items excluded are:

- Chassis electrical systems and components installed by chassis manufacturer including, but not limited to: printed circuit boards, switches, relays, fuses, and similar equipment.
- Separately manufactured items installed by bidder including, but not limited to: batteries, sirens, battery chargers, inverters, light bars and similar equipment. These are covered by warranties supplied by the manufacturer of the components.
- Periodic tightening and cleaning of connection terminals as this is considered routine maintenance.
- Normal wear, abuse, accident, negligence or unapproved alteration of original parts.

Wharton Fire Department

Heavy Rescue Specification

SVI

STRUCTURAL WARRANTY - TEN (10) YEARS

The contractor shall warrant that each new rescue body (exclusive of paint, finish, hardware, moldings, windows, and other appointments and accessories) is structurally sound and free of all structural defects of both material and workmanship and further warrants that it will maintain such structural integrity for a period of **ten (10) years** from the completion date listed on the Manufacturer's data plate attached to the vehicle inside the cab.

The contractor further warrants that this structural integrity warranty may be transferred to a second purchaser providing the vehicle is inspected by the original contractor or their authorized representative within thirty (30) days of ownership transfer. To maintain warranty coverage, the proper ownership transfer papers shall be kept on file at contractor's facility.

In the event of a chassis remount, this structural warranty shall remain in effect providing that the re-chassis work is completed by the contractor or a facility which obtains written authorization from the contractor.

Should repairs become necessary under the terms of this warranty, the extent of the repair shall be determined solely by the Manufacturer and shall be repaired by the contractor or an Authorized Service Center designated by the contractor. The expense of any transportation to or from the ASC shall be the responsibility of the WHARTON VOLUNTEER FIRE DEPARTMENT and is not an item covered by this warranty.

There shall be a Warranty Certificate supplied with the completed apparatus to detail the warranty configuration.

PAINT WARRANTY - SEVEN (7) YEARS

The exterior paint and finish on the portion of the unit painted by the contractor shall be warranted against cracking, checking, hazing, chalking, or fading or peeling of the topcoat or any layers from the substrate due to defects in manufacturing or improper preparation for a period of **seven (7) years** from acceptance.

CONSTRUCTION PERIOD

The completed vehicle shall be delivered within three hundred sixty five (365) days after receipt of a purchase order, or contract.

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to WHARTON VOLUNTEER FIRE DEPARTMENT as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

OVERALL HEIGHT

The overall height (OAH) of the vehicle shall be approximately 127" (10' - 7") from the ground. This measurement shall be taken on flat ground with the tires properly inflated, in the unloaded condition, at that highest point of the vehicle.

Wharton Fire Department

Heavy Rescue Specification

SVI

OVERALL LENGTH

The overall length (OAL) of the vehicle shall be approximately 453 - 1/2" (37' - 9 1/2").

PRE-CONSTRUCTION AND FINAL INSPECTION TRIPS

There will be a pre-construction trip and a final inspection trip to the Body Manufacturer's factory. There will be four (4) representatives of the WHARTON VOLUNTEER FIRE DEPARTMENT on each of the trips. The cost of transportation, food, and lodging shall be borne by the Body Manufacturer.

DELIVERY AND DEMONSTRATION

The contractor shall be responsible for the delivery of the completed unit to the WHARTON VOLUNTEER FIRE DEPARTMENTS location. On initial delivery of the apparatus, the contractor shall supply a qualified representative to demonstrate the apparatus and provide initial instruction to representatives of the WHARTON VOLUNTEER FIRE DEPARTMENT regarding the operation, care, and maintenance of the apparatus and equipment supplied at the WHARTON VOLUNTEER FIRE DEPARTMENTS location.

The delivery engineer shall set delivery and instruction schedule with the person appointed by WHARTON VOLUNTEER FIRE DEPARTMENT.

After delivery of the apparatus, the WHARTON VOLUNTEER FIRE DEPARTMENT shall be responsible for ongoing training of its personnel to proficiency regarding the proper and safe use of the apparatus and associated equipment as defined in NFPA 1002, *Standard for Fire Apparatus Driver/Operator Professional Qualifications*, and NFPA 1500, *Standard on Fire Department Occupational Safety and Health Program*.

SPARTAN METRO STAR ELFD, 4-DOOR CHASSIS WITH 20" RAISED ROOF

The cab and chassis shall include design considerations for multiple emergency vehicle applications, rapid transit and maneuverability. This chassis shall be manufactured for heavy duty service with strength and capacity for a duty rating of one hundred (100) percent loaded full time.

MODEL YEAR

The chassis shall have a vehicle identification number that reflects a 2009 model year.

COUNTRY OF SERVICE

The chassis shall be put in service in the country of United States of America (USA).

APPARATUS TYPE

Wharton Fire Department

Heavy Rescue Specification

SVI

The apparatus shall be created for the Emergency Services Industry and include the functions of a Rescue which shall include the functions of a multipurpose vehicle which primarily provides support services at emergency scenes.

TRUCK TYPE

The chassis shall be manufactured as a truck style and designed to include permanently mounted compartments behind the cab, known as the body. The body of the truck shall be supplied and installed by the apparatus manufacturer.

AXLE CONFIGURATION

The chassis shall offer a single rear drive axle with a single front steer axle configuration (4 X 2).

GROSS AXLE WEIGHT RATINGS FRONT

The gross apparatus weight rating and the gross capacity weight rating shall be adequate to carry the weight of equipment and the apparatus, with water tanks full and other tanks at full capacity, miscellaneous equipment and all personnel weights considered as recommended by the most current edition of NFPA 1901.

The chassis front gross axle weight rating (GAWR) shall be 23,000 pounds. This rating shall require special approval from the wheel manufacturer.

GROSS AXLE WEIGHT RATINGS REAR

The chassis rear gross axle weight rating (GAWR) shall be 27,000 pounds.

CAB STYLE

The cab shall be a custom, enclosed model, built specifically for the fire service by a company specializing in cab and chassis design for all fire service applications.

The cab shall be manufactured for heavy-duty service utilizing adequate strength and capacity for the application of protecting firefighters. The cab shall be of a modular design offering improved strength, durability and reduced weight. The modular design shall allow for faster, less costly replacement of components. Per pound, sheet panel aluminum extrusions offer a higher tensile strength, 45,000 PSI, and yield strength, 40,000 PSI, than that of lower grade sheet such as 3003-H13. For this reason, the cab shall be of aluminum extrusion construction, which shall offer superior strength and the truest, flattest surface ensuring less expensive paint repairs if needed.

The method of cab construction shall use a process incorporating techniques outlined in accordance with the American Welding Society D1.1-96 requirements for structural steel welding. All aluminum welding shall be completed to the American Welding Society and ANSI D1.2-96 requirements for structural welding of aluminum.

To provide a superior finish by reducing welds that fatigue cab metal; the roof, the rear wall and side panels shall be assembled using proven industrial adhesives, designed specifically for aluminum fabrication, which exceed the strength of a weld, for construction.

Wharton Fire Department

Heavy Rescue Specification

SVI

All interior and exterior seams shall be sealed for optimum noise reduction in addition to the most favorable efficiency for heating and cooling retention.

The cab shall be constructed of 5052-H32 Marine Grade, one hundred percent primary aluminum plate. A single formed, one (1) piece extrusion, manufactured from 6061-T6 100 percent primary one-quarter inch thick aluminum shall be used for the "A" pillar adding strength and rigidity to the cab as well as additional roll-over protection. The cab side wall skins and shall be 0.125 inch thick, the rear wall and roof skin shall be 0.19 inch thick, the front skin shall be 0.125 inch thick.

The cab shall incorporate tongue and groove fitted 6061-T6 0.25 inch thick aluminum extrusions for extreme duty situations. The cab shall include multi-layer composite insulation for improved cab heating and cooling in addition to noise reduction.

Proposals offering products built with anything less than the alloy-temper mentioned or from any other material, other than aluminum, shall not be considered. Additionally, any cabs utilizing recycled or recovered aluminum plate or extrusion products shall not be considered due to impurities in the composition leading to a lack of strength.

The cab shall incorporate a fully enclosed design, allowing for a spacious cab area with no partition between the front and rear sections of the cab. The walls of the vehicle shall include roof supports allowing for an open design. The outside dimension of the cab shall be 94 inches wide with a minimum interior width of 88 inches.

The cab overall length shall be 148.00 inches in length with 74.00 inches from the centerline of the front of the axle to the back of the cab. The cab shall include a 20.00 inch raised roof increasing the head room over the crew area. The cab shall offer an interior height of 58.00 inches from the front floor to the headliner and a rear floor to headliner height of 75.00 inches in the crew area, at a minimum. All interior measurements shall include the area within the interior trimmed surfaces and not to any unfinished surface.

In order to offer the optimum amount of cab space to occupants, there shall be no consideration given for any cab unable to comply with the minimum measurements for interior cab space as listed.

The cab shall include a driver and officer area with two (2) cab door openings. The front door opening shall offer a clear door opening of 43.00 inches wide X 56.00 inches high. The rear door opening shall offer a clear door opening of 34.00 inches wide X 84.00 inches high. This style of cab shall also include a crew area offering up to ten (10) seating positions.

The cab shall incorporate a (2) step configuration from the ground to the cab floor for each door opening. The lower step shall be constructed of heavy duty safety grating which meets or exceeds Federal Specification RRG-1602-latest revision and performs under dry, greasy, muddy, soapy and icy conditions and offers open drainage.

The first step for the driver and officer area shall measure 11.44 inches deep X 31.13 inches wide. The intermediate step shall measure 8.75 inches deep X 33.00 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 11.00 inches.

The first step for the crew area shall measure 12.13 inches deep X 20.44 inches wide. The intermediate step shall measure 10.50 inches deep X 23.00 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 12.50 inches.

The cab front shall be constructed of 5052-H32 Marine Grade, .090 of an inch thick, one hundred percent primary aluminum plate which shall include a classic front appearance. The front of the cab shall include a cast molded module accommodating up to (4) Hi/Low beam headlights and (2) turn signal lights or up to (4) warning lights.

Wharton Fire Department

Heavy Rescue Specification

SVI

CAB FRONT FASCIA

The front cab fascia shall be constructed of 5052-H32 Marine Grade, 0.090 of an inch thick, one hundred percent primary aluminum plate which shall be an integral part of the cab.

The cab fascia will encompass the entire front of the aluminum cab structure from the bottom of the windshield to the bottom of the cab and shall be the "Classic" design.

The front cab fascia shall include two (2) molded plastic modules on each side accommodating a total of up to four (4) Hi/Low beam headlights and two (2) turn signal lights or up to four (4) warning lights. Two (2) chrome plated molded plastic bezels shall be provided on each side around each set of two lamps.

FRONT GRILLE

The front fascia shall include a box style, stainless steel front grille 39.00 inches wide X 33.50 inches high X 1.50 inches deep. The grille shall include a minimum free air intake of 632.90 square inches shall be installed on the front of the cab with the upper portion of the grille hinged. The grille shall include two (2) flush push button latches which shall allow access to the front fluid fills of the cab. The front grille shall include a cast diamond shape at the top and offer easy access in examination of and adding engine oil or wiper washer fluid as well as access to the windshield wiper motor and linkage.

CAB ENGINE TUNNEL

The cab interior shall include a fixed type engine tunnel cover sized to accommodate an engine with a smaller block. The engine tunnel shall be an integral part of the cab constructed of 5052-H32 Marine Grade, .090 of an inch thick, one hundred percent primary aluminum plate. The tunnel shall be a maximum of 41.50 inches wide X 23.00 inches high.

The engine tunnel shall be insulated with multi-layer insulating material, consisting of foam, a sound barrier of 1.00 pounds per square foot with a facing which resists heat transfer. This insulation shall be held in place by adhesive, aluminum stick pins and retention caps. Any exposed insulation seams and edges shall be sealed reducing moisture and debris.

Wharton Fire Department

Heavy Rescue Specification

SVI

CAB ENTRY DOORS

The cab shall include a driver and officer area with two cab door openings which offer a clear door opening of 40.75 inches wide.

The doors shall be constructed of extruded aluminum with a nominal thickness of .125 inch. The exterior skins shall be constructed of .125 inch aluminum plate. The cab shall include four (4) entry doors as high as possible for ease of entering and egress when outfitted with an SCBA.

All cab and crew doors shall be of substantial weight for the optimum strength and rigidity for the best performance in all cab crash testing. Any cab with front and crew doors manufactured of less than the material thickness of .125 inch in both the extrusion and exterior skin shall not be considered.

The doors shall include a double rolled style automotive rubber seal around the perimeter of each door frame and door edge which ensures a weather tight fit.

All door hinges shall be hidden within flush mounted cab doors for a pleasing smooth appearance and perfect fit along each side of the cab. Each hinge shall be .375 inch piano style and be constructed of stainless steel.

The piano style hinge and hidden flush mounted door is the most favorable construction keeping dirt and debris out of the hinge allowing for optimum operation throughout the lifetime of the door.

Proposals offering door hinge thickness any less than stated shall not be considered.

Proposals including doors that do not comply with the flush mounting as described or those including exposed hinges shall not be considered.

CAB ENTRY DOOR TYPE

All entry doors shall be of a flush, full height design and shall be located on the sides of the cab.

LH EXTERIOR REAR COMPARTMENT

The cab shall contain an exterior compartment on the left side of the cab behind the rear door. The compartment opening shall be 16.25 inches wide X 21.19 inches high. The compartment size shall be 17.84 inches wide X 21.19 inches high X 21.19 inches deep. The compartment shall include a 17.13 inch wide, 32.00 inch high and 1.50 inch thick hinged box pan style flush mount door with a locking bent D-ring slam latch. There shall be a switch to activate the open compartment warning light in the cab in the event the door is left ajar.

LH EXTERIOR REAR COMPARTMENT LIGHTING

Wharton Fire Department

Heavy Rescue Specification

SVI

There shall be one (1) SoundOff Signal brand LED strip light installed to illuminate the exterior rear compartment on the left side of the cab. The strip light shall be 10" long and shall include three (3) bright white Gen3 LEDs for long life and low amp draw.

RH EXTERIOR REAR COMPARTMENT

The cab shall contain an exterior compartment on the right side of the cab behind the rear door. The compartment opening shall be 16.25 inches wide X 21.19 inches high. The compartment size shall be 17.84 inches wide X 21.19 inches high X 21.19 inches deep. The compartment shall include a 17.13 inch wide, 32.00 inch high and 1.50 inch thick hinged box pan style flush mount door with a locking bent D-ring slam latch. There shall be a switch to activate the open compartment warning light in the cab in the event the door is left ajar.

RH EXTERIOR REAR COMPARTMENT LIGHTING

There shall be one (1) SoundOff Signal brand LED strip light installed to illuminate the exterior rear compartment on the right side of the cab. The strip light shall be 10" long and shall include three (3) bright white Gen3 LEDs for long life and low amp draw.

CAB STRUCTURAL WARRANTY

The cab structure shall be warranted for a period of ten (10) years. Warranty conditions may apply and shall be listed in the detailed warranty document that shall be provided upon request.

CAB TEST INFORMATION

The cab shall have successfully achieved survival of the International crash test ECE-29, Addendum 28, Revision 1 as indicated below.

As part of the ECE regulation 29 test, the frontal area of the cab is struck by a 3,700 pound pendulum weight. The weight is brought back to a sixty degree angle and then the weight is released and allowed to swing forward, imparting some 32,600 pounds foot of force to the cab front face. The cab shall be so constructed that after the test, there will be minimal intrusion of the cab structure into the passenger area. The doors shall remain usable for both entry and exit. Also, as part of the test the cab roof must withstand a static load bearing test. The cab shall withstand a weight of over 60,000 pounds without permanent damage or collapse. The above tests shall be witnessed by and attested to by an independent third party. The test results shall be recorded on/by cameras, high speed imagers, accelerometers and strain gauges, with notarized copies of the letters verifying the test results and videos of said test shall be available upon request.

Wharton Fire Department

Heavy Rescue Specification

SVI

CAB PAINT EXTERIOR

The cab shall be painted prior to the installation of glass accessories and all other cab trim to ensure complete paint coverage and the maximum in corrosion protection of all metal surfaces.

All metal surfaces on the entire cab shall be ground by disc to remove any surface oxidation or surface debris which may hinder the paint adhesion. Once the surface is machine ground a high quality acid etching of base primer shall be applied. Upon the application of body fillers and their preparation, the cab shall be primed with a coating designed for corrosion resistance and surface paint adhesion. The maximum thickness of the primer coat shall be 2.00 mils.

The entire cab shall then be coated with an intermediate solid or epoxy surfacing agent that is designed to fill any minor surface defects, provide an adhesive bond between the primer and the paint and improve the color and gloss retention of the color. The finish to this procedure shall be a sanding of the cab with 360 grit paper, the seams shall be sealed with SEM brand seam sealer and painted with two (2) to four (4) coats of an acrylic urethane type system designed to retain color and resist acid rain and most atmospheric chemicals found on the fire ground or emergency scene.

The cab shall then be painted with the upper and lower colors specifically designated by the customer with a minimum thickness of two 2.00 mils of paint, followed by a clear top coat not to exceed 2.00 mils.

CAB PAINT MANUFACTURER

The cab shall be painted with PPG Industries paint.

CAB PAINT PRIMARY/ LOWER COLOR

The lower paint color shall be painted with PPG paint number FBCH 911620 . The MAROON paint color shall match Sikkens Autocoat LV FLNA 30165.

CAB PAINT SECONDARY/UPPER CAB COLOR

The upper paint color shall be PPG FBCH 2185 White.

CAB PAINT EXTERIOR BREAK LINE

The upper and lower paint shall meet at a break line on the cab which shall fall approximately 1.00 inch under the door windows and above the door handles. The break line shall extend in a straight line and fall approximately 1.00 inch under the windshield and above the windshield wipers on the front of the cab.

Wharton Fire Department

Heavy Rescue Specification

SVI

CAB PAINT PINSTRIPE

Where the upper and lower paint colors meet a temporary 0.50 inch black pinstripe shall be applied over this break line to offer a more finished look prior to the final pinstripe being installed by the OEM.

CAB PAINT WARRANTY

The cab and chassis shall be covered by a limited manufacturer paint warranty which shall be in effect for 10 years from the first owners date of purchase or in service or the first 100,000 actual miles, whichever occurs first.

ELECTRICAL SYSTEM

The chassis shall include a single starting electrical system which shall include a 12 volt direct current Weldon brand of multiplexing system, suppressed per SAE J551. The wiring shall be appropriate gauge cross link with 311 degree Fahrenheit insulation. All SAE wires in the chassis shall be color coded and shall include the circuit number and function where possible. The wiring shall be protected by 275 degree Fahrenheit minimum high temperature flame retardant loom. All nodes and sealed Deutsch connectors shall be waterproof.

APPARATUS WIRING PROVISION

An apparatus wiring panel shall be installed on the officer side bulkhead below the dash which shall include eight (8) open circuits consisting of three (3) 20 amp, one (1) 30 amp, three (3) 10 amp, and one (1) 15 amp circuit, with relays and breakers with trigger wires which shall be routed to the rocker switch panel.

MULTIPLEX DISPLAY

The multiplex electrical system shall include a Weldon Vista III display which shall be located on the left side of the dash in the switch panel. The Vista III shall feature a full color LCD display screen which includes a message bar displaying the time of day, the current ambient outside temperature and important messages requiring acknowledgement by the user which shall all be displayed on the top of the screen in the order they are received. There shall be virtual controls for the auto climate control and on-board diagnostics. The display screen shall be video ready for back- up cameras, thermal cameras, and DVD.

The Vista III display shall measure approximately 10.38 inches wide X 7.50 inches overall. The display shall offer varying fonts and background colors. The display shall be fully programmable to the needs of the customer and shall offer virtually infinite flexibility for screen configuration options.

Wharton Fire Department

Heavy Rescue Specification

SVI

VEHICLE DATA RECORDER

The chassis shall have a Weldon Vehicle Data Recorder system installed. The system shall be designed to meet NFPA 1901 and shall be integrated with the Weldon Multiplex electrical system. The following information shall be recorded:

- Vehicle Speed
- Acceleration
- Deceleration
- Engine Speed
- Engine Throttle Position
- ABS Event
- Seat Occupied Status
- Seat Belt Status
- Master Optical Warning Device Switch Position
- Time
- Date

Each portion of the data shall be recorded at the specified intervals and stored for the specified length of time to meet NFPA 1901 guidelines and shall be retrievable by connecting a laptop computer to the VDR system.

POWER & GROUND STUD

A 40 amp battery direct power and ground stud shall be provided and installed in the electrical distribution panel. The stud shall be size #10 and protected with a 40 amp circuit breaker.

AUXILIARY POWER & GROUND STUD

An auxiliary set of power and ground studs shall be provided and installed behind the electrical center cover with a 40 amp breaker. The studs shall be .375 inch diameter and capable of carrying up to a 40 amp load switched with the master power switch.

EXTERIOR ELECTRICAL TERMINAL COATING

All terminals exposed to the elements will be sprayed with a yellow protective rubberized coating to prevent corrosion.

Wharton Fire Department

Heavy Rescue Specification

SVI

ENGINE

The power plant for the vehicle shall offer a high pressure performance, turbo charged engine which shall feature a high pressure common rail fuel system. This system shall be coupled with a proven Holset turbo which delivers outstanding performance at ratings up to 425 HP. The Cummins ISL engine shall include replaceable mid-stop cylinder liners plus heavy duty roller followers, targeted piston cooling and 30% more efficient oil cooling for improved durability and reliability. The heavy duty design shall also feature stronger braking capacity.

The engine shall be EPA certified to meet the very latest emissions standards without compromising performance, reliability or durability. The Cummins ISL 425 engine shall feature an air charge cooled engine which consists of an in line six (6) cylinder, four cycle diesel powered engine. The engine shall offer a rating of 425 horse power at 2100 RPM which shall be governed at 2200 RPM. The torque rating shall feature 1200 foot pounds of torque at 1300 RPM with 543 cubic inches of displacement. The Cummins ISL 425 engine shall feature an electronic governor.

A wiring harness shall be supplied ending at the back of the cab. The harness shall include a connector which shall allow an optional harness for the pump panel. The included circuits shall be provided for a tachometer, oil pressure, engine temperature, hand throttle, high idle and a PSG system. A circuit for J1939 data link shall also be provided at the back of the cab.

The engine shall include an engine mounted combination full flow/by-pass oil filter with replaceable spin on cartridge for use with the engine lubrication system. The engine shall include Citgo brand Citgard 500, or equivalent SAE 15W40 CJ4 low ash engine oil which shall be utilized for proper engine lubrication.

DIESEL PARTICULATE FILTER CONTROLS

There shall be two (2) controls for the diesel particulate filter. One (1) control shall be for regeneration and one (1) control shall be for regeneration inhibit.

ENGINE PROGRAMMING HIGH IDLE SPEED

The engine high idle control shall maintain the engine idle at approximately 1250 RPM when engaged.

ENGINE HIGH IDLE CONTROL

The vehicle shall be equipped with an automatic high-idle speed control. It shall be pre-set so when activated, it will operate the engine at the appropriate RPM to increase alternator output. This device shall operate only when the master switch is activated and the transmission is in neutral with the parking brake set. The device shall disengage when the operator depresses the brake pedal, or the transmission is placed in gear, and shall be available to manually or automatically re-engage when the brake is released, or when the transmission is placed in neutral. There shall be an indication on the Vista screen for the high idle speed control.

Wharton Fire Department

Heavy Rescue Specification

SVI

ENGINE PROGRAMMING ROAD SPEED GOVERNOR

The engine shall include programming which will govern the top speed of the vehicle.

AUXILIARY ENGINE BRAKE

A Jacobs engine compression brake, for the six (6) cylinder engine shall be provided. The engine compression brake shall actuate the vehicles brake lights when engaged. A cutout relay shall be installed to disable the compression brake when in pump mode or when an ABS event occurs. The engine brake shall activate upon 0% accelerator when in operation mode.

AUXILIARY ENGINE BRAKE CONTROL

An engine compression brake control device shall be included. The electronic control device shall monitor various conditions and shall activate the engine brake only if all of the following conditions are simultaneously detected: a valid gear ratio is detected; the driver has requested or enabled engine compression brake operation; the throttle is at a minimum engine speed position; and the electronic controller is not presently attempting to execute an electronically controlled final drive gear shift. The compression brake shall be controlled via an off/low/high virtual button through the Vista display.

FLUID FILLS

The front of the chassis shall accommodate fluid fills for the engine oil, and the power steering fluid through the grille. This area shall also accommodate checks for the engine oil, and power steering fluid.

ELECTRONIC ENGINE OIL LEVEL INDICATOR

The engine oil shall be monitored electronically and shall send a signal to activate a light in the instrument panel when levels fall below normal. The light shall activate in a low oil situation upon turning on the master battery and ignition switches without the engine running.

ENGINE WARRANTY

The Cummins engine shall be warranted for a period of five (5) years or 100,000 miles, whichever occurs first.

ENGINE PROGRAMMING REMOTE THROTTLE

The engine ECM (Electronic Control Module) discreet wire remote throttle circuit shall be turned off for use with a J1939 based pump controller or when the discreet wire remote throttle controls are not required.

Wharton Fire Department

Heavy Rescue Specification

SVI

ENGINE PROGRAMMING IDLE SPEED

The engine low idle speed will be programmed at 700 rpm.

ENGINE FAN DRIVE

The engine cooling system fan shall be direct drive belt driven on the engine.

ENGINE COOLING SYSTEM

There shall be a heavy-duty aluminum cooling system designed to meet the demands of the fire industry. The cooling system shall have the capacity to keep the engine properly cooled under all conditions of road and pumping operations. The cooling system shall be designed and tested to meet or exceed the requirements specified by the engine and transmission manufacturer and all EPA requirements. The complete cooling system shall utilize heavy-duty welds and be mounted to isolate the entire system from vibration or stress. The individual cores of the cooling system shall be mounted in a manner to allow expansion and contraction at various rates without inducing stress into the adjoining cores.

The cooling system shall be comprised of a stacked, single depth package that provides the maximum cooling capacity for the specified engine as well as offers excellent serviceability. The main components shall include a surge tank, a charge air cooler, a recirculation shield, and a radiator.

Proposals unable to offer a stacked single depth cooling package shall not be considered.

There shall be a single depth core that allows greater efficiency, enhanced serviceability, and lighter weight with a higher ambient capability. The cooling package core shall not protrude below the frame of the vehicle by more than 1.1 inch. This feature shall improve the angle of approach thereby reducing possible damage.

The radiator shall be a cross-flow design constructed completely of aluminum with welded side tanks. The radiator shall include a minimum of a 627 square inch core and shall be bolted to the bottom of the charge air cooler to allow a single depth core, thus allowing a more efficient and serviceable cooling system. The radiator shall be equipped with a drain cock to drain the coolant for serviceability.

The cooling system shall include a one piece injected molded Polymer fan blade designed to provide long life in harsh environments. Polymer fans provide a significant weight reduction over metal fans providing longer life for fan clutch linings and bearings along with increased fan belt life.

The cooling system shall be equipped with a surge tank that is capable of removing entrained air from the system. The surge tank shall be equipped with a low coolant probe and sight glass to monitor the level of the coolant. The surge tank shall have a cap that meets the engine manufactures pressure requirements as well as the system design requirements.

All radiator tubes shall be formed from aluminized steel tubing. Recirculation shields shall be installed where required to prevent heated air from reentering the cooling package and affecting performance. When a center bumper compartment is installed an additional shield may be required to redirect the airflow into the coolers.

The charge air cooler shall be a cross-flow design constructed completely of aluminum with welded side tanks. The charge air cooler shall have a minimum of a 390 square inch core and be bolted to the top of the radiator to allow a single depth core, thus allowing a more efficient and serviceable cooling system.

All charge air cooler tubes shall be formed from aluminized steel tubing and installed with silicone hump hoses and stainless steel "constant torque" style clamps meeting the engine manufactures requirements.

Wharton Fire Department

Heavy Rescue Specification

SVI

ENGINE COOLANT

The cooling package shall include Extended Life Coolant (ELC). The use of ELC provides longer intervals between coolant changes over standard coolants providing improved performance. The coolant shall contain a 50/50 mix of ethylene glycol and de-ionized water to keep the coolant from freezing to a temperature of -34 degrees F.

Proposals offering supplemental coolant additives (SCA) shall not be considered, as this is part of the extended life coolant makeup.

ELECTRONIC COOLANT LEVEL INDICATOR

The instrument panel shall feature a low engine coolant indicator light which shall be located in the center of the instrument panel. An audible tone alarm shall also be provided to warn of a low coolant incident.

COOLANT HOSES

The cooling systems hose shall be formed silicone hose and formed aluminized steel tubing and include stainless steel constant torque band clamps.

ENGINE AIR INTAKE

The engine air intake system shall include an ember separator air intake filter which shall be located in the front of the cab behind the officer side fascia. This filter shall protect the downstream air filter from embers using a combination of unique flat and crimped metal screens constructed into a galvanized steel frame. This multilayered screen shall be designed to trap embers or allow them to burn out before passing through the pack, while creating only minimal air flow restriction through the system. Periodic cleaning or replacement of the screen shall be all that is required after installation.

The engine shall also include an air intake filter which shall be bolted to the frame and located under the front of the cab on the officer side. The completely disposable dry type filter shall ensure containment of dust and debris safely contained inside the disposable housing, eliminating the chance of contaminating the air intake system during air filter service via a leak-tight seal.

The air flow distribution and dust loading shall be uniform throughout the high-performance filter cone pack, which shall result in increased capacity and lower pressure differential for improved horsepower and fuel economy. The air intake shall be mounted within easy access via a hinged panel behind the headlight module. The air intake system shall include a restriction indicator light in the warning light cluster which shall activate when the air cleaner element requires replacement.

The charge air cooler hose shall be formed from aluminized steel tubing and include silicone hump hose with stainless expansion rings and stainless steel "constant torque" style clamps meeting the engine manufactures requirements.

Proposals shall include an indication light representative of the need for replacement of the air intake filter and shall be located at the front of the vehicle.

Wharton Fire Department

Heavy Rescue Specification

SVI

AIR INTAKE SKIDPLATE

A skid plate shall be supplied for the engine air intake system below the right front side of the cab. The skid plate shall be bolted to the bottom flange of the right side frame rail to provide additional protection for the air intake system.

ENGINE EXHAUST SYSTEM

The exhaust system shall include a diesel particulate filter and a diesel oxidation catalyst to meet current EPA standards.

The system shall utilize 0.065 inch thick stainless steel exhaust tubing between the engine turbo and the diesel particulate filter. This section of the exhaust system shall be wrapped with a thermal cover in order to retain the necessary heat for system regeneration. Zero leak clamps seal all system joints between the turbo and diesel particulate filter.

From the diesel particulate filter to the end of the tailpipe the system shall be plumbed with 0.065 inch thick aluminized steel tubing connected with overlapping band style clamps. The discharge shall terminate horizontally on the officer side of the vehicle ahead of the rear tires.

The exhaust system shall be mounted below the frame in the inboard position maximizing space for the body compartments.

ENGINE EXHAUST ACCESSORIES

An exhaust temperature mitigation device shall be shipped loose for installation by the body manufacturer on the vehicle. The temperature mitigation device shall lower the temperature of the exhaust by combining ambient air with the exhaust gasses at the exhaust outlet.

TRANSMISSION

The drive train shall include an Allison Gen IV-E model EVS 3000 torque converting, automatic transmission which shall include electronic controls. The transmission shall feature two (2) 10-bolt PTO pads located on the converter housing.

The transmission shall include two (2) internal oil filters and Castrol TranSynd™ synthetic TES 295 transmission fluid which shall be utilized in the lubrication of the EVS transmission. An electronic oil level sensor shall be included with the readout located in the shift selector.

The Gen IV-E transmission shall include prognostic diagnostic capabilities. These capabilities shall include the monitoring of the fluid life, filter change indication, and transmission clutch maintenance.

The transmission gear ratios shall be:

1st- 3.49:1; 2nd- 1.86 to 1; 3rd- 1.41 to1; 4th- 1.00 to 1; 5th- 0.75 to 1; 6th-0.64 to 1 (if applicable); Rev- 5.03 to 1.

TRANSMISSION MODE PROGRAMMING

The transmission, upon start-up, will select the fifth speed operation without the need to press the mode button.

Wharton Fire Department

Heavy Rescue Specification

SVI

TRANSMISSION FEATURE PROGRAMMING

The EVS group package number 127 shall contain the 199 vocational package in consideration of the duty of this apparatus for rescue. This package shall incorporate an automatic neutral with selector override. This feature commands the transmission to neutral when the park brake is applied, regardless of drive range requested on the shift selector. This requires re-selecting drive range to shift out of neutral for the override.

An 8 pin Delphi connector will be provided next to the steering column connector. This will contain the following input/output circuits to the transmission tcm.

Function ID	Description	Wire assignment
C	PTO Request	143
F	Aux. Function Range Inhibit (Special)	101/142
G	PTO Enable Output (See Input Function C)	130
S	Neutral Indicator for PTO	145
	Signal Return	103

ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR

The transmission fluid shall be monitored electronically and shall send a signal to activate a light in the instrument panel when levels fall below normal.

TRANSMISSION SHIFT SELECTOR

An Allison pressure sensitive range selector touch pad shall be provided and located to the right of the driver within clear view and easy reach. The shift selector will provide a prognostic indicator (wrench symbol) between the selected and attained indicators.

TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE

When the auxiliary brake is engaged, the transmission shall automatically seek shifting to second gear to decrease the rate of speed assisting the secondary braking system and slowing the vehicle speed.

TRANSMISSION WARRANTY

The Allison EVS series transmission shall be warranted for a period of five (5) years with unlimited mileage. Parts and labor shall be included in the warranty.

Wharton Fire Department

Heavy Rescue Specification

SVI

TRANSMISSION COOLING SYSTEM

The transmission shall include an air to oil cooler integrated into the lower portion of cooling package. The transmission cooling system shall meet all transmission manufacturer requirements. The cooling system shall feature a circuit provision located within the hydraulic transmission oil which shall provide for rapid warm up to the optimum transmission operating temperature.

Proposals offering water to oil style transmission cooling systems shall not be accepted.

LH PTO

A Spartan supplied ten (10) bolt standard duty clutched drive PTO shall be installed on the transmission. Installation shall include mounting of the PTO and wiring the unit with a control switch.

LH PTO MODEL

A ten (10) bolt Chelsea model 277-XMFJP-B5XD heavy duty transmission driven PTO shall be installed. The clutched shifted PTO is designed specifically for the Allison world transmission and provides torque ranges from 250 to 335 lb. ft.

PTO LOCATION

The transmission driven power take off (PTO) shall be mounted in the 9:00 o'clock position.

PTO CONTROL

The left hand power take off shall be controlled by the transmission. It will use a virtual switch on vista with text messages. Disable is displayed when switch is off. Enable is displayed when the switch is turned on. Active is displayed when the switch is on with positive engagement of the power take off.

Required operating conditions for enabling this function are:

- Throttle position is low
- Engine speed is within customer modifiable constant limits
- Output speed is within customer modifiable constant limits
- Park brake set

DRIVELINE

Wharton Fire Department

Heavy Rescue Specification

SVI

All drivelines shall be heavy duty metal tube and equipped with Spicer 1710 series universal joints. The shafts shall be dynamically balanced prior to installation to alleviate future vibration. A splined slip joint shall be provided in each driveshaft and shall be coated with Glide coat®.

FUEL FILTER/WATER SEPARATOR

The fuel system shall have a Fleetguard FS1003 fuel filter/water separator as a primary filter. The fuel filter shall have a drain valve.

A water in fuel sensor shall be provided and wired to an instrument panel lamp and audible alarm to indicate when water is present in the fuel/water separator.

A secondary fuel filter shall be included as approved by the engine manufacturer.

FUEL LINES

The fuel system lines shall be black textile braid covered high tensile steel reinforced wire braided supply and return hoses with steel reusable fittings installed from the tank to engine.

FUEL SHUTOFF VALVE

A fuel shutoff valve shall be installed in the fuel draw line at the primary fuel filter to allow the fuel filter to be changed without loss of fuel to the fuel pump.

A second fuel shutoff valve shall be installed in the fuel draw line, near the fuel tank to allow maintenance to be performed with minimal loss of fuel.

FUEL TANK

The fuel tank shall have a minimum capacity of sixty-eight (68) gallons and measure 35.00 inches wide X 17.00 inches high X 29.00 long. The baffled tank shall be made of 14 gauge aluminized steel. The tank exterior is painted with a PRP Corsol™ black anti-corrosive exterior metal treatment finish. This results in a tank which offers the internal and external corrosion resistance.

The fuel tank shall be mounted 2.00 inch below the frame, behind the rear axle. The tank can be easily lowered and removed for service purposes.

The tank shall have a vent port to facilitate venting to the top of the fill neck for rapid filling without "blow-back" and a roll over ball check vent for temperature related fuel expansion and draw.

Dual draw tubes and dual sender ports shall be installed. A 2.00 inch NPT fill ports shall be available for right or left hand fill. A 0.5 inch NPT drain plug shall be centered in the bottom of the tank.

Wharton Fire Department

Heavy Rescue Specification

SVI

FUEL TANK FILL PORT

The fuel tank fill ports shall be provided with the right fill port located in the middle position and the left fill ports located one (1) in the forward position and one (1) in the middle position of the fuel tank.

FRONT AXLE

The front axle shall be a Meritor Easy Steer Non drive front axle, model number MFS-23. The axle shall include a 3.74 inch drop and a 71.00 inch king pin intersection (KPI). The axle shall include a conventional style hub with a standard knuckle. The weight capacity for the axle shall be rated to 23,000 pounds. This rating shall require special approvals from the wheel manufacturers.

FRONT WHEEL BEARING LUBRICATION

The front axle wheel bearings shall be lubricated with clear oil. The oil level can be visually checked via clear inspection windows in the front axle hubs.

FRONT SHOCK ABSORBERS

Two (2) Bilstein inert, nitrogen gas filled shock absorbers shall be provided and installed as part of the suspension system. The shocks shall be a monotubular design and fabricated using a special extrusion method, utilizing a single blank of steel without a welded seam, achieving an extremely tight peak-to-valley tolerance and maintains consistent wall thickness. The monotubular design shall provide superior strength while maximizing heat dissipation and shock life.

The ride afforded through the use of a gas shock is more consistent and shall not deteriorate with heat, the same way a conventional oil filled hydraulic shock would.

The Bilstein front shocks shall include a digressive working piston assembly allowing independent tuning of the compression and rebound damping forces to provide optimum ride and comfort without compromise. The working piston design shall feature fewer parts than most conventional twin tube and "road sensing" shock designs and shall contribute to the durability and long life of the Bilstein shock absorbers.

Proposals offering the use of conventional twin tube or "road sensing" designed shocks shall not be considered.

FRONT SUSPENSION

The front suspension shall include nine (9) leaf, 53.38 inch long and 4.00 inches wide taper leaf springs with a military double wrapped front eye. Both spring eyes shall have a case hardened threaded bushing installed with lubrication counter bore and lubrication land off cross bore with grease fitting. The spring capacity shall be rated at 23,000 pounds.

STEERING COLUMN/ WHEEL

Wharton Fire Department

Heavy Rescue Specification

SVI

The cab shall include a Douglas Autotech steering column shall be a seven (7) position tilt and 2.25 inch telescopic type with an 18.00 inch steering wheel located on the left side of the cab designating the drivers position. The steering wheel shall be covered with black absorbite padding.

The steering column shall contain a horn button, self-canceling turn signal switch, four-way hazard switch and headlamp dimmer switch.

POWER STEERING PUMP

The hydraulic power steering pump shall be a TRW PS and shall be gear driven from the engine. The pump shall be a balanced, positive displacement, sliding vane type.

ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR

The power steering fluid shall be monitored electronically and shall send a signal to activate a light in the instrument panel when levels fall below normal.

FRONT AXLE CRAMP ANGLE

The chassis shall have a front axle cramp angle of 48 degrees to the left and 44 degrees to the right.

POWER STEERING GEAR

The power steering gear shall be a TRW model TAS 85 with an assist cylinder.

CHASSIS ALIGNMENT

The chassis frame rails shall be cross checked to insure the length and to make sure each is square. The front and rear axles shall be laser aligned, additionally the tires and wheels shall be aligned and toe-in set on the front tires. The completed apparatus shall be rechecked for proper alignment once the chassis has been fully loaded.

REAR AXLE

The rear axle shall be a Meritor model RS-25-160. The axle shall be built of superior construction and quality components to provide the rugged dependability needed to stand up to the industrys demands. The axle shall include rectangular shaped, hot-formed housings for extra strength and rigidity. The axles shall also include torsion flow axle shafts that feature a surface hardness which resists fatigue and a resilient core which absorbs shock. There shall be unitized pinion seals within the axle helping to prevent leakage and harmful road contaminants from entering the axle components. The axle shall include a rigid differential case for high axle strength and reduced maintenance.

Wharton Fire Department

Heavy Rescue Specification

SVI

The axle shall include single reduction gearing and shall have a rated capacity of 27,000 pounds.

REAR WHEEL BEARING LUBRICATION

The rear axle wheel bearings shall be lubricated with oil.

REAR AXLE DIFFERENTIAL LUBRICATION

The rear axle differential shall be lubricated with oil.

VEHICLE TOP SPEED

The top speed of the vehicle shall be approximately 68 MPH +/- 2 MPH at governed engine RPM.

REAR SUSPENSION

The single rear axle suspension shall feature a Neway AD-127 air suspension. The suspension shall include optimized air springs mounted to the equalizing beams and integral transverse beam. An adjustable torque rod and adjustable track bar shall also be included.

Dual air height control valves shall be installed to ensure equal frame height on both sides of the vehicle regardless of the load. The rear suspension is run flat capable at reduced speeds.

The rear suspension capacity shall be rated at 24,000 to 27,000 pounds.

REAR SHOCK ABSORBERS

Shock absorbers shall be supplied by the suspension manufacturer and installed on the rear axle suspension.

FRONT TIRE

The front tires shall be Michelin 425/65R22.5 "L" tubeless radial XFE regional tread.

The front tire stamped load capacity shall be 22,800 pounds per axle with a speed capacity of 65 miles per hour when properly inflated to 120 pounds per square inch.

The front tire US Fire Service Intermittent Usage load capacity shall be 23,000 pounds per axle with a speed capacity of up to 75 miles per hour when properly inflated to 120 pounds per square inch.

Wharton Fire Department

Heavy Rescue Specification

SVI

REAR TIRE

The rear tires shall be Michelin 12R-22.5 16PR "H" tubeless radial XZE regional tread.

The rear tire stamped load capacity shall be 27,120 pounds per axle with a speed capacity of 75 miles per hour when properly inflated to 120 pounds per square inch.

The rear tire US Fire Service Intermittent Usage load capacity shall be 28,880 pounds per axle with a speed capacity of 75 miles per hour when properly inflated to 120 pounds per square inch.

TIRE PRESSURE EQUALIZATION SYSTEM

The rear dual tires shall include the Crossfire dual tire equalization system provided on both sets of dual tires on the rear axle. The Crossfire pressure system shall equalize and monitor the valve which is mounted between the dual tires. This shall bolt easily to the drive axle end allowing air to flow freely from one tire to the other, maintaining equal tire pressure and load distribution. The Crossfire system shall maximize tire life, decrease rolling resistance for increased fuel mileage and improve stability braking and overall safety.

TIRE PRESSURE INDICATOR

There shall be a pop up style tire pressure indicator at the front tire valve stem on the vehicle that shall indicate if there is insufficient pressure in the specific tire.

FRONT WHEEL

The front wheels shall be Alcoa hub piloted, 12.25 inch X 22.50 inch aluminum wheels with the Alcoa XBR Dura-Bright® wheel treatment as an integral part of the wheel. Alcoa XBR Dura-Bright® wheels keep their shine without polishing; the wheels shall come clean simply by spraying with soap and water. Brake dust, grime and dulling oxidation shall wash off with no scrubbing and no special chemicals required.

REAR WHEEL

The rear wheels shall be Alcoa hub piloted, 8.25 inch X 22.50 inch aluminum wheels with the Alcoa XBR Dura-Bright® wheel treatment as an integral part of the wheel. Alcoa XBR Dura-Bright® wheels keep their shine without polishing; the wheels shall come clean simply by spraying with soap and water. Brake dust, grime and dulling oxidation shall wash off with no scrubbing and no special chemicals required.

BALANCE WHEELS AND TIRES

All of the wheels and tires, including any spare wheels and tire assemblies, shall be dynamically balanced.

Wharton Fire Department

Heavy Rescue Specification

SVI

WHEEL TRIM

The front wheels shall include stainless steel lug nut covers and stainless steel baby moons with cutouts for oil seal viewing (there shall be no cutout on front drive, IFS axles, or when the front wheel bearing lubrication is grease). The covers and baby moons shall feature a mirror shine finish and shall be shipped loose with the chassis for installation by the apparatus builder.

The rear wheels shall include stainless steel lug nut covers and band mounted spring clip stainless steel high hats, also in a mirror shine finish, which shall be shipped loose with the chassis for installation by the apparatus builder.

The lug nut covers, baby moons, and high hats shall be RealWheels® brand, and constructed of 304L grade, non-corrosive stainless steel meeting D.O.T. certification standards.

BRAKE SYSTEM

A rapid build-up air brake system shall be provided. The air brakes shall include a two (2) air tank, three (3) reservoir system with a total of 4152 cubic inch of air capacity. A floor mounted treadle valve shall be mounted inside the cab for graduated control of applying and releasing the brakes. An inversion valve shall be installed to provide a service brake application in the unlikely event of primary air supply loss.

The rear axle spring brakes shall automatically apply in any situation when the air pressure falls below 25 PSI and shall include a mechanical means for releasing the spring brakes when necessary. An audible alarm shall designate when the system air pressure is below 60 PSI.

A four (4) sensor, four (4) modulator anti-lock braking system (ABS) shall be installed on the front and rear axles in order to prevent the brakes from locking or skidding while braking during hard stops or on icy or wet surfaces. This in turn shall allow the driver to maintain steering control under heavy braking and in most instances, shorten the braking distance. The electronic monitoring system shall incorporate diagonal circuitry which shall monitor wheel speed during braking through a sensor and tone ring on each wheel. A dash mounted ABS lamp shall be provided to notify the driver of a system malfunction. The ABS system shall automatically disengage the auxiliary braking system device when required. The speedometer screen shall be capable of reporting all active defaults using PID/SID and FMI standards.

Automatic traction control which shall be installed on the single rear axle. The automatic traction control system shall apply the anti-lock braking system when the drive wheels loose traction. The system shall scale the electronic engine throttle back to prevent wheel spin while accelerating on ice or wet surfaces.

Additional handling capabilities shall include roll stability control which shall monitor the vehicles rollover threshold based on the lateral acceleration. The system shall activate a computerized device which shall slow the vehicle when the threshold is exceeded in either direction. Normal vehicle operation shall resume once the problematic conditions cease. Roll stability control shall be integral with the ABS and ATC systems. A virtual style switch shall be provided and properly labeled "mud/snow". When the switch is pressed once, the system shall allow a momentary wheel slip to obtain traction under extreme mud and snow conditions. During this condition the ATC light shall blink continuously notifying the driver of activation. Pressing the switch again shall deactivate the mud/snow feature.

The electronic stability control unit (ESC) is a functional extension of the electronic braking system. It is able to detect any skidding of the vehicle about its vertical axis as well as any rollover tendency. The control unit comprises an angular-speed sensor that measures the vehicles motion about the vertical axis, caused, for instance, by cornering or by skidding

Wharton Fire Department

Heavy Rescue Specification

SVI

on a slippery road surface. An acceleration sensor measures the vehicles lateral acceleration. The CAN bus provides information on the steering angle. On the basis of lateral acceleration and steering angle, an integrated microcontroller calculates a theoretical angular speed for the stable vehicle condition.

FRONT BRAKES

The front brakes shall be Meritor EX225 Disc Plus disc brakes with 17" vented rotors.

REAR BRAKES

The rear brakes shall be Meritor EX225 Disc Plus disc brakes with 17.00 inch vented rotors.

PARK BRAKE

Upon application of the push-pull valve in the cab, the rear brakes will engage via mechanical spring force. This is accomplished by dual chamber rear brakes, satisfying the FMVSS parking brake requirements.

PARK BRAKE CONTROL

A Meritor-Wabco manual hand control push-pull style valve shall operate the parking brake system. The control shall be yellow in color.

The parking brake actuation valve shall be mounted on the left hand dash to the right of the steering column within easy reach of the driver.

AIR DRYER

The brake system shall include a Wabco System Saver 1200 air dryer with an integral heater with a Metri-Pack sealed connector. The air dryer incorporates an internal turbo cutoff valve that closes the path between the air compressor and air dryer purge valve during the compressor "unload" cycle. The turbo cutoff valve allows purging of moisture and contaminants without the loss of turbo boost pressure. The air dryer shall be located on the right frame rail behind the officer step.

FRONT BRAKE CHAMBERS

The front brakes shall be provided with MGM type 24 long stroke brake chambers.

Wharton Fire Department

Heavy Rescue Specification

SVI

REAR BRAKE CHAMBERS

The rear axle shall include TSE 24/30 H.O.T. (High Output Technology) brake chambers shall convert the energy of compressed air into mechanical force and motion. This shall actuate the brake camshaft, which in turn shall operate the foundational brake mechanism forcing the brake pads against the brake rotor.

AIR COMPRESSOR

The air compressor provided for the engine shall be a Wabco® SS318 single cylinder pass-through drive type compressor which shall be capable of producing 18.7 CFM at 1200 engine RPMs. The air compressor shall feature a higher delivery efficiency translating to more air delivery per horsepower absorbed. The compressor shall include an aluminum cylinder head which shall improve cooling, reduce weight and decrease carbon formation. Superior piston and bore finishing technology shall reduce oil consumption and significantly increasing the system component life.

AIR GOVERNOR

An air governor shall be provided to control the cut-in and cut-out pressures of the engine mounted air compressor. The governor shall be calibrated to meet FMVSS requirements. The air governor shall be located on the air cleaner bracket on the right frame rail behind the officer step.

MOISTURE EJECTORS

Automatic moisture ejectors with a manual drain provision shall be installed on all reservoirs of the air supply system.

AIR SUPPLY LINES

A dual air system plumbed with color coded reinforced nylon tubing air lines shall be installed on the chassis. The primary (rear) brake line shall be green, the secondary (front) brake line red, the parking brake line orange and the auxiliary (outlet) will be blue.

Brass compression type fittings shall be used on the nylon tubing. All drop hoses shall include fiber reinforced neoprene covered hoses.

AIR HORN SHUTOFF VALVE

A shut-off valve located in the drivers dash shall be installed in the air horn supply line.

Wharton Fire Department

Heavy Rescue Specification

SVI

WHEELBASE

The chassis wheelbase shall be 238.00 inches.

REAR OVERHANG

The chassis rear overhang shall be 90.00 inches.

FRAME

The frame shall consist of double channel side rails and cross members forming a ladder style frame. The sides of the rails shall be constructed of "C" channel, 10.25 inches high X 3.5 inches deep X .38 inches thick with an inner channel of 9.44 inches high X 3.13 inches deep and .38 inches thick, 110,000 psi minimum yield high strength low alloy steel. Each rail shall be considered on the following key items: Each rail shall be rated by a Resistance Bending Moment (RBM) minimum of 3,213,100 inch pounds and have a minimum section modulus of 29.21 cubic inches calculated by the radius method. The frame shall measure 35.00 inches in width.

RBM refers to the measure of stiffness of a cross section relative to the yield stress of the material the frame is manufactured from.

Every cross sectional profile of an object has a measure of its mechanical properties based on its shape. These properties of its shape can be broken down relative to the horizontal and vertical direction, represented as I_{xx} and I_{yy} . These act as a measure of the shapes resistance to bending.

The section modulus of mass of this profile takes into consideration the stresses imposed on this profile when a load is applied, by considering the maximum distance from the center of the profile to its outer most extremity. Section modulus is a method of measurement for the relative stiffness of a beam section and is based on the horizontal and vertical directional value plus the distance from the center of mass to the extremities of the cross section from the coordinate axis, such that $Z_{yy} = I_{yy}/Y$ and $Z_{xx} = I_{xx}/X$.

Proposals calculating the frame strength using the "box method" shall not be considered.

Proposals including heat treated rails shall not be considered. Heat treating frame rails produces rails that are not uniform in their mechanical properties throughout the length of the rail. Rails made of high strength, low alloy steel are already at the required yield strength prior to forming the rail.

A minimum of seven (7) fully gusseted 0.25 inch thick cross members shall be installed. The inclusion of the engine mounting, body mounting, pump mounting or bumpers shall not be considered as a cross member. The cross members shall be attached using grade 8 flanged head bolts and flanged lock nuts. Each cross member shall be mounted to the frame rails a minimum of utilizing 0.25 inch thick gusset reinforcement plates at all corners balancing the area of force throughout the entire frame.

Wharton Fire Department

Heavy Rescue Specification

SVI

Any proposals not including additional reinforcement for each cross member shall not be considered.

All holes for bolts shall be drilled into the frame rails, preventing fracture or fatigue. Each hole shall be custom placed relative to its component preventing unnecessary holes that present fatigue along each frame rail.

The frames proposed shall be custom drilled for each component and shall not include any unnecessary holes.

All relief areas shall be cut in with a minimum 2.00 inch radius at intersection points with the edges ground to a smooth finish to prevent a stress concentration point.

The frame and cross members shall carry a lifetime warranty to the original purchaser. A copy of the frame warranty shall accompany the bid.

Proposals offering warranties for frames not including cross members shall not be considered.

FRAME WARRANTY

The frame and cross members shall carry a lifetime warranty to the original purchaser.

REAR TOW DEVICE

Two (2) heavy duty painted tow eyes shall be installed below the frame at the rear of the chassis. The tow eyes shall be fabricated from 0.75 inch thick #1020 ASTM-36 hot rolled steel. The inside diameter of the tow eye shall be 2.00 inches and shall have a chamfered edge. The tow eyes shall be bolted directly to the chassis frame with grade 8 bolts.

FRAME CLEAR AREA

The chassis frame shall be left clear of chassis mounted components inside or outside the frame rails within the first 30.00 inches behind the cab to allow space for OEM installed components. Cross members may be installed in the clear area if required for proper frame or driveline configuration.

FRAME PAINT

The frame shall be powder coated black prior to any attachment of components.

All powder coatings, primers and paint shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 shall not have a fail of more than ten (10) squares. The pencil hardness test per ASTM D3363 shall have a final post-curved pencil hardness of H-2H. The direct impact resistance, per ASTM D2794, shall have a direct impact resistance of 120.00 inches per pound at 2 mils. The salt spray resistance per ASTM B-117-97 shall pass 500 hours of salt spray test. The applied process shall allow the application of other products over it and still maintain or exceed the 500 hours salt spray test.

Wharton Fire Department

Heavy Rescue Specification

SVI

Any proposals offering painted frame with variations from the above process shall not be accepted. The film thickness of vendor supplied parts shall also be sufficient to meet the performance standards as stated above.

FRONT BUMPER

The cab shall include a five (5) piece, structural channel front bumper. The bumper shall be constructed of ASTM A-36 steel; the bumper shall then be painted. The bumper shall include a .38 thick structural steel channel which shall be 12.00 inches high and 101.00 inch wide, with angled front corners.

FRONT BUMPER EXTENSION LENGTH

The front bumper shall be extended 28.00 inches ahead of the cab.

FRONT BUMPER EXTENSION WIDTH

The front bumper extension shall include an overall width of 34.25 inches.

FRONT BUMPER PAINT

The front bumper shall include a finish topcoat painted the same as the lower cab color.

AIR HORN

The front bumper shall include two (2) Hadley brand E-Tone air horns which shall measure 24.00 inches long with a 6.00 inch round flare. The air horn shall be a trumpet style and shall include a chrome finish on the inside and a black painted finish on the outside of the trumpet.

AIR HORN LOCATION

The air horns shall be recess mounted in the front bumper face, one (1) on the driver side of the bumper in the inboard position relative to the left hand frame rail and one (1) on the officer side of the bumper in the inboard position relative to the right hand frame rail.

AIR HORN RESERVOIR

Wharton Fire Department

Heavy Rescue Specification

SVI

One (1) air tank, with a 1200 cubic inch reservoir, shall be installed on the chassis to act as a supply tank for operating air horns. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

ELECTRONIC SIREN SPEAKER

The bumper shall include two (2) Cast Products Inc. model SA4301, 100 watt speaker which shall be recess mounted within the bumper fascia. The speaker shall include a flat mounting flange and be chrome in color.

ELECTRONIC SIREN SPEAKER LOCATION

The speakers shall be located one (1) on the drivers side and one (1) on the officers side of the bumper fascia, outboard of the frame rails.

FRONT BUMPER TOW HOOKS

Two (2) heavy duty chrome plated tow hooks shall be installed below the front bumper, rearward position and bolted directly to the chassis frame with grade 8.00 bolts.

CAB TILT SYSTEM

The entire cab shall be capable of tilting 45 degrees to allow for easy maintenance of the engine and transmission.

The electric-over-hydraulic lift system shall include an ignition interlock and red cab lock down indicator lamp on the tilt control which shall illuminate when holding the "Down" button to indicate safe road operation.

It shall be necessary to activate the master battery switch and set the parking brake in order to tilt the cab. As a third precaution the ignition switch must be turned off to complete the cab tilt interlock safety circuit.

Two (2) spring-loaded hydraulic hold down hooks located outboard of the frame shall be installed to hold the cab securely to the frame. Once the hold-down hooks are set in place, it shall take the application of pressure from the hydraulic cab tilt lift pump to release the hooks.

Two (2) cab tilt cylinders shall be provided with velocity fuses in each cylinder port. The cab tilt pivots shall be 1.90" ball and be anchored to frame brackets with 1.25" diameter studs.

A steel safety channel assembly shall be installed on the right side cab lift cylinder to prevent accidental cab lowering. The safety channel assembly shall fall over the lift cylinder when the cab is in the fully tilted position. A cable release system shall also be provided to retract the safety channel assembly from the lift cylinder to allow the lowering of the cab.

CAB TILT AUXILIARY PUMP

Wharton Fire Department

Heavy Rescue Specification

SVI #

A manual cab tilt pump module shall be attached to the rear surface of the driver side battery box.

Wharton Fire Department

Heavy Rescue Specification

SVI

CAB TILT CONTROL RECEPTACLE

The cab tilt shall include a receptacle which shall be temporarily located on the right hand chassis rail rear of the cab to provide a place to plug in the cab tilt remote control pendant. The tilt pump shall include 8.00 feet of cable with a 6-pin Deutsch connector that includes a cap. The remote control pendant shall also include 20.00 feet of cable which also includes a mating connector.

CAB WINDSHIELD

The cab windshield shall have a surface area of 2908.00 square inches and be of a two (2) piece wraparound design for maximum visibility.

The distance from the driver and officer to the windshield shall be a minimum of 42.00 inches at the furthest seated position. This distance shall ensure the safety of the driver and officer from intruding objects in the unlikely event of a head on collision.

The glass utilized for the windshield a standard automotive tint. The left and right windshield shall be fully interchangeable thereby minimizing stocking and maintenance costs. All proposals offering windshields not in compliance with the minimum measurement of surface area stated above and are not fully interchangeable shall not be considered.

GLASS FRONT DOOR

The front cab doors shall include a window which is 27.00 inches in width X 26.00 inches in height. These windows shall have the capability to roll down completely into the door housing. This shall be accomplished manually utilizing a crank style handle on the inside of the door.

There shall be an irregular shaped fixed window which shall measure 2.50 inches wide at the top, 8.00 inches wide at the bottom X 26.00 inches in height, more commonly known as "cozy glass" ahead of the front door roll down windows.

The windows shall be mounted within the frame of the front doors trimmed with a black anodized ring on the exterior.

GLASS TINT FRONT DOOR

The windows located in the left and right front doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS REAR DOOR RH

The rear right hand side door shall include a window which is 27.00 inches in width X 26.00 inches in height. This window shall roll up and down manually utilizing a crank style handle on the inside of the door.

Wharton Fire Department

Heavy Rescue Specification

SVI

GLASS TINT REAR DOOR RH

The window located in the right hand side rear window shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS REAR DOOR LH

The rear left hand side door shall include a window which is 27.00 inches in width X 26.00 inches in height. This window shall roll up and down manually utilizing a crank style handle on the inside of the door.

GLASS TINT REAR DOOR LH

The window located in the left hand side rear door shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS SIDE MID RH

The cab shall include a window on the officers side behind the front and ahead of the crew doors which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

GLASS TINT SIDE MID RH

The window located on the right hand side of the cab between the front and rear doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS SIDE MID LH

The cab shall include a window on the drivers side behind the front door and ahead of the crew door and above the wheel well which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

Wharton Fire Department

Heavy Rescue Specification

SVI

GLASS TINT SIDE MID LH

The window located on the left hand side of the cab between the front and rear doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS UPPER SIDE FRONT

The raised roof on the driver and officer sides of the cab shall include a window which is 6.00 inches wide X 14.00 inches high. These windows shall be fixed within this space. These windows shall be in the shape of a right angle and be mounted in a black rubberized frame.

GLASS TINT UPPER SIDE FRONT

The windows located in the upper section on the left and right side towards the front of the cab shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS UPPER SIDE MID

The middle section of the raised roof on the driver and officer sides of the cab shall include a window in the middle of the cab which is 16.00 inches wide X 14.00 inches high. These windows shall be fixed within this space. These windows shall be in the shape of a right angle and be mounted in a black rubberized frame.

GLASS TINT UPPER SIDE MID

The windows located in the upper section on each side in the middle of the cab shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS UPPER SIDE REAR DOOR

The upper portion on the rear door of the raised roof cab shall include a window which is 27.00 inches wide X 14.00 inches high on the driver and officer sides. These windows shall be fixed within this space. These windows shall be rectangular in shape and be mounted in a black rubberized frame.

Wharton Fire Department

Heavy Rescue Specification

SVI

GLASS TINT UPPER SIDE REAR DOOR

The window located in the upper section on the crew doors of the cab shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

CLIMATE CONTROL

The cab shall include a 57,600 BTU @ 425 CFM front overhead heater/defroster which shall be provided and installed above the windshield between the sun visors. The temperature and blower controls shall be located on the heater/defroster unit.

The cab shall also include a combination heater air-conditioning unit mounted on the engine tunnel. This unit shall offer eight (8) adjustable louvers, (4 forward facing , four rearward facing) a temperature control valve and two (2) blowers offering three (3) speeds which shall be capable of circulating 550 cubic feet of air per minute. The unit shall be rated for 36,000 BTU of cooling and 45,000 BTU of heating. The temperature and blower controls shall be located on the heater/air conditioning unit.

All auxiliary heating units (if optionally equipped) shall be plumbed in series independent of the heater/defroster system with one (1) seasonal shut-off valve at the front corner on the officer side of the cab.

The air conditioning system shall be capable of lowering the cab interior temperature from 100 degrees to 70 degrees within thirty minutes, with a relative humidity of sixty percent.

The air conditioner lines shall be a mixture of custom bent zinc coated steel fittings and Aero-quip GH 134 flexible hose with Aero-Quip EZ-Clip fittings.

CLIMATE CONTROL ACTIVATION

The heating controls, and air conditioning if included, shall be located on the Vista screen as well as on the climate control unit.

A/C CONDENSER LOCATION

A roof mounted A/C condenser shall be installed centered on cab forward of raised roof against the slope rise.

A/C COMPRESSOR

The air-conditioning compressor shall be a belt driven, engine mounted, open type compressor that shall be capable of producing a minimum of 13000 BTU at 1500 engine RPMs. The compressor shall utilize R-134A refrigerant and PAG oil.

Wharton Fire Department

Heavy Rescue Specification

SVI

CAB CIRCULATION FANS FRONT

The cab shall include two (2) individually switched all metal construction 6.00 inch windshield defogger fans which shall be installed in the front cab corners.

CAB CIRCULATION FANS REAR

The cab shall include two (2) individually switched all metal construction 6.00 inch window defogger fans which shall be installed in the upper rear cab corners as far outboard as possible.

CAB INSULATION

The cab ceiling and walls shall include 1.00 inch thick foam insulation. The insulation shall include a foil facing which includes grid reinforcement. The insulation shall act as a barrier absorbing noise as well as assisting in sustaining the desired climate within the cab interior.

UNDER CAB INSULATION

The underside of the cab tunnel surrounding the engine shall be lined with foam insulation, engineered for application inside diesel engine compartments.

The foam insulation shall measure .56 inch thick including a 1.0#/sf PVC barrier and a moisture and heat reflective foil backing, reinforced with fiberglass strands. The foil surface acts as protection against moisture and other contaminants.

The insulation shall act as a noise barrier, absorbing noise thus keeping the decibel level in the cab well within NFPA recommendations. And as an additional benefit, the insulation shall assist in sustaining the desired temperature within the cab interior.

The insulation shall be held in place by 3 mils of acrylic pressure sensitive adhesive and aluminum pins with hard hat, hold in place fastening heads.

The foam shall meet or exceed MVSS 302 flammability test.

The foam shall be cut precisely to fit each section and sealed for additional heat and sound deflection.

INTERIOR TRIM FLOOR MAT

The floor of the cab shall be covered with a multi-layer mat consisting of 0.25 inch sound absorbing closed cell foam and a 0.06 inch non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive with aluminum corner trim. All exposed seams shall be sealed with a silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention.

Wharton Fire Department

Heavy Rescue Specification

SVI

INTERIOR TRIM VINYL

The cab interior shall include trim on the front and rear crew ceiling, the cab walls and the rear wall of the cab. The trim shall be constructed of insulated vinyl over a hard board backing. The material shall be securely fastened to the interior of the cab utilizing snap style fasteners with a decorative fastener for a more appealing appearance.

HEADER TRIM

The cab interior shall include a header over the driver and officer dash which shall be constructed of 5052-H32 Marine Grade, .090 of an inch thick, one hundred percent primary aluminum plate. The aluminum shall be painted with Zolotone in the same color as the remainder of the cab. The header shall include a drop down panel with a flush push button style latch. The header shall include a cut out to accommodate the sun visors. There shall be two openings covered in heavy duty grating for the accommodation of speakers.

INTERIOR TRIM SUN VISOR

The header shall include two (2) 7.00 inches high X 18.00 inches wide impact resistant, transparent acrylic polycarbonate sun visors with a smoke gray tint shall be provided and installed on the header above the driver and officer.

The see thru visors are designed for maximum flexibility of positioning utilizing an arm with virtually unlimited adjustability with 13.50 inch long lateral travel of the tinted visor at the end of the arm which can be locked in place by a thumbscrew.

The visors are easily adjusted and can be placed into a chosen position with one hand. The sun visors will help protect vehicle occupants from solar glare without obscuring their vision.

TRIM LH DASH

The left hand dash shall be a one (1) piece durable vacuum formed ABS composite housing which shall be custom molded for a perfect fit around the instrument panel and the lower control panels to the left and right of the steering column.

TRIM CENTER DASH

The main center dash area shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick, one hundred percent primary aluminum plate.

Wharton Fire Department

Heavy Rescue Specification

SVI

TRIM RH DASH

The right hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick, one hundred percent primary aluminum plate and shall include a glove compartment with a hinged door and a Mobile Data Terminal (MDT) provision. The glove compartment size will measure 14.00 inches wide X 6.38 inches high X 5.88 inches deep. The MDT provision shall be provided above the glove compartment, recessed 3.00 inches below the surface of the dash and measure 16.00 inches wide X 14.00 inches deep.

ENGINE TUNNEL TRIM

The cab engine tunnel shall be covered with .44 of an inch thick multi-layer mat consisting of .25 inch closed cell foam, .13 of an inch thick rubber and .06 inch thick non-slip pebble grain.

POWER POINT DASH MOUNT

The cab interior shall include two (2) each 12 volt cigarette lighter type receptacle in the center cab dash as a dedicated power source panel for any additional portable or mobile items. The receptacles shall be wired to be hot at all times.

STEP TRIM

The cab steps shall include Grip Strut® metal grating on the first step, the step closest to the ground. The step shall include a frame which is integral with the construction of the cab for rigidity and strength. The metal grating shall allow water and other debris to flow through rather than becoming packed under the step. The entire middle step shall be integral with the cab in construction and shall be trimmed in an adhesive back grit material adding slip resistance to the painted step.

INTERIOR DOOR TRIM

The doors of the cab shall include an aluminum plate the same weight and grade as the cab on the interior of the door. The aluminum shall be then painted.

DOOR TRIM CUSTOMER NAMEPLATE

The interior door trim on the front doors shall include a customer nameplate which states the vehicle was custom built for their Department.

Wharton Fire Department

Heavy Rescue Specification

SVI

CAB DOOR TRIM REFLECTIVE

In accordance with the current standards of NFPA, the body builder shall provide 96.00 square inches of reflective material on the interior of each cab door.

INTERIOR GRAB HANDLE "A" PILLAR

A rubber covered 11.00 inch grab handle shall be provided on the inside of the cab on the hinge post at the driver and officer doors. The handle shall assist personnel in exiting and entering the cab.

INTERIOR GRAB HANDLE FRONT DOOR

Each front door shall include one (1) ergonomically contoured 9.00 inch cast aluminum handle mounted horizontally on the interior door panels. The handles shall feature a textured black powder coat finish and provide ease of access and exiting the cab.

INTERIOR GRAB HANDLE REAR DOOR

A black powder coated cast aluminum assist handle shall be provided on the inside of each rear crew door the full width of the door below the window glass and shall measure 30 inches in length. The handle shall assist personnel in exiting and entering the cab.

INTERIOR FLOOR MAT COLOR

The cab interior floor mat shall be gray in color.

INTERIOR TRIM VINYL COLOR

The cab interior vinyl trim surfaces shall be gray in color.

INTERIOR ABS TRIM COLOR

The cab interior vacuum formed ABS composite trim surfaces shall be gray in color.

CAB PAINT INTERIOR

The interior metal surfaces shall be painted with a Zolatone #20-72 silver gray texture finish.

Wharton Fire Department

Heavy Rescue Specification

SVI

CAB PAINT INTERIOR DOOR TRIM

The inner door panel surfaces shall be painted with a Zolatone #20-72 silver gray texture finish.

DASH PANEL GROUP

The main center dash area shall include three (3) removable panels located one (1) to the right of the driver position, one (1) in the center of the dash and one (1) to the left of the officer position. The center panel shall be within comfortable reach of both the driver and officer.

SWITCHES CENTER PANEL

The center dash panel shall include six (6) switch positions in the upper left portion of the panel.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SWITCHES LEFT PANEL

The left dash panel shall include one (1) wiper switch which shall be located in the left hand side of the panel.

SWITCHES RIGHT PANEL

The right dash panel shall include no rocker switches or legends.

SWITCH PANEL IGNITION

The vehicle shall be equipped with a keyless ignition and master, with an "Off/ On" and a two switch for "Off/ Start".

SEAT BELT WARNING

A Weldon seat belt warning system, integrated with the Vehicle Data Recorder system, shall be installed for each seat within the chassis. The system shall provide visual and audible warning when any seat is occupied (sixty pounds minimum), the corresponding seat belt remains unfastened, and the park brake is released.

Wharton Fire Department

Heavy Rescue Specification

SVI

Once activated, the visual and audible indicators shall remain active until all occupied seats have the seat belts fastened. The dash shall include a display on the Weldon Vista screen(s) indicating the occupancy of each seat.

SEAT MATERIAL

The seats shall include a covering of high strength, wear resistant fabric made of durable ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids.

SEAT COLOR

All seats supplied on the chassis shall be gray in color. This material shall be semi-resistant to UV rays and from being saturated or contaminated by fluids.

WHARTON VOLUNTEER FIRE DEPARTMENT'S SEAT BACK LOGO

The seat back shall include the Wharton Volunteer Fire Department's logo. The logo shall be centered on the standard headrest of the seat back and on the left side of a split headrest.

SEAT DRIVER

The driver's seat shall be an H.O. Bostrom Firefighter Sierra model seat. The seat shall feature eight (8) way electric positioning. The eight (8) positions shall include up and down, fore and aft and front and rear tilt. The seat shall also feature integral springs to isolate shock.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a red, three-point shoulder harness with the lap belt, automatic retractor and buckle as an integral part of the seat assembly.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 37.00 inches measured with the seat height adjustment raised to the upper limit of its travel.

This model of seat shall have successfully completed the static load tests by FMVSS 207, 209, 210 and 302 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK DRIVER

The driver's seat shall include a standard seat back incorporating the all belts to seat feature (ABTS). The seat back shall feature a contoured, adjustable head rest.

Wharton Fire Department

Heavy Rescue Specification

SVI #

Wharton Fire Department

Heavy Rescue Specification

SVI

SEAT OFFICER

The officer's seat shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion. The seat shall be mounted in a fixed position.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a red, three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 37.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK OFFICER

The officers seat shall include a standard seat back incorporating the all belts to seat feature (ABTS). The seat back shall feature a contoured, adjustable head rest.

POWER SEAT WIRING

The power seat or seats installed in the cab shall be wired directly to battery power.

SEAT REAR FACING OUTER LOCATION

The crew area shall include two (2) rear facing crew seats, which include one (1) located directly behind the driver seat and one (1) located directly behind the officer seat.

Wharton Fire Department

Heavy Rescue Specification

SVI

SEAT CREW REAR FACING OUTER

The crew area shall include a seat in the rear facing outboard position which shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion. The seat shall be mounted in a fixed position.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a red, three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 37.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK REAR FACING OUTER

The rear facing outer seat(s) shall include a standard seat back incorporating the all belts to seat feature (ABTS). The seat back shall feature a contoured head rest.

SEAT MOUNTING REAR FACING OUTER

The rear facing outer seat shall be mounted facing the rear of the cab.

SEAT BELT ORIENTATION CREW

The crew position seat belts shall follow the standard orientation which extends from the outboard shoulder extending to the inboard hip.

SEAT FORWARD FACING CENTER LOCATION

The crew area shall include two (2) forward facing center crew seats with both located at the center of the rear wall.

Wharton Fire Department

Heavy Rescue Specification

SVI

SEAT CREW FORWARD FACING CENTER

The crew area shall include a seat in the forward facing center position which shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion. The seat shall be mounted in a fixed position.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a red, three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 37.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK FORWARD FACING CENTER

The crew area seating shall include a seat back in the rear facing center position which shall be comprised of a standard seat back. The seat back shall feature an all belts to seat (ABTS) style safety restraint. The ABTS feature shall include a red, three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The seat back shall feature a contoured, adjustable head rest.

SEAT MOUNTING FORWARD FACING CENTER

The forward facing center seats shall be installed facing the front of the cab.

SEAT FRAME FORWARD FACING

The forward facing center seating positions shall include an enclosed seat frame which is located and installed on the rear wall. There shall be one (1) access point to this storage area via the front of the seat frame. The seat frame shall measure 42.38 inches wide X 12.38 inches high X 22.00 inches deep and shall be fully open offering storage within this area. The seat frame shall be constructed of 5052-H32 Marine Grade, .190 inch thick, 100 percent primary smooth aluminum plate. The seat box shall be painted with the same color as the remaining interior.

Wharton Fire Department

Heavy Rescue Specification

SVI

SEAT FRAME FORWARD FACING STORAGE ACCESS

There shall be one (1) access point to the storage area centered on the front of the seat frame. This access point shall be covered by a hinged door which measures 41.75 inches wide X 8.63 inches high to allow access for storage in the seat box. The doors and the forward facing seat panel shall be painted the same as the interior of the cab.

CAB FRONT UNDERSEAT STORAGE ACCESS

The left and right front under seat storage areas shall each have a solid aluminum hinged door with a non-locking latch. The doors shall be painted to match the interior metal surfaces of the cab.

WINDSHIELD WIPER SYSTEM

The cab shall include a parallel arm wiper system which shall clear the windshield of water, ice and debris. There shall be two (2) windshield wipers, one (1) for the driver and one (1) for the officer, which shall be affixed to a rod style arm. The system shall include dual motors which shall initiate the arms in which both the driver and officer windshield wipers are attached, initiating a back and forth motion for each wiper. The wiper motors shall be activated by an intermittent wiper control located within easy reach of the drivers position.

ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR

The windshield washer fluid level shall be monitored electronically and shall send a signal to activate a light in the instrument panel when levels fall below normal.

CAB DOOR HARDWARE

The cab entry doors shall be equipped with exterior pull handles, suitable for use while wearing firefighter gloves. The handles shall be aluminum with a polished chrome plated finish. The exterior pull handles shall include a scuff plate behind the handle constructed of polished stainless steel. All doors shall be keyed alike and designed to prevent accidental lockout.

The interior latches shall be black flush paddle type, which are incorporated into an upper door panel.

DOOR LOCKS

The entry doors shall include an independent manual door lock actuated through a toggle switch located on the interior of the cab door near the paddle handle or by using a Trimark key through the exterior of the door.

Wharton Fire Department

Heavy Rescue Specification

SVI

DOOR LOCK LH REAR CAB COMPARTMENT

The driver side rear compartment shall feature a manual door lock.

DOOR LOCK RH REAR CAB COMPARTMENT

The officer side rear compartment shall feature a manual door lock.

GRAB HANDLES

The cab shall include one (1) each 18.00 inch knurled, anti-slip, one-piece exterior assist handle behind each cab door. The assist handle shall be made of 14 gauge 304- stainless steel and be 1.25 inch diameter to enable non-slip assistance with a gloved hand.

REARVIEW MIRROR

Ramco model CRM-1750-3HR bus style mirrors shall be provided. The mirror heads shall be injection molded chrome plated ABS plastic and shall measure 9.50 inches wide X 17.50 inches high. The mirrors shall be mounted one (1) on each the driver and officer doors of the cab with polished die-cast aluminum arms.

The mirrors shall feature an upper convex glass, a middle flat glass, and a lower convex glass that shall all be remote controlled and heated. The mirror control switches shall be located within easy reach of the driver and a mirror heat switch shall be provided on the dash. The mirrors shall be manufactured using the finest quality non-glare glass and shall feature a rigid mounting thereby reducing vibration. The mirrors shall be corrosion free under all weather conditions.

REARVIEW MIRROR HEAT SWITCH

The heated rearview mirrors shall be controlled through a virtual button on the multiplex display.

TRIM LOWER SIDE

A stainless steel trim band, 12.00 inches high, with upper and lower black and chrome trim moldings, shall be installed on the lower exterior sides of the cab and doors. The trim shall be installed so that the top edge is even with the top of the front bumper, and shall be affixed without holes and fasteners.

Wharton Fire Department

Heavy Rescue Specification

SVI

TRIM LOWER SIDE FRONT

A stainless steel trim band, 12.00 inches high, with upper and lower black and chrome trim moldings, shall be installed on the lower exterior sides of the cab between the front bumper and the front doors. The trim shall be installed so that the top edge is even with the top of the front bumper, and shall be affixed without holes and fasteners.

CAB FENDER

Full width wheel well liners shall be installed on the extruded cab to limit road splash and enable easier cleaning. The two-piece liners shall consist of an inner liner 16.00 inches wide made of vacuum formed ABS composite and an outer fenderette 3.50 inches wide made of 14 gauge 304 polished stainless steel.

MUD FLAPS FRONT

The front wheel wells shall have mud flaps installed on them.

CAB EXTERIOR MODEL NAMEPLATE

The cab shall include custom "Metro Star" nameplates on the front driver and officer side doors.

CAB EXTERIOR FRONT & SIDE EMBLEMS

The chassis shall include three (3) chassis manufacturers emblems. There shall be one (1) installed on the front air intake grille and one (1) installed on each side of the cab above the wheel well.

IGNITION

The master starting system, ignition system shall include chrome thumb turn switch which shall be mounted on the driver side of the cab to the left of the steering wheel on the dash. Each switch will be accompanied by (1) green LED indication light which shall light when the ignition is in the "ON" position and (1) for the master battery switch when in the "ON" position. The thumb turn switches shall also be accompanied by a chrome push button which shall only operate when both the master battery and ignition thumb switches are in the "ON" position.

BATTERY

The single start electrical system shall include (6) Harris BCI 31 950 CCA batteries with a 210 minute reserve capacity and 4/0 welding type dual path starter cables per SAE J541. The cables shall have encapsulated ends with heat shrink and sealant.

Wharton Fire Department

Heavy Rescue Specification

SVI

BATTERY BOX

The batteries shall be contained within two (2) black powder coated steel battery boxes which shall be located on the driver and officer side of the chassis, securely bolted to the frame rails. The boxes shall include drain holes in the bottom for sufficient drainage of water and shall include phenolic board battery hold downs and a durable, Dry-Deck in the bottom of the tray under each battery to allow for air flow and drainage.

BATTERY CABLE

The starting system shall include cables which shall be protected by 275 degree F. minimum high temperature flame retardant loom, sealed and encapsulated at the ends with heat shrink and sealant.

BATTERY JUMPER STUD

The starting system shall include battery jumper studs. These studs shall be located in the forward most portion of the driver's side lower step. The studs shall allow the vehicle to be jump started, charged, or the cab to be raised in an emergency in the event of battery failure.

ALTERNATOR

The starting system shall include a 320 amp Leece-Neville 12 volt alternator. The alternator shall include a self-exciting integral regulator.

BATTERY CONDITIONER

A Kussmaul 35/10 battery conditioner shall be supplied. The battery conditioner shall provide a 35 amp output for the chassis batteries and a 10 amp battery saver output. The battery conditioner shall be mounted in the cab behind the driver's seat.

BATTERY CONDITIONER DISPLAY

A Kussmaul battery conditioner display shall be supplied. The battery conditioner display shall be mounted in front of the driver side door just below the windshield.

AUXILIARY AIR COMPRESSOR

Wharton Fire Department

Heavy Rescue Specification

SVI

A Kussmaul Auto Pump 120V air compressor shall be supplied. The air compressor shall be installed behind the officer's seat. The air compressor shall be plumbed to the air brake system to maintain air pressure.

ELECTRICAL INLET

A Kussmaul 20 amp super auto-eject electrical receptacle shall be installed on the drivers side of the cab ahead of the front door. It shall automatically eject the plug when the starter button is depressed.

The U.L. maximum allowable amperage draw on receptacles is generally 80% of their listed rating, for example, the 20 amp receptacle should not carry more than 16 amp continuous load. When adding the different amperage draws of the components being installed on the chassis be sure to factor in whether the components will draw a continuous load or intermittent load.

Amp Draw Reference List:

Kussmaul 1000 Charger - 3.5 Amps

Kussmaul 1200 Charger - 10 Amps

Kussmaul 35/10 Charger - 10 Amps

1000W Engine Heater - 8.33 Amps

1500W Engine Heater - 12.5 Amps

120V Air Compressor - 4.2 Amps

ELECTRICAL INLET COLOR

The Kussmaul Auto- Eject electrical inlet connection shall include a red cover.

HEADLIGHTS

The cab front shall include (4) rectangular halogen headlamps with separate high and low beams mounted in bright chrome bezels. The headlamps shall be equipped with the "Daytime Running" light feature, which shall illuminate the headlights to 80% brilliance when the ignition switch is in the "On" position and the parking brake is released.

The headlights shall be controlled via a virtual button on the Vista display.

FRONT TURN SIGNALS

The front fascia shall include two (2) Whelen model 600 4.00 inch X 6.00 inch programmable LED amber turn signals which shall be installed in the upper position over the warning lights.

HEADLIGHT LOCATION

The headlights shall be located on the front fascia of the cab directly below the front warning lights.

Wharton Fire Department

Heavy Rescue Specification

SVI

SIDE MARKER/TURN SIGNALS

The sides of the cab shall include (2) LED round side marker lights which shall be provided just behind the front cab radius corners.

MARKER AND ICC LIGHTS

In accordance with FMVSS, there shall be five (5) cab LED marker lamps designating identification, center and clearance provided. These lights shall be installed on the face of the cab within full view of other vehicles from ground level.

GROUND LIGHTS

Each door shall include incandescent NFPA compliant light heads mounted to the under side of the cab. The lights shall include a polycarbonate lens, a housing which is vibration welded and a bulb which shall be shock mounted for extended life. The ground lighting shall be activated by the opening of either door on the respective side of the cab as well as through the Vista screen.

STEP LIGHTS

The middle step located at each door shall include a NFPA compliant 4.00" round incandescent light which shall activate with the opening of the respective door.

The lights shall have 21 candle power of illumination and draw 1.5 amps.

ENGINE COMPARTMENT LIGHTS

There shall be an incandescent NFPA compliant light mounted under the engine tunnel for area work lighting on the engine. The light shall include a polycarbonate lens, a housing which is vibration welded and a bulb which shall be shock mounted for extended life.

FRONT SCENE LIGHTS

The front of the cab shall include two (2) Fire Research Focus model FCA800-H15 contour roof mount lights mounted to the brow of the cab.

Each lamp head shall have one (1) High Intensity Discharge (HID) 150 watt 12 volt bulb. The bulb will draw 12.5 amps and generate 11,250 lumens. The lamp head shall direct 50 percent of the light onto the action area while providing 50 percent to illuminate the working area. The lamp head shall be no more than 4 7/8" high by 10" wide. The lamp heads and brackets shall be powder coated white.

Wharton Fire Department

Heavy Rescue Specification

SVI

FRONT SCENE LIGHT LOCATION

There shall be two (2) scene lights mounted to the front brow of the cab in the outboard position centered over the outer front marker lights.

FRONT SCENE LIGHTS ACTIVATION

The front scene lights shall be activated by a virtual button on the MUX display.

SIDE SCENE LIGHT MODEL

The side of the cab shall include two (2) Fire Research Optimum model OPA230-H15 scene lights, one (1) each side which shall be recess mounted. The housing shall have cutout dimensions not to exceed 3 3/16" deep by 3 1/4" high by 8 11/16" wide. The lamp head shall protrude no more than 3 3/4" from the housing flange. Wiring shall extend from the bottom of the recessed housing.

Each lamp head shall have one (1) High Intensity Discharge (HID) 150 watt 12 volt bulb. The bulb shall draw 12.5 amps and generate 11,250 lumens. The lamp head shall produce a uniform beam that lights up an area 100° vertically by 150° horizontally. The lamp head and flange shall be powder coated white.

SIDE SCENE LIGHT LOCATION

The scene lighting located on the left and right sides of the cab shall be mounted in the upper rear portion of the 20.00 inch raised roof of the cab behind the rear crew doors.

SIDE SCENE ACTIVATION

The scene lighting shall be individually activated through two (2) rocker switches, one (1) per side and through the multiplex display located within the cab.

INTERIOR OVERHEAD LIGHTING

The cab shall include an incandescent dome lamp with a red and white lens located over each door. The dome lamps shall be rectangular in shape and shall measure 9.50 inches in length and approximately 5.00 inches wide including a black colored bezel. The white lamp shall be activated by its respective door when opened and via the multiplex display and both the red and white lamp shall be activated by an individual switch on the light.

A three (3) light module with dual map light shall be located in the headliner, over the engine tunnel.

Wharton Fire Department

Heavy Rescue Specification

SVI

AUXILIARY DOME LIGHT RH

The officer position shall include two (2) 7.00 inch round auxiliary dome lamp in the headliner of the cab, the lens on one (1) lamp shall be clear and the other lens shall be red in color. The lamps shall be activated by an individual switch located on the side of the lamp.

AUXILIARY DOME LIGHT MID CREW

The area within the middle of the crew cab shall include three (3) 7.00 inch dome lamps within the headliner, one clear and two red. The clear lamp shall be located in the center and the red lamps will be mounted inboard of the outer rear facing seats. The clear lamp shall be activated by the rear doors as well as an individual switch located on the side of the lamp. The red lamps shall be activated with a switch on the lamp only.

MAP LIGHTS

A Sunnex gooseneck style instrument panel map light with switch at base shall be installed on the officer side of the dash panel within easy reach.

HANDHELD SPOTLIGHTS

The officer position shall include a 12 volt Pulsar 500 hand-held spotlight which shall offer 500,000 candle power will be shipped loose.

DO NOT MOVE APPARATUS LIGHT

The front headliner of the cab shall include a red flashing light, located in the center for greatest visibility. The light shall be 6.00 inches long X 2.50 inches wide X 1.75 inches high and shall be clearly labeled "Do Not Move Apparatus". In addition to the flashing red light, an audible alarm shall be included which shall sound when a door is open and the parking brake is released.

The light and alarm shall be interlocked for activation when a cab door is not firmly closed, an apparatus cabinet door is not closed and the parking brake is released.

MASTER WARNING SWITCH

The optical warning system shall be controlled by a master switch which shall include all "ON" and all "OFF" capability via a virtual button within the MUX display. All warning lights which are "ON" when the master switch is activated shall also activate. This switch shall be clearly labeled for identification.

Wharton Fire Department

Heavy Rescue Specification

SVI

HEADLIGHT FLASHER

An alternating high beam headlamp flashing system shall be installed into the high beam headlamp circuit which shall allow the high beams to flash alternately from left to right.

Deliberate operator selection of high beams will override the flashing function until low beams are again selected. Per NFPA, these clear flashing lights will also be disabled "On Scene" when the park brake is applied.

ALTERNATING HEADLIGHT SWITCH

The flashing headlights shall be activated through a virtual button on the MUX display.

INBOARD FRONT WARNING LIGHTS

The cab front fascia shall include dual Whelen series 600 Super LED warning lights which shall offer multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be surface mounted to the front fascia of the cab within a chrome bezel in the inboard position.

INBOARD FRONT WARNING LIGHTS COLOR

The front warning lights mounted on the fascia for the inboard position shall be clear.

OUTBOARD FRONT WARNING LIGHTS

The cab front fascia shall include dual Whelen series 600 Super LED warning lights which shall offer 14 flash patterns plus a steady burn for solid colors and 20 flash patterns plus a steady burn for split colors. The lights shall be surface mounted to the front fascia of the cab within a chrome bezel in the outboard position.

OUTBOARD FRONT WARNING LIGHTS COLOR

The front warning lights mounted on the fascia for the outboard position shall be red with a clear lens.

FRONT WARNING SWITCH

The front warning lights shall be controlled through a virtual control on the MUX display. This switch shall be clearly labeled for identification.

Wharton Fire Department

Heavy Rescue Specification

SVI

INTERSECTION WARNING LIGHTS

The chassis shall include two (2) Whelen series 600 Super LED intersection warning lights, one (1) each side, which shall offer multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.

INTERSECTION WARNING LIGHTS COLOR

The intersection lights shall be red with a clear lens.

INTERSECTION WARNING LIGHTS LOCATION

The intersection lights shall be mounted in the rear position on the side of the bumper.

SIDE WARNING LIGHTS

The cab sides shall include a Whelen series 600 Super LED 4"x6" warning light, one (1) each side, which shall offer multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.

SIDE WARNING LIGHTS COLOR

The warning lights located on the side of the chassis shall be red with clear lens.

SIDE WARNING LIGHTS LOCATION

The warning lights on the side of the cab shall be mounted over the front wheel well directly over the center of the front axle.

SIDE AND INTERSECTION WARNING SWITCH

The side warning lights shall be controlled through a virtual control on the MUX display. This switch shall be clearly labeled for identification.

HORN RING SELECTOR SWITCH

A virtual button on the MUX display shall allow control to either the air horn or the electric horn from the steering wheel horn button. The electric horn shall sound by default when the selector switch is in either position which is in accordance with FMVSS requirements.

Wharton Fire Department

Heavy Rescue Specification

SVI

AIR HORN ACTIVATION

The air horn actuation shall be accomplished by the steering wheel horn button and a black push button on the switch panel. An air horn activation circuit shall be provided to the chassis harness pump panel harness connector.

BACK-UP ALARM

An ECCO model 575 backup alarm shall be installed at the rear of the chassis with an output level of not less than 107 dB. The alarm will automatically activate when the transmission is placed in reverse.

INSTRUMENTATION

An ergonomically designed instrument panel shall be provided. The gauges shall be backlit with red LED lamps. All gauges shall be driven by stepper motor movements. The instrumentation system shall be multiplexed and shall receive engine and transmission information over the J1939 data bus to reduce redundant sensors.

The instrument panel shall contain the following gauges:

One (1) electronic tachometer shall be included. The scale on the tachometer shall read from 0 to 3000 RPM.

One (1) electronic speedometer with an integral LCD odometer/ trip odometer and hour meter shall be included. The speedometer shall have a dual scale with miles per hour (MPH) as the dominant scale and kilometers per hour (KPH) on the minor scale. The speedometer scale shall read from 0 to 90 MPH (0 to 140 KPH). The odometer shall display up to 9,999,999.9 miles. The trip odometer shall display up to 9,999.9 miles. The LCD screen shall also be capable of displaying certain diagnostic functions. The hour meter shall display engine hours of operation.

One (1) three function gauge with primary system, secondary system and fuel level shall be included. The scale on the air pressure gauges shall read from 0 to 140 pounds per square inch (PSI). The air pressure scales shall be non-linear to expand the scales in the region of normal operation. A red indicator light in the gauge shall indicate a low air pressure. The scale on the fuel level gauge shall read from empty to full. A yellow indicator light shall indicate low fuel at the quarter tank level.

One (1) four function gauge with engine oil pressure, coolant temperature, transmission oil temperature and a voltmeter shall be included. The scale on the engine oil pressure gauge shall read from 0 to 140 pounds per square inch (PSI). The engine oil pressure scale shall be non-linear to expand the scale in the region of normal operation. A red indicator light in the gauge shall indicate low engine oil pressure. The scale on the coolant temperature gauge shall read from 160 to 250 degrees Fahrenheit (F). A red indicator light in the gauge shall indicate high coolant temperature. The scale on the transmission oil temperature gauge shall read from 100 to 300 degrees Fahrenheit (F). A red indicator light in the gauge shall indicate high transmission oil temperature. The scale on the voltmeter shall read from 8 to 16 volts. A red indicator light shall indicate high or low system voltage.

The instrument panel shall contain an Annunciator Module that contains the following indicator lights. All indicator lights shall contain LED lamps.

Wharton Fire Department

Heavy Rescue Specification

SVI

RED LAMPS

Stop Engine - indicates critical engine fault. (5)
Park Brake - indicates park brake is set.
Volts - indicates high or low system voltage. (4)
Low Oil Press - indicates low engine oil pressure. (4)
High Coolant Temp - indicates excessive engine coolant temperature. (4)
High Trans Temp - indicates excessive transmission oil temperature. (4)
Low Air - indicates low air pressure in either system one or system two. (4)
Low Coolant Level - indicates low engine coolant level. (1) (5)
Air Filter - indicates excessive engine air intake restriction. (5)
Brake System Fault indicates a failure in the brake system (hydraulic brake systems only). (5)
Seat Belt Indicator indicates when a seat is occupied and corresponding seat belt remains unfastened.

YELLOW LAMPS

Check Engine - indicates engine fault. (5)
Check Trans - indicates transmission fault. (5)
Wait to Start - indicates active engine air preheat cycle. (2) (5)
ABS - indicates anti-lock brake system fault. (5)
Water in Fuel - indicates presence of water in fuel filter. (1) (5)
Check Message Center indicates there is a fault message present in the LCD digital display.
SRS indicates a problem in the RollTek supplemental restraint system. (1) (5)
DPF indicates a restriction of the diesel particulate filter. (3) (5)
HEST indicates a high exhaust system temperature. (3) (5)
MIL indicates an engine emission control system fault. (3) (5)
Low Fuel indicates low fuel. (4)

GREEN LAMPS

Left and Right turn signal indicators.
Aux Brake Active - indicates secondary braking device is active. (1)
High Idle - indicates engine high idle is active. (1)
ATC indicates low wheel traction for automatic tractions control equipped vehicles, also indicates mud/snow mode is active for ATC system. (1) (5)
OK to Pump indicates the pump engage conditions have been met. (1)
Pump Engaged indicates the pump is currently in use. (1)

BLUE LAMPS

High beam indicator.

The instrumentation system shall provide a constant audible alarm for the following situations:

Low air pressure.
Low engine oil pressure.
High engine coolant temperature.
High transmission oil temperature.
Low coolant level. (1)
High or low system voltage
Critical engine fault (Stop Engine).

Wharton Fire Department

Heavy Rescue Specification

SVI

The Check Message Center icon will illuminate and a message will be displayed in the LCD screen for the following situations:

- Cab Ajar
- Low Oil Level
- Door Ajar
- Engine Communication Error
- Transmission Communication Error
- ABS Communication Error
- High Coolant Temp
- Turn Signal Reminder (turn signal left on for more than one (1) mile)
- Low Fuel
- Low Oil Pressure
- Low Coolant Level
- Low Battery Voltage
- High Battery Voltage
- Low Primary Air Pressure
- Low Secondary Air Pressure
- High Trans Temp

The instrumentation system will provide a continuous alarm for the following situations:

- Stop Engine
- Low Coolant Level (1)
- Brake System Fault
- Check Trans
- Check Engine
- ABS
- Engine Communications Error
- Transmission Communications Error
- ABS Communications Error
- Low Fuel
- Low Primary Air Pressure
- Low Secondary Air Pressure
- Low or High Battery Voltage
- High Trans Temp
- Low Oil Pressure
- High Coolant Temp

The instrumentation system will provide a 160 millisecond second alarm every 880 milliseconds for the following situations:

- Seat Belt
- Air Filter
- Water in Fuel (1)
- Cab Ajar
- Low Oil Level
- Door Ajar

The instrumentation system will provide a 160 millisecond second alarm every 5 seconds for the following situation:
Turn Signal Reminder (turn signal left on for more than one (1) mile)

Wharton Fire Department

Heavy Rescue Specification

SVI

- (1) Feature only available when optionally equipped.*
- (2) Feature only available on engines with pre-heat capability.*
- (3) Feature only on vehicles with diesel particulate filter (DPF).*
- (4) Warning light is present in gauge.*
- (5) A message in the LCD screen will also be displayed.*

RADIO

A Panasonic compact disc player with AM/FM stereo receiver, weather band and four (4) speakers shall be installed in the cab. The receiver shall be installed above the driver position. The speakers shall also be installed inside the cab with two (2) speakers recessed within the headliner of the front of the cab just behind the windshield and two (2) speakers in the upper rear corners of the cab.

RADIO ANTENNA

A small antenna shall be located on the driver side of the cab roof for AM/FM and weather band reception.

CAMERA SYSTEMS

An Audiovox Voyager heavy duty rearview camera system shall be supplied. One (1) camera with a teardrop shaped chrome plated housing shall be shipped loose for OEM installation in the body to afford the driver a clear view of the rear of the vehicle and one (1) shall be mounted on the officer side of the cab below windshield ahead of the front door at approximately the same level as the cab door handle. The cameras shall be wired to a single Weldon Vista display located on the drivers side dash. The rear camera shall activate when the transmission is placed in reverse and the right camera shall activate with the right side turn signal. Each camera shall also be activated by a button on the Vista display.

CAB EXTERIOR PROTECTION

The cab face shall have a removable plastic film installed over the painted surfaces to protect the paint finish during transport to the body manufacturer.

FIRE EXTINGUISHER

A 2.50 pound BC D.O.T approved fire extinguisher shall be shipped loose with the cab.

ROAD SAFETY KIT

The cab and chassis shall include one (1) emergency road side triangle kit.

Wharton Fire Department

Heavy Rescue Specification

SVI

DOOR KEYS

The cab and chassis shall include a total of four (4) door keys for the manual door locks.

AS BUILT WIRING DIAGRAMS

The cab and chassis shall include one (1) complete set of wiring schematics and option wiring diagrams.

WARRANTY - CAB AND CHASSIS

The chassis manufacturer shall warrant to the original purchaser the custom fire truck chassis for a period of twelve (12) months, or the first 24,000 miles, whichever occurs first. The warranty period shall commence on the date the vehicle is delivered to the end user. The warranty shall include conditional items listed in the detailed warranty document which may be provided upon request.

OPERATORS AND PARTS LIST MANUAL

There shall be two (2) chassis operator's manual which includes a parts list including wiring and air plumbing diagrams provided and shipped loose with the vehicle. All standard wiring and plumbing diagrams shall be created specifically to the chassis model.

ENGINE AND TRANSMISSION OPERATION MANUALS

There shall be two (2) sets of engine operation and maintenance manuals and two (2) sets of transmission operation manuals specific to the models ordered included with the final vehicle in the ship loose items.

ENGINE SERVICE MANUALS

There shall be one (1) set of the following Cummins ISC/ISL engine service reference manuals which shall be provided with the final vehicle.

Engine Troubleshooting and Repair Manual, part number 4021418
Electronic Control System Troubleshooting and Repair Manual, part number 4021443
Operation and Maintenance Manual, part number 4021427
Wiring Diagram, part number 3666416

Wharton Fire Department

Heavy Rescue Specification

SVI

TRANSMISSION SERVICE MANUALS

There shall be two (2) sets of the following manuals included with the chassis relative to the Allison 3000 transmission:

Allison Parts Catalog, part number PC2809EN
Allison Service Manual, part number SM2148EN
Allison Technician Manual, part number GN2055EN
Electronic Controls Troubleshooting Manual, part number TS2973EN
Mechanics Tips, part number MT3004EN

CHASSIS MODIFICATIONS

LUBRICATION AND TIRE DATA PLATE

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Pump transmission lubrication fluid . . (if applicable)
- Pump priming system fluid, if applicable . . (if applicable)
- Drive axle(s) lubrication fluid
- Air conditioning refrigerant . . (if applicable)
- Air conditioning lubrication oil . . (if applicable)
- Power steering fluid
- Cab tilt mechanism fluid . . (if applicable)
- Transfer case fluid . . (if applicable)
- Equipment rack fluid (if applicable)
- CAFS air compressor system lubricant . . (if applicable)
- Generator system lubricant . . (if applicable)
- Front tire cold pressure
- Rear tire cold pressure
- Maximum tire speed ratings

Wharton Fire Department

Heavy Rescue Specification

SVI

VEHICLE DATA PLATE

A permanent label in the driving compartment which indicates the following:

- Filter part numbers for the
 - Engine
 - Transmission
 - Air
 - Fuel
- Serial numbers for the
 - Engine
 - Transmission
- Delivered Weights of the Front and Rear Axles
- Paint Brand and Code(s)
- Sales Order Number

OVERALL HEIGHT, LENGTH DATA PLATE

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in feet and inches or in meters, the length of the completed fire apparatus in feet and inches or in meters, and the GVWR in tons or metric tons.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

ACCIDENT PREVENTION

There shall be a placard in the cab seating area which reads, "ALL OCCUPANTS MUST BE SEATED AND BELTED WHEN THE APPARATUS IS IN MOTION".

PERSONNEL CAPACITY

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

ACCIDENT PREVENTION

Wharton Fire Department

Heavy Rescue Specification

SVI

If the rear bumper is 8" deep or more, there shall be a placard on the rear face of the body, in clear sight from the ground, which reads, "WARNING - DO NOT RIDE ON STEPS OR DECK AREAS WHILE THE APPARATUS IS IN MOTION. DEATH OR SERIOUS INJURY MAY RESULT".

WEARING HELMET WARNING

A label stating "DO NOT WEAR HELMET WHILE SEATED" shall be visible from each seating location.

BUMPER GRAVEL SHIELD

The front bumper extension shall have a 3/16" NFPA compliant aluminum tread plate gravel shield. The gravel shield shall cover the full width of the front bumper to the front of the cab and the full height of the bumper on each end.

RESCUE BUMPER COMPARTMENT

The bumper extension shall have three (3) compartments. There shall be two (2) compartments outboard of the frame rail. The curbside compartment will hold one (1) low pressure air hose reel. The streetside compartment will hold an electric cord reel. There shall be one (1) compartment between the chassis frame rails. It will hold two (2) Holmatro bulkhead fittings and provided storage for two (2) loose 32' sections of Holmatro Core hose.

A single lid shall cover all three (3) compartments. The lid shall be 1/8" NFPA compliant aluminum tread plate with stainless steel hinges and single point lift/turn latches. The compartment lid shall have two (2) pneumatic spring devices, one (1) at each end.

Compartment shall have a surface mounted light near door opening that will be automatically activated when door is opened, and switched for compartment door ajar warning system provided in cab.

Rubber bumpers shall be provided as required to prevent door from hitting cab.

The following shall be located in the bumper:

Bumper: Components, Reels - Elec.

Wharton Fire Department

Heavy Rescue Specification

SVI

- One (1) Hannay ECR1616-17-18 cable reel(s) capable of storing 150' of 10/3 electric cable shall be mounted in the streetside front bumper compartment. The rewind switch for each reel shall be located adjacent to the reel it controls.

Electric reel shall be mounted in streetside bumper compartment.

- The cable reel shall be equipped with 150' of 10/3 SEOOW yellow cable, a molded plastic ball clamp, and a single heavy duty L5-30 twist-lock female plug at the end.
- One (1) Akron model EJB, cast aluminum electrical power distribution box with yellow powder coat painted finish shall be provided. The power distribution box shall include:
 - A 12" pigtail that terminates in an L5-30 configuration to match the cable on the cord reel. The outlet configuration shall include:
 - One (1) L5-20 single twist lock receptacle
 - One (1) L5-20 single twist lock receptacle
 - One (1) L5-20 single twist lock receptacle
 - One (1) L5-20 single twist lock receptacle
- One (1) EJB vertical apparatus mounting bracket - treadplate
- One (1) Hannay EF1514-17-18 low pressure air hose reel(s) capable of storing 100' of low pressure air hose. The rewind button for each reel shall be located adjacent to the reel it controls.

Air reel will be located on curbside of front bumper.

- The hose reel shall be equipped with 100' of 3/8 low pressure air hose. Molded plastic ball clamp shall be provided on the hose to stop it at the 4-way roller. The hose shall be Red in color.
- The air supply shall be from the mobile breathing air system. A reel shut-off valve, pressure regulator, and 0-150 psi gauge shall be provided on an aluminum control panel next to the air reel.
- Two (2) Holmatro CORE "straight" bulkhead fittings shall be installed in the front bumper, one (1) each in the curbside and streetside bumper compartments. The bulkhead fittings shall be dealer supplied.

(2) Holmatro bulkhead fittings will be provided to SVI by Metro Fire.

- Installation provisions for two (2) 32' "CORE" hydraulic hose pigtails that connect the hydraulic rescue pump mounted in the rescue body to the "Bulkhead" fittings located in the front bumper extension. Hoses will be dealer supplied.

Wharton Fire Department

Heavy Rescue Specification

SVI

AIR HORN(S)

The air horn(s) shall be supplied and installed by the cab/chassis manufacturer.

FRONT TOW PROVISIONS

The front tow provisions shall be supplied and installed by the cab/chassis manufacturer.

EXHAUST

The exhaust system shall be as provided by cab/chassis manufacturer. No other alternation or modifications are required.

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the apparatus or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position.

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

MUDFLAPS

There shall be rubber mudflaps furnished and installed behind each set of tires.

REAR CAB AREA LAYOUT

CAB INTERIOR CABINET - CURBSIDE ON REAR WALL

There shall be one (1) full height cabinet with roll-up doors provided in the cab interior. The cabinet shall be constructed of 1/8" smooth finish aluminum and finished with a dark gray hammer tone powder coat for a hard and durable surface. The cabinet shall be approximately 28" wide, 16" deep, and consume the area from the door to rear wall and from floor to within a few inches of the cab roof.

- There shall be one (1) OnScene Solutions LED Nightstik(s) mounted vertically inside the cabinet. The LED Nightstik(s) shall be a 54" section.
- There shall be two (2) vertically adjustable shelf/shelves in each of the above cabinets. It shall have a 1.25" lip to contain items while minimizing space used.

Wharton Fire Department

Heavy Rescue Specification

SVI

There shall be one (1) 120 volt outlet(s) located in the walk-in area of the body.

- The receptacle shall be a 4-plex, 15 amp, straight-blade (NEMA 5-15R).

CAB INTERIOR CABINET - STREETSIDE ON REAR WALL

There shall be one (1) full height cabinet with roll-up doors provided in the cab interior. The cabinet shall be constructed of 1/8" smooth finish aluminum and finished with a dark gray hammer tone powder coat for a hard and durable surface. The cabinet shall be approximately 28" wide, 16" deep, and consume the area from the door to rear wall and from floor to within a few inches of the cab roof.

- There shall be two (2) vertically adjustable shelf/shelves in each of the above cabinets. It shall have a 1.25" lip to contain items while minimizing space used.
- The receptacle shall be a 4-plex, 15 amp, straight-blade (NEMA 5-15R).
- There shall be one (1) OnScene Solutions LED Nightstik(s) mounted vertically inside the cabinet. The LED Nightstik(s) shall be a 54" section.

CENTER REAR FACING CABINET/DESK TOP

There shall be one (1) cabinet/desk top with an open front provided in the cab interior . The cabinet shall be approximately 38" wide x 20" deep x 31" high, and consume the area between the rear facing jump seats. The cabinet shall be constructed of 1/8" smooth finish aluminum and finished with a dark gray hammer tone powder coat for a hard and durable surface.

Deleted hinged doors. Adjust price!!!

- There shall be one (1) 120 volt, 20 amp, duplex straight-blade receptacle (NEMA 5-20R) outlet(s) provided on the rear face of the cabinet/desk top.
- There shall be one (1) vertically adjustable shelf/shelves in each of the above cabinets. It shall have a 1.25" lip to contain items while minimizing space used.
- There shall be one (1) 120 volt outlet strip(s) approximately 2' long with straight blade household type outlets provided on the rear top edge of the cabinet/desk top. A 15 ampere circuit breaker protection shall be provided for each strip.

CAB INTERIOR CABINET - OVERHEAD

There shall be two (2) overhead cabinet(s) provided on interior. Cabinet(s) shall be constructed of 1/8" smooth finish aluminum, and painted with a dark gray hammer tone powder coat paint finish for a hard durable surface. Each cabinet shall be approximately 14" high x 14" deep x 40" wide.

The above cabinet(s) shall have sliding clear Lexan door(s).

Wharton Fire Department

Heavy Rescue Specification

SVI

CAB COMMAND 120V INTERIOR LIGHT(S)

There shall be one (1) 120 volt, interior light fixture(s) installed above the desk/deck area under the overhead cabinet(s). Fixture shall be provided with single bulb and switch on fixture. Exact location to be determined at the preconstruction meeting.

FUEL FILL

There shall be one (1) Cast Products fuel fill door located in the streetside exterior wheel well panel, behind the rear axle. The fill door shall have a spring-loaded hinged door and a permanent label with the text "DIESEL FUEL ONLY".

BODY TYPE

BODY DESIGN

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the WHARTON VOLUNTEER FIRE DEPARTMENT to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the WHARTON VOLUNTEER FIRE DEPARTMENT from such repair and shall NOT be used.

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

Wharton Fire Department

Heavy Rescue Specification

SVI

EXTERIOR ALUMINUM BODY

The fabrication of the body shall be constructed from aluminum 3003H-14 alloy smooth plate. This shall include compartment front panel, vertical side sheets, side upper rollover panels, rear panels and compartment door frames.

The body compartment floors and exterior panels shall be constructed with not less than 3/16" (.187) aluminum 3003H-14 smooth plate. Interior compartment dividing walls shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Lighter gauge sheet metal will not be acceptable in these areas.

The door side frame openings shall be formed "C" channel design. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be preformed, then positioned in body and welded into final position.

Compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

All exterior seams in sheet metal below frame, and around the rear wheel well area shall be welded continuous to prevent moisture from entering compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel bolts, nuts, and sheet metal screws shall be used in mounting exterior trim, hardware and equipment.

Exterior compartments shall have louvers in lower back wall of compartment for ventilation.

ROOF CONSTRUCTION

The roof shall be integral with the body and shall be all welded construction. The roof shall be reinforced with 2" x 2" tubing running the full width of the body. All seams in the roof area shall be welded prior to paint to prevent entry of moisture.

Wharton Fire Department

Heavy Rescue Specification

SVI

BODY SUBFRAME

To assure proper body alignment and clearance, the body subframe shall be constructed directly on the chassis.

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.

The body subframe shall be constructed from 6061T6 aluminum alloy tubing. Subframe shall consist of two (2) 2" x 6" x 1/4" aluminum tubes, the same width as the chassis frame rails, NO EXCEPTION. Welded to this tubing shall be crossmembers of 2" x 6" x 1/4" aluminum. These crossmembers shall extend the full width of the body to support the compartments. Crossmembers shall be located at front and rear of the body, below compartment divider walls, and in front and rear of wheel well opening. Additional aluminum crossmembers shall be located as necessary to support walkway or heavy equipment.

To form the frame, the tubing shall be beveled and welded at each joint using 5356 aluminum alloy welding wire.

BODY MOUNTING

The body subframe shall be fastened to the chassis frame with a minimum of eight (8) spring loaded body mounts. Each mount shall be configured using a two-piece encapsulated slide bracket. The two (2) brackets shall be fabricated of heavy duty 1/4" thick steel and shall have a powder coat finish to prevent any corrosion. Each mounting assembly shall utilize two (2) 3/4" diameter x 6" long grade 8 bolts and two (2) heavy duty springs. The assembly design shall allow the body and subframe to act as one (1) component, separate from the chassis. As the chassis frame twists under driving conditions, the spring mounting system shall eliminate any stress from being transferred into the body. The spring loaded body mounts shall also prevent frame side rail or body damage caused by unevenly distributed stress and strains due to load and chassis movement.

Body mountings that do not allow relief from chassis movement will not be acceptable.

10" REAR STEP BUMPER

The full width rear bumper shall be constructed from 2" x 2" x 1/4" aluminum tubing frame and covered with 3/16" NFPA compliant aluminum tread plate. The bumper shall extend from the rear vertical body panel 10" and provide a rear step with a minimum of 1/2" space at body for water drainage.

REAR TOW EYES

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the body subframe, below the apparatus body. The tow eyes shall be fabricated from steel plate and shall have a black powder coat finish.

Wharton Fire Department

Heavy Rescue Specification

SVI

TRAILER HITCH

A Class III, 7,500 lbs. weight carrying capacity (gross trailer weight) rear hitch receiver shall be provided below the rear bumper. The receiver shall be attached to the apparatus body frame.

The hitch shall be complete with a 2" square receiver. Without the use of a "weight distribution" ball hitch the Class III receiver shall have a capacity of 5,000 lbs. gross trailer weight.

For hydraulic brake equipped or electric brake equipped trailer towing capability, a primary electrical receptacle shall be provided near the hitch point and shall match the umbilical cable specified.

An auxiliary electrical receptacle shall be provided near the hitch point and shall match the umbilical cable specified for optical warning lights.

A label shall be provided in a location in which it is visible to an operator making trailer connections. The label shall state the maximum GVWR and tongue weight of the trailer that can be safely towed with the hitch system.

Two (2) safety chain attachment points shall be provided near the hitch point for hitches designed to use safety chains, each designed with an ultimate strength of not less than the maximum GVWR specified on label.

GROUND LIGHTS

Two (2) OnScene Solutions 9" LED Nightstik ground lights shall be mounted below the rear bumper.

WHEEL WELL EXTERIOR PANEL

The exterior panel of the body wheel well enclosure shall be constructed from 1/8" aluminum smooth plate.

DIEFORMED BEADED EDGE BODY FENDERS

A die formed beaded edge shall be provided along the radius of the wheel well opening for a finished appearance.

WHEEL WELL LINERS

The wheel wells shall be provided with an easily removable polymer, circular inner fender liner. The inner liner shall be bolted to the wheel well with stainless steel bolts and spaced away from the wheel well so the liner will not accumulate dirt or water.

Wharton Fire Department

Heavy Rescue Specification

SVI

SCBA BOTTLE COMPARTMENTS

There shall be three (3) SCBA compartments located adjacent to the rear wheels. There shall be two (2) on the curbside and one (1) on the streetside of the apparatus body. Each compartment shall have a Cast Products aluminum door assembly with a positive catch latch. The compartment shall allow the storage of SCBA bottles up to 7-3/4" in diameter.

ALUMINUM BODY PAINT SPECIFICATIONS

The final finishing of this apparatus shall be to fire apparatus standards exhibiting excellent gloss, durability, and color retention properties. Commercial type paint finish shall not be acceptable. A warranty sheet with all conditions shall be provided with completed apparatus.

All flush mounted lights, drip moldings, windows, and other equipment shall be fitted to the apparatus prior to paint finishing, then removed to assure full paint coverage under all equipment.

The apparatus body shall be sanded smooth on all exterior surfaces to assure removal of all imperfections in metal surface and to assure good adhesion of paint to body. All metal surfaces shall be chemically cleaned and metal etched with acid cleaner prior to paint.

The body shall receive a corrosion resistant epoxy primer coat. The primer coat shall be lightly sanded to assure a smooth surface for a final coat. All seams and corners in sheet metal on interior and exterior shall be sealed with automotive type caulk prior to painting finish coat.

Prior to the assembly and reinstallation of lights, handrails, door hardware, and any miscellaneous items, an isolation tape, or gasket material must be used to prevent damage to the finish painted surfaces.

Touch-up paint shall be provided with completed apparatus.

PAINT FINISH - SINGLE COLOR

The apparatus body shall be painted single color with PPG Delfleet paint with clear coat for a high gloss, hard finish.

- Paint Color: Match cab/chassis supplied paint color.

The painted body shall be finished with a clear coat of acrylic urethane for paint protection and maximum quality finish.

PAINT WARRANTY

The apparatus shall be provided with a ten (10) year non-prorated warranty to the original Owner. Warranty is provided by PPG Inc. A "PPG Warranty" sheet with all conditions shall be provided with the delivered apparatus.

Wharton Fire Department

Heavy Rescue Specification

SVI

BODY UNDERCOATING

The entire underside of apparatus body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas to retard corrosion under the apparatus.

UNDERCOAT WARRANTY

The undercoating shall be provided with a warranty by its manufacturer for the lifetime of the vehicle. The re-spray warranty shall be transferable between vehicle owners. Should the coating applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

COMPARTMENT INTERIOR FINISH

The compartment interior (below exterior drip rail line) shall be treated with phosphoric acid and epoxy primer will be applied 1.0 mil thick. All body seams will be caulked with urethane seam sealer and painted with an epoxy primer and (Two) 2 coats of textured Zolatone paint. Zolatone catalysts will be added to the Zolatone to help in resisting moisture and provide a more durable finish. Paint color shall be gray.

ROOF COMPARTMENT INTERIOR FINISH

The roof compartment shall be treated with phosphoric acid and epoxy primer will be applied 1.0 mil thick. All body seams will be caulked with urethane seam sealer and painted with an epoxy primer and (Two) 2 coats of textured Zolatone paint. Zolatone catalysts will be added to the Zolatone to help in resisting moisture and provide a more durable finish. Paint color shall be gray.

REFLECTIVE STRIPE AND LETTERING

The apparatus will be striped and lettered as per the WHARTON VOLUNTEER FIRE DEPARTMENT's instructions. The design and layout of the striping and lettering will be determined at the pre-construction meeting.

All retroreflective materials shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

All retroreflective materials used that are colors not listed in ASTM D 4956, Section 6.1.1, shall have a minimum coefficient of retroreflection of 10 with observation angle of 0.2 degrees and entrance angle of -4 degrees.

Any printed or processed retroreflective film construction used shall conform to the standards required of an integral colored film as specified in ASTM D 4956, Section 6.1.1.

Wharton Fire Department

Heavy Rescue Specification

SVI

EXTERIOR COMPARTMENT DOORS

ROLL-UP DOOR CONSTRUCTION - ROBINSON (ROM)

The apparatus shall be equipped with Robinson Series III roll-up exterior compartment doors. Robinson roll-up doors shall be complete with the following features;

- Doors shall be front roll with drum positioned at upper front portion of compartment to afford maximum clearances and head room for mounting equipment to ceiling of compartment
- There shall be a non-abrasive side brush seals
- Magnetic door ajar system must be integrated in lift bar handle and the retainer block to signal open door. No mechanical switches or switches interior to the compartment shall be used
- Every slat must have interlocking end shoes to prevent slat from moving side-to-side and binding the door
- Between each slat must be a co-extruded PVC inner seal to prevent metal-to-metal contact and to repel moisture. This inner seal is not visible to detract from appearance of door
- Slat are to have interlocking joints with a folding locking flange to provide security and prevent penetration by sharp objects
- Slat to be double-wall extrusion 1.366" high by .315" thick. Exterior surface to be flat and interior surface to be concave to prevent loose equipment from interfering with door operation
- Latch system to be a full width one piece lift bar operable by one (1) hand
- A 2" wide finger pull integrated into the bottom rail extrusion for easy one (1) hand opening and closing
- Clip system that connects the curtain slats to the operator drum which allows for easy tension adjustment without tools
- Each roll-up door shall have a 4" diameter counterbalance operator drum to assist in lifting the door.
- Track shall be one-piece aluminum that has an attaching flange and finishing flange incorporated into its design
- Drip rail will have specially designed seal that prevents the seal from scratching the door
- Bottom rail extrusion must have smooth back to prevent loose equipment from jamming the door
- Bottom rail to have "V" shaped double seal to prevent water and debris from entering the compartment
- Standard replacement parts to be shipped from the United States and available in as little as 48 hours

Each shutter door shall decrease the compartment door frame opening approximately 2.00" in width and approximately 4.50" in height for the bottom section of door assembly.

EXTERIOR ROLL-UP DOOR FINISH - SATIN

The roll-up doors shall have a satin aluminum finish on the door slats and the door trim components.

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface .

Wharton Fire Department

Heavy Rescue Specification

SVI

BODY HEIGHT MEASUREMENTS

The vertical body dimensions shall be as follows:

AHEAD OF REAR AXLE

	<u>Description</u>	<u>Dimension</u>
A	Bottom of Subframe to Top of Body	84.0"
B	Bottom of Subframe to Bottom of Body	25.0"
C	Vertical Door Opening	
	-with roll-up door	67.5"
	-with hinged door	71.5"

ABOVE REAR AXLE

	<u>Description</u>	<u>Dimension</u>
D	Vertical Door Opening - Above Rear Wheel	
	-with roll-up door	34.0"
	-with hinged door	37.0"

BEHIND REAR AXLE

	<u>Description</u>	<u>Dimension</u>
E	Bottom of Subframe to Bottom of Body	20.0"
F	Vertical Door Opening	
	-with roll-up door	62.0"
	-with hinged door	66.0"

GENERAL

	<u>Description</u>	<u>Dimension</u>
G	Bottom of Drip Rail to Top of Body	33.5"

(Dimensions are generic and subject to change during the actual design process)

Wharton Fire Department

Heavy Rescue Specification

SVI

UPPER BODY COMPARTMENTS

The forward transverse compartment shall be approximately 90.0" wide x 26.0" long x 33.5" deep. There shall be three (3) compartments parallel to the sides of the body, two (2) on the streetside and one (1) curbside. The one (1) curbside compartment will be approximately 97.0" wide x 27.0" long x 33.5" deep. The two (2) streetside compartments will be approximately 71" wide x 27.0" long x 33.5" deep. The compartments shall be separated by stationary vertical partitions located under each door sill. Each compartment shall be integral with the body construction, and will not be bolted or add-on modules. The outside walls of each compartment will be double walled to prevent equipment from denting the outside painted surface.

Each compartment shall have a lift-up type compartment door hinged on the outboard side. Each door shall be fabricated from 3/16" aluminum tread plate. Each door shall have two (2) pneumatic type cylinders, one (1) at each end, attached to cast aluminum brackets mounted to the interior surface of the door to hold the door in both the opened and closed positions. Each door shall be mounted using 16" long, equally spaced, 14 gauge stainless steel hinges, with 1/4" stainless steel pin. The gravity-driven, sealed, ball-style tilt switch shall be mounted to one of the cast aluminum mounting brackets to activate the door open indicator system and the interior compartment light. A polyester barrier film gasket shall be placed between stainless steel hinge and the body mounting surface as necessary to prevent corrosion caused by dissimilar metals.

Each compartment door shall overlap a 2" vertical lip on the body roof to prevent entry of moisture and sealed with automotive type rubber molding to provide a weather resistant seal.

Each compartment shall have a horizontally mounted OnScene Solutions LED Night Stik on the underside of the door that will be automatically activated when the door is opened and wired to the NFPA required hazard warning light provided in cab.

(4) upper roof compartments will be furnished.

UPPER BODY WALKWAY

A recessed walkway shall be provided recessed at the center of the roof area. The walkway shall be finished with NFPA compliant 3/16" aluminum tread plate with continuously welded seams to prevent moisture penetration into apparatus body. Drains shall be installed in the walkway to allow moisture to drain to the ground through flexible drain hose.

WALKWAY LIGHTS

Two (2) OnScene Solutions 9" LED Night Stik lights provided to illuminate the upper body walkway area. The lights shall be activated when the parking brake is set.

Each light shall be mounted in a mirror polished cast aluminum housing to protect against damage from personnel or equipment.

Wharton Fire Department

Heavy Rescue Specification

SVI

ROOF ACCESS STAIRWAY

The rear of the body shall be provided with a recessed center stairway approximately 34" wide. Stairs treads shall be formed 3/16" NFPA compliant aluminum tread plate with reinforcement as necessary.

STAIRWAY HANDRAILS

There shall be two (2) handrails provided, one (1) on each side wall of recessed center stairway. The handrails shall be angled for optimum use during ingress or egress of the upper walkway area.

Handrails shall be NFPA compliant 1-1/4" extruded aluminum tubing with chrome plated end stanchions.

WALKWAY LIGHTS

Two (2) OnScene Solutions 9" LED Night Stik lights provided to illuminate the upper body walkway area. The lights shall be activated when the parking brake is set.

Each light shall be mounted in a mirror polished cast aluminum housing to protect against damage from personnel or equipment.

STEP COMPARTMENT(S) - LOWER

There shall be two (2) compartment(s) located in the roof access stairway area. Each compartment shall have a horizontally hinged door with a D-ring handle. Each compartment shall be manufactured to prevent road debris, dirt and moisture from entering the enclosure. The compartment(s) shall be 26" wide x 8" high x the maximum appropriate dimensions based upon requirements for structural integrity of the body.

Each Compartment shall have an OnScene Solutions LED Night Stik that will be automatically activated when the door is opened and wired to the NFPA required hazard warning light provided in the cab.

FOLD-DOWN STEP

There shall be one (1) fold-down step located at the bottom of the roof access stairway to reduce the distance from the ground to the first step. The step shall manually fold up into the stairway during travel. The step shall activate the "Hazard Warning Light" in the cab when not in the stowed position.

REAR BODY HANDRAILS

There shall be two (2) vertical handrails on the rear of the body. Handrails shall be NFPA compliant 1-1/4" extruded aluminum tubing with chrome plated end stanchions.

Wharton Fire Department

Heavy Rescue Specification

SVI

BODY WIDTH DIMENSIONS

The body shall be 100.0" wide, not including drip rail or non-permanent fixtures. Interior compartment depth dimensions shall be:

<u>Area Description</u>	<u>Dimension</u>
Transverse Area:	95.5"
- Above Top of Subframe	
Compartment Depth:	24.5"
- Below Top of Subframe	
- Ahead of Rear Axle	
Compartment Depth:	23.5"
- Below Top of Subframe	(Eng. Note)
- Behind the Rear Axle	

(Dimensions are generic and subject to change during the actual design process)

Wharton Fire Department

Heavy Rescue Specification

SVI

STREETSIDE COMPARTMENT - FRONT (S1)

The interior useable compartment width shall be approximately 64.0" wide.

The compartment door opening shall be approximately 57.0" wide.

This compartment shall have a Robinson roll-up door with an exterior satin aluminum finish.

- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan / splash guard shall be provided with the rollup door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT COMPONENTS

- There shall be vertically mounted shelf trac for shelving installation.
- There shall be one (1) permanent shelf approximately 24" deep centered on the upper front wall of the body directly under the Command Light. The WHARTON VOLUNTEER FIRE DEPARTMENT's electric rescue tool power unit will be mounted to shelf.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 94" deep and as wide as the compartment layout or door opening permits, capable of extending out either side of the body located above the level of the chassis frame rails.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) 150 lbs. slide out and down tray(s) with an OnScene Solutions base approximately 46" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- Two (2) vertically mounted OnScene Solutions LED Nightstiks.
- The controls for the specified light tower(s).

Wharton Fire Department

Heavy Rescue Specification

SVI

- One (1) WHARTON VOLUNTEER FIRE DEPARTMENT supplied electric hydraulic power unit(s). One (1) 240 VAC twist lock receptacle with switch shall be provided on wall within easy reach of operator for turning the power unit ON/OFF.
- There shall be one (1) underbody slide-out step.
- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.
- The 12 volt electrical distribution panel shall be located in the streetside front lower compartment.

Wharton Fire Department

Heavy Rescue Specification

SVI

STREETSIDE COMPARTMENT - AHEAD OF REAR WHEELS (S2)

The interior useable compartment width shall be approximately 64.0" wide.

The compartment door opening shall be approximately 57.0" wide.

This compartment shall have a Robinson roll-up door with an exterior satin aluminum finish.

- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan / splash guard shall be provided with the rollup door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT COMPONENTS

- There shall be vertically mounted shelf trac for shelving installation.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. Tray(s) shall be vertically adjustable.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with a OnScene Solutions base approximately 46" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) 150 lbs. slide out and down tray(s) with an OnScene Solutions base approximately 46" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.

Wharton Fire Department

Heavy Rescue Specification

SVI

- There shall be one (1) transverse module(s) for the following long tools and equipment:
 - One (1) WHARTON VOLUNTEER FIRE DEPARTMENT supplied Stokes Basket(s). Manufacturer, model number and dimensions of the Stokes Basket(s) shall be provided during the pre-construction meeting.
 - One (1) Body Manufacturer supplied Little Giant No. 1AA - 17 "A" frame ladder.
 - There shall be four (4) OnScene Solutions cargo straps provided to secure the stored equipment.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- Two (2) vertically mounted OnScene Solutions LED Nightstiks.
- There shall be one (1) underbody slide-out step.
- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.

Wharton Fire Department

Heavy Rescue Specification

SVI

STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S3)

The interior useable compartment width shall be approximately 59.0" wide.

The compartment door opening shall be approximately 52.0" wide.

This compartment shall have a Robinson roll-up door with an exterior satin aluminum finish.

- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan / splash guard shall be provided with the rollup door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT COMPONENTS

- There shall be vertically mounted shelf trac for shelving installation.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 30" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 30" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails. It shall be vertically adjustable in height.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- Two (2) vertically mounted OnScene Solutions LED Nightstiks.
- Air storage module consisting of six (6) 6,000 psi, ASME air storage cylinders.

Wharton Fire Department

Heavy Rescue Specification

SVI

STREETSIDE COMPARTMENT - REAR (S4)

The interior useable compartment space shall be approximately 70.0" wide.

The compartment door opening shall be approximately 63.0" wide.

This compartment shall have a Robinson roll-up door with an exterior satin aluminum finish.

- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan / splash guard shall be provided with the rollup door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT COMPONENTS

- There shall be vertically mounted shelf trac for shelving installation.
- There shall be one (1) adjustable shelf/shelves approximately 24" deep.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) 750 lbs. slide-out tray(s) with an OnScene Solutions base approximately 70" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails. It shall be vertically adjustable in height.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) slide-out smooth aluminum vertical tool board(s) approximately 24" deep.
 - The tool board(s) will be bolted to compartment floor.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on both sides of the toolboard. The striping shall be 2" wide and red/white in color.

Wharton Fire Department

Heavy Rescue Specification

SVI

- There shall be one (1) vertical compartment partition dividing compartment into left and right sides located in compartment.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door in the left portion of the compartment, directly below the specified 750 lbs. roll-out tray. The floor shall have a 2" vertical lip and a 1" return to increase strength.

Floor will be extended in left portion of compartment only.

- Two (2) vertically mounted OnScene Solutions LED Nightstiks.
- There shall be one (1) underbody slide-out step.
- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.

Wharton Fire Department

Heavy Rescue Specification

SVI

CURBSIDE COMPARTMENT - FRONT (C1)

The interior useable compartment width shall be approximately 64.0" wide.
The compartment door opening shall be approximately 57.0" wide.
This compartment shall have a Robinson roll-up door with an exterior satin aluminum finish.

- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan / splash guard shall be provided with the rollup door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT COMPONENTS

- There shall be vertically mounted shelf trac for shelving installation.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 94" deep, capable of extending out either side of the body located above the level of the chassis frame rails.
- There shall be one (1) 150 lbs. slide out and down tray(s) with an OnScene Solutions base approximately 46" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- Two (2) vertically mounted OnScene Solutions LED Nightstiks.
- The cab tilt control pendant.
- One (1) 120/240 VAC load center.
- The FRC FROG-D generator gauge panel.
- There shall be one (1) underbody slide-out step.

Wharton Fire Department

Heavy Rescue Specification

SVI

- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.

Wharton Fire Department

Heavy Rescue Specification

SVI

CURBSIDE COMPARTMENT - AHEAD OF REAR WHEEL (C2)

The interior useable compartment width shall be approximately 64.0" wide.

The compartment door opening shall be approximately 57.0" wide.

This compartment shall have a Robinson roll-up door with an exterior satin aluminum finish.

- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan / splash guard shall be provided with the rollup door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT COMPONENTS

- There shall be vertically mounted shelf trac for shelving installation.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. Tray(s) shall be vertically adjustable.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with a OnScene Solutions base approximately 46" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) 150 lbs. slide out and down tray(s) with an OnScene Solutions base approximately 46" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.

Wharton Fire Department

Heavy Rescue Specification

SVI

- There shall be one (1) transverse module(s) for long tools and equipment which extends to the opposite side of the body.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- Two (2) vertically mounted OnScene Solutions LED Nightstiks.
- The specified portable winch shall be mounted in compartment using a heavy duty "U" shaped channel. Winch receiver tube and mounting pin shall be utilized to hold in place during travel.
- There shall be one (1) underbody slide-out step.
- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.

Wharton Fire Department

Heavy Rescue Specification

SVI

CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C3)

The interior useable compartment width shall be approximately 59.0" wide.

The compartment door opening shall be approximately 52.0" wide.

This compartment shall have a Robinson roll-up door with an exterior satin aluminum finish.

- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan / splash guard shall be provided with the rollup door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT COMPONENTS

- There shall be vertically mounted shelf trac for shelving installation.
- There shall be one (1) adjustable shelf/shelves approximately 30" deep.
- There shall be one (1) 1,000 lbs. slide-out tray(s) with an OnScene Solutions base approximately 30" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) spare SCBA cylinder rack(s). Each rack shall be manufactured using 8" OD PVC tubing.
 - The SCBA bottle rack will be capable of storing twelve (12) SCBA cylinders up to 7.5" diameter.
- Two (2) vertically mounted OnScene Solutions LED Nightstiks.
- Air storage module for cascade system.

Wharton Fire Department

Heavy Rescue Specification

SVI

CURBSIDE COMPARTMENT - REAR (C4)

The interior useable compartment space shall be approximately 70.0" wide.

The compartment door opening shall be approximately 63.0" wide.

This compartment shall have a Robinson roll-up door with an exterior satin aluminum finish.

- There shall be NO keyed lock on this roll-up compartment door.
- One (1) nylon strap shall be provided to assist in closing the door. The strap shall be fastened to the left side of the lower inside door sill. The strap shall extend from the left side of the lower inside door sill to a footman loop attached to the center of the left side of the door frame.
- One (1) aluminum drip pan / splash guard shall be provided with the rollup door.

Compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT COMPONENTS

- There shall be vertically mounted shelf trac for shelving installation.
- One (1) Lista Drawer Cabinet model STO900-0602F-NB-IDL NR. The cabinet will have six (6) individually locking drawers and will be RED in color. The cabinet will be 39-3/8" high x 28-1/4" wide x 22-1/2" deep.

Get correct dimension and pricing for smaller tool box.

- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- One (1) Hannay ECR1616-17-18 cable reel(s) capable of storing 150' of 10/3 electric cable. The rewind switch for each reel shall be located adjacent to the reel it controls.
 - The cable reel shall equipped with 150' of 10/3 SEOW yellow cable, a molded plastic ball clamp, and a single heavy duty L5-30 twist-lock female plug at the end.
 - One (1) Akron model EJB, cast aluminum electrical power distribution box with yellow powder coat painted finish shall be provided. The power distribution box shall include:
 - A 12" pigtail that terminates in an L5-30 configuration to match the cable on the cord reel. The outlet configuration shall include:
 - One (1) L5-20 single twist lock receptacle
 - One (1) L5-20 single twist lock receptacle
 - One (1) L5-20 single twist lock receptacle
 - One (1) L5-20 single twist lock receptacle

Wharton Fire Department

Heavy Rescue Specification

SVI

- One (1) EJB vertical apparatus mounting bracket - treadplate
- One (1) Hannay EF1514-17-18 low pressure air hose reel(s) capable of storing 100' of low pressure air hose. The rewind button for each reel shall be located adjacent to the reel it controls.
 - The hose reel shall be equipped with 100' of 3/8 low pressure air hose. Molded plastic ball clamp shall be provided on the hose to stop it at the 4-way roller. The hose shall be Red in color.
 - The air supply shall be from the mobile breathing air system.
 - The air supply shall be from the mobile breathing air system. A reel shut-off valve, pressure regulator, and 0-150 psi gauge shall be provided at the air control panel.
- Two (2) vertically mounted OnScene Solutions LED Nightstiks.
- The controls for the specified light tower(s).
- One (1) Bauer model CFSII-2S (Containment Type), two (2) position filling station(s) with cascade controls.
 - One (1) refill port shall be located on the front of the right side panel on the filling station.
 - The fill station fill whip(s) shall terminate in a high pressure 4,500 psi, CGA-347 threaded SCBA connectors.
- There shall be one (1) underbody slide-out step.
- One (1) OnScene Solutions 9" LED Nightstik ground light shall be provided below the body.

Wharton Fire Department

Heavy Rescue Specification

SVI

ROOF ACCESS STAIRWAY

The rear of the body shall be provided with a recessed center stairway approximately 34" wide.

PLASTIC FLOOR AND SHELF TILE

All compartment floors, shelves, and trays shall be covered with Turtle Tile plastic interlocking grating.

- The plastic floor tile shall be black
- The plastic edge trim shall be yellow.

ROPE TIE-OFF OR PORTABLE WINCH RECEIVERS

The completed unit shall have an integrated receiver system for use with rope rescue accessories and/or electric winch components. Each receiver shall have the following load rating:

	<u>STRAIGHT PULL</u>	<u>SAFETY FACTOR</u>
Rope Tie Off:	600 LBS.	15:1
Winch:	1,000 LBS	4:1

The following items shall be provided to accomplish rope rescue or portable winch operations:

- Two (2) rope tie off anchor accessories shall be provided with the completed vehicle. Each accessory shall include a push button detent pin to lock it in place. The tie off accessories shall have an eyelet for use with a rope rescue carabiner. A mounting bracket shall be provided to store each rope tie off accessory in a body compartment, location shall be determined by the WHARTON VOLUNTEER FIRE DEPARTMENT.
- One (1) Ramsey model QM5000 - 5,000 lb. 12 volt electric winch furnished with the completed apparatus. It shall be capable of being stored in a compartment and mounted to the apparatus by inserting the mounting point into a properly rated receiver. A minimum of 80' of 1/4" stranded galvanized steel cable with pinned utility hook shall be installed on the drum. A 25' remote control shall be provided with the assembly that permits the Operator to stand at a safe operating distance from the cable and winch.
- There shall be one (1) receiver tube(s) located at the front bumper for use with a portable winch or tie-off point accessory.
 - There shall be one (1) 12 volt plug with a quick connect used to power the portable winch.
 - There shall be one (1) rubber cover / plug for the receiver.

Wharton Fire Department

Heavy Rescue Specification

SVI

- There shall be one (1) receiver tube(s) located on the streetside of the body in the forward portion of the wheel well panel for use with a portable winch or tie-off point accessory.
 - There shall be one (1) 12 volt plug with a quick connect used to power the portable winch.
 - There shall be one (1) rubber cover / plug for the receiver.
- There shall be one (1) receiver tube(s) located on the curbside of the body in the forward portion of the wheel well panel for use with a portable winch or tie-off point accessory.
 - There shall be one (1) 12 volt plug with a quick connect used to power the portable winch.
 - There shall be one (1) rubber cover / plug for the receiver.
- The rear center mounted trailer hitch shall be compatible with a pinnable rope tie-off accessory or a portable winch.
 - There shall be one (1) 12 volt plug with a quick connect used to power the portable winch.
 - There shall be one (1) rubber cover / plug for the receiver.

SIDE BODY PROTECTION - RUB RAIL

There shall be side rub rails provided below the compartment door openings on both the streetside and curbside. The rub rail shall be fabricated from 6063 extruded aluminum, measuring approximately 2-3/4" high x 1-3/8" thick with tapered aluminum end caps. The rub rail shall be bolted to the body using stainless steel bolts and 1-1/2" diameter x 5/8" thick rubber mount isolators to prevent damage to the body. The rails shall incorporate LED clearance marker lighting recessed into the rail fascia to avoid damage to the light in case of impact. The rub rail shall have an accessory mounting track integrated into the backside of the rail to allow mounting of accessories such as ground lighting.

- 3M™ Diamond Grade™ Conspicuity striping shall be provided in the rubrail. The striping shall be red/white in color.

Wharton Fire Department

Heavy Rescue Specification

SVI

COMPARTMENT COMPONENTS DESCRIPTIONS

All interior compartment components shall be fabricated as follows:

ADJUSTABLE SHELVING HARDWARE

Adjustable shelving hardware shall be provided indicated in the numbered compartment list.

The shelving hardware shall include a minimum of four (4) aluminum shelf tracs mounted vertically on compartment side walls or vertical partitions. There shall be one (1) cast aluminum shelf bracket per vertical shelf trac to mount each shelf, tray, or adjustable storage module. Shelving hardware shall be of heavy duty quality with unlimited vertical adjustment settings.

ADJUSTABLE SHELF/SHELVES

Adjustable shelf/shelves shall be provided in exterior compartment as indicated in the numbered compartment list.

Shelves shall be fabricated from 3/16" (.188) aluminum 3003H-14 alloy smooth plate with a 2" vertical flange along the front and rear edges. Shelves shall be designed to be used with flanges either in the upward position to hold various equipment on shelf, or in the downward position for sweep-out shelf surface.

All shelves shall be fully adjustable, from top to bottom of the compartment. There shall be at least four (4) vertical mounting channels and shelving hardware, two (2) each side of compartment. Shelving hardware shall be of heavy duty quality with unlimited vertical adjustment settings.

SLIDE-OUT EQUIPMENT TRAY - (400 LB CAPACITY)

Slide-out equipment tray(s) shall be provided in exterior compartment, as indicated in the numbered compartment list.

Trays shall be fabricated from 3/16" (.188) aluminum 3003H-14 alloy smooth plate. Trays shall be built with a 3" vertical lip, with welded corners, to form a box type tray surface. Sliding tracks shall be Accuride 502 series. The length shall be per numbered compartment list and the extension shall be 100% of the slide length. Slides shall be constructed of formed steel with ball bearings mounted in triple track rails. The tray shall be rated for a maximum 400 lbs. evenly distributed load.

Tray(s) shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.

Wharton Fire Department

Heavy Rescue Specification

SVI

HEAVY DUTY 100% EXTENSION EQUIPMENT SLIDE - (1,000 LB. CAPACITY)

Heavy duty slide-out equipment tray(s) shall be provided in exterior compartment as indicated in the numbered compartment list.

Trays shall be fabricated from 3/16" (.188) aluminum 3003H-14 alloy smooth plate. Trays shall be built with a 4" high vertical lip with welded corners to form a box type tray surface. The tray shall be mounted on a slide frame constructed of anodized aluminum extrusion(s). The frame shall be assembled using stainless steel fasteners (no welds). Each slide shall use a three extrusion rail design utilizing twelve to sixteen (12 - 16) urethane rollers. Each roller shall contain two (2) precision roller bearings mounted in an aluminum hub with a molded on urethane cover. The rollers shall not lose contact with the rail extrusion during operation of the slide unit. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release). The slide shall lock in the closed and full extension positions. The slide shall be rated for a maximum evenly distributed load of 1,000 lbs.

HEAVY DUTY 100% EXTENSION EQUIPMENT SLIDE - (750 LB. CAPACITY)

Heavy duty slide-out equipment tray(s) shall be provided in exterior compartment as indicated in the numbered compartment list.

Trays shall be fabricated from 3/16" (.188) aluminum 3003H-14 alloy smooth plate. Trays shall be built with a 4" high vertical lip with welded corners to form a box type tray surface. The tray shall be mounted on a slide frame constructed of anodized aluminum extrusion(s). The frame shall be assembled using stainless steel fasteners (no welds). Each slide shall use a three extrusion rail design utilizing twelve to sixteen (12 - 16) urethane rollers. Each roller shall contain two (2) precision roller bearings mounted in an aluminum hub with a molded on urethane cover. The rollers shall not lose contact with the rail extrusion during operation of the slide unit. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release). The slide shall lock in the closed and full extension positions. The slide shall be rated for a maximum evenly distributed load of 750 lbs.

HEAVY DUTY 70% EXTENSION EQUIPMENT SLIDE TRANSVERSE (1,000 LBS. CAPACITY)

Heavy duty slide-out equipment tray(s) shall be provided in exterior compartment as indicated in the numbered compartment list.

Trays shall be fabricated from 3/16" (.188) aluminum 3003H-14 alloy smooth plate. Each tray shall be built with a 4" high vertical lip with welded corners to form a box type tray surface. The tray shall be mounted on a slide frame constructed of anodized aluminum extrusion(s). The frame shall be assembled using stainless steel fasteners (no welds). Each slide shall use a two extrusion rail design utilizing twenty (20) urethane rollers. Each roller shall contain two (2) precision roller bearings mounted in an aluminum hub with a molded on urethane cover. Each slide shall have two (2) cable operated, spring loaded latches operated by two (2) large hand openings with red pull handles (Pull to Release). The slide shall lock in the closed and full extension position in two (2) directions. The slide shall be rated for a maximum distributed load of 1,000 lbs.

Wharton Fire Department

Heavy Rescue Specification

SVI

HEAVY DUTY EQUIPMENT TRAYS - SLIDE OUT AND DOWN (250 LBS. CAPACITY)

Heavy duty slide-out equipment tray(s) shall be provided in exterior compartment as indicated in the numbered compartment list.

Trays shall be fabricated from 3/16" (.188) aluminum 3003H-14 alloy smooth plate. Each tray shall be built with a 4" high vertical lip with welded corners to form a box type tray surface. The tray shall be mounted on a slide frame constructed of anodized aluminum extrusion(s). The frame shall be assembled using stainless steel fasteners (no welds). Each slide shall use a two extrusion rail design utilizing four (4) urethane rollers. Each roller shall contain two (2) precision roller bearings mounted in an aluminum hub with molded on urethane cover. The roller shall not lose contact with the rail extrusion during operation of the slide unit. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release). The slide shall lock in the closed position. The slide shall be rated for a maximum evenly distributed load of 250 lbs.

HEAVY DUTY EQUIPMENT TRAYS - SLIDE OUT AND DOWN (150 LBS. CAPACITY)

Heavy duty slide-out equipment tray(s) shall be provided in exterior compartment as indicated in the numbered compartment list.

Trays shall be fabricated from 3/16" (.188) aluminum 3003H-14 alloy smooth plate. Each tray shall be built with a 4" high vertical lip with welded corners to form a box type tray surface. The tray shall be mounted on a slide frame constructed of anodized aluminum extrusion(s). The frame shall be assembled using stainless steel fasteners (no welds). Each slide shall use a two extrusion rail design utilizing four (4) urethane rollers. Each roller shall contain two (2) precision roller bearings mounted in an aluminum hub with molded on urethane cover. The roller shall not lose contact with the rail extrusion during operation of the slide unit. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release). The slide shall lock in the closed position. The slide shall be rated for a maximum evenly distributed load of 150 lbs.

SLIDE-OUT TOOL BOARD (SMOOTH ALUMINUM)

Slide-out tool board(s) shall be provided in the exterior compartment as indicated in the numbered compartment list.

Tool boards shall be fabricated of 3/16" (.188) aluminum 3003H-14 alloy smooth plate with double flange at the outer edge to provide an easy grip handle. The top and bottom of tool board shall be provided with Accuride 502 series slide tracks. The length shall be per numbered compartment list and the extension shall be 100% of the slide length. Slide tracks shall be constructed from formed steel with ball bearings in triple track rails. The board shall be rated for a maximum 200 lbs. evenly distributed load.

Tool board(s) shall utilize a pneumatic cylinder to hold the tool board in both the opened and closed positions. Both the upper and lower roller slide shall be mounted to Shelf Trac to allow the tool board to be adjusted horizontally for best fit in the compartment.

Wharton Fire Department

Heavy Rescue Specification

SVI

COMPARTMENT PARTITIONS

Vertical compartment partitions shall be provided as indicated in the numbered compartment list. Partitions shall be fabricated of 3/16" thick (.188) smooth aluminum with 1" "L" outer edge. Bolted angles shall be provided at top and bottom of partition to secure partition in place, but allow future removal without cutting of partition.

TRANSVERSE STORAGE MODULE

Transverse storage module for long equipment shall be provided as indicated in the numbered compartment list.

The module shall be fabricated from 1/8" (.125") thick smooth aluminum. Exact size and layout shall be approved prior to construction.

SCBA CYLINDER RACK

A spare SCBA cylinder storage rack shall be provided and located as indicated in the numbered compartment list.

The rack shall have a shell fabricated of 1/8" (.125) thick smooth aluminum. There shall be a 2" slope in the rack to keep the bottles from sliding out. The air bottle storage tubes shall be fabricated of PVC tube. There shall be rubber matting installed inside each storage tube for bottle protection.

LISTA DRAWER CABINET

Lista Drawer Cabinet(s), model ST0900-0602F-NB-IDL-NR, shall be provided in exterior compartment as indicated in the numbered compartment list.

The drawer cabinet(s) shall be 39-3/8" high x 28-1/4" wide x 22-1/2' deep. The cabinet shall have six (6) individual locking drawers. The drawers shall have usable heights as follows: three (3) 3", one (1) 5", one (1) 7", one (1) 9". The cabinet shall be RED in color.

COMPARTMENT LIGHTING

Each enclosed equipment compartment greater than 4 ft³ (0.1 m³) in volume and having an opening greater than 144 in.² (92,900 mm²) shall have sufficient compartment lighting to provide a minimum of 2 fc (20 lx) at any location on the floor of the compartment without any shelves, dividers, or equipment in the compartment.

Compartments such as ladder tunnels, pike pole storage tubes, or underbody compartments designed around the volumetric requirements of specific equipment that can be removed without the use of article illumination shall not be required to have compartment lighting.

All compartments shall be equipped with OnScene Nightstik LED lights with the following minimum light requirements;

- Full Height Compartments, 54" Section (36 LED's)
- Wheel well Compartments, 36" Section (24 LED's)

Wharton Fire Department

Heavy Rescue Specification

SVI

- Rear Rescue Compartment, 54" Section (36 LED's)
- Low Compartments, 18" Section (12 LED's), Vertical
- Low Compartments, 36" Section (24 LED's), Horizontal

The OnScene Nightstik lights shall be rated at 100,000 hours of service and shall be provided with a 5 year free replacement warranty.

ELECTRIC CORD REEL

Electric cord reel(s) shall be provided in exterior compartment as indicated in the numbered compartment list.

The 120 volt cord reel(s) shall be Hannay with electric rewind, equipped with fully enclosed 45 amp, three (3) conductor collector rings.

The 12 volt reel rewind system shall be directly wired to the chassis battery system with heavy duty stranded copper wire, with guarded finger type rewind button located within easy reach of the operator.

Each reel shall have a Hannay 4-way roller assembly to permit cable to feed directly off the reel and away from compartment. Plastic roller assemblies are not acceptable.

The wiring from the generator system shall be through Carflex electrical weatherproof conduit, with stranded copper wiring. The wiring shall terminate in a sealed conduit box at the reel with mechanical type connectors for quick removal of wiring.

Cord Reel General Requirements

All permanently mounted cord reels shall be rated for continuous duty and installed to be accessible for removal, cord access, maintenance, and servicing.

The power rewind cord reel spool area shall be visible to the operator during the rewind operation, or the reel spool shall be encapsulated to prevent cord from spooling off the reel.

Rollers or guides shall be provided, where required, to prevent damage to the cord at reel spools or compartment openings.

Rewind Provision

Power rewind type reels shall have the control in a position where the operator can observe the rewinding operation.

If a reel is in an enclosure or out of direct view, the cord entry point to the enclosure shall be visible to the operator of the reel control.

The rewind control or crank shall not be more than 72 in. (1830 mm) above the operator's standing position. The rewind control shall be marked with a label indicating its function and shall be guarded to prevent accidental operation.

Cord

The reel shall be designed to hold 110 percent of the capacity needed for the intended cord length.

Wharton Fire Department

Heavy Rescue Specification

SVI

The wire size shall be in accordance with *NFPA 70*, Table 400.5(A), but in no case shall it be smaller than 12AWG. Electrical cord shall be Type SEOOW, Type SOOW, or Type STOOW.

A label that indicates the following information shall be provided in a visible location adjacent to any permanently connected reel:

- (1) Current rating
- (2) Current type
- (3) Phase
- (4) Voltage
- (5) Total cord length

POWER DISTRIBUTION BOX

Where a power distribution box is hardwired to the end of a cord that is stored on a fixed cord reel or other fixed storage means, the following requirements shall apply;

The remote power distribution box shall be listed for use in a wet location.

The distribution box shall be as follows:

- (1) Protected from corrosion
- (2) capable of being carried with a gloved hand
- (3) Designed to keep the exterior electrical components above 2 in. (51 mm) of standing water

Inlets, receptacles, circuit breakers, or GFCI devices shall not be mounted on the top surface of the horizontal plane.

Branch circuit breakers shall be installed in the remote power distribution box if the overcurrent device protecting the feed cord to the box is too large to protect the wiring supplying the devices plugged onto the distribution box.

Remote power distribution boxes shall have a light on the box to indicate the power is on. The light shall be visible in a 360 degree plane from a minimum of 200 ft (60 m) in complete darkness. The light shall be mechanically protected to prevent damage.

The hardwired portable cord connection to the box shall have strain relief and meet the intended usage requirements.

LOW PRESSURE AIR HOSE REEL

Air hose reel(s) shall be provided in exterior compartment as indicated in the numbered compartment list.

The air reel(s) shall be Hannay, low pressure design, with electric rewind.

The 12 volt electrical rewind circuit shall be directly wired to the chassis battery system with heavy duty stranded copper cable. The rewind button shall be located adjacent to the hose reel within easy access of Operator.

Each reel shall have a Hannay 4-way roller assembly to permit cable to feed directly off the reel and away from compartment. **Plastic roller assemblies are not acceptable.**

Air hose shall have a ball clamp located near end of hose.

Wharton Fire Department

Heavy Rescue Specification

SVI

UTILITY AIR SYSTEM

The intent of this section is to create an air supply of sufficient pressure and volume to operate air bags and air powered tools.

AIR COMPRESSOR

One (1) W.W. Grainger model 4B228 or equal, 240 volt electric powered air compressor shall be installed on apparatus. Unit shall meet or exceed the following minimum requirements:

- Supply a minimum 9.1 SCFM @ 125 PSI.
- Powered by a 3.1 HP, 230 VAC electric motor.
- Have a heavy duty two (2) cylinder motor.
- 20 gallon capacity tank.
- Relief valve.
- Equipped with automatic moisture ejector and bleed valves to prevent moisture buildup.
- Meets all ASME standards.
- 135 PSI maximum pressure.
- 33" L x 19.5" W x 31" H

BREATHING AIR STORAGE SYSTEM

Breathing air system shall be provided with a air storage module consisting of:

- Six (6) 6,000 psi, ASME air storage cylinders shall be provided which comply with 49 CFR 178.37, "Specification 3AA and 3AAX seamless steel cylinders," or 29 CFR 1910.169, "Air receivers". Each cylinder shall be permanently stamped or identified in accordance with DOT or ASME regulations.

Each cylinder shall have a working pressure of 6,000 psi with a 3:1 safety factor and nominal capacity of 491 cu. ft. at 6,000 psi.

If the air storage was cascaded the system would be capable of filling approximately seventy one (71) 45 cu.ft. 2,216 psi, or fifty two (52) 45 cu.ft. 4,500 psi SCBA bottles (based on residual pressure of 500 psig).

There shall be a label which reads, "HIGH PRESSURE - 6,000 psi BREATHING AIR".

The air tank manufacturer shall provide a copy of either the U.S. Department of Transportation (DOT) certificate Report of Inspection of Gas Cylinders or the ASME certificate Manufacturers Data Report for Pressure Vessels, and the certificate shall be delivered with the fire apparatus.

Relief valves on transportable air tanks shall be of the ASME type on ASME cylinders and of the DOT type on DOT cylinders or equal for the rated pressure.

Valves installed on air tanks shall meet the requirements of the Compressed Gas Association regarding pressure and usage with compressed air.

Wharton Fire Department

Heavy Rescue Specification

SVI

If the installation utilizes cylinders that require periodic testing, a label shall be placed on or near the operators panel that provides the following:

- (1) The original cylinder test date stamped on the cylinders
- (2) The recommended testing interval
- (3) Five additional open spaces, appropriately labeled, for the user to enter actual retesting dates

The manufacturers test date (month and year) on each air tank shall be current within 12 months of the apparatus delivery date.

Air Tank Mounting

Air tanks shall be mounted in an arrangement that will hold the tanks in all types of mobile use.

A protective device(s) shall be provided to protect the air tank valve(s) and associated piping from damage as a result of accidental impact. The protective device(s) shall not prevent access for operation and inspection.

The air tank mounting shall facilitate removal of air tanks for inspection, testing, or service.

Air tanks shall be installed so that all air tanks, control valves, and associated piping are readily accessible.

Air tanks shall be mounted in such a fashion to permit visual inspection of external surfaces and emergency access to shutoff of tank valves.

The air tank location shall be away from any heat producing devices such as the generator engine or exhaust.

FILL STATION

There shall be one (1) Bauer model CFSII-2S (Containment Type) filling station(s) with cascade controls furnished and installed in the apparatus body per the itemized compartment list.

This specification is for a containment type fill station to refill self-contained breathing apparatus (SCBA). The fill station shall be designed for a maximum working pressure of 6,000 psig. All equipment shall be new and of current design and manufacture. Used and/or refurbished equipment is unacceptable.

"CONTAINMENT TYPE" FILL STATION

A front loading, 2-position, containment type fill station shall totally enclose the SCBA cylinders during the refilling process. The fill station shall contain the cylinder and any fragments of the cylinder in the unlikely event of a cylinder exploding during the refilling process. The filling station shall vent the expanding air away from the Operator.

The fill station shall incorporate a 1/4" thick steel plate door reinforced by two (2), 1/4" thick steel SCBA holders, providing a total 1/2" thick steel protective safety barrier between the Operator and the cylinder refilling process, and a 1/4" thick steel outer enclosure. The fill station shall be ergonomically designed for maximum Operator safety and convenience during the refilling process. The fill station door and cylinder holder assembly shall tilt out towards the Operator providing unobstructed access to the cylinder holder to load and unload the cylinders at waist height. Each cylinder holder shall be lined with UHMW polyethylene strips to prevent scuffing the outer surface of the cylinders. For complete Operator protection, the fill station shall include a 3-point pneumatic safety interlock system. An interlock shall prevent refilling the

Wharton Fire Department

Heavy Rescue Specification

SVI

cylinders while the fill station door is open. A manually activated door interlock shall latch the fill station door in the closed position. The third interlock verifies that the fill station door is closed and latched. The refilling process can commence only when all three (3) safety interlocks are satisfied, **NO EXCEPTIONS**.

Two (2) fill hoses shall be located within the fill station's steel outer enclosure. Each fill hose shall be equipped with a bleed valve and fill adapter of choice. There shall be CGA 346 male adapters to anchor the fill hoses when not in use.

Wharton Fire Department

Heavy Rescue Specification

SVI

CONTROL AND FILLING PANEL

The central fill/control panel shall be furnished to facilitate the filling of SCBA bottles from the storage system. All of the filling and air flow control shall be controlled and monitored from this central panel.

The top control panel shall include:

- Inlet pressure gauge from storage
- One (1) 0-6,000 psi adjustable regulators with relief valve set for storage bottle pressure
- One (1) fill pressure gauge
- Two (2) fill pressure gauges and "On/Off" valves, one (1) for each fill position
- Door interlock switch

The side control panel shall include:

- Storage pressure gauge for each air storage cylinder.
- High pressure valve for each air storage cylinder.
- External supply air connection for filling storage cylinders.

The panel shall be designed in such a way so that each filling whip can be protected with its own individual relief valve. This will allow for a full range of filling pressures offering maximum protection.

All piping and tubing shall be properly supported and protected to prevent damage from vibration during shipment, operation or maintenance. Piping and tubing shall be installed in a neat and orderly arrangement, adapting to the contours of the station. All instrument tubing shall be 300 series stainless steel.

All control panel mounted pressure gauges shall have a 2-1/2" diameter face and be liquid filled. All panel mounted components shall be labeled with and engraved nameplate.

TESTING AND PREPARATION OF FILL STATION

The fill station design shall have been tested and certified by an independent third-party testing organization per NFPA 1901. Proof of such testing shall be available for review upon the Fire Department's request. Each fill station shall be bench tested by the Manufacturer prior to shipment. A copy of the Manufacturer's test report shall accompany the unit at shipment, **NO EXCEPTIONS**.

An Operator's instruction and maintenance manual shall be supplied with the unit. The manual shall be as detailed as possible, outlining all operating and maintenance instructions. The manual shall include detailed illustrated drawings along with a complete parts list for all illustrated components. Warnings and safety precautions shall be included in the manual.

A fill station nameplate shall be securely affixed to station's frame in a conspicuous location.

Wharton Fire Department

Heavy Rescue Specification

SVI

STEP / GROUND LIGHTS

Step and ground lights shall be OnScene Solutions 9" LED Nightstik and be placed at any entry door and step where personnel climb on or descend from the apparatus to ground level. OnScene LED lights shall have 6 LED lights per 9" light, and shall be rated at 100,000 hours of service. On Scene Solutions LED lights shall be have a 5 year free replacement warranty.

All of the required step and ground lights shall be activated when the parking brake is set.

Wharton Fire Department

Heavy Rescue Specification

SVI

LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC

General

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125 % of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10 %. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

Wharton Fire Department

Heavy Rescue Specification

SVI #

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Wharton Fire Department

Heavy Rescue Specification

SVI

Circuits shall be provided with properly rated low voltage overcurrent protective devices. Such devices shall be readily accessible and protected against heat in excess of the overcurrent device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

- (1) SAE J156, *Fusible Links*
- (2) SAE J553, *Circuit Breakers*
- (3) SAE J554, *Electric Fuses (Cartridge Type)*
- (4) SAE J1888, *High Current Time Lag Electric Fuses*
- (5) SAE J2077, *Miniature Blade Type Electrical Fuses*

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125 % of maximum current for which the circuit is protected.

Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.

Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- (1) The propulsion engine and transmission
- (2) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- (3) The radio(s) at a duty cycle of 10 percent transmit and 90 % receive (for calculation and testing purposes, a default value of 5 A continuous)
- (4) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
- (5) The minimum optical warning system, where the apparatus is blocking the right-of way
- (6) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
- (7) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

Wharton Fire Department

Heavy Rescue Specification

SVI

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

Electromagnetic Interference

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

12 VOLT MULTIPLEX CONTROL CENTER

The apparatus shall have a multiplexed 12 volt electrical system that will provide complete diagnostic capability. The system shall have the capability of delivering multiple signals via a CAN bus, utilizing specifications set forth by SAE J1939. The system shall be node based to maximize stability so that failure of one node does not affect the operation of the other nodes. The system shall use shielded twisted-pair wire for transmission of system function signals. The shielded wire shall provide protection against EMI and RFI noise interruptions.

The multiplex system shall be responsible for providing power management functions as well as load shedding. The warning light system shall be controlled by the multiplex system. The system shall be capable of displaying text and/or graphic messages on a display module. The system shall be based on solid-state technology and shall include self-contained diagnostic indicators.

Wharton Fire Department

Heavy Rescue Specification

SVI

BATTERY SYSTEM

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

A master load disconnect switch shall be provided between the starter solenoid(s) and the remainder of the electrical loads on the apparatus. The starter solenoids shall be connected directly to the batteries.

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not through the master load disconnect switch.

A green "battery on" pilot light that is visible from the driver's position shall be provided.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within 5 seconds.

BATTERY SWITCH

One (1) battery "On/Off" switch in cab located within easy reach of Driver with green "BATTERY ON" pilot light that is visible from the driver's position shall be provided. The switch and pilot light shall be supplied and installed by the cab/chassis manufacturer.

BATTERY SOLENOID

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

Wharton Fire Department

Heavy Rescue Specification

SVI

BATTERY CONDITIONER

The battery conditioner shall be supplied and installed by the cab chassis manufacturer.

ENGINE COMPARTMENT LIGHT

Engine compartment light(s) shall be supplied and installed by the cab chassis manufacturer.

CAB HAZARD WARNING LIGHT

A red "HAZARD" warning light shall be supplied and installed by the cab/chassis manufacturer. Light shall illuminate automatically to warn the Driver of the following when the apparatus parking brake is not fully engaged:

- Any passenger or compartment door is open
- Equipment rack is not in stowed position
- Light tower is extended

The light shall be labeled "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

BACK-UP ALARM

An electronic back-up alarm shall be supplied and installed by the cab/chassis manufacturer. The back-up alarm shall actuate automatically when the transmission gear selector is placed in reverse.

REAR VIEW CAMERA

The cab chassis provided rear view camera shall be installed on the rear of the body.

TAIL LIGHTS

Rear body tail lights shall be vertically mounted per Federal Motor Vehicle Safety Standards. The following lights shall be furnished:

- Two (2) Whelen amber LED 600 Series 60A00TAR turn signal lights
- Two (2) Whelen red LED 600 Series 60R00XRR stop/tail lights
- Two (2) Whelen Halogen 600 Series 60J000CR back-up lights with clear lens

Each of the lights above shall be mounted in a 6EFLANGE, chrome finish bezel.

Wharton Fire Department

Heavy Rescue Specification

SVI

MIDSHIP MARKER/TURN SIGNAL

Two (2) Whelen LED mid ship body clearance marker/turn signal lights (T0A00MAR) shall be installed. There shall be one (1) light on each side of the body, in the wheel well, ahead of the rear axle. Both lights shall have an amber lens and operate with the chassis clearance marker and turn signals.

MARKER LIGHTS

The apparatus body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) regulations. All body clearance lights shall be LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

LICENSE PLATE MOUNTING BRACKET

There shall be one (1) Cast Products aluminum license plate mounting with chrome shielded license plate light mounted on the rear of the body.

ELECTRONIC SIREN

One (1) Whelen model 295SLSA1 electronic siren control with standard hard wired microphone and user programmable siren tones. Siren to be installed in cab within easy access of Driver.

SIREN SPEAKER

The siren speaker(s) shall be supplied and installed by the cab/chassis manufacturer.

SIDE SCENE LIGHTS

There shall be four (4) Whelen 810 series (10" x 8") surface mounted Opti-Scene lights (810CA0ZR) provided on the upper body. Each light will have a 8-32 degree lens and chrome flange. They will be equally divided between the curbside and streetside.

Two (2) switches shall be provided, one (1) for the streetside scene lights, and one (1) for the curbside scene lights.

The lights shall be switched at the Vista display in the cab.

REAR SCENE LIGHTS

Wharton Fire Department

Heavy Rescue Specification

SVI

Two (2) Whelen 810 series (10" x 8") surface mounted Opti-Scene lights (810CA0ZR) shall be provided on the upper rear body to light the work area immediately behind the vehicle to a level of at least 3 fc (30 lx) within a 10 ft x 10 ft (3 m x 3 m) square. Each light will have a 8-32 degree lens and chrome flange.

The lights shall be switched at the Vista display in the cab.

The rear scene lights shall also be activated when the apparatus is in reverse.

TRAFFIC DIRECTIONAL LIGHT

One (1) Whelen TA4437L LED eight (8) lights, split two-piece housing, traffic directional warning device with 30' control cable shall be located on upper rear body. The control head shall be located in the cab within easy reach of Driver.

- The traffic directional light shall be surface mounted on upper rear body.

WARNING LIGHT PACKAGE

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two separate signaling modes during emergency operations. One mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

Wharton Fire Department

Heavy Rescue Specification

SVI

UPPER LEVEL OPTICAL WARNING DEVICES

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

ZONE A - FRONT WARNING LIGHTS

There shall be one (1) Whelen Edge FN72QLED LED 72" lightbar permanently mounted to the cab roof.

The lightbar configuration (streetside to curbside) shall be:

1	Red Linear LED - Side Facing	Clear
2	Red Corner LED	Clear
3	Blank	Clear
4	Clear Linear LED	Clear
5	Blank	Clear
6	Red Linear LED	Clear
7	Blank	Clear
8	Blank	Clear
9	Red Linear LED	Clear
10	Blank	Clear
11	Clear Linear LED	Clear
12	Blank	Clear
13	Red Corner LED	Clear
14	Red Linear LED - Side Facing	Clear

All clear lights shall shut down when the parking brake is set to comply with "Blocking" mode requirements as outlined in NFPA 1901.

The lightbar shall be separately switched at the vista display in the cab.

ZONES B AND D - SIDE WARNING LIGHTS

UPPER REAR CORNER WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") red linear Super-LED lights provided, one (1) each side.

The lights shall be switched at the Vista display in the cab.

Wharton Fire Department

Heavy Rescue Specification

SVI #

Each light shall have a clear lens (90CC5FCR) and chrome flange.

Wharton Fire Department

Heavy Rescue Specification

SVI

UPPER FORWARD CORNER WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") red linear Super-LED lights provided, one (1) each side.

The lights shall be switched at the Vista display in the cab.

Each light shall have a clear lens (90CC5FCR) and chrome flange.

ZONE C - REAR WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") red linear Super-LED lights provided, one (1) each side.

The lights shall be switched at the Vista display in the cab.

Each light shall have a clear lens (90RR5FCR) and chrome flange.

LOWER LEVEL OPTICAL WARNING DEVICES

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1220 mm) above level ground for small apparatus.

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

ZONE A - FRONT WARNING LIGHTS

The warning lights shall be supplied and installed by the cab/chassis manufacturer. They shall be Whelen lights to complete an NFPA compliant lower level warning light system.

The lights shall be switched at the Vista display in the cab.

ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)

The warning lights shall be supplied and installed by the cab/chassis manufacturer. They shall be Whelen lights to complete an NFPA compliant lower level warning light system.

The lights shall be switched at the Vista display in the cab.

Wharton Fire Department

Heavy Rescue Specification

SVI

ZONES B AND D - BODY INTERSECTOR LIGHT (BODY WHEELWELL AREA)

There shall be two (2) Whelen 500 series (5" x 2") red linear Super-LED lights provided, one (1) each side.

The lights shall be switched at the Vista display in the cab.

Each light shall have a clear lens (50R02ZCR) and chrome finished flange.

ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") red linear Super-LED lights provided, one (1) each side.

The lights shall be switched at the Vista display in the cab.

Each light shall have a clear lens (60R02FCR) and chrome finished flange.

ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") red linear Super-LED lights provided, one (1) each side.

The lights shall be switched at the Vista display in the cab.

Each light shall have a clear lens (60R02FCR) and chrome finished flange.

ONAN PTO GENERATOR

The apparatus shall be equipped with an Onan Protec PTO generator system with a capacity of 30,000 watts at 120/240 VAC, 250/125 amps., single phase. Current frequency shall be stable at 60 hertz.

The transmission's PTO port and PTO, or the split shaft PTO, and all associated drive shaft components shall be rated to support the continuous duty torque requirements of the generator's continuous duty rating as stated on the power source nameplate.

Where the generator is driven by the chassis engine and transmission through a split shaft PTO, the driving compartment speedometer shall register when the generator drive system is engaged.

Where the generator is driven by the chassis engine and transmission through a split shaft PTO and a chassis transmission retarder is furnished, it shall be automatically disengaged for generator operations.

The direct drive generator shall be mounted so that it does not change the ramp breakover angle, angle of departure, or angle of approach as defined by other components, and it shall not extend into the ground clearance area.

The direct drive generator shall be mounted away from exhaust and muffler areas or provided with a heat shield to reduce operating temperatures in the generator area.

Wharton Fire Department

Heavy Rescue Specification

SVI

GENERATOR ENGAGEMENT

A "Generator Engaged" indicator shall be provided in the driving compartment to indicate that the generator shift has been successfully completed.

An "OK to Operate Generator" indicator shall be provided in the driving compartment to indicate that the generator is engaged (if not always engaged), the transmission is in the proper gear (if required, automatic transmissions only), and the parking brake is engaged (if applicable).

An interlock system shall be provided to prevent advancement of the engine speed in the driving compartment or at any operator's panel unless the parking brake is engaged, and the transmission is in neutral or the output of the transmission is correctly connected to a pump or generator instead of the drive wheels.

WARRANTY PERIOD

Provided such goods are operated and maintained in accordance with Onan's written instructions, Onan warrants that the Protec YDCR series PTO generators shall be free from defects in material and workmanship for a period of five (5) years or one thousand (1,000) hours, whichever comes first, from the date of delivery to the first purchaser.

GENERATOR SPLASH GUARD

A powder coat painted splash cover shall be installed to reduce the amount of road spray on the frame mounted PTO generator. A V-ring seal shall also be installed in the cover to provide additional protection against contaminants reaching the generator front seals.

GENERATOR MOUNTING

The generator shall be mounted between the chassis frame rails. The generator mounting brackets shall be fabricated using heavy duty steel tubing, or structural channel. The generator mounting shall be bolted and removable so that the generator can be lowered from under apparatus for service, if necessary. The generator case shall not extend below the bottom edge of the apparatus body.

MANUALS AND SCHEMATICS

Two (2) complete manuals on parts list, maintenance, wiring schematics, hydraulic schematics, circuit boards, voltage regulator board and other components shall be provided on delivery.

Wharton Fire Department

Heavy Rescue Specification

SVI

POWER-TAKE-OFF GENERATOR DRIVE

There shall be a "Hot Shift" power-take-off (PTO) installed on the transmission PTO by the cab chassis manufacturer. The "Hot Shift" PTO is provided to allow the engagement of the PTO at higher engine RPM speeds. The PTO output shall be connected to the generator through hollow tube type driveline with heavy duty universals.

The engagement of the PTO shall be in the chassis cab with a rocker switch and red pilot light to note engagement of the PTO.

The power supply to the PTO engagement control shall be wired to the parking brake and a neutral position transmission switch to prevent engagement unless the vehicle is stopped and transmission has been placed in neutral.

ENGINE SPEED CONTROL

An engine speed auxiliary control device (high idle switch or throttle) shall be installed to maintain a stable cycle output from generator when the apparatus is parked.

An interlock shall prevent the operation of the engine speed auxiliary control device unless the parking brake is engaged and the transmission is in neutral or park, or the parking brake is engaged and the engine is disengaged from the drive wheels.

The engine shall be prevented from regulating its own engine speed during times when engine rpm control is critical for consistent apparatus functions such as generator, water pump, or aerial operation.

GENERATOR MONITORING PANEL

To properly monitor the generator performance and load demand during operation, the generator installation shall be equipped with a full instrument monitor panel.

This unit shall be manufactured by FRC model FROG-D and mounted next to the circuit breaker panel. This generator output display shall consolidate five (5) generator monitoring instruments into one device. The display case shall be waterproof and have dimensions not to exceed 4 1/4" high by 4 1/4" wide by 3 1/4" deep.

The following continuous displays shall be provided with super bright LED digits more than 1/2" high:

- Generator frequency in hertz
- Line 1 current in amperes
- Line 2 current in amperes
- Generator voltage in volts

The program shall support the accumulation of elapsed generator hours and the monitoring of engine oil temperature. Generator hours and oil temperature shall be displayed at the push of a button.

Wharton Fire Department

Heavy Rescue Specification

SVI

LOADCENTER

The loadcenter shall be a Cutler Hammer, BR Series, specifically designed for protection and distribution of 120/240 volt AC, such as lighting and small motor branch circuits. The loadcenter enclosure shall be made of 16 gauge galvanized sheet steel. The galvanized coating provides corrosion protection and as such does not require paint. All trims used on the BR Loadcenter shall be chromate sealed and finished with electro disposition epoxy paint (ASA61) which exceeds requirements for outdoor and indoor applications. A combination surface/flush cover with integral door shall be supplied.

The loadcenter shall be UL / CSA listed, **NO EXCEPTIONS** will be allowed.

OUTLETS AND CIRCUITS

The generator shall supply the electrical equipment and outlets outlined below. Proper circuit protection shall be installed as noted:

- Two (2) 120 volt exterior outlets, one (1) each side near rear wheel well area.
 - The receptacle shall be 20 amp, twist-lock (NEMA L5-20R).
- Two (2) 120 volt exterior outlets, one (1) each side rear of body.
 - The receptacle shall be 20 amp, twist-lock (NEMA L5-20R).

GENERAL REQUIREMENTS

Stability

Any fixed line voltage power source producing alternating current (ac) shall produce electric power at 60 Hz, ± 3 Hz when producing power at all levels between no load and full rated power. Any fixed line voltage power source shall produce electric power at the rated voltage ± 10 percent when producing power at all levels between no load and full rated power.

The maximum voltage supplied to portable equipment shall not exceed 275 volts to ground. Higher voltage shall be permitted only when used to operate fixed wired, permanently mounted equipment on the apparatus.

Conformance with National Electrical Code

All components, equipment, and installation procedures shall conform to *NFPA 70, National Electrical Code*, except where superseded by the requirements of this chapter. Where the requirements of this chapter differ from those in *NFPA 70*, the requirements in this chapter shall apply.

Where available, line voltage electrical system equipment and materials included on the apparatus shall be listed and used only in the manner for which they have been listed. All equipment and materials shall be installed in accordance with the manufacturer's instructions.

Wharton Fire Department

Heavy Rescue Specification

SVI

Location Ratings

Any equipment used in a dry location shall be listed for dry locations. Any equipment used in a wet location shall be listed for wet locations.

Any equipment, except a PTO-driven generator, used in an underbody or under chassis location that is subject to road spray shall be either listed as Type 4 or mounted in an enclosure that is listed as Type 4.

If a PTO-driven generator is located in an underbody or under chassis location, the installation shall include a shield to prevent road spray from splashing directly on the generator.

Grounding

Grounding shall be in accordance with 250.34(A) and 250.34(B) of *NFPA 70*. Ungrounded systems shall not be used.

Only stranded or braided copper conductors shall be used for grounding and bonding.

The grounded current-carrying conductor (neutral) shall be insulated from the equipment-grounding conductors and from the equipment enclosures and other grounded parts.

The neutral conductor shall be colored white or gray in accordance with 200.6, "Means of Identifying Grounded Conductors," of *NFPA 70*.

Any bonding screws, straps, or buses in the distribution panelboard or in other system components between the neutral and equipment-grounding conductor shall be removed and discarded.

Bonding

The neutral conductor of the power source shall be bonded to the vehicle frame. The neutral bonding connection shall occur only at the power source. In addition to the bonding required for the low voltage return current, each body and each driving or crew compartment enclosure shall be bonded to the vehicle frame by a copper conductor.

The conductor shall have a minimum ampere rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated ampere on the power source specification label.

A single conductor that is sized to meet the low voltage and line voltage requirements shall be permitted to be used.

Ground Fault Circuit Interrupters

In special service vehicles incorporating a lavatory, sink, toilet, shower, or tub, 120 V, 15 or 20 A receptacles within 6 ft (1.8 m) of these fixtures shall have ground fault circuit interrupter (GFCI) protection. GFCIs integrated into outlets or circuit breakers or as stand-alone devices shall be permitted to be used in situations.

Power Source General Requirements

All power source system mechanical and electrical components shall be sized to support the continuous duty nameplate rating of the power source.

The power source shall be shielded from contamination that would prevent the power source from operating within its design specifications.

Wharton Fire Department

Heavy Rescue Specification

SVI

Power Source Rating

For power sources of 8 kW or larger, the power source manufacturer shall declare the continuous duty rating that the power source can provide when installed on fire apparatus according to the manufacturer's instructions and run at 120°F (49°C) air intake temperature at 2000 ft (600 m) above sea level.

The rating on the power source specification label shall not exceed the declared rating from the power source manufacturer.

Access shall be provided to permit both routine maintenance and removal of the power source for major servicing. The power source shall be located such that neither it nor its mounting brackets interfere with the routine maintenance of the fire apparatus.

Instrumentation

If the power source is rated at less than 3 kW, a "Power On" indicator shall be provided. If the power source is rated at 3 kW or more but less than 8 kW, a voltmeter shall be provided.

If the power source is rated at 8 kW or more, the following instrumentation shall be provided at an operator's panel:

- (1) Voltmeter
- (2) Current meters for each ungrounded leg
- (3) Frequency (Hz) meter
- (4) Power source hour meter

The instrumentation shall be permanently mounted at an operator's panel. The instruments shall be located in a plane facing the operator. Gauges, switches, or other instruments on this panel shall each have a label to indicate their function.

The instruments and other line voltage equipment and controls shall be protected from mechanical damage and not obstructed by tool mounting or equipment storage.

An instruction plate(s) that provides the operator with the essential power source operating instructions, including the power-up and power-down sequence, shall be permanently attached to the apparatus at any point where such operations can take place.

Operation

Provisions shall be made for placing the generator drive system in operation using controls and switches that are identified and within convenient reach of the operator.

Where the generator is driven by the chassis engine and engine compression brakes or engine exhaust brakes are furnished, they shall be automatically disengaged for generator operations.

Any control device used in the generator system power train between the engine and the generator shall be equipped with a means to prevent unintentional movement of the control device from its set position in the power generation mode.

If there is permanent wiring on the apparatus that is designed to be connected to the power source, a power source specification label that is permanently attached to the apparatus at the operator's control station shall provide the operator with the information required.

Wharton Fire Department

Heavy Rescue Specification

SVI

The power source, at any load, shall not produce a noise level that exceeds 90 dBA in any driving compartment, crew compartment, or onboard command area with windows and doors closed or at any operator's station on the apparatus.

Power Supply Assembly

The conductors used in the power supply assembly between the output terminals of the power source and the main overcurrent protection device shall not exceed 12 ft (4 m) in length.

All power supply assembly conductors, including neutral and grounding conductors, shall have an equivalent amperage rating and shall be sized to carry not less than 115 percent of the amperage of the nameplate current rating of the power source.

If the power supply assembly connects to the vibrating part of a generator (not a connection on the base), the conductors shall be flexible cord or other fine-stranded conductors enclosed in metallic or nonmetallic liquid tight flexible conduit rated for wet locations and temperatures not less than 194°F (90°C).

Overcurrent Protection

Manually resettable overcurrent devices shall be installed to protect the line voltage electrical system components.

Power Source Protection

A main overcurrent protection device shall be provided that is either incorporated in the power source or connected to the power source by a power supply assembly.

The size of the main overcurrent protection device shall not exceed 100 percent of the rated amperage stated on the power source specification label or the rating of the next larger available size overcurrent protection device, where so recommended by the power source manufacturer.

If the main overcurrent protection device is subject to road spray, the unit shall be housed in a Type 4-rated enclosure.

Branch Circuit Overcurrent Protection

Overcurrent protection devices shall be provided for each individual circuit and shall be sized at not less than 15 amps in accordance with 240.4, "Protection of Conductors," of *NFPA 70*.

Any panelboard shall have a main breaker where the panel has six or more individual branch circuits or the power source is rated 8 kW or larger.

Each overcurrent protection device shall be marked with a label to identify the function of the circuit it protects.

Dedicated circuits shall be provided for any large appliance or device (air conditioning units, large motors, etc.) that requires 60 percent or more of the rated capacity of the circuit to which it is connected, and that circuit shall serve no other purpose.

Wharton Fire Department

Heavy Rescue Specification

SVI

Panelboards

All fixed power sources shall be hardwired to a permanently mounted panelboard unless one of the following conditions exists:

- (1) All line voltage power connections are made through receptacles on the power source and the receptacles are protected by integrated overcurrent devices.
- (2) Only one circuit is hardwired to the power source, which is protected by an integrated overcurrent device.

The panel shall be visible and located so that there is unimpeded access to the panelboard controls. All panelboards shall be designed for use in their intended location. The panel(s) shall be protected from mechanical damage, tool mounting, and equipment storage.

Where the power source is 120/240 V and 120 V loads are connected, the apparatus manufacturer or line voltage system installer shall consider load balancing to the extent that it is possible.

Wiring Methods

Fixed wiring systems shall be limited to the following:

- (1) Metallic or nonmetallic liquid tight flexible conduit rated at temperatures not less than 194°F (90°C) with stranded copper wire rated for wet locations and temperatures not less than 194°F (90°C)
- (2) Type SOW, SOOW, SEOW, or SEOOW flexible cord rated at 600 V and at temperatures not less than 194°F (90°C)

Electrical cord or conduit shall not be attached to chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components, or low voltage wiring and shall be arranged as follows:

- (1) Separated by a minimum distance of 12 in. (300 mm) from exhaust piping or shielded from such piping
- (2) Separated from fuel lines by a minimum distance of 6 in. (150 mm)

A means shall be provided to allow "flexing" between the driving and crew compartment, the body, and other areas or equipment whose movement would stress the wiring.

Electrical cord or conduit shall be supported within 6 in. (150 mm) of any junction box and at a minimum of every 24 in. (600 mm) of run.

Supports shall be made of nonmetallic materials or of corrosion-resistant or corrosion-protected metal. All supports shall be of a design that does not cut or abrade the conduit or cord and shall be mechanically fastened to the apparatus.

Only fittings and components listed for the type of cord or conduit being installed shall be used.

Splices shall be made only in a listed junction box.

Additional Requirements for Flexible Cord Installations

Where flexible cord is used in any location where it could be damaged, it shall be protected by installation in conduit, enclosures, or guards.

Where flexible cord penetrates a metal surface, rubber or plastic grommets or bushings shall be installed.

Wharton Fire Department

Heavy Rescue Specification

SVI

Wiring Identification

Each line voltage circuit originating from the main panelboard shall be identified.

The wire or circuit identification either shall reference a wiring diagram or wire list or shall indicate the final termination point of the circuit.

Where prewiring for future power sources or devices exists, the un-terminated ends shall be marked with a label showing their wire size and intended function.

Wiring System Components

Only stranded copper conductors with an insulation rated for temperatures of at least 194°F (90°C) and wet locations shall be used. Conductors in flexible cord shall be sized in accordance with Table 400.5(A) of *NFPA 70*. Conductors used in conduit shall be sized in accordance with 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*. Aluminum or copper-clad aluminum conductors shall not be used.

All boxes shall conform to and be mounted in accordance with Article 314, "Outlet, Device, Pull, and Junction Boxes; Conduit Bodies; Fittings; and Manholes," of *NFPA 70*. All boxes shall be accessible using ordinary hand tools. Boxes shall not be permitted behind welded or pop-riveted panels.

The maximum number of conductors permitted in any box shall be in accordance with 314.16, "Number of Conductors in Outlet, Device, and Junction Boxes, and Conduit Bodies," of *NFPA 70*.

All wiring connections and terminations shall provide a positive mechanical and electrical connection. Connectors shall be installed in accordance with the manufacturer's instructions. Wire nuts or insulation displacement and insulation piercing connectors shall not be used.

Each switch shall indicate the position of its contact points (i.e., open or closed) and shall be rated for the continuous operation of the load being controlled. All switches shall be marked with a label indicating the function of the switch. Circuit breakers used as switches shall be "switch rated" (SWD) or better. Switches shall simultaneously open all associated line voltage conductors. Switching of the neutral conductor alone shall not be permitted.

Line voltage circuits controlled by low voltage circuits shall be wired through properly rated relays in listed enclosures that control all non-grounded current-carrying conductors.

Receptacles and Inlet Devices

Wet and Dry Locations

All wet location receptacle outlets and inlet devices, including those on hardwired, remote power distribution boxes, shall be of the grounding type, provided with a wet location cover, and installed in accordance with Section 406.8, "Receptacles in Damp or Wet Locations," of *NFPA 70*.

All receptacles located in a wet location shall be not less than 24 in. (600 mm) from the ground. Receptacles on off road fire apparatus shall be a minimum of 30 in. (750 mm) from the ground. All receptacles located in a dry location shall be of the grounding type and shall be at least 12 in. (300 mm) above the interior floor height. No receptacle shall be installed in a face-up position.

The face of any wet location receptacle shall be installed in a plane from vertical to not more than 45 degrees off vertical.

Wharton Fire Department

Heavy Rescue Specification

SVI

Wiring: All electrical wiring shall be fine stranded copper type THHN. The wire shall be sized to load and circuit breaker rating. Wiring shall be color coded and printed with function every 3" for easy identification.

Conduit: All 120/240 volt wiring in the apparatus body shall be through flexible moisture resistant reinforced conduit, with proper seal tight connectors and hardware.

Receptacle Label

Each receptacle shall be marked with a label indicating the nominal line voltage (120 volts or 240 volts) and the current rating in amps of the circuit. If the receptacle is DC or other than single phase, that information shall also be marked on the label.

All receptacles and electrical inlet devices shall be listed to UL 498, *Standard for Safety Attachment Plugs and Receptacles*, or other recognized performance standards.

Receptacles used for DC voltages shall be rated for DC service.

Wiring Schematics

An "As-Built" Wiring diagrams for line voltage systems shall be provided to include the following information;

- (a) Pictorial representations of circuit logic for all electrical components and wiring
- (b) Circuit identification
- (c) Connector pin identification
- (d) Zone location of electrical components
- (e) Safety interlocks
- (f) Alternator–battery power distribution circuits
- (g) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems

Wharton Fire Department

Heavy Rescue Specification

SVI

120/240 VAC SCENE LIGHTING

REAR TRIPOD SCENE LIGHTS

Two (2) Fire Research Focus, model FCA642-M10, tripod telescopic light shall be provided. The light pole shall be anodized aluminum and have a knurled twist lock mechanism to secure the extension pole in position. The extension pole shall extend 16" and rotate 360 degrees. An internal brake shall slow the extension pole during lowering. The outer pole shall be a grooved aluminum extrusion. The folding legs shall be anodized aluminum tubing with plastic endcaps. The fully extended tripod system shall exceed a height of 6' and be less than 3 1/2' when collapsed. Wiring shall extend from the pole bottom with a 4' retractile cord.

The lamphead shall have one (1) quartz halogen 1000 watt 120 volt bulb. The bulb shall draw 8.3 amps and generate 22,000 lumens. The bulb shall be accessible through the front. The lamphead shall direct 50 percent of the light onto the action area while providing 50 percent to illuminate the working area. The lamphead angle of elevation shall be adjustable at a pivot in the mounting arm and the position locked with a round knurled locking knob. The lamphead shall incorporate heat-dissipating fins and be no more than 5" deep by 3 3/8" high by 15" wide. Scene lights shall be provided with a lens or a means for preventing damage from water spray and shall be listed for wet location usage.

A weatherproof on-off toggle switch shall be mounted in a switchbox below the lamphead. A wire guard shall be furnished to protect the lamphead glass.

A tripod truck mount bracket set shall be provided for each light. Each set shall include a lower base plate, an upper lock with a quick release spring loaded locking pin, and a shim set.

Make: Fire Research
Model: Focus
P/N: FCA642-M10-ON-6F3

Wharton Fire Department

Heavy Rescue Specification

SVI

COMMAND LIGHT TOWER WITH METAL HALIDE BULB OPTION AND LOWER BANK BACKLIGHT

The apparatus shall be equipped with one (1) all-electric Command Light(s). The unit shall not require tapping into vehicle braking system to be operated, eliminating the chance for vehicle brake problems. Hydraulic or pneumatic type floodlights are not acceptable alternatives to the all-electric light tower specified.

Note: The Contractor will furnish the Command Light to the Body Manufacturer.

The light bank shall have four (4) weatherproof, 1,500 watt, 240-volt quartz halogen lights and (2) two 1,000 watt metal halide lights. Light heads shall be mounted in three (3) pairs, giving two (2) vertical lines of three (3) when the lights are in the upright position. Power for light bank shall be transmitted through power collecting rings thus allowing 360+ degree continuous rotation in either direction

The lower pair of light heads shall be capable of being rotated about a horizontal axis to provide light down on the vehicle or to the opposite side of the vehicle.

Positioning of the light bank shall be accomplished with maintenance free, heavy-duty 12-volt linear actuators.

The Command Light assembly shall be all aluminum construction, with stainless steel shafts and bronze bushings for long life and low maintenance.

Light tower shall be controlled with a hand-held umbilical line remote control. Command Light to be equipped with "Auto-Park" automatic nesting feature.

Command Light controls shall feature:

- Three (3) switches, one (1) for each light bank
- One (1) light bank rotation switch
- One (1) switch for elevating lower stage
- One (1) switch for elevating upper stage
- One (1) light to indicate when light bank is out of roof nest position
- One (1) light to indicate when light bank is rotated to proper nest position

Command Light controls shall be located per itemized compartment list.

The light tower shall have a full extension of 10' - 6" from mounted position and shall extend from nested position to full upright in 20 seconds.

The overall size of the nested light tower shall be approximately 48" wide x 73" long x 15.1/4" high, and weigh approximately 350 lbs.

A flashing warning light signal shall be provided indicating when a light tower is not in nested position as required by NFPA 1901.

The operational envelope of the mast shall be automatically illuminated whenever the mast assembly is being raised, lowered, or rotated as required by NFPA 1901.

The Command Light shall be covered by a One Year limited warranty from defects in materials and workmanship.

Wharton Fire Department

Heavy Rescue Specification

SVI

The specified light tower(s) shall be recessed into the roof of the apparatus body so that no part of the light tower extends above the roof line. The recessed area shall have two (2) water drain holes (in opposite corners) with flexible 1" diameter hose routed to the area below the body.

COMMAND LIGHT - KNIGHT TOWER w/ BACKLIGHT

The apparatus shall be equipped with one (1) all-electric floodlight tower(s). The unit shall not require tapping into vehicle braking system to be operated, eliminating the chance for vehicle brake problems. Hydraulic or pneumatic type floodlights are not acceptable alternatives to the all-electric light tower specified. NO EXCEPTIONS.

Note: The Contractor will furnish the Knight Light to the Body Manufacturer.

The light tower shall have six (6) weatherproof, 500 watt, 120 volt quartz halogen lights. Light heads shall be mounted in three (3) pairs, giving two (2) vertical lines of three (3) when the lights are in the upright position. The light tower shall have slip-rings for a full 360 degree rotation and capable of rotating either direction from a stowed position, NO EXCEPTIONS.

The lower pair of light heads shall be capable of being rotated about a horizontal axis to provide light down on the vehicle or to the opposite side of the vehicle.

The light tower shall be capable of overhanging the side or back of the vehicle (depending on mounting location) to provide maximum illumination and a warming area adjacent to the vehicle, NO EXCEPTIONS.

Positioning of the light bank shall be accomplished with maintenance free, heavy duty 12 volt linear actuators.

The light tower shall be all aluminum construction, with stainless steel shafts and bronze bushings for long life and low maintenance.

Light tower shall be controlled with a hand-held umbilical line remote control. The storage station for the remote control unit shall be equipped with a button to activate the "Auto-Park" automatic nesting feature.

Command Light controls shall include:

- Three (3) switches, one (1) for each light bank.
- One (1) light bank rotation switch.
- One (1) switch for elevating lower stage.
- One (1) switch for elevating upper stage.
- One (1) light to indicate when light bank is out of roof nest position.
- One (1) light to indicate when light bank is rotated to proper nest position.
- One (1) back light rotation switch
- One (1) "On/Off" switch for the top mounted strobe (optional)

The controls shall be located per the itemized compartment list.

The light tower shall have a full extension over 7' from mounted position and extend from nest position to full upright in 15 seconds. The overall size of nested light tower shall be approximately 23" wide x 47" long x 11 3/4" high, and weight approximately 120 lbs.

A flashing warning light shall be provided in cab, indicating when a light tower is not in nested position as required by NFPA 1901. The operational envelope of the mast shall be automatically illuminated whenever the mast assembly is being raised, lowered, or rotated as required by NFPA 1901.

Wharton Fire Department

Heavy Rescue Specification

SVI

The Command Light shall be covered by a one (1) year limited warranty from defects in materials and workmanship. An operation, maintenance, and parts manual shall be provided with the delivered apparatus.

The specified light tower(s) shall be recessed into the roof of the apparatus body so that no part of the light tower extends above the roof line. The recessed area shall have two (2) water drain holes (in opposite corners) with flexible 1" diameter hose routed to the area below the body.

EQUIPMENT

The following equipment shall be furnished with the completed Special Service vehicle;

- One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.
- There shall be two (2) NFPA approved aluminum wheel chocks provided for 44" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20 % grade, with the transmission in neutral, and the parking brake released.
 - The wheel chock(s) shall be mounted behind rear wheels, below body on streetside.
- One (1) Little Giant model 1AA -17 "A" frame type aluminum combination ladder(s) shall be provided with the completed unit. Ladder mounting shall be per itemized compartment list or specified by the WHARTON VOLUNTEER FIRE DEPARTMENT.
 - The ladder(s) shall be mounted on vehicle, per itemized compartment list.
- Two (2) Streamlight LiteBox Vehicle Mounting Systems shall be provided. Each flashlight shall be orange in color. Each flashlight shall have a 12 volt DC charger and vehicle mount kit. Each flashlight shall have a 20 watt spotlight style bulb and reflector. The flashlights shall be wired to batter direct unless otherwise specified by the customer.
 - The flashlight(s) shall be mounted on the completed unit, locations as per the WHARTON VOLUNTEER FIRE DEPARTMENT.