

City of Jasper Fire Department

Production Specification

Contents

INTERNET IN-PROCESS SITE	7
HIGHWAY PERFORMANCE	7
SERVICEABILITY	7
FIRE APPARATUS DOCUMENTATION	8
OPERATIONS AND SERVICE DOCUMENTATION	9
NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVE	10
STATEMENT OF EXCEPTIONS	10
CARRYING CAPACITY	10
TESTING	12
ROAD TEST	12
LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST	12
TEST SEQUENCE	12
1. RESERVE CAPACITY TEST	13
2. ALTERNATOR PERFORMANCE TEST	13
TEST AT IDLE	13
TEST AT FULL LOAD	13
3. LOW VOLTAGE ALARM TEST	13
LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST	13
DOCUMENTATION	13
UL 120/240 VAC CERTIFICATION	14
DIELECTRIC VOLTAGE WITHSTAND TEST	15
WARRANTY	15
GENERAL LIMITED WARRANTY - TWO (2) YEARS	16
LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS	16
STRUCTURAL WARRANTY - TEN (10) YEARS	16
UNDERCOAT WARRANTY	16
PAINT LIMITED WARRANTY - TEN (10) YEARS	16
GRAPHICS LIMITED WARRANTY	16
CONSTRUCTION PERIOD	16

City of Jasper Fire Department

Production Specification

OVERALL HEIGHT REQUIREMENT	16
OVERALL LENGTH	17
OVERALL WIDTH	17
PRE-CONSTRUCTION CONFERENCE	17
FINAL INSPECTION CONFERENCE	17
DELIVERY AND DEMONSTRATION	17
FERRARA CAB CHASSIS SPECIFICATION	18
CHASSIS MODIFICATIONS	54
LUBRICATION AND TIRE DATA PLATE	54
VEHICLE DATA PLATE	55
OVERALL HEIGHT, LENGTH DATA PLATE (US)	55
FRONT BUMPER EXTENSION	56
BUMPER GRAVEL SHIELD	56
RESCUE BUMPER COMPARTMENT	57
AIR HORN(S)	58
GROUND LIGHTS	58
FRONT TOW PROVISIONS	58
EXHAUST	58
SEAT BELT COLOR	58
SEAT BELT WEB LENGTH - CUSTOM CAB	59
SEAT BELT / VDR SYSTEM - CUSTOM CAB	59
HELMET STORAGE	59
HELMET STORAGE	59
CAB CRASH TEST CERTIFICATION	59
CAB MIRRORS, DRIVER ADJUSTABLE	59
MUDFLAPS	59
AIR BRAKE SYSTEM QUICK BUILD-UP	59
ROAD EMERGENCY SAFETY KIT	60
CAB INTERIOR CABINET - CENTER REAR WALL	60
FUEL FILL	60
BODY DESIGN	60

City of Jasper Fire Department

Production Specification

EXTERIOR ALUMINUM BODY	61
ROOF CONSTRUCTION WITH COMPARTMENTS	62
BODY SUBFRAME	62
BODY MOUNTING	63
10" REAR STEP BUMPER	63
REAR TOW EYES	63
GROUND LIGHTS	63
WHEEL WELL EXTERIOR PANEL	63
STAINLESS STEEL BODY FENDERS	63
WHEEL WELL LINERS	63
BODY PAINT SPECIFICATIONS	64
BODY PAINT PREPARATION	64
PAINT PROCESS	64
BODY UNDERCOATING	65
UNDERCOAT WARRANTY	65
PAINT WARRANTY	65
COMPARTMENT INTERIOR FINISH	66
REFLECTIVE STRIPE REQUIREMENTS	66
REFLECTIVE STRIPE - CAB SIDE	66
REFLECTIVE STRIPE - CAB FRONT	66
CHEVRON STRIPE - CAB BUMPER	67
REFLECTIVE STRIPE - BODY SIDES	67
CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS	67
LETTERING	68
SIDE CAB DOOR LETTERING	68
UPPER BODY SIDE LETTERING	68
REAR BODY LETTERING	68
FRONT OF CAB LETTERING	68
DIAL 911	68
LETTERING ALLOWANCE	68
EXTERIOR COMPARTMENT DOORS	69

City of Jasper Fire Department

Production Specification

ROLL-UP DOOR CONSTRUCTION - AMDOR	69
BODY HEIGHT MEASUREMENTS	69
ROOF ACCESS STAIRWAY	71
STEP COMPARTMENT(S) - LOWER	71
STEP COMPARTMENT - UPPER	71
FOLD-DOWN STEP	72
REAR BODY HANDRAILS	72
BODY WIDTH DIMENSIONS	72
STREETSIDE COMPARTMENT - FRONT (S1)	72
COMPARTMENT LAYOUT	73
STREETSIDE COMPARTMENT - AHEAD OF REAR WHEELS (S2)	74
COMPARTMENT LAYOUT	75
STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S3)	75
COMPARTMENT LAYOUT	76
STREETSIDE COMPARTMENT - REAR (S4)	77
COMPARTMENT LAYOUT	77
CURBSIDE COMPARTMENT - FRONT (C1)	78
COMPARTMENT LAYOUT	79
CURBSIDE COMPARTMENT - AHEAD OF REAR WHEEL (C2)	80
COMPARTMENT LAYOUT	80
CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C3)	82
COMPARTMENT LAYOUT	82
CURBSIDE COMPARTMENT - REAR (C4)	83
COMPARTMENT LAYOUT	83
ROOF ACCESS STAIRWAY	84
STAIRWAY HANDRAILS	84
ROPE ANCHOR OR PORTABLE WINCH RECEIVERS	84
LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC	86
12 VOLT DIAGNOSTIC RELAY CONTROL CENTER	89
ROCKER SWITCH PANEL	89
BATTERY SWITCH	90

City of Jasper Fire Department

Production Specification

BATTERY SOLENOID	90
BATTERY CONDITIONER	91
ENGINE COMPARTMENT LIGHT	91
CAB HAZARD WARNING LIGHT	91
BACK-UP ALARM	91
REAR VIEW CAMERA	91
TAIL LIGHTS	91
MIDSHIP MARKER/TURN SIGNAL	92
MARKER LIGHTS	92
REAR BUMPER MARKER LIGHTS	92
CAB STEP LIGHTS / GROUND LIGHTS	92
LICENSE PLATE LIGHT	92
ELECTRONIC SIREN	92
SIREN SPEAKER	93
TRAFFIC DIRECTIONAL LIGHT	93
WARNING LIGHT PACKAGE	93
UPPER LEVEL OPTICAL WARNING DEVICES	94
LOWER LEVEL OPTICAL WARNING DEVICES	95
ONAN PTO GENERATOR	96
GENERATOR ENGAGEMENT	97
WARRANTY PERIOD	97
GENERATOR SPLASH GUARD	97
GENERATOR MOUNTING	97
MANUALS AND SCHEMATICS	97
POWER-TAKE-OFF GENERATOR DRIVE	97
LOADCENTER	98
GENERATOR MONITORING PANEL	98
SHORE POWER INLET - BATTERY CHARGER	98
OUTLETS AND CIRCUITS	99
LINE VOLTAGE ELECTRICAL SYSTEM	99
GENERAL REQUIREMENTS	99

City of Jasper Fire Department

Production Specification

120/240 VAC SCENE LIGHTING	107
SIDE UPPER RECESSED SCENE LIGHTS	107
LIGHT TOWER	107
Light Tower Paint	108
EQUIPMENT PAYLOAD WEIGHT ALLOWANCE	109
EQUIPMENT	109
REMAINING NFPA MINOR EQUIPMENT BY PURCHASER	111

City of Jasper Fire Department

Production Specification

INTERNET IN-PROCESS SITE

The manufacturer shall post and maintain a website where the City of Jasper Fire Department will be able to view digital images of their apparatus as its being built. The digital images shall be posted once a week starting when the body begins production or when the cab/chassis arrives and shall continue until the final completion of unit.

VEHICLE STABILITY SUPPLIED WITH CAB/CHASSIS

The cab/chassis shall be equipped with a stability control system. The system shall have, at a minimum, a steering wheel position sensor, a vehicle yaw sensor, a lateral accelerometer and individual wheel brake controls.

FIRE APPARATUS PERFORMANCE

The fire apparatus shall meet the requirements of this standard at elevations of 2000 ft (600 m) above sea level.

The fire apparatus shall meet all the requirements of this standard while stationary on a grade of 6 percent in any direction.

The fire apparatus shall meet the requirements of this standard in ambient temperature conditions between 32°F (0°C) and 110°F (43°C).

HIGHWAY PERFORMANCE

The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

- 1) Accelerating from 0 to 35 mph (55 km/hr) within 25 seconds on a 0 percent grade
- 2) Attaining a speed of 50 mph (80 km/hr) on a 0 percent grade
- 3) Maintaining a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent

The maximum top speed of fire apparatus with a GVWR over 26,000 lb (11,800 kg) shall not exceed either 68 mph (109 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gal (4732 L), or the GVWR of the vehicle is over 50,000 lb (22,680 kg), the maximum top speed of the apparatus shall not exceed either 60 mph (95 km/hr) or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

SERVICEABILITY

The fire apparatus shall be designed to allow the manufacturer's recommended routine maintenance checks of lubricant and fluid levels to be performed by the operator without lifting the cab of a tilt-cab apparatus or without the need for hand tools.

Where special tools are required for routine service on any component of the apparatus, such tools shall be provided with the apparatus.

City of Jasper Fire Department

Production Specification

Apparatus components that interfere with repair or removal of other major components shall be attached with fasteners, such as cap screws and nuts, so that the components can be removed and installed with ordinary hand tools. These components shall not be welded or otherwise permanently secured into place.

FIRE APPARATUS DOCUMENTATION

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

- 1) The manufacturer's record of apparatus construction details, including the following documents:
 - a) Owner's name and address
 - b) Apparatus manufacturer, model, and serial number
 - c) Chassis make, model, and serial number
 - d) GAWR of front and rear axles and GVWR
 - e) Front tire size and total rated capacity in pounds (kilograms)
 - f) Rear tire size and total rated capacity in pounds (kilograms)
 - g) Chassis weight distribution in pounds (kilograms) with water and manufacturer-mounted equipment (front and rear)
 - h) Engine make, model, serial number, rated horsepower and related speed, and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio
 - i) Type of fuel and fuel tank capacity
 - j) Electrical system voltage and alternator output in amps
 - k) Battery make, model, and capacity in cold cranking amps (CCA)
 - l) Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
 - m) Ratios of all driving axles
 - n) Maximum governed road speed
 - o) Pump make, model, rated capacity in gallons per minute (liters per minute where applicable), maximum discharge pressure capability rating, and serial number
 - p) Pump transmission make, model, serial number, and gear ratio
 - q) Auxiliary pump make, model, rated capacity in gallons per minute (liters per minute where applicable), and serial number
 - r) Water tank certified capacity in gallons or liters
 - s) Foam tank (if provided) certified capacity in gallons (liters)
 - t) Aerial device type, rated vertical height in feet (meters), rated horizontal reach in feet (meters), and rated capacity in pounds (kilograms)
 - u) Paint manufacturer and paint number(s)
 - v) Company name and signature of responsible company representative
 - w) Weight documents from a certified scale showing actual loading on the front axle, rear axle(s), and overall fire apparatus (with the water tank full but without personnel, equipment, and hose)
- 2) Certification of compliance of the optical warning system (*see 13.8.16*)
- 3) Siren manufacturer's certification of the siren (*see 13.9.1.1*)
- 4) Written load analysis and results of the electrical system performance tests (*see 13.14.1 and Section 13.15*)
- 5) Certification of slip resistance of all stepping, standing, and walking surfaces (*see 15.7.4.5*)
- 6) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability (*see 16.2.4.1*)
- 7) If the apparatus is equipped with a fire pump and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions (*see 16.2.4.2*)
- 8) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications (*see 16.3.1*)
- 9) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed (*see 16.3.2.2*)

City of Jasper Fire Department

Production Specification

- 10) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test (see 16.5.2.2)
- 11) If the apparatus has a fire pump with a maximum discharge pressure capability rating that exceeds the hydrostatic test pressure of 16.5.2.1, the pump manufacturer's certification of the hydrodynamic test
- 12) If the apparatus has a fire pump, the certification of inspection and test for the fire pump (see 16.13.1.1.5 or 16.13.1.2.4 as applicable)
- 13) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test (see Section 17.13)
- 14) When the apparatus is equipped with a water tank, the certification of water tank capacity (see Section 18.6)
- 15) If the apparatus has an aerial device, the certification of inspection and test for the aerial device (see Section 19.24)
- 16) If the apparatus has an aerial device, all the technical information required for inspections to comply with NFPA 1911
- 17) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy (see 20.10.4.2) and the final installer's certification the foam proportioning system meets this standard (see 20.11.2)
- 18) If the system has a CAFS, the documentation of the manufacturer's pre delivery tests (see Section 21.9)
- 19) If the apparatus has a line voltage power source, the certification of the test for the power source (see 22.15.7.2)
- 20) If the apparatus is equipped with an air system, air tank certificates (see 24.5.1.2), the SCBA fill station certification (see 24.9.6), and the results of the testing of the air system installation (see 24.14.5 and 24.15.4)
- 21) Any other required manufacturer test data or reports

OPERATIONS AND SERVICE DOCUMENTATION

The contractor shall deliver with the fire apparatus complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service, and operations of the fire apparatus and all major components thereof.

The contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- 1) Manufacturer's name and address
- 2) Country of manufacture
- 3) Source for service and technical information
- 4) Parts replacement information
- 5) Descriptions, specifications, and ratings of the chassis, pump (if applicable), and aerial device (if applicable)
- 6) Wiring diagrams for low voltage and line voltage systems to include the following information:
 - a) Pictorial representations of circuit logic for all electrical components and wiring
 - b) Circuit identification
 - c) Connector pin identification
 - d) Zone location of electrical components
 - e) Safety interlocks
 - f) Alternator–battery power distribution circuits
 - g) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- 7) Lubrication charts
- 8) Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
- 9) Precautions related to multiple configurations of aerial devices, if applicable
- 10) Instructions regarding the frequency and procedure for recommended maintenance
- 11) Overall apparatus operating instructions

City of Jasper Fire Department

Production Specification

- 12) Safety considerations
- 13) Limitations of use
- 14) Inspection procedures
- 15) Recommended service procedures
- 16) Troubleshooting guide
- 17) Apparatus body, chassis and other component manufacturer's warranties
- 18) Special data required by this standard
- 19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus
- 20) One copy of the latest edition of FAMA's *Fire Apparatus Safety Guide*

The contractor shall deliver with the apparatus all manufacturer's operations and service documents supplied with components and equipment that are installed or supplied by the contractor.

NFPA REQUIRED DOCUMENTATION FORMAT - USB FLASH DRIVE

The vehicle construction details and the operations and service documentation as required per NFPA 1901 latest edition shall be provided on a USB Flash Drive. These manuals shall be divided into sections for ease of reference. There shall be two (2) USB flash drives provided with the completed vehicle.

FIRE APPARATUS SAFETY GUIDE

A Fire Apparatus Safety Guide published by Fire Apparatus manufacturer's Association shall be provided with delivered vehicle. This manual includes essential safety information for fire fighters, fire chiefs, apparatus mechanics, and fire department safety officers. The guide is applicable to municipal, wildland, and airport fire fighting apparatus manufactured on either custom or commercial chassis.

STATEMENT OF EXCEPTIONS

The final-stage manufacturer shall deliver with the fire apparatus either a certification that the apparatus fully complies with all requirements of this standard or alternatively, a Statement of Exceptions specifically describing each aspect of the completed apparatus that is not fully compliant with the requirements of this standard at the time of delivery.

The Statement of Exceptions shall contain, for each noncompliant aspect of the apparatus or missing required item, the following information:

- 1) A separate specification of the section of the applicable standard for which compliance is lacking
- 2) A description of the particular aspect of the apparatus that is not in compliance therewith or required equipment that is missing
- 3) A description of the further changes or modifications to the delivered apparatus that must be completed to achieve full compliance
- 4) Identification of the entity that will be responsible for making the necessary post delivery changes or modifications or for supplying and installing any missing required equipment to the apparatus to achieve full compliance with this standard

Prior to or at the time of delivery of the apparatus, the Statement of Exceptions shall be signed by an authorized agent of the entity responsible for final assembly of the apparatus and by an authorized agent of the purchasing entity, indicating mutual understanding and agreement between the parties regarding the substance thereof.

CARRYING CAPACITY

City of Jasper Fire Department

Production Specification

The GAWR and the GCWR or GVWR of the chassis shall be adequate to carry the weight of the completed vehicle when loaded to its estimated in-service weight. The Body Manufacturer shall establish the estimated in service weight during the design of the vehicle

The estimated in-service weight shall include the following:

- 5) The chassis, body and tank(s)
 1. Full fuel, lubricant, and other chassis or component fluid tanks or reservoirs
 2. Full water and other agent tanks
 3. *250 lb (114 kg) in each seating position
 4. Fixed equipment such as pumps, aerial devices, generators, reels and air systems as installed
 5. Ground ladders, suction hose, designed hose load in their hose beds and on their reels
 6. An allowance for miscellaneous equipment that is the greatest of the following:
 7. The values shown in Table 12.1.2
 - h) A purchaser-provided list of equipment to be carried with weights
 - i) A purchaser-specified miscellaneous equipment allowance

The manufacturer shall engineer and design the fire apparatus such that the completed apparatus, when loaded to its estimated in-service weight, with all movable weights distributed as close as is practical to their intended in-service configuration, does not exceed the GVWR.

A final manufacturer's certification of the GVWR or GCWR, along with a certification of each GAWR, shall be supplied on a label affixed to the vehicle.

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed unequipped fire apparatus in feet and inches (meters), the length of the completed fire apparatus in feet and inches (meters), and the GVWR in tons (metric tons).

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

Apparatus Type	Equip. Storage Area	Apparatus Size	Equipment Allowance	
			lb.	kg.
Special Service Fire Apparatus	Minimum of 120 cu ft (3.4 cu mt) of enclosed compartmentation.	10,000 lb to 15,000 lb (4,500 kg to 7,000 kg) GVWR	2,000	910
		15,001 lb to 20,000 lb (7,001 kg to 9,000 kg) GVWR	2,500	1,135
		20,001 lb to 30,000 lb (9,001 kg to 14,000 kg) GVWR	3,000	1,350
		30,001 lb to 40,000 lb (14,001 kg to 18,000 kg) GVWR	4,000	1,800
		40,001 lb to 50,000 lb (18,001 kg to 23,000 kg)	6,000	2,700

City of Jasper Fire Department

Production Specification

		GVWR		
		50,001 lb to 60,000 lb (23,001 kg to 27,000 kg) GVWR	8,000	3,600
		60,001 lb and up (27,001 kg) GVWR	10,000	4,500

TESTING

ROAD TEST

Road test shall be conducted in accordance with this section to verify that the completed apparatus is capable of compliance with Roadability Section.

The tests shall be conducted at a location and in a manner that does not violate local, state or provincial or federal traffic laws.

The tests shall be conducted on dry, level, paved roads that are in good condition. The apparatus shall be loaded to its estimated in service weight.

The engine shall not operate in excess of the maximum governed speed. Acceleration tests shall consist of two runs in opposite directions over the same route. The fire apparatus shall attain a speed of 35 mph (55 km/hr) from a standing start within 25 seconds. The fire apparatus shall attain a minimum top speed of 50 mph (80 km/hr).

If the apparatus is equipped with an auxiliary braking system, the Body Manufacturer shall road test the system to confirm that the system is functioning as intended by the auxiliary braking system manufacturer.

If the apparatus is equipped with an air brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 20 mph (32.2 km/hr) in a distance not exceeding 35 ft (10.7 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

If the apparatus is equipped with a hydraulic brake system, the service brakes shall bring the apparatus, when loaded to its GVWR, to a complete stop from an initial speed of 30 mph (48.2 km/hr) in a distance not exceeding 88 ft (26.8 m) by actual measurement on a paved, level, dry surface road that is free of loose material, oil or grease.

LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST

The vehicles low voltage electrical system shall be tested and certified by the manufacturer. The certified test results shall be delivered with the completed vehicle. Tests shall be performed when the air temperature is between 0°F and 110°F (-18°C and 43°C).

TEST SEQUENCE

The following three (3) tests shall be performed in the order in which they appear below. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for ten (10) minutes. Failure of any of these tests shall require a repeat of the sequence.

City of Jasper Fire Department

Production Specification

1. RESERVE CAPACITY TEST

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

2. ALTERNATOR PERFORMANCE TEST

TEST AT IDLE

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

TEST AT FULL LOAD

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the warning system required in 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system, 23.6 V dc for a 24 V nominal system, or 35.4 V dc for a 42 V nominal system for more than 120 seconds shall be considered a test failure.

3. LOW VOLTAGE ALARM TEST

The following test shall be started with the engine off and the battery voltage at or above 12 V for a 12 V nominal system, 24 V for a 24 V nominal system or 36 V for a 42 V nominal system.

With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals.

The test shall be considered a failure if the alarm does not sound in less than 140 seconds after the voltage drops to 11.70 V for a 12 V nominal system, 23.4 V dc for a 24 V nominal system, or 35.1 V for a 42 V nominal system.

The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

LOW VOLTAGE - ELECTRICAL SYSTEM PERFORMANCE TEST

DOCUMENTATION

The manufacturer shall deliver the following with the fire apparatus:

- j) Documentation of the electrical system performance tests

City of Jasper Fire Department

Production Specification

- 1) A written electrical load analysis, including the following:
 - 2) The nameplate rating of the alternator
 - a) The alternator rating
 - b) Each of the component loads specified that make up the minimum continuous electrical load
 - c) Additional electrical loads that, when added to the minimum continuous electrical load, determine the total continuous electrical load
 - d) Each individual intermittent electrical load

UL 120/240 VAC CERTIFICATION

The 120/240 volt electrical system shall be third-party, independent, audit-certified through Underwriters Laboratory (UL) to the current edition of NFPA 1901 to perform as listed below;

The prime mover shall be started from a cold start condition, and the unloaded voltage and frequency shall be recorded.

The line voltage electrical system shall be loaded to at least 100% of the continuous rated wattage stated on the power source specification label. Testing with a resistive load bank shall be permitted.

The power source shall be operated in the manner specified by the apparatus manufacturer as documented on instruction plates or in operation manuals. The power source shall be operated at a minimum of 100% of the continuous rated wattage as stated on the power source specification label for a minimum of two (2) hours.

The load shall be adjusted to maintain the output wattage at or above the continuous rated wattage during the entire 2-hour test.

The following conditions shall be recorded at least every 1/2 hour during the test:

- e) The power source output voltage, frequency and amperes
 - 1) The prime mover's oil pressure, water temperature and transmission temperature, if applicable
 - 2) The power source hydraulic fluid temperature, if applicable
 - 3) The ambient temperature and power source air inlet temperature

The following conditions shall be recorded once during the test for power sources driven by dedicated auxiliary internal combustion engines:

- 4) Altitude
 - 1) Barometric pressure
 - 2) Relative humidity

If the generator is driven by the chassis engine and the generator allows for operation at variable speeds, the chassis engine speed shall be reduced to the lowest rpm allowed for generator operation and the voltage and frequency shall be recorded.

The load shall be removed and the unloaded voltage and frequency shall be recorded.

Voltage shall be maintained within $\pm 10\%$ of the voltage stated on the power source specification label during the entire test. Frequency shall be maintained within ± 3 Hz of the frequency stated on the power source specification label during the entire test.

The total continuous electrical loads, excluding those loads associated with the equipment defined in NFPA 22.15.7.3.11.2, shall be applied during the testing unless an auxiliary engine drives the power source.

City of Jasper Fire Department

Production Specification

If the apparatus is equipped with a fire pump, the 2-hour certification test of the power source shall be completed with the fire pump pumping at 100% capacity at 150 psi (1000 kPa) net pump pressure. The test shall be permitted to be run concurrently with the pump certification test.

DOCUMENTATION

The Body Manufacturer shall deliver the following with the fire apparatus:

The results of each test shall be recorded on an appropriate form and provided with the delivery of the fire apparatus.

DIELECTRIC VOLTAGE WITHSTAND TEST

The line voltage wiring and permanently connected devices and equipment shall be subjected to a dielectric voltage withstand test of 900 volts for one (1) minute. The testing shall be performed after all body work has been completed.

The test shall be conducted as follows:

- 3) Isolate the power source from the panel board and disconnect any solid state low voltage components
 - 1) Connect one lead of the dielectric tester to all the hot and neutral buses tied together
 - 2) Connect the other lead to the fire apparatus frame or body
 - 3) Close any switches and circuit breakers in the circuit(s)
 - 4) Apply the dielectric voltage for one (1) minute in accordance with the testing equipment manufacturer's instructions

The electrical polarity of all permanently wired equipment, cord reels and receptacles shall be tested to verify that wiring connections have been properly made.

Electrical continuity shall be verified from the chassis or body to all line voltage electrical enclosures, light housings, motor housings, light poles, switch boxes and receptacle ground connections that are accessible to fire fighters in normal operations.

If the apparatus is equipped with a transfer switch, it shall be tested to verify operation and that all non grounded conductors are switched.

Electrical light towers, floodlights, motors, fixed appliances and portable generators shall be operated at their full rating or capacity for 30 minutes to ensure proper operation.

WARRANTY

A full statement shall be provided of the warranties for the vehicle(s) being bid. Warranties should clearly describe the terms under which the vehicle manufacturer accepts responsibility for the cost to repair defects caused by faulty design, quality of work or material and for the applicable period of time after delivery.

Cost of repairs refers to all costs related thereto including, but not limited to, the cost of materials and the cost of labor.

The Body Manufacturer shall warrant all materials and accessories used on the vehicle(s), whether fabricated by manufacturer or purchased from an outside source and will deal directly with the City of Jasper Fire Department

City of Jasper Fiire Department

Production Specification

on all warranty work.

GENERAL LIMITED WARRANTY - TWO (2) YEARS

The vehicle shall be free of defects in material and workmanship for a period of two (2) years or 36,000 miles (or 57,936 kilometers), whichever occurs first starting thirty (30) days after the original invoice date.

The Contractor must be the "single source" coordinator of all warranties on the vehicle.

LOW VOLTAGE ELECTRICAL WARRANTY - FIVE (5) YEARS

The vehicle low voltage electrical system shall be free of defects in material and workmanship for a period of five (5) years or 60,000 miles (or 96,561 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

STRUCTURAL WARRANTY - TEN (10) YEARS

The body shall be free of structural or design failure or workmanship for a period of ten (10) years, or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date.

UNDERCOAT WARRANTY

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

PAINT LIMITED WARRANTY - TEN (10) YEARS

The body shall be free of bubbling or peeling as a result of a defect in the method of manufacture for a period of ten (10) years or 100,000 miles (or 160,934 kilometers), whichever occurs first, starting thirty (30) days after the original invoice date. **Pro-rated warranties will not be acceptable.**

GRAPHICS LIMITED WARRANTY

The 3M graphics installation shall be warranted for a period of two (2) years. The 3M materials installed on completed vehicle shall be warranted for seven (7) years. The 3M Diamond grade film (if specified) shall be warranted for ten (10) years.

CONSTRUCTION PERIOD

The completed vehicle shall be delivered within three hundred sixty five (365) days after receipt of a purchase order or contract.

Contractor shall not be held liable for delays of chassis delivery due to accidents, strikes, floods or other events not subject to their control. Contractor shall provide immediate written notice to City of Jasper Fiire Department as to delays and to what extent these delays have in completing vehicle within the stated construction time period.

OVERALL HEIGHT REQUIREMENT

City of Jasper Fiire Department

Production Specification

The overall height (OAH) of the vehicle shall not exceed 124 (10' - 4") from the ground. This measurement shall be taken on flat ground with the tires properly inflated, in the unloaded condition, at that highest point of the vehicle.

OVERALL LENGTH

The overall length (OAL) of the vehicle shall not exceed 402" (33' - 6").

OVERALL WIDTH

The overall width (OAW) of the body at drip rails shall be 102" (8' - 6"), and body shall be 100" (8' - 4").

ANGLE OF APPROACH

The angle of approach for this vehicle shall not be less than eight (8) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1901.

ANGLE OF DEPARTURE

The angle of departure for this vehicle shall not be less than eight (8) degrees when it is loaded to the estimated in-service weight as specified by the current edition of NFPA 1901.

PRE-CONSTRUCTION CONFERENCE

A pre-construction conference shall be required at the Contractor's factory for four (4) personnel from the City of Jasper Fiire Department to finalize all construction details prior to manufacturing.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the pre-construction conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

FINAL INSPECTION CONFERENCE

A final inspection conference shall be required at the Contractor's factory for four (4) personnel from the City of Jasper Fiire Department to inspect the vehicle and construction details prior to shipment of the completed vehicle. This inspection shall take place after any specified striping and lettering is installed.

The Contractor shall at his/her expense, provide transportation, lodging, rental car and meal expenses during the final inspection conference. Any travel distance greater than 250 miles shall be by non-stop commercial air travel.

DELIVERY AND DEMONSTRATION

The Contractor shall be responsible for the delivery of the completed unit to the City of Jasper Fiire Department's location. On initial delivery of the apparatus, the Contractor shall supply a qualified representative to demonstrate the apparatus and provide initial instruction to representatives of the City of Jasper Fiire Department regarding the operation, care and maintenance of the apparatus and equipment supplied at City of Jasper Fiire Department location.

The Delivery Engineer shall set delivery and instruction schedule with the person appointed by City of Jasper Fiire Department.

After delivery of the apparatus, the City of Jasper Fiire Department shall be responsible for ongoing training of its

City of Jasper Fire Department

Production Specification

personnel to proficiency regarding the proper and safe use of the apparatus and associated equipment.

FERRARA CAB CHASSIS SPECIFICATION

One (1)

CUSTOM CHASSIS

It is the intent of the technical specifications contained herein to ensure the custom cab and chassis specified shall be engineered, designed, and manufactured exclusively for heavy-duty continuous use in extreme environments and rigorous adverse conditions.

Each custom cab and chassis shall be manufactured in strict compliance with all applicable requirements as set forth in the current edition of the NFPA (National Fire Protection Association) pamphlet 1901 with maximum safety as the key focus throughout the design and development phase of each fire and rescue chassis.

One (1)

FRONT BUMPER EXTENSION

There shall be a twenty-eight inch (28") frame extension provided. The extension shall be made from heavy-duty steel in both C-channel and tubular shapes. The frame rail extension material shall measure 7" high x 3-1/2" wide x .375" wall thickness.

Extension shall be bolted to the chassis frame rails through reinforcement plates, backed by the engine mounting crossmember. Fasteners utilized shall be Grade 8 bolts.

One (1)

TOW EYES, FRONT

Two-(2) heavy-duty painted tow eyes shall be mounted to the bottom of the front bumper frame extension rails fabricated from 1" thick steel. The tow eyes shall have an inside eye diameter of 2.0" with chamfered edge. The tow eyes shall be attached with Grade 8 bolts.

One (1)

FRONT BUMPER

There shall be a 12" high, two rib front bumper constructed of highly polished, 10 gauge stainless steel. The bumper shall be a full wrap around type extending across the entire width of the cab. The return portion of the wrap around shall make up the majority of the bumper extension, measuring up to 24" in length.

There shall be a structural steel backing plate to reinforce the stainless steel bumper. This backing plate shall match the contour of the stainless steel bumper and shall be fabricated from 1/4" steel C-channel. The backing plate shall be attached to the chassis frame rails with Grade 8 bolts.

One (1)

MECHANICAL SIREN

One (1) Federal Signal Q2B siren model Q2B-012NNSD electro-mechanical siren shall be installed thru the front bumper centered between the frame rails. The Q2B siren shall be a streamlined, chrome plated siren designed to provide reliable and long-life operation. The electro-mechanical siren shall produce the distinctive Q2B sound that is a registered trademark of Federal Signal, and shall be provided with a heavy duty clutch and an electric brake.

City of Jasper Fire Department

Production Specification

The Q2B siren shall measure 10.5" high x 14" long x 10" deep and shall produce 123 decibels at ten feet. The siren shall operate off the vehicles 12V system. The Q2B siren shall be recess mounted in the front of the vehicle.

The siren brake switch shall be located within reach of the driver.

One (1)

SIREN WIRING

The siren activation switch shall be wired thru the chassis park brake and operate in the "Response Mode" only.

One (1)

SIREN FOOT SWITCHES

Two-(2) foot operated switches shall be installed, one-(1) on each side on the driver and officer's side wired to the mechanical siren.

One (1)

AIR HORN, PASSENGER'S SIDE

There shall be one-(1) 24" long Grover air horn installed in compliance with NFPA thru the front bumper, passenger's side, outboard of the frame rail. The air horn shall be plumbed to the chassis, air supply system thru an air protection valve, and manufactured from spun brass material with an easily separated die cast sounding unit for serviceability.

One (1)

AIR HORN, DRIVER'S SIDE

There shall be one-(1) 24" long Grover air horn installed in compliance with NFPA thru the front bumper, driver's side, outboard of the frame rail. The air horn shall be plumbed to the chassis, air supply system thru an air protection valve, and manufactured from spun brass material with an easily separated die cast sounding unit for serviceability.

One (1)

SPEAKER, DRIVER'S SIDE

There shall be one-(1) speaker shall be installed thru the front face of the bumper, driver's side, outboard.

One (1)

The speaker shall be a Cast Products, 100-watts wired to the electronic siren.

One (1)

AIR HORN CONTROL, LANYARD

There shall be one-(1) Lanyard air horn control installed in the cab between the driver and the officer. The Lanyard shall be wired thru the chassis air brake system.

One (1)

AIR HORN WIRING

The air horns shall be active in both the "Scene" and "Response Mode".

One (1)

FRONT AXLE

City of Jasper Fire Department

Production Specification

The front axle shall be a Meritor MFS-20 with 20,000-pound capacity equipped with oil seals and transparent cover for oil level inspection.

One (1)

CHASSIS CAB TO AXLE

The chassis wheelbase shall be 134 inches.

One (1)

CHASSIS FRAME RAILS

The chassis frame rails shall be constructed of 110,000-PSI minimum yield steel that has been formed into a "C" channel shape with dimension of 10.50" x 3.50" x .375 inches.

An inner frame liner of 110,000 Pound minimum yield with dimension of 9.69" x 3.13" x .313" shall be provided for additional strength and to reduce deflection. The frame liner shall run from centerline of front axle to rear of the mainframe rail. This liner shall be mitered at 45 degrees at the front axle.

The resulting frame system shall have a minimum section modulus of 30.38 cubic inches with a resisting bending moment of 3,342,000-inch pounds per rail.

The frame rails shall be powder coated in order to insure superior paint adhesion. Frame cutouts for the engine shall be made with a plasma torch in order to minimize the heat-affected zone caused by the cut.

All frame-mounted components shall be secured with grade eight bolts with hardened washers and distorted thread locknuts. Flanged head bolts with nylon locking nuts, or huck bolts shall not be acceptable.

One (1)

PAINT, FRAME RAIL

The frame and running gear shall be painted gloss enamel black. The running gear shall consist of the axles, drivelines, air tanks, steering gear, frame mounted brackets, drag link, and fuel tank.

The air system piping and electrical harnesses shall not be installed until after the paint has cured. This shall insure complete coverage behind those items as well as that air piping and wiring harnesses are not.

One (1)

STEERING SYSTEM

The steering system shall be a package certified by TRW for the application. All components from the steering column to the drag link shall be manufactured by TRW.

The steering system shall use a TAS-65 steering gear with an RCS-55 slave gear, which has the capacity to static steer the chassis loaded to 21,500 pounds with 425-size tires. The use of two-(2) equal size gears or a single gear with an assist cylinder shall not be acceptable.

One (1)

CHASSIS ALIGNMENT

The chassis frame rails shall be measured to insure the length is correct and cross checked to make sure they run parallel and are square to each other. The front and rear axles shall be laser aligned. The front tires and

City of Jasper Fire Department

Production Specification

wheels shall be aligned and toe-in set on the front tires by the chassis manufacturer. Cramp angle is set to achieve the greatest turning radius possible with the selected components of the vehicle. Each front wheel is set to zero degrees. The wheel is then turned until it reaches the steering stops. This measurement is the cramp angle.

One (1)

FRONT SUSPENSION

The front suspension shall be parabolic (taper leaf) spring type, with three-(3) leaves 20,000 pounds capacity. The leaves shall be a minimum of 4" wide x 54" long (flat), with grease fittings for lubrication installed in the spring pins. Axle stops with energy absorbing jounce bumpers shall be supplied on the spring top pad. Double acting Koni shock absorbers shall be provided on the front suspension.

One (1)

FRONT BRAKES

The front axle shall be equipped with EX-225 air operated disc brakes and ventilated rotors.

One (1)

CRAMP ANGLE

The cramp angle of the front axle shall be 43 degrees.

One (1)

FRONT TIRES

The front tires shall be Goodyear 385/65R22.5 Load Range "J" G-296 MSA all-weather treads.

The Intermittent Fire Service load capacity shall be 20,000 pound with a speed rating of 68 miles per hour when properly inflated to 120 pounds per square inch with steel or aluminum wheels.

The Fire Service rating is defined as no more than 50 miles of continuous operation at maximum load or without stopping for at least 20 minutes. The Emergency vehicle must reduce its speed to no more than 50 MPH after the first 50 miles of travel.

One (1)

FRONT WHEELS

The front axle wheels shall be Alcoa Polished Aluminum for 385 tires with a rating of 20,000-pounds.

One (1)

FRONT WHEEL TRIM

The front axle wheels shall be trimmed with stainless steel hub and lug nut covers. The axle's hub covers shall be equipped with holes for oil level viewing.

One (1)

MUD FLAPS, FRONT

The front axle mud flaps shall be constructed from hard black rubber and installed behind the front axle.

One (1)

REAR AXLE

City of Jasper Fire Department

Production Specification

The rear axle shall be a Meritor RS-25-160 with a 27,000-pound service rating. The axle shall be equipped with oil seals.

One (1)

REAR SUSPENSION

The rear axle suspension shall leaf spring type rated at 27,000 pounds capacity. The main spring pack shall have fourteen (14) leaves with a four (4) leaf auxiliary pack. The suspension shall be a torque leaf, variable rate, self-leveling slipper type.

One (1)

REAR AXLE DIFFERENTIAL

The Meritor RS series rear axle shall have a standard differential.

One (1)

VEHICLE TOP SPEED

The rear axle shall be geared for a top speed of 65-68 MPH at governed engine speed.

One (1)

REAR BRAKES

The rear axle shall be equipped with 16-1/2" x 7" S-Cam air operated brakes with automatic slack adjusters.

One (1)

REAR TIRES

The rear tires shall be Goodyear 12R22.5 Load Range "H" G622 RSD all season traction treads.

The load capacity shall be 27,000 pound with a speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch with steel or aluminum wheels.

One (1)

REAR WHEELS

The rear wheels shall be Alcoa Polished aluminum, 8.25" X 22.5"10-bolt, hub-piloted. The outside wheels shall have polished outer surface. The ground rating shall be a minimum of 27,000 pounds.

One (1)

REAR WHEEL TRIM

The rear axle wheels shall be trimmed with stainless steel "Lincoln Hat" hub and lug nut covers.

One (1)

TIRE PRESSURE MONITORING SYSTEM

Each tire installed on the apparatus shall be equipped with a tire pressure monitoring device. The device shall consist of a valve stem cap to with an LED tire alert to indicate tire pressure conditions. The LED shall flash when the tire drops 8 psi below the factory setting.

City of Jasper Fire Department

Production Specification

One (1)

AUTOMATIC TIRE CHAINS

The rear axle shall be equipped with an ON-SPOT automatic tire chain system. The system shall provide instant traction at the touch of a button, without having to stop the vehicle.

The driver's dash shall have an electric control switch, clearly labeled for operation of the tire chains. The switch shall be provided with a guard to prevent accidental deployment of the tire chains. The switch when activated shall open a frame mounted solenoid, allowing air from the chassis air system to enter the spring loaded air cylinder and lower the chain wheel. The rubber covered chain wheel shall contact the inside of the tire causing the chain wheel to rotate and deploy the chains. The ON-SPOT automatic chains shall have six (6) lengths of chain, spaced at 60-degree intervals on the chain wheel, ensuring two chains between the tire and road surface for instant traction in slippery conditions whether accelerating, braking, or in a wheel lock up condition. The ON-SPOT chains shall be operable in either forward or reverse.

When the chains are no longer needed the process is reversed, the dash board switch is turned off and the air is exhausted from the cylinder. The return springs in the air cylinder brings the chain wheels back to their resting position.

One (1)

HOSE AND HARNESS ROUTING

Battery cables, hydraulic hoses and air lines shall be routed through the vertical face of the chassis frame rails using bulkhead connectors. The use of grommets through frame rails, as well as running hoses or cables under, over or ahead of the chassis frame rails to achieve positive connections shall not be acceptable.

For ease of maintenance, the wiring harnesses, hydraulic hoses and air hoses shall be divided down each frame rail. The hydraulic and air hoses shall be run, primarily, down the inside of the right side frame rail, while the electrical harnesses shall be run, primarily, down the left side frame rail. Harnesses and hoses shall be mounted using rubber coated, stainless steel holders and, where necessary, heat resistant zip loom.

One (1)

AIR BRAKE SYSTEM

The air brake system shall meet the requirements of FMVSS-121. The system shall consist of three-(3) reservoirs with a total capacity of 5100 cubic inches. The system shall be of dual circuit and quick build up design powered by an engine mounted gear driven air compressor. The system shall be protected by a heated air dryer with heated automatic moisture ejector on the wet tank and quarter turn brass drain valves on the other tanks.

The entire chassis air system shall be plumbed utilizing reinforced nylon air lines. All of the airlines shall be color coded to correspond with an air system schematic and shall be adequately protected from heat and chafing.

One (1)

The system shall be plumbed using color-coded nylon airlines with brass push-lock fittings.

One (1)

ACCESSORY AIR TANK

One (1) 1700 cubic inch additional reservoir(s) shall be connected to the chassis air system to provide an air supply for accessories such as air powered tools. This reservoir shall include a pressure protection valve on the inlet side to allow full use of this tank without draining air from the chassis air system.

One (1)

AUXILIARY AIR INLET

City of Jasper Fire Department

Production Specification

An air inlet shall be located inside the driver's door and incorporate a check valve.

One (1)

ANTI-LOCK BRAKES W/ATC & ELECTRONIC STABILITY CONTROL

The apparatus shall have a Wabco ABS-based Electronic Stability Control (ESC), which offers another level of vehicle control. This automatic braking management system reduces the possibility of a side rollover and assists in the directional stability of apparatus. Upon reaching critical lateral acceleration thresholds, the system intervenes to regulate the vehicles deceleration and braking functions. Reducing the engine's RPM by overriding the foot throttle input and applying the engine retarder (if equipped) to slow the apparatus giving the driver added control and maneuverability. The ESC shall also apply braking power to selective wheel of the front and rear axles to assist in stabilizing the apparatus to its intended direction. This selective braking application and reduction of speed and torque reduces the possibility of spinouts and side rollovers even in adverse conditions.

The system includes a Wabco 4-channel Anti-Lock Braking System shall be installed which includes four-(4) wheel sensors and four-(4) modulators to control and compensate braking force at each wheel. This system shall monitor all wheel ends regardless of suspension type, and which axle it sees braking forces first.

An ABS warning light shall be installed on the driver's dash that remains illuminated until the vehicle is moving at least four-(4) miles per hour. An ABS test switch shall be installed in the "Diagnostic Information Panel" that when pressed, sends the system into diagnostic mode causing the ABS light to blink (I/O) indicating a flash code. A listing of flash code definitions is listed in the Wabco Owner's Manual.

Automatic Traction Control (ATC) shall be installed to sense wheel slip, apply air pressure to brakes, and reduce engine torque to provide improved traction. An ATC indicator light shall illuminate when the system is active.

A mud and snow switch shall be provided. When the switch is in the "ON" position, it shall allow momentary wheel slip to obtain traction under extreme mud and snow conditions.

The system also includes a Steering Angle Sensor (SAS), which informs the system of the degree in which the steering is turned to one side or the other. Along with the SAS, an ESC module is mounted mid frame at the rear of the chassis cab to detect roll, pitch, and yaw angles and computes which wheel(s) brake(s) shall be acted upon.

One (1)

AIR DRYER

The air system shall include a Wabco System Saver 1200 air dryer with integral 12-volt heated moisture ejector. The air dryer shall have a spin on desiccant cartridge and incorporate an integral turbo cutoff valve. The turbo cutoff allows the air dryer to purge water and contaminants without any loss of turbo boost or engine horsepower.

One (1)

ENGINE

The vehicle shall be equipped with a Cummins ISL 450 turbocharged diesel engine. Standard features include an electronic governor, electronically controlled unit injectors, Farr air cleaner, a 12-volt starter Delco 39 MT, and an 18.7 CFM compressor. The oil filter shall be a full flow and bypass design.

This engine conforms to the US 2013 EPA regulations for heavy-duty diesel engines.

City of Jasper Fire Department

Production Specification

ENGINE SPECIFICATIONS

- 5) Model: ISL
- Number of Cylinders: Six (6)
 - Bore and Stroke: 4.49" X 5.69"
 - Displacement: of 8.9 L
 - Rated Horsepower: 450 @ 2100 RPM
 - Peak Torque: 1250 @ 1400 RPM
 - Governed Speed: 2200 RPM

One (1)

TRANSMISSION

The chassis shall be equipped with an Allison 3000 EVS automatic transmission. It shall have 4th gear operating controls and programmed for Fire Apparatus vocation. An electronic oil level indicator shall be provided as well as a diagnostic reader port connection. The transmission shall be geared to provide one-to-one ratio in fourth gear for fire pump applications. The transmission fifth gear shall be an overdrive ratio, permitting the vehicle to reach its top speed at the governed engine speed.

The transmission shall be equipped with an automatic neutral feature. Applying the parking brake shall command the transmission to neutral, regardless of drive range requested on the shift selector which shall require re-selecting the drive range to shift out of neutral.

The transmission shall be equipped with dual PTO ports with engine speed capabilities. The transmission shall be cooled by the radiator-mounted heat exchanger. The transmission fluid shall meet Allison specification TES-295.

One (1)

TRANSMISSION SHIFTER, PUSH BUTTON

The transmission shall be controlled by an Allison push button shifter internally illuminated for night operation. The shifter shall be mounted on the dash to the right of the steering column. The transmission shall be capable of five-(5) speed operation.

The transmission shall be equipped with the oil level sensor (OLS); this sensor shall allow the operator to obtain an indication of the fluid level the shift selector. The sensor display shall provide the following checks, correct fluid level, low fluid level and high fluid level.

One (1)

DRIVELINES

The chassis shall be equipped with Neapco 1710 series driveshaft with full round yokes and universal joints. The driveshaft tubing shall be a minimum of 4.00" diameter with .134" wall thickness. The drivelines shall be balanced at a minimum of 3000 RPM.

One (1)

DRIVELINE INSTALLATION

The drivelines shall be balanced and permanently installed according to manufactures recommendations.

One (1)

ENGINE COMPRESSION BRAKE

City of Jasper Fire Department

Production Specification

The engine shall come equipped with a Jacobs "C-Brake" compression brake controlled by two-(2) switches located in the cab, an on/off and low/medium/high. The compression brake shall interface with the anti-lock brake controller to prevent engine brake operation during adverse braking conditions.

A pump shift, interlock circuit shall be provided to prevent the engine brake from activating during pumping operation.

One (1)

ENGINE COOLING SYSTEM

The engine cooling system shall have the capacity to cool the engine according to the engine manufacturer's requirements.

RADIATOR

The engine radiator shall be of a bolted design and have a minimum core area of 1400 square inches. The top and bottom tanks shall be stamped 16-gauge steel. The tanks shall be attached to the header assemblies with a minimum of fifty-(50), 5/16" bolts. The spacing between fasteners shall not exceed 2.00 inches in order to minimize the possibility of leaks.

The header plates shall be made of 16-gauge brass while the tubes shall be .0068-inch thick brass and .076 by .625 inches in size. The tubes shall have a smooth bore with welded seams which allows for cleaning of the radiator.

The radiator shall contain three rows of tubes with a minimum of 87 tubes per row for a total of not less than 261 tubes. The tubes shall be arranged in an inline profile across the core. Louvered serpentine fins constructed of copper with a density not greater than 16 fins per inch shall be used in the construction of the radiator.

The radiator tubes shall be attached to the header plates with a dual bonding process. The coolant side connection shall be welded, while the air side shall be soldered.

The top tank shall include an integral de-aeration tank, which removes air from the engine water. A low coolant warning shall be incorporated to alert the driver.

The bottom tank of the radiator shall incorporate an oil to water plate-type cooler for the transmission. The cooler is designed to cause a turbulent flow of the transmission oil through the core to force heat transfer. The cooler shall be sufficient to cool Allison Transmission without output retarders.

A high efficiency fan shall be direct driven by the engine and surrounded by a fan shroud. The sweep of the fan shall not exceed the width of the radiator core.

CHARGE AIR COOLER

The charge air cooler shall be constructed of aluminum with cast, aluminum side tanks. The cooler shall have a frontal core area of not less than 888 square inches.

The exterior fins shall be louvered serpentine design constructed of .006-inch thick aluminum and have a density no greater than seven-(7) fins per inch. The internal fins shall be designed to create air turbulence in order to increase heat transfer efficiency.

City of Jasper Fire Department

Production Specification

The charge air cooler shall be mounted directly ahead of the radiator and to the radiator headers. Rubber isolators shall be used at the mounting points to reduce transmission of vibrations.

The piping between the charge air cooler and engine shall use four-(4) ply silicone woven Nomex hoses with stainless steel bands. The bands are used to maintain the shape of the hose during changing turbo boost pressures. The hoses shall be attached with stainless steel constant tension hose clamps.

One (1)

COOLING SYSTEM FAN

The engine cooling system shall incorporate a thermostatically controlled fan clutch. When the fan clutch is disengaged, the vehicle shall have improved vehicle performance, cab heating in cold climates, and fuel economy, while eliminating the potential dangers associated with a fan going from non-rotating to rotating as found with other style fan clutches.

The fan shall automatically lock-up when the vehicle is placed in pumping mode.

A shroud and recirculation shields system shall be used to ensure that once air has passed through the radiator, the same air is not drawn through again.

One (1)

RADIATOR COOLANT, LONG LIFE

The coolant system shall contain a mixture to keep the coolant from freezing to a temperature of -34 degrees F.

The coolant supplied shall be Long Life Coolant compatible with the engine manufacturer's requirement.

One (1)

COOLANT HOSES

The chassis shall be equipped with silicone hoses for the radiator and heater circuits.

One (1)

COOLANT HOSE CLAMPS

Gates PowerGrip clamps shall be provided for all coolant and heater hoses. The maintenance-free clamps retain dynamic tension and never need retightening. These clamps stop leaks, even on out-of-round applications. The clamps are made from a heat sensitive thermoplastic with memory to prevent over or under tightening. The clamps shall have a temperature range of -40 degrees F to -302 degrees F.

One (1)

AUXILIARY ENGINE COOLER

The cooling system shall have a tube and bundle engine cooler mounted in the upper radiator water pipe. Water from the fire pump shall be circulated through 1/2" tubing to the cooler. A valve located on the pump panel shall control the cooling circuit.

One (1)

SKID PLATE, RADIATOR PROTECTION

City of Jasper Fire Department

Production Specification

To protect the radiator a bolt on 1/4" thick steel skid plate shall be installed under the radiator. The skid plate shall protect the radiator from debris or obstruction under the chassis. The skid plate shall be designed so the angle of approach is not affected.

One (1)

FUEL TANK

The chassis shall be equipped with a 50-gallon rear mounted fuel tank. The tank shall be constructed of 12-gauge steel with stainless steel mounting straps and rubber isolators secured to the bottom flange of the chassis framereils. The tank shall be baffled to prevent sloshing, vented, and have a drain plug installed on the bottom. A 240-33 ohm fuel-sending unit shall be provided and broadcast across the SAE J1939 data link.

The tank shall be certified to meet FMCSR 393.65 and 393.67.

One (1)

FUEL LINES

The fuel lines shall be wire braid reinforced fuel grade hose. They shall have reusable fittings and be routed along the inside of the frame rails. Fuel lines shall be protected against chaffing by non-conductive, frame mounted standoff fasteners and, where necessary, with heavy-duty plastic zip loom.

One (1)

FUEL SHUTOFF VALVES

One (1) fuel shutoff valves shall be installed in the suction side of the fuel lines near the fuel filters to prevent the loss of prime during fuel filter maintenance.

One (1)

FUEL FILTER

The Cummins engine shall be supplied with a fuel water separator with a bottom drain valve.

One (1)

EXHAUST SYSTEM

The apparatus shall contain a particulate filter and SCR (Selective Catalytic Reduction) device downstream of the engine's turbo. This filter and SCR device are required to maintain US 2010 EPA Emissions. This filter and SCR device replaces the conventional style filter. The location has been engineered, tested, and set to allow for proper regeneration. Therefore, this filter cannot be removed, altered, or relocated.

An indicator light panel for this system shall be located in the cab informing the driver of the systems status. At times a forced regeneration may be required, which would be indicated by a combination of illuminating and/or flashing lights depending on the engine model.

A momentary switch labeled "Regen" shall be located within reach of the driver's seated position. The regeneration switch initiates the forced regeneration. A momentary DPF inhibit switch prevents the vehicle from having the ability to regenerate. Once the inhibit feature has been activated the ignition switch must be cycled off/on to return the vehicle to normal regen. All vehicles equipped with pumping applications shall allow for passive regeneration whenever the system requires and the engine is at its proper parameters unless inhibited by the DPF inhibit switch. In no way shall this feature affect the RPM of the engine being controlled by the pump operator.

City of Jasper Fire Department

Production Specification

The engine exhaust system shall be horizontal in design using stainless steel tubing mounted under the frame rail right side extending forward of the rear wheels.

An exhaust temperature mitigation device shall be installed. The temperature mitigation device shall lower the temperature of the exhaust by combining ambient air with the exhaust gasses at the exhaust outlet.

One (1)

ALTERNATOR

The alternator shall be a Delco Remy model 55SI 430 amp. The alternator shall be engine driven via a poly-groove power belt with an automatic tensioner. The alternator shall be a brushless design. The alternator shall meet all current applicable NFPA 1901 Edition requirements for performance.

One (1)

BATTERY SYSTEM

The battery system shall be a single system consisting of six-(6) Group 31, 12-volt DC, heavy-duty, high cycle automotive batteries. The battery bank shall have a minimum group rating of 3750 cold cranking amperes (CCA) and a reserve of 1,080 minutes at 80 degrees Fahrenheit.

All battery wiring shall be welded battery cable capable of handling 125% of the actual load. It shall be run through a heat resistant flexible nylon "HTZL" loom rated at a minimum of 300 degrees Fahrenheit. All cable connections shall be machine crimped and soldered.

One (1)

BATTERY BOXES

The chassis batteries shall be mounted in welded and bolted stainless steel battery box. The battery hold-downs shall be made of structural, stainless steel angle. Painted carbon steel battery boxes shall not be acceptable.

One (1)

STAINLESS STEEL BATTERY BOX COVERS

Each battery box shall include a stainless steel cover which protects the top of the batteries from road spray. Each cover shall include flush latches which shall keep the cover secure as well as a handle for convenience when opening.

The cab doors shall use internal and external paddle latches with a rubber gasket isolating the latch from the painted outside surface. The external latch shall have a chrome plated finish and the interior latch shall be cast aluminum. Both latches shall be oversized for easy access with a gloved hand.

One (1)

BATTERY JUMPER STUDS

One-(1) set of battery jumper studs shall be provided on the chassis. The studs shall be connected to the chassis batteries with 1/0 color coded cables, red for the positive cable and black for the negative cable. The studs shall be protected with color coded plastic covers when not being used.

City of Jasper Fire Department

Production Specification

A tag shall be provided for positive/negative terminals.

One (1)

The battery jumper studs shall terminate at the driver's side battery box.

One (1)

SWITCH, MASTER BATTERY DISCONNECT

The chassis batteries shall be wired in parallel to a single 12-volt electrical system, controlled through a heavy-duty, Guest brand rotary type, master disconnect switch. The master disconnect switch shall be located within easy access of the driver upon entering or exiting the cab. All electrical circuits shall be disconnected when the switch is in the "OFF" position.

One (1)

TOTAL SYSTEM LOAD MANAGER W/HIGH IDLE

The apparatus shall be equipped with a Class 1 Total System Manager (TSM) for performing electrical load management. The TSM shall have two-(2) modes of operation, a "Calling Right of Way" and a "Blocking Right of Way". The "Blocking Right of Way" mode is activated only when the park brake is set. Load shedding shall "only" occur when the apparatus is in the "Blocking Right of Way" mode or when the battery voltage level reaches your programmed shed level.

Outputs 1-12 shall be independently programmable to sequence on with the ignition or master warning switch. Outputs 1-12 shall also be programmable to be activated during the "Calling Right of Way" mode and or the "Blocking Right of Way" mode. Output 13 is user configurable output and is programmable for activating between 10.5 and 15 volts. Output 14 shall provide a low voltage warning for an isolated battery. Output 15 shall be designated to activate a fast idle system. Output 16 shall provide a low voltage alarm that activates at the NFPA required 11.8 volts.

The Total System Manager shall have an internal digital display to indicate systems voltage is in normal operation mode and indicates the output configuration during programmable mode.

The Total System Manager shall be protected against reverse polarity and shorted outputs, and be enclosed in a metal enclosure to enhance EMR/RFI protection.

One (1)

BATTERY CHARGER

A Kussmaul Auto Charge 1200 series model 091-187-12-Remote shall be mounted in the vehicle to maintain the chassis electrical system.

The onboard automatic battery charger shall sense battery voltage drop and recharge the batteries to full capacity. The state of charge shall be indicated by the bar graph located on the front of the unit.

The charger shall have the following operational specifications:

Input: 120 volts, 60 Hz, 10 amps
Output: 12 volts DC, 40 Amps
Input Fuse: 15 amps, Fast Acting
Voltage Sense: Remote Electronic

The battery charger shall supply a 'single battery bank' with automatic operation and with an aluminum enclosure. The system shall have a built-in sense circuit to check battery voltage 120 times a second; the system shall

City of Jasper Fiire Department

Production Specification

compensate for voltage drop in charging wires and provide quick recharging with no overcharging. The unit shall include front panel connections for a remote display.

One (1)

SUPER AUTO-EJECT(S), 20 AMP

There shall be provided one (1) super auto-eject type receptacle(s) model 091-55-20. A solenoid wired to the vehicle starter is energized when the engine is started. This instantaneously drives the plug from the receptacle. The receptacle shall be provided with a weatherproof cover. The cover shall be spring loaded to close, preventing water from entering when the shoreline is not connected. The super auto eject receptacle shall be mounted in a location specified by the department and is designed to accept a 120V AC from a shoreline plug.

The UL maximum allowable amperage draw on receptacles is generally 80% of their listed rating, for example, the 20-amp receptacle should not carry more than 16-amp continuous load. When adding the different amperage draws of the components being installed on the chassis, be sure to figure in whether the components shall draw a continuous load or intermittent load.

One (1)

The Auto Eject cover(s) shall be a Kussmaul 091-55YW, yellow in color.

One (1)

SHORE POWER INLET PLATE

A shore-power "Inlet Plate" shall be permanently affixed at or near the power inlet.

The plate shall indicate the following:

- Type of Line Voltage
- Current Rating in Amps
- Power Inlet Type (DC or AC)

One (1)

DISPLAY, BAR GRAPH

The charger shall include a model 091-199-001 remote digital display.

One (1)

UREA STORAGE TANK

There shall be a 5-gallon urea tank located under the extended portion on the cab. A urea level gauge shall be provided in the cab on the main instrument panel.

One (1)

There shall be a DEF fuel fill assembly mounted in the left crew cab extension. The fill assembly shall be equipped with a 14-gauge 304 brushed stainless steel door and fuel fill cap with retention ring. The assembly shall be properly labeled "DIESEL EXHAUST FLUID ONLY".

One (1)

CUSTOM CAB

City of Jasper Fire Department

Production Specification

The cab shall be an engine forward extended, medium four-door, (raised roof) full tilt. The cab shall be an "Open Interior" roll cage design requiring no inner walls or vertical interior supports. The cab roof shall be raised 8 inches providing additional headroom above the crew area. The raised portion shall start midway over the driver and officer seats. The cabs seating capacity for emergency personnel shall be six.

All storage areas inside the cab shall fully comply with NFPA 1901 restraint requirements of 9G's.

CRASH TEST

The cab shall exceed the strict and detailed requirements of the Economic Commission for Europe Structural Standard, ECE-29R. The test shall consist of an impact load test and a vertical load test to the cab.

The cab shall have a frontal impact tests via pendulum, with an impact load in excess of 127% of the ECE-29R Standard. The estimated speed of the 3736-lb (1698-kg) pendulum shall be a minimum of 18.2 mph. The cab doors shall be closed during the impact test but be able to open after impact. There shall be no passenger intrusions or any structural component failures. The cab shall meet or exceed all criteria of this portion of the test.

In conjunction with the frontal impact test, a vertical load test shall be implemented to the cab. The cab roof shall be loaded with a minimum of 65,979 lbs. (29.53 metric tons). There shall be no failure to the cab structure or mountings, any passenger compartment intrusion or degradation of occupant survival space, or any other structural failure. The cab shall meet or exceed all criteria of this portion of the test.

A complete photographic, video, data, and dimensional record of these tests shall be available and placed on record for customer evaluations.

CAB MATERIALS

The cab shall be constructed entirely of aluminum alloy extrusions and 3/16" (.188) thick, 5052-H32 alloy, marine grade aluminum sheets. The corner posts, door slam posts, roof rails and doorframes shall be made of custom extrusions designed specifically for this cab with slots for inserting the skin. The rear wall and roof shall be reinforced with a grid of rectangular extrusions, which are welded to the overall cab extrusion framework. The front corner caps shall consist of castings designed specifically for this cab with relief areas cast in place for attachment of roof skin and intersecting structural extrusions. Overlapping formed corner caps are not acceptable.

CAB DIMENSIONS

- Overall width skin to skin: 96 inches
- Overall vehicle width: 116 inches (w/standard mirrors)
- Overall length: 136 inches
- Cab Height Front: 87 inches
- Cab Height Rear: 95 inches
- Center of front axle to back of cab: 62 inches
- Windshield area: 4100 square inches
- Front grill opening: 430 square inches
- Side grill opening: 105 square inches
- Cab full tilt angle: 45 degrees
- Cab full tilt height: 187 inches
- Floor to ceiling in front: 60 inches
- Floor to ceiling in rear: 66 inches
- Engine cover height: not to exceed 27-1/2" front-to-back and side-to-side

City of Jasper Fire Department

Production Specification

- The Driver shall have no less than 24-1/4" of hip room
- The Officer shall have no less than 23-1/4" of hip room

DOUBLE WALL CAB FACE

The cab front shall be of double wall construction resulting in a sealed firewall. The inner and outer shall both be formed from 3/16" thick, 5052 H32 alloy aluminum with structural aluminum reinforcements. This design provides for increased structural integrity, crew safety, and reduced road noise in the passenger area. The outer wall is used for mounting forward lighting, grill and windshield wipers. The inner portion shall be treated with a heavy black undercoating material for corrosion prevention.

SEALED ENGINE TUNNEL

The engine tunnel shall be a structural part of the passenger cab, constructed from welded 3/16" aluminum plate and reinforced with aluminum extrusions. The rear of the engine tunnel shall be no less than 57" inches from the rear wall of the cab, allowing maximum legroom for forward facing passenger. After welding, the seams shall be completely sealed with silicone caulking.

Engine enclosures that are not an integral part of the cab structure are not acceptable.

The interior of the engine tunnel shall be insulated with 1" thick foil backed insulating foam, attached with stud and button method. A cross-section analysis of the insulation shall reveal a 1/8" thick barrier material for additional noise and heat insulation.

CAB FLOORS

Cab floors shall be constructed from an aluminum extruded frame and 3/16" thick aluminum plate. Floor mats and insulation are detailed later in this specification.

The forward cab floor shall be as large as possible for both the driver and officer. Floorboards shall extend in width from the side of the engine tunnel, all the way to the cab door inner panel. They shall extend forward from the seat riser to the inner portion of the double wall cab face. The officer shall have approximately 28" of foot room.

The entire rear floor of the cab, to reduce trip and fall hazards, shall be a single plane. In applications requiring the use of a top-mounted PTO, a raised area in the floor may be required.

For maximum crew comfort and eliminate leg fatigue during emergency responses, the floor beneath the rear facing jump seats shall be large enough for a seated firefighter to rest both feet side-by-side. Cab floor designs that are wide enough for only one foot shall not be accepted.

CAB CORROSION PROTECTION

A corrosion preventative material shall be applied during cab construction. A ten-(10) year warranty against corrosion perforation shall be provided for the cab.

WHEEL WELL LINERS

Full wheel well liners shall be installed beneath the cab to protect the bottom of the cab from road splash. The liners shall be constructed of aluminum and be full width.

City of Jasper Fire Department

Production Specification

The wheel well liners shall be attached with threaded fasteners and be easily removable for service.

FENDERETTES

Bright polished stainless steel fenderettes shall be installed at the wheel well openings. A rubber gasket shall be installed between the fenderette and cab to eliminate contact of dissimilar metals.

WINDSHIELD

The windshield shall have approximately 4100 square inches of unobstructed viewing area. It shall be a two-(2) piece design with tinted automotive safety glass, with a wraparound design. A .030-inch thick vinyl layer shall separate the laminated glass.

All other cab glass shall be tinted and tempered.

INTERMITTENT WINDSHIELD WIPERS

Two electric "Pantograph" style windshield wipers shall be installed on the front face of the cab. The motors shall operate through a 72-degree sweep and include 24-inch blades to give superior wiper coverage. A washer reservoir of not less than 70 ounces shall be mounted a latched door recessed in the officer's step.

A switch located on the turn signal control arm shall operate the intermittent wipers.

EXTERIOR GRAB HANDLES

Stainless steel handrails with a knurled, slip-resistant finish shall be positioned behind each cab door. Grab rails shall be minimum 24" in length. Molded rubber gasket shall be mounted between the grab handles and the cab in order to prevent corrosion due to dissimilar metals being in contact.

EXTREME DUTY CAB INTERIOR

Cab floors shall be covered with a pebble grain rubber matting with barrier type insulation. Edges of the insulation shall be trimmed with a cast aluminum foot plate for a pleasing appearance.

An insulated covering shall be fitted over the engine tunnel. Made from the same material as the cab floor insulation, this covering shall insulate the cab from engine heat and noise. A Cast Products aluminum door on top of the engine tunnel shall provide access for fluid checks.

The back side of the engine cover, as well as a 2" to 3" return on the top side, shall be covered with a sprayed aluminum panel and be of sufficient strength to allow for 9G resistant mounting of any optional hand lights, entry tools, or other fire rescue equipment specified by the customer.

The cab shall have a custom built, smooth aluminum plate dashboard, overhead console, glove box, instrumentation panel and switch panel. The front overhead shall include room for the three sun visors and the door open indicator light.

The front door posts shall be trimmed with styled aluminum covers that conceal any wiring, as well as including a mounting area for rubberized grab handles. The center windshield post shall be covered F-Shield paint finish.

Prior to installing the headliner and rear wall panel, minimum R-7 insulation, shall be installed between the interlocking extrusions.

City of Jasper Fire Department

Production Specification

These covers serve to finish the interior, cover wiring harnesses and insulate the interior from sound and heat.

CAB STEPS

All cab steps shall be of a stationary, fixed design that use no moving parts and requires no periodic maintenance other than cleaning.

There shall be an open-grip, bright finish step at each cab door opening. The area under the step shall be enclosed to prevent road dirt from entering the cab. There shall be provisions made at the front of the step for easily flushing out any dirt accumulation.

At each door, opening there shall also be an intermediate cab step. Intermediate steps shall be full width of the doorstep area and constructed from embossed aluminum tread plate.

CAB STEP HEIGHTS

The distance from level ground to the first cab step shall be 19-21 inches without using swing-down style or under-cab "stirrup" auxiliary steps.

The distance from first cab step to intermediate step shall be approximately 12.5 inches front and rear.

The distance from intermediate step to cab floor shall be approximately 9.5 inches in the front and 12 inches in the rear.

One (1)

CAB DOORS

All cab doors shall be "Barrier Type" and designed not cover the step well area. Each cab door shall be flush type with a minimum opening of 85 degrees.

The front doors shall be approximately 40" inches wide by 67" inches tall. The doors shall have a two-piece window, one operational and one fixed. The combined viewing area shall be no less than 796 square inches. For added safety, the front door windows shall slant down maximum visibility.

The rear doors shall be approximately 34" inches wide by 75" inches tall. The doors shall have a two-piece window, one operational and one fixed. The combined viewing area shall be no less than 867 square inches. There crew area windows shall have a dark tint applied.

The doors shall include a bulb style rubber seal around the perimeter of each door frame ensuring a weather tight fit.

One (1)

HEATED/REMOTE CAB MIRRORS

Two side-mounted rear view mirrors shall be installed with a 14.5" X 7" mirror head and a separate 6" x 8" parabolic mirror. The mirror head shall be heated and remotely adjustable by the driver. The mirrors shall be aerodynamically designed to reduce wind buffeting and resultant vibration. The housings shall be a finished black in color.

The mirrors support tubes shall be 7/8" stainless steel, with breakaway mounting brackets.

City of Jasper Fire Department

Production Specification

One (1)

DOOR HINGES

Each cab door shall be attached to the cab with two concealed automotive style hinges with restraining strap.

One (1)

CAB DOOR LOCKS

There shall be individual manual twist type door locks at each door handle. In accordance with FMVSS 206, all exterior door locks shall be keyed alike.

One (1)

CAB DOOR WINDOWS, ELECTRIC

All cab door windows shall be electrically operated. The driver's door shall contain four-(4) switches to control the operation at each door. All remaining doors shall contain one-(1) heavy-duty switch to control the window operation located on top of the door panel.

One (1)

FIXED CAB WINDOW, LEFT SIDE

A window of not less than 16-1/2" wide by 33-1/2" high shall be installed in the left sidewall of the cab between the front and rear door. The glass shall be tempered and retained with one-piece triple locking rubber lacing dark tint.

One (1)

FIXED CAB WINDOW, RIGHT SIDE

A window of not less than 16-1/2" wide by 33-1/2" high shall be installed in the right sidewall of the cab between the front and rear door. The glass shall be tempered and retained with one-piece triple locking rubber lacing dark tint.

One (1)

CAB TILT LOCK

The cab shall be supported at four points. At the front, there shall be two center bonded bronze bushings. At the rear, there shall be two hydraulic locking latches.

The cab shall tilt 45 degrees by means of a pair of hydraulic cylinders driven by the electric pump. The tilt system geometry shall be designed in such a way that the maximum hydraulic pressure in the system does not exceed one-half the pressure rating of the cylinders or pump when the cab is empty. This allows the Fire Department to leave some equipment in the cab when maintenance is required (although this equipment must be secured).

Once the cab is fully tilted, a safety latch shall automatically engage and act as a positive lock. The lock is released by a pull cable. The hydraulic cylinders shall be equipped with velocity fuses to prevent the cab from falling, should the hydraulic system fail.

The front of the cab pivots and rides on the center bonded bushings by means of lubricated pivot pins that retain the cab yoke in the bushings. The bushings allow limited movement of the cab, and isolate the cab from noise and vibration.

City of Jasper Fire Department

Production Specification

The rear mounts consist of a pair of hydraulic cab latches mounted on rubber cushioned mounting brackets. Latches release when the pressure in the tilt system exceeds 500 PSI.

An ignition interlock system shall be installed for cab tilt operation. Cab tilt operation requires the master battery switch to be in the on position with the parking brake applied.

One (1)

CAB TILT PUMP W/MANUAL BACKUP

An electric over hydraulic cab lifting pump shall be provided to tilt the cab for engine and transmission service. The pump shall be operated by a remotely wired control box with coiled cord, weather resistant plug, and receptacle. An interlock shall be provided preventing the cab from inadvertently rising until the transmission is placed in the neutral position and the parking brake is set.

In the event of electrical failure, a hydraulic manual backup shall be provided to tilt the cab.

One (1)

HEATING/AIR CONDITIONING SYSTEM

The climate control system shall use three-(3) heater-air conditioner units.

The front circuits shall use two-(2) heater-air conditioning units, mounted under the dash on the driver's side and under the officer's side. These units are each rated at 14,700 BTU heating and 19,200 BTU cooling. The units shall blow up toward the windshield through adjustable vents in the dash. Additionally, there shall be two-(2) adjustable vents each side to direct air at the lower portion of the driver and officer seating areas. Two switches, including low/med/high and heat/off/ ac, shall control the front system.

A blend air switch shall be installed to operate both the front heating and cooling systems. This provides hot and dry air for defogging purposes.

The two front systems shall combine to put out a total of 688 CFM air flow.

The rear circuit shall use one large heater-air conditioner unit with a rating of 34,150 BTU cooling and 36,000 BTU heating. It shall be mounted under the forward facing rear seats. Ducting shall run up the rear wall to adjustable vents (minimum of six) running along the center of the ceiling toward the front of the cab. Two-(2) switches including high/med/low and heat/off/AC shall control the unit. In addition to the rear control switches, there shall be an ON/OFF switch located near the driver to disable the rear unit if needed.

The rear system shall put out a total of 640 CFM air flow.

The total system shall have a capacity of 72,550 Btu cooling, 65,400 Btu heating and a total in-cab air flow of 1,328 CFM.

The entire roof and back wall shall be heavily insulated with 1" foam to enhance the cooling system.

Both heaters shall be plumbed with a shut off valve at the engine.

The air conditioning system shall be powered through two (2) engine driven 9.5 cubic inch compressors.

Two (2) roof top condensers, each rated at 38,700 Btu, shall be provided.

One (1)

City of Jasper Fire Department

Production Specification

The two-(2) roof top condenser housings shall be black in color.

One (1)

SEAT MATERIAL

The seats shall be covered with Durawear material.

One (1)

SEAT COLOR

The cab seats shall be black in color.

One (1)

DRIVER'S SEAT

The driver's seat shall be a Bostrom Sierra Model, 500 ABTS, AIR-50RX/HD/ABTS/LH high-back with air ride suspension. The seat shall have 4-way adjustability by the driver in accordance with SAE J1517. The seat shall be equipped with an integrated 3-point seat belt with RiteHite adjustment and an automatic retractor. The belt shall be red in color to meet current NFPA requirements.

One (1)

OFFICER'S SEAT

The officer's seat shall be a Bostrom Sierra 500 ABTS (All Belts to Seats)FX/ABTS RH. The seat shall be equipped with an integrated 3-point shoulder harness with lap belt, RiteHite adjustment and an automatic retractor built into the seat assembly. The belt shall be red in color to meet current NFPA requirements.

One (1)

CREW SEAT, DRIVER'S SIDE REAR FACING

The officer's side outboard rear facing crew seat shall be a Bostrom 500 Flip-Up ABTS (All Belts to Seats). The seat will be a H. O. Bostrom Sierra, 500 Series, FX/ABTS LH fixed high back bucket seat. The flip up seat will have a tapered and padded low profile, extended, seat cushion. The seat will have a tapered and padded low profile seat cushion. A two-(2) way, fore and aft seat base will be provide.

A suspension seat safety system will be included. When activated the system will pretension the seat belt then retract the seat to its lowest travel position.

The seat will be equipped with a red integrated 3-point shoulder harness with lap built into the seat assembly with RiteHite™ Seat Belt customized fit Adjustment

One (1)

CREW SEAT, OFFICER'S SIDE REAR FACING

The officer's side outboard rear facing crew seat shall be a Bostrom 500 Flip-Up ABTS (All Belts to Seats). The seat will be a H. O. Bostrom Sierra, 500 Series, FX/ABTS RH fixed high back bucket seat. The flip up seat will have a tapered and padded low profile, extended, seat cushion. The seat will have a tapered and padded low profile seat cushion. A two-(2) way, fore and aft seat base will be provide.

A suspension seat safety system will be included. When activated the system will pretension the seat belt then retract the seat to its lowest travel position.

City of Jasper Fire Department

Production Specification

The seat will be equipped with a red integrated 3-point shoulder harness with lap built into the seat assembly with RiteHite™ Seat Belt customized fit Adjustment

One (1)

FRONT GRILLE

The front grille shall be a mirror polished stainless steel box style assembly with 448 square inches of open area. The grille shall measure 48" wide x 23.13" high x 1.56" deep.

One (1)

SIDE INTAKE GRILLES W/EMBER SEPARATOR

Bright stainless steel grilles shall be installed approximately 70" above ground level one-(1) each side cab between the front and rear cab doors. The grilles shall have a minimum open area of not less than 119 square inches serving as an air intake and warm air dispersant system.

An Ember Separator shall be installed between the stainless steel grill and the air filter system allowing fresh air to pass through to the engine while preventing particles of .039 inches (1.0 mm) or larger from entering the system in accordance with the latest version of NFPA easily accessible through the exterior stainless steel grille.

The right side grille shall be notched to allow easy access without removing the cab handrail.

One (1)

EXTERIOR TRIM, REAR CAB STEP WELL

The rear cab door stepping surfaces shall be trimmed with aluminum tread plate. There shall be tread plate covers that provide access to the chassis battery system.

One (1)

TREAD PLATE BACK OF CAB

The entire back wall of the cab shall be covered with 1/8" (.125") thick aluminum tread plate. The tread plate shall be coated with a rust inhibitor and fastened to the cab with stainless steel fasteners. A bead of caulking shall be applied to the perimeter of the tread plate.

One (1)

CAB CORROSION PROTECTION AND SOUND DEADENING

The apparatus cab shall be completely covered in one of two types of paint, prior to installation of any interior or exterior components, including insulation and floor mats. This process shall be required to guard against corrosion as well as to keep the cab as quiet as possible for firefighters.

The entire underside and double wall area at the front of the cab shall be cleaned, primed and sprayed with black F-Shield as a finish coat. This shall include any areas that are not normally visible after the cab is complete.

The entire cab interior shall be sprayed with F-Shield, as described later in these specifications. F-Shield shall be sprayed over the ceiling, floor, side walls, forward fire wall, rear wall, dash, engine tunnel, interior cab doors and both sides of the cab door panels.

City of Jasper Fire Department

Production Specification

The cab exterior shall be completely finish painted with DuPont paint, as described later in these specifications. This shall include the areas under any optional rear wall or cab roof diamond plate overlays.

The fire department shall, through the Virtual Manufacturing feature described earlier in these specifications, have the ability to see these areas covered with F-Shield prior to installation of items such as engine tunnel insulation, cab interior insulation and headliners, engine tunnel covering, floor mats, cab inner door panels, etc.

As a result of these cab corrosion protection measures, a ten-(10) year warranty against cab corrosion shall be provided to the fire department.

One (1)

INTERIOR CAB FINISH

The interior of the cab shall be painted with a black "F-Shield". The cab metal finish shall be covered with a coat of adhesion promoting primer.

"F-Shield" is a 100% solids, state-of-the art, VOC-free, plural-component, pure polyuria elastomeric membrane. This seamless system exhibits extraordinary performance characteristics. F-Shield is based on amine-terminated polyether resins, amine chain extenders and MDI pre-polymers. This membrane achieves an extremely tough, flexible, chemical and abuse resistant finish. F-Shield shall be used in specified areas for maximum protection.

The headliner (front and rear) and rear wall (if applicable) shall be covered with heavy-duty black vinyl.

One (1)

FLOOR MATS/ENGINE TUNNEL COVERING

The floor mats and engine tunnel shall be covered with black pebble grain vinyl with 1/4" (.250") foam backing. The edges of the floor mats shall be trimmed with a cast aluminum foot plate for a pleasing appearance.

One (1)

INTERIOR TRIM, REAR WALL ALUMINUM PANAL

The entire interior rear wall of the cab shall be covered with 3/16" (.1875") smooth aluminum plate coated with "F-Shield".

"F-Shield" is a 100% solids, state-of-the art, VOC-free, plural-component, pure polyuria elastomeric membrane. This seamless system exhibits extraordinary performance characteristics. F-Shield is based on amine-terminated polyether resins, amine chain extenders and MDI pre-polymers. This membrane achieves an extremely tough, flexible, chemical and abuse resistant finish. F-Shield shall be used in specified areas for maximum protection.

The color of the rear wall panel shall match the interior of the cab unless otherwise specified.

One (1)

ENGINE TUNNEL EQUIPMENT MOUNTING PLATE

There shall be one-(1) equipment mounting plate installed on the engine tunnel constructed of 3/16" smooth aluminum plate covered with "F-Shield".

"F-Shield" is a 100% solids, state-of-the art, VOC-free, plural-component, pure polyuria elastomeric membrane. This seamless system exhibits extraordinary performance characteristics. F-Shield is based on amine-terminated

City of Jasper Fire Department

Production Specification

polyether resins, amine chain extenders and MDI pre-polymers. This membrane achieves an extremely tough, flexible, chemical and abuse resistant finish. F-Shield shall be used in specified areas for maximum protection.

One (1)

CAB GRAB HANDLES, INTERIOR

Two-(2) interior grab handles installed in the cab on the "A" posts, one-(1) each side. The grab handles shall be constructed of rubberized steel.

Four-(4) interior grab handles installed in the cab, one-(1) each side on top of the front door panels adjacent to fixed window and one-(1) each side on the rear door panels. The grab handles shall be constructed of 1-1/4" knurled stainless steel. The grab rails shall be mounted with chrome plated end stanchions.

There shall be one-(1) interior grab handle installed on the inside of each rear cab door. The handles shall extend horizontally with width of the window just above the window sill. The grab handles shall be constructed of bright stainless steel.

One (1)

MAP BOOK HOLDER

A map book holder shall be installed in the cab as directed by the Fire Department. The map book holder shall be constructed of smooth aluminum with a Velcro retaining strap. The map book holder shall be painted to match the interior color of the cab.

One (1)

GLOVE BOX

The glove box shall be an integral part of the welded aluminum dashboard assembly and located on the officer side of the cab. The storage area of the glove box shall bolt in place for easy service access. The door shall be drop down style and constructed from brushed stainless steel with a recessed latch. The area above the glove box shall be flat for a work surface or optional MDT mounting.

One (1)

SUN VISORS

The cab shall be equipped with three-(3) sun visors. The visors shall be installed on the overhead panel and provide approximately 90 percent coverage across the width of the cab. The visors shall be approximately 26" wide and 6" tall.

One (1)

CAB DOOR PANELS

There shall be four-(4) interior front and rear door panels installed constructed of brushed stainless steel extending from the bottom of the window to the top of the lower kick plate.

One (1)

REFLECTIVE STOP SIGNS

There shall be four-(4) "STOP" signs installed in the cab, one-(1) on the lower door panel of each cab door.

One (1)

City of Jasper Fire Department

Production Specification

INSTRUMENTATION

For easy viewing, gauges shall be white faced with black lettering and adjustable intensity, LED backlighting. In order to reduce replacement and maintenance costs, the gauges provided shall be separate from one another and not in a cluster or arrangement. The gauges shall meet SAE J-1939 protocol to eliminate redundant sending units. Gauges must be fully sealed to 6 psi. Gauges shall have an operating temperature range of -40F to 185F. The gauge crystal shall be polycarbonate, anti-fog, and anti-scratch coated. The panels shall be divided into groups of instruments that make identification sensible and easy to view.

The following panels shall be included:

- One driver side hinged gauge panel
- One driver side message center and indicator light panel
- Driver side pump shift panel (if required)
- Driver side park brake panel
- Driver side diagnostic connector
- Driver side ignition/climate control panel
- Center mounted rocker switch and siren panel, with a maximum capacity of 20 switches
- Officer side information panel

The following instruments shall be included:

- Dial Type speedometer with digital odometer and trip odometer that is active when pumping
- Dial Type tachometer with digital hour meter and trip hour meter along with a digital, four-line diagnostic display
- Dial Type engine oil pressure gauge with warning light and alarm
- Dial Type water temperature with warning light and alarm
- Dial Type transmission temperature with warning light and alarm
- Dial Type front air pressure gauges with warning light and alarm
- Dial Type rear air pressure gauge with warning light
- Dial Type voltmeter
- Dial Type fuel level gauge with low fuel indicator level
- Dial Type Diesel Exhaust Fluid gauge with low level indicator
- Air cleaner restriction light
- High beam indicator
- Parking brake indicator
- Turn signal indicators
- Diagnostic indicators for airbag, engine, transmission, and ABS

An anti-lock braking system (ABS) test switch and parking brake control valve shall be located to the right of the steering column.

SERVICE ACCESS

The driver's instrumentation area shall be made of textured black non-glare panels affixed to the aluminum dash. There shall be a single gauge panel, secured with a bottom hinge and four (4) quarter-turn fasteners. Access to the gauge clusters shall be accomplished simply by releasing the latches and pulling the panel outward. Other gauge access designs are not acceptable.

City of Jasper Fire Department

Production Specification

The chassis electrical panel shall be located in the center of the aluminum dash, between the switch panel and the windshield. There shall be a lift up cover, with two (2) recessed lift-and-turn latches for quick access to the panel. The underside of the panel shall have a pre-printed diagram that clearly depicts the function of each circuit breaker and relay. The vehicle load manager shall be located in this panel. The opening to the electrical shall measure approximately 19" wide near the switch panel and 37" wide toward the windshield.

Electronic diagnostic connections for the engine, transmission, and ABS brakes shall be located in the lower-left panel on the cab dash.

One (1)

DRIVER'S INFORMATION DISPLAY

There shall be a 10.8" x 2.44" display panel on the driver's gauge cluster that will illuminate various caution and warning indicator lamps. This display also contains a 340 x 90 monochrome LCD for display of specific and user selectable data. The display unit reads data from the J1939-11 powertrain communications network. Display will be capable of but not limited to the following features:

- Auto Self-Test
- Viewing the state of each digital or analog input to the unit
- Viewing the state of each output
- Allows users ability to set service reminders by distance or hours of operation
- Allows users ability to set data screens in various formats i.e. bar graph / text
- Viewable active and stored powertrain ECU fault data.
- Diagnostics screen allows user to select and view a specific source such as engine / transmission
- Display is selectable between English and metric readings.
- Messages and Icons will pop up in display when a condition exists such as:

Transmission oil life, filter or other service needed as reported by the Allison Transmission ECU
Engine conditions: Low oil pressure, high coolant temperature, low coolant level, water in fuel, check / stop engine, regeneration needed, high exhaust temp

Indicator lights may also accompany pop up messages:

- Door ajar indicator will also pop up a "Do Not Move Vehicle, Check all doors and Items that Raise or extend beyond apparatus cab or body" message

One (1)

CHASSIS ELECTRICAL SYSTEM

The chassis shall include a single starting electrical system which shall include a 12 volt direct current system, suppressed per SAE J551. The wiring shall be appropriate gauge cross link with 311 degree Fahrenheit insulation. All SAE wires in the chassis shall be color coded and shall include the circuit number and function where possible. The wiring shall be protected by 257 degree Fahrenheit minimum high temperature flame retardant loom.

CHASSIS COLOR CODED WIRING

All chassis wiring shall be type "GXL" in accordance with S.A.E. J1128 and NFPA-1901. ALL wiring shall be **COLOR CODED** and continuously marked with the circuit number and function.

City of Jasper Fire Department

Production Specification

A battery "loop back" ground circuit shall be supplied for the EDS system to reduce the possible effects of Electromagnetic and Radio Frequency Interference.

The chassis cab, engine and transmission shall be electrically bonded to the chassis frame rails with braided ground straps.

One (1)

MAIN CENTER DASH

The main center dash area shall include three (3) removable panel's located one (1) to the right of the driver position, one (1) in the center of the dash and one (1) to the left of the officer position. The center panel shall be within comfortable reach of both the driver and officer. The panel shall be constructed of 5052-H32 Marine Grade, 1/8 inch thick aluminum plate.

The left dash panel shall include ten (10) switches. There shall be eight (8) switches across the top of the panel and two (2) staggered on the lower portion of the panel. The transmission shifter and instrument lamp dimmer control shall be provided on the right side of the panel.

The center dash panel shall include lighted rocker switches with a legend. The non-specified switches shall be two-position, black switches with an indicator light. All switch legends shall have backlighting provided. The center portion shall be used for electronic siren mounting.

The right dash panel shall be blank.

One (1)

VEHICLE DATA RECORDER

Apparatus shall be equipped with a Class1 "Vehicle Data Recorder and Seat Belt Warning System" (VDR/SBW) that is connected to the power train CAN (Controller Area Network) bus consisting of transmission (TCM), engine control (ECM) and antilock brake (ABS) modules mounted on the apparatus. The VDR/SBW will function per NFPA 1901-2009 sections 4.11 (Vehicle Data Recorder) utilizing the power train's J1939 data and 14.1.3.10 (Seat Belt Warning) using the Class1 "Seat Belt Input Module" for seat occupied and belt status information.

The VDR data shall be downloadable by USB cable to a computer using either Microsoft™ or Apple™ Operating Systems using Class 1/ O.E.M. supplied reporting software.

There shall be a seat belt indicator system supplied in the cab. The indicator system shall indicate seat belt use for each individual seating position when the seat is occupied, the seat belt remains unfastened and the parking brake is released.

A display panel shall be supplied in the dash area. The panel shall have an audible indicators and a red light display to indicate that a seat belt has not been fastened.

One (1)

SEAT BELT WARNING SYSTEM

Mounted in the overhead console in the driver's area the indicator system shall indicate seat belt use for each individual seating position when the seat is occupied, the seat belt remains unfastened and the parking brake is released.

One (1)

STEERING COLUMN

City of Jasper Fire Department

Production Specification

The steering column shall be a Douglas Autotec tilt and telescope. A lever mounted on the side of the column shall control the tilt and telescope features. A Signal-Stat (self-canceling) turn signal switch shall be mounted to the column. The steering shaft from the column to the meter box shall have a rubber boot to cover the shaft slip and a second rubber boot to seal the passage hole in the floor.

The steering wheel shall be 18 inches in diameter.

The Signal-Stat turn signal switch shall include the following functions:

- Left and right turn signals
- High beam dimmer control
- Hazard warning switch
- Two speed with intermittent windshield wiper control
- Windshield washer control

One (1)

CHARGING PORT(S), 12-VOLT DUAL USB

There shall be one (1) Kussmaul model 019-219, 12-volt USB dual charging port(s) provided in the cab. The charging port(s) shall be equipped with one-(1) 1.0 amp connection and one-(1) 2.1 amp connection with built in LED indicator that indicates when the device(s) are powered.

The charging port(s) shall be wired to direct battery power with the appropriate wire size and fuse.

The charging port(s) shall be located in the emergency switch panel.

One (1)

POWER AND GROUND STUDS

The electrical distribution panel shall include two (2) power studs. The studs shall be size #10 and each of the power studs shall be circuit protected with a fuse of the specified amperage. One (1) power stud shall be capable of carrying up to a 40 amp battery direct load and one (1) power stud shall be capable of carrying up to a 20 amp ignition switched load. The two (2) power studs shall share one (1) #10 ground stud.

Two (2)

12-VOLT POWER OUTLETS

There shall be two (2) 12-volt power outlets provided in the cab.

Two (2)

The power outlets shall be wired to direct battery power with the appropriate wire size and fuse.

One (1)

ANTENNA INSTALLATION

There shall be one (1) antenna supplied by the customer and installed by the apparatus body builder.

The items must be sent to the manufacturer in advance, and marked with name and shop order number for identification.

City of Jasper Fire Department

Production Specification

One (1)

RADIO POWER CIRCUIT

A 50 amp switched battery power circuit with manual reset shall be installed centered in the dash to activate the radio.

One (1)

12-VOLT FUSE BLOCK

There shall be one (1) Blue Sea fuse block 5025 installed in a location determined by the customer. The unit shall include a six-(6) 12 volt constant power supply ports and grounding buss with easily changeable fuses. The unit shall have a 100 amp total operating range.

One (1)

ELECTRONIC SIREN

There shall be one-(1) Whelen model WS-295HFS2 hands free siren control head mounted in the center switch panel. The siren button shall be activated when the siren is in hands free mode. The siren shall incorporate a rotary selector. There shall be an on/off power switch, a push button switch for manual siren or air horn tones, and a noise-canceling microphone with volume control.

One (1)

HORN, ELECTRIC

A single electric horn activated by the steering wheel horn button shall be provided.

One (1)

BACK-UP ALARM

There shall be one-(1) Whelen model WBUA107, 107 dB, electronic back-up alarm installed at the rear of the apparatus. The alarm shall be wired to the transmissions output signal and is automatically activated when the transmission is shifted into reverse.

One (1)

LIGHTS, CAB DOME

Four-(4) Whelen 6" Round Super-LED model 60CREGCS shall be provided in the cabs headliner. The steady burn 12v interior light shall incorporate six red and six clear Super-LEDs and a clear non-optic translucent hard coated polycarbonate lens for maximum output. The hard coated lens shall provide extended life/luster protection against UV and chemical stresses. The conformal coated PC board and foam in place gasket shall provide additional protection against environmental elements. The 60CREGCS includes Hi/Low intensity mode standards and On/Off dual switch function. The solid state interior light shall be vibration resistant. The interior light is covered by a five year factory warranty

The white LED lights shall be activated when any cab door is in the open position automatically switching off all red lights currently on and reactivated when the door is closed.

Two (2)

LIGHTS, ADDITIONAL CAB DOME

City of Jasper Fire Department

Production Specification

There shall be One (1) additional Whelen 6" Round Super-LED model 60CREGCS shall be provided in the cab headliner in the crew area center one each side near rear seats. The steady burn 12v interior light shall incorporate six red and six clear Super-LEDs and a clear non-optic translucent hard coated polycarbonate lens for maximum output. The hard coated lens shall provide extended life/luster protection against UV and chemical stresses. The conformal coated PC board and foam in place gasket shall provide additional protection against environmental elements. The 60CREGCS includes Hi/Low intensity mode standards and On/Off dual switch function. The solid state interior light shall be vibration resistant. The interior light is covered by a five year factory warranty

The white LED lights shall be activated when any cab door is in the open position automatically switching off all red lights currently on and reactivated when the door is closed.

One (1) **LIGHT, DOOR AJAR**

A red door ajar flashing light, Whelen OS Series LED shall be mounted on the driver's side face of the overhead panel. A chrome flange is to be supplied with the light.

This light is wired with a flasher to the power panel for completion to circuit on the body.

The light circuit shall be wired so that the light circuit is deactivated when the parking brakes of the apparatus are applied.

A label shall be applied adjacent to the light 'DOOR OPEN'.

One (1) **LIGHTS, STEP WELL**

Six-(6) TecNiq D04 Linear Dragon LED lights shall be provided, two-(2) in each front cab step well and one-(1) in each rear cab step well. Each light shall activate when the cab door is opened.

One (1) **LIGHTS, ENGINE MAINTENANCE**

Two-(2) white 4" LED round lights shall be mounted under the cab. The lights shall automatically activate when the cab is tilted.

One (1) **STANDARD FRONT LIGHTING**

The headlamps, turn signals, front warning, and intersection lights shall be located within chrome warning light modules.

One (1) **HEADLIGHTS**

Four-(4) JW Speaker LED rectangular headlights shall be installed in the warning light modules, two-(2) each side. The headlights shall be mounted in the upper positions of the module.

One (1) **DAYTIME RUNNING LIGHTS W/ALTERNATING HEADLIGHT FLASHER**

City of Jasper Fire Department

Production Specification

The apparatus shall be equipped with Daytime Running Lights. This feature shall control 80% of the low beam headlamp illumination. The Daytime Running lights shall operate only when the ignition switch is in the "On" position and the parking brake is released. The headlight circuitry shall override the Daytime Running Lamp feature when the headlight switch is in the "On" position. The vehicle identification lamps shall not illuminate in the Daytime Running Lamp mode.

A solid state-alternating flasher shall be installed on the high beam side of the headlamps. A rocker switch located in the cab shall control the module. If high beam lights are required, activating the headlight dimmer switch shall automatically over-ride the flasher when the headlight switch is in the "On" position.

One (1)

TURN SIGNALS

Whelen model 600 amber LED turn signal lamps shall be installed directly below the low beam headlights in the warning light modules.

One (1)

TURN SIGNAL/MARKER LIGHTS

Whelen model 400 amber LED lamps shall be mounted outboard of the turn signal at a 45-degree angle off the front of the cab. The lamps are part of the warning light module, and are visible from both the front and side of the vehicle.

One (1)

LED CORNERING LIGHTS

Whelen model 400 flashing LED-cornering lamps shall be mounted below the marker light in the warning light module. The lamps are mounted at a 45-degree angle off the front of the cab and are visible from the side and front of the vehicle.

One (1)

DOT LIGHTS

There shall be five-(5) LED marker lights installed on the cabs roof located as high as practical and spaced per DOT guidelines.

One (1)

LIGHTS, INBOARD LOWER FRONT WARNING

Two-(2) Whelen 600 Series Super-LED model 60R02FRR shall be installed, one-(1) each side inboard of the turn signal in the warning light modules. The warning light shall incorporate red Linear Super-LEDs, a red optic hard coated polycarbonate lens, and utilize a metalized reflector with integrated TIR hybrid optics for maximum output. The hard coated lens shall provide extended life/luster protection against UV and chemical stresses. The encapsulated lens/reflector assembly and conformal coated PC board shall provide additional protection against environmental elements. The solid state warning lights shall be vibration resistant. The self-contained flashing light shall have 14 Scan-Lock flash patterns including synchronize feature and steady burn. The warning light is covered by a five year factory warranty.

One (1)

LIGHTS, CAB

City of Jasper Fire Department

Production Specification

There shall be one-(1) Whelen 2G Series model 20C0CDCD 4" LED light mounted under each cab door illuminating the area below providing a safe entrance and exit for cab occupants. All cab ground lights shall automatically activate when any cab door is opened and by a switch located on the dash.

The 12v steady burn compartment light(s) shall incorporate 12 clear LED and a clear optic hard coated polycarbonate lens. The hard coated lens shall provide extended life/luster protection against UV and chemical stresses. The encapsulated coated PC board and lens fitted with foam in place gasket assembly shall provide additional protection against environmental elements. The solid state compartment light shall be vibration resistant. The 20C0CDCD will contain 350 usable lumens. An installation kit including mounting hardware and rubber gasket shall be provided. The 20C0CDCD will contain a 12" terminated pigtail with a waterproof Deutsch® connector. The compartment light is covered by a five year factory warranty.

One (1)

LIGHTBAR, 72" WHELEN FREEDOM IV

A Whelen Edge Ultra Freedom IV Linear Super-LED LC Series 72" lightbar model F4N7QLED shall be provided. The F4N7QLED lightbar shall incorporate an anodized extruded heavy duty aluminum base and cover chassis with two front red corner modules with two red endcap modules, two interior white modules, and ten interior red modules. The front of each corner module shall consist of 12 red Linear Super-LEDs installed on a conformal coated PCB board with a thermal pad/aluminum bracket heat sink assembly. The short red endcap Linear Super-LED lights shall incorporate six red Super-LED installed on a conformal coated PCB board with a thermal pad/aluminum bracket heat sink assembly. The long red interior Linear Super-LED lights shall incorporate 12 red Super-LED installed on a conformal coated PCB board with a thermal pad/aluminum bracket heat sink assembly. The long white interior Linear Super-LED lights shall incorporate 12 white Super-LEDs installed on a conformal coated PCB board with a thermal pad/aluminum bracket heat sink assembly. The all modules will utilize a Diamond Optix™ metalized reflector and two optic collimators. All electronic components shall be conformal coated to provide additional protection. The outer lens construction shall consist of two clear Uni-Dome top lenses with a clear center lens and utilize two liquid injection molded wiper seal dividers for maximum protection against environmental elements. Metal top shields installed on the Uni-Domes and center lens shall provide protection from climatic conditions and provides passive solar radiation to direct heat away from internal components.

The F4N7QLED shall have an electronic LC I/O board. The solid state I/O board shall be microprocessor controlled. The I/O board shall have built-in reverse polarity protection and output-short protection. The I/O board shall have the ability to flash twenty two Super-LED warning lights. There shall be a data bank of 12 Scan-Lock™ flash patterns including steady burn with low power and cruise light functions. The cruise light function shall allow the user the four corner modules as marker courtesy lights. The F4N7QLED will have the capability to install a traffic advisor in the rear of the lightbar. The I/O board shall also have outputs to add takedown, alley lights, and auxiliary lights for each set of lights to be controlled in pairs.

All lightheades shall be installed in the F4N7QLED with the aid of black polycarbonate snap-in mounting brackets. The solid state lightbar shall be vibration resistant. The lightbar will contain a 17' 2/c 8GA unterminated power cable and 17' 17/c 22GA unterminated control cable. All electronic components are covered by a five year factory warranty. The F4N7QLED shall include a permanent mount kit with hardware.

The lightbar shall be controlled in the following manner:

Calling for Right of Way - All Positions
Blocking Right of Way - Clear shall not be Active

The lights shall be activated by a single emergency light switch located on the master light switch panel in the cab.

City of Jasper Fire Department

Production Specification

The lightbar shall meet NFPA 1901 edition as configured.

One (1)

LIGHT, DRIVER/PASSENGER'S SIDE BROW

Two-(2) brow lights shall be installed on the front cab roof, one-(1) on the driver's and one-(1) on the passenger's side. The mounting brackets shall be attached to the bottom of the lamp head and be machined to conform to the roof radius. Wiring shall extend from a weatherproof strain relief at the rear of the lamp head.

Two (2) Whelen Pioneer Plus Model PFP2 light head(s) shall be provided. The 168 watt +12v DC Pioneer lighthead shall incorporate Super-LED® dual flood light installed in a die-cast white powder coated aluminum housing. The PFP2 configuration shall consist of 60 white Super-LEDs with a clear optic collimator/metalized reflector assembly and a clear non-optic polycarbonate lens. The Pioneer flood light shall have 16,000 usable lumens.

The lens/reflector assembly shall utilize a liquid injected molded silicone gasket to be resistant to water, moisture, dust, and other environmental conditions. The hard coated lens shall provide extended life/luster protection against UV and chemical stresses. The PFP2 shall be vibration resistant. The Pioneer PC boards shall be conformal coated for additional protection. Two breathable membrane patches shall be installed to the bottom of the housing to maintain a consistent internal pressure. The PFP2 shall have extended LED operation with low current consumption and low operating temperature. The Pioneer light shall be SAE 1113-42 compliant and Class 5 testing for EMI. The PFP2 is covered by a five year factory warranty.

One (1)

CAB PAINT FINISH, TWO TONE

The custom cab shall have a two-tone paint finish. The paint colors shall be furnished by the customer. The break in the color shall be at the bottom of the chassis window, unless otherwise specified by the department.

All cab exterior components including doors and glass, shall be removed. The complete cab exterior shall be thoroughly sanded, solvent cleaned and finished with high luster polyurethane paint before mounting of body to assure full coverage of paint to all surfaces.

One (1)

UPPER CAB PAINT FINISH

The upper cab exterior shall have no mounted components prior to painting to assure full coverage of metal treatments.

These steps are followed as recommended by the paint manufacturer to provide a lasting and high quality gloss finish. All paint products shall be provided by DuPont.

One (1)

UPPER CAB PAINT COLOR/CODE

The upper cab paint code shall be White, 854064.

One (1)

PRIMARY/LOWER CAB PAINT FINISH

City of Jasper Fire Department

Production Specification

The primary/lower cab exterior shall have no mounted components prior to painting to assure full coverage of metal treatments.

These steps are followed as recommended by the paint manufacturer to provide a lasting and high quality gloss finish. All paint products shall be provided by DuPont.

One (1)

PRIMARY/LOWER CAB PAINT COLOR/CODE

The primary/lower cab paint code shall be Red, 854008.

One (1)

CAB PAINT BREAK LINE STRIPE

A 1/4" wide black paint pin stripe shall be added to the cab, two tone paint scheme. This stripe shall be at the line break

One (1)

INTERCOM SYSTEM - FIRECOM

A FIRECOM 210 series intercom system shall be installed to provide noise suppression while providing clear voice communications for two-(2) seated positions in the cab. There shall be an optional connection for the installation of a pump panel station.

Communications are provided by two-(2) under the helmet headsets. This system includes:

- Intercom System
- UH51 Headsets
- HM10 Plug-In Module
- Optional Mobile Radio Interface
- Optional Pump Panel Station

The driver and officer headsets include the intercom and two-way radio communication functions.

One (1)

MASTER INTERCOM STATION

A Firecom model 210 intercom shall be provided and installed in the unit. This system shall have the capability of installing up to two-(2) positions. This unit shall have mobile radio compatibility. This system eliminates clipped words and reduces siren and background noise. A membrane switch provides adjustable volume and advanced noise reducing circuitry shall be incorporated into this system. The controls shall be large, readily accessible and the LED shall provide system status day or night. The power connector shall be a 12-volt nominal power supply.

This intercom shall have a two-(2) year warranty.

One (1)

MOBILE RADIO INTERFACE

The intercom system shall be provided with a Firecom mobile radio interface cable between the Departments radio and the Firecom system for the specified location.

City of Jasper Fire Department

Production Specification

Customer must specify make and model radio.

One (1)

DRIVER'S HEADSET

There shall be a model UH51 headset provided for the driver position. The headset shall provide a single plug under helmet radio transmit headset. It shall have a (PTT) "Push to Talk" located on the dome. The headset shall come with an adjustable volume, noise canceling electric microphone, adjustable head strap, and flexible style boom for rotation of right or left dress. The headset shall provide high clarity speakers and fully shielded EMI/RFI protected cabling to maximize performance. The headset shall have liquid foam ear seals and provide 24 dB of noise reduction.

The headset shall have a two-(2) year warranty.

One (1)

There shall be one-(1) HM10 headset plug in module provided for the driver's headset. The module is used to connect the intercom via the module RJ-14 jack. The module features a connector guard to protect against moisture and dust.

One (1)

OFFICER'S HEADSET

There shall be a model UH51 headset provided for the officer's position. The headset shall provide a single plug under helmet radio transmit headset. It shall have a (PTT) "Push to Talk" located on the dome. The headset shall come with an adjustable volume, noise canceling electric microphone, adjustable head strap, and flexible style boom for rotation of right or left dress. The headset shall provide high clarity speakers and fully shielded EMI/RFI protected cabling to maximize performance. The headset shall have liquid foam ear seals and provide 24 dB of noise reduction.

The headset shall have a two-(2) year warranty.

One (1)

There shall be one-(1) HM10 headset plug in module provided for the officer's headset. The module is used to connect the intercom via the module RJ-14 jack. The module features a connector guard to protect against moisture and dust.

One (1)

CARRYING CAPACITY PLATE

A permanently attached carrying capacity plate in accordance with NFPA 1901 Standards shall be installed in plain view of the driver.

The tag shall include the following:

- Overall height
- Overall length
- GVWR
- Seating capacity

City of Jasper Fire Department

Production Specification

One (1)

SEATING CAPACITY PLATE

A permanently attached Seating Capacity Plate shall be mounted in the cab in plain view that reads "Seating Capacity – 4 People".

Each seating position that is not, intended to be used during transit shall be individually labeled as follows:

"WARNING THIS SEAT IS NOT TO BE OCCUPIED WHILE VEHICLE IS IN MOTION"

One (1)

OCCUPANCY/SEAT BELT PLATE

Occupancy / Seat Belt plates shall be provided and installed visible from each seated position, which reads:

"OCCUPANTS MUST BE SEATED AND BELTED WHEN THE APPARATUS IN MOTION"

One (1)

"DO NOT WEAR HELMET" PLATE

A plate shall be installed visible from each seating position that states:

"DO NOT WEAR HELMET WHILE SEATED"

One (1)

OVERALL HEIGHT/LENGTH/WEIGHT PLATE

An Overall Height/Length/Weight information plate shall be installed that can be clearly identified and visible to the driver while in the seated position showing the apparatus completed overall height, length, (in feet and inches) and gross vehicle weight (in tons) current to the apparatus manufactured date.

If changes to the vehicle occur while in service, the department must revise the overall height-length-weight plate.

One (1)

FLUID CAPACITY PLATE

A permanently affixed fluid date plate shall be installed in the driving compartment to indicate the type and quantities of the following fluid used in the vehicle.

- Engine Oil
- Engine Coolant
- Chassis Transmission Fluid
- Pump Transmission Lubrication Fluid (if applicable)
- Pump Primer Fluid (if applicable)
- Drive Axle Lubrication Fluid
- Air Conditioning Refrigerant
- Air Conditioning Lubrication Oil
- Power Steering Fluid
- Cab Tilt Mechanism Fluid

City of Jasper Fire Department

Production Specification

- Transfer Case Fluid
- Equipment Rack Fluid
- Air Compressor System Lubricant
- Generator System Lubricant
- Front Tire Pressure - Cold
- Rear Tire Pressure - Cold

The following information shall also be supplied on the Fluid Data Plate:

- Chassis Manufacturer
- Production Number
- Paint Number
- Year Built
- Date Shipped
- Vehicle Identification Number

One (1)

MOVEMENT WARNING PLATE

A permanently affixed Movement Warning plate shall be installed near the door ajar light that reads:

"DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

One (1)

"DO NOT RIDE" PLATE

A permanently affixed "DO NOT RIDE" warning plate shall be installed located on the stepping areas of the vehicle warning personnel that riding on or in these areas while the vehicle in motion is prohibited.

CAB TO AXLE DIMENSION

Cab to axle will be 134".

CHASSIS MODIFICATIONS

LUBRICATION AND TIRE DATA PLATE

A permanent label in the driving compartment shall specify the quantity and type of the following fluids used in the vehicle and tire information:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Pump transmission lubrication fluid . . (if applicable)
- Pump priming system fluid, if applicable . . (if applicable)
- Drive axle(s) lubrication fluid
- Air conditioning refrigerant . . (if applicable)
- Air conditioning lubrication oil . . (if applicable)
- Power steering fluid

City of Jasper Fire Department

Production Specification

- Cab tilt mechanism fluid . . (if applicable)
- Transfer case fluid . . (if applicable)
- Equipment rack fluid (if applicable)
- CAFS air compressor system lubricant . . (if applicable)
- Generator system lubricant . . (if applicable)
- Front tire cold pressure
- Rear tire cold pressure
- Maximum tire speed ratings

VEHICLE DATA PLATE

A permanent label in the driving compartment which indicates the following:

- Filter part numbers for the;
 - Engine
 - Transmission
 - Air
 - Fuel
- Serial numbers for the;
 - Engine
 - Transmission
- Delivered Weights of the Front and Rear Axles
- Paint Brand and Code(s)
- Sales Order Number

OVERALL HEIGHT, LENGTH DATA PLATE (US)

The fire apparatus manufacturer shall permanently affix a high-visibility label in a location visible to the driver while seated.

The label shall show the height of the completed fire apparatus in feet and inches, the length of the completed fire apparatus in feet and inches, and the GVWR in pounds.

Wording on the label shall indicate that the information shown was current when the apparatus was manufactured and that, if the overall height changes while the vehicle is in service, the fire department must revise that dimension on the plate.

City of Jasper Fire Department

Production Specification

PERSONNEL CAPACITY

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

SEAT BELT WARNING - FAMA06/07

A safety sign FAMA06 shall be visible from each seat that is not equipped with occupant restraint and therefore not intended to be occupied while the vehicle is in motion.

A safety sign FAMA07, which warns of the importance of seat belt use, shall be visible from each seat that is intended to be occupied while the vehicle is in motion.

EQUIPMENT MOUNTING FAMA10

A safety sign FAMA10, which warns of the need to secure items in the cab, shall be visible inside the cab.

FIRE SERVICE TIRES - FAMA12

A safety sign FAMA12, which warns of the special requirements for fire service-rated tires, shall be visible to the driver entering the cab of any apparatus so equipped.

HELMET WARNING - FAMA15

A safety sign FAMA15, which warns not to wear helmets while the vehicle is in motion, shall be visible from each seat that is intended to be occupied while the vehicle is in motion.

CLIMBING METHOD - FAMA23

A safety sign FAMA23, which warns of the proper climbing method, shall be visible to personnel entering the cab and at each designated climbing location on the body.

REAR STEP CROSSWALK WARNING - FAMA24

A safety sign FAMA24, which warns personnel not to ride on the vehicle, shall be located at the rear step areas and at any cross walkways.

FINAL STAGE MANUFACTURER VEHICLE CERTIFICATION

A final stage manufacturer vehicle certification label shall be provided and installed in the driver cab door jamb area.

FRONT BUMPER EXTENSION

The front bumper of the chassis shall be extended approximately 28" ahead of the cab by the cab/chassis manufacturer.

BUMPER GRAVEL SHIELD

The front bumper extension shall have a 3/16" NFPA compliant aluminum tread plate gravel shield. The gravel shield shall cover the full width of the front bumper to the front of the cab and the full height of the bumper on

City of Jasper Fire Department

Production Specification

each end.

RESCUE BUMPER COMPARTMENT

The front bumper shall have a minimum 28" extension and have three (3) individual compartments. Two (2) compartments shall be provided outboard of the chassis frame rails each capable of storing one (1) low pressure air, electric, or hydraulic hose reel. The floors of the outboard compartments shall be sloped to increase the angle of approach. One (1) compartment shall be located in center of extension located between the chassis frame rails to store equipment, or hydraulic rescue tools.

A 6.5" high single lid shall cover all three (3) compartments fabricated from 1/8" NFPA compliant aluminum tread plate with stainless steel hinges, chrome lift handle, two (2) rubber "T-handle" type latches, and two (2) gas shock type hold open devices, one (1) at each end. A "Not a Step" label shall be provide on outer lid surface.

Bumper compartment shall have a one (1) OnScene 36" LED light near door opening to provide a minimum of 2 fc (20 lx) at any location on the floor of the compartment without any equipment in the compartment. Light shall be automatically activated when door is opened. A flashing warning light signal shall be provided indicating when parking brake is released that a compartment door is not in a closed position as required by NFPA 1901.

The following shall be located in the bumper:

- One (1) Hannay EF2016-17-18 hydraulic hose reel(s) with painted finish capable of storing 100' of dual line hydraulic hose. The rewind button for each reel shall be located adjacent to the reel it controls.
- The hydraulic reel shall be equipped with 75' of Genesis high pressure 10,500 PSI hydraulic hose with OSC couplings and a molded plastic ball clamp. The hose shall be red in color.
- The hydraulic reel shall connect to the hydraulic pump with one (1) 30' Genesis hydraulic hose(s) with OSC couplings at pump end.

Effective May 1, 2014, all Hurst 5,000 PSI hoses and hose reels will be a grey/yellow twin-line with black guards. In order to differentiate the hoses, a set of inserts will be shipped with each hose so that you may designate which color each hose is

- The fairlead roller shall be mounted directly to the reel.
- One (1) Hannay EF2016-17-18 hydraulic hose reel(s) with painted finish capable of storing 100' of dual line hydraulic hose. The rewind button for each reel shall be located adjacent to the reel it controls.
- The hydraulic reel shall be equipped with 75' of Genesis high pressure 10,500 PSI hydraulic hose with OSC couplings and a molded plastic ball clamp. The hose shall be blue in color.
- The hydraulic reel shall connect to the hydraulic pump with one (1) 30' Genesis hydraulic hose(s) with OSC couplings at pump end.

Effective May 1, 2014, all Hurst 5,000 PSI hoses and hose reels will be a grey/yellow twin-line with black guards. In order to differentiate the hoses, a set of inserts will be shipped with each hose so that you may designate which color each hose is

City of Jasper Fire Department

Production Specification

- The fairlead roller shall be mounted directly to the reel.

AIR HORN(S)

The air horn(s) shall be supplied and installed by the cab/chassis manufacturer.

GROUND LIGHTS

There shall be two (2) OnScene 8" Access LED lights installed below bumper capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting shall be switchable but activated automatically when the vehicle park brake is set.

FRONT TOW PROVISIONS

The front tow provisions shall be supplied and installed by the cab/chassis manufacturer.

AIR INTAKE SYSTEM

An air filter shall be provided in the engine's air intake system by the customer cab/chassis manufacturer.

Air inlet restrictions shall not exceed the engine manufacturer's recommendations.

The air inlet shall be equipped with a means of separating water and burning embers from the air intake system.

This requirement shall be permitted to be achieved by either of the following methods:

- Provision of a device such that burning particulate matter larger than 0.039 in. (1.0 mm) in diameter cannot reach the air filter element.
- 1. Provision of a multi screen ember separator capable of meeting the test requirements defined in the Parker Hannafin, Racor Division, publication LF 1093-90, *Ember Separation Test Procedure*, or an equivalent test.

EXHAUST

The exhaust system shall be as provided by cab/chassis manufacturer. The tailpipe may require some modifications for proper ground clearances and fit with body.

The exhaust piping and discharge outlet shall be located or shielded so as not to expose any portion of the vehicle or equipment to excessive heating.

Exhaust pipe discharge shall be directed away from any operator's position or entry doors on body.

Where parts of the exhaust system are exposed so that they are likely to cause injury to operating personnel, protective guards shall be provided.

SEAT BELT COLOR

Section 14.1.3.4 of the NFPA 1901 Standards, requires all seat belt webbing in cab to be bright red or bright orange in color, and the buckle portion of the seat belt shall be mounted on a rigid or semi rigid stalk such that the buckle remains positioned in an accessible location.

City of Jasper Fire Department

Production Specification

SEAT BELT WEB LENGTH - CUSTOM CAB

Sections 14.1.3.2 and 14.1.3.3 of the NFPA 1901 standards, require the effective seat belt web length for a Type 1 lap belt for pelvic restraint to be a minimum of 60", and a Type 2 pelvic and upper torso restraint-style seat belt assembly to be a minimum of 110".

The chassis seat belt web length as supplied by the custom chassis manufacturer shall be compliant to NFPA Standards 14.1.3.2 and 14.1.3.3.

SEAT BELT / VDR SYSTEM - CUSTOM CAB

The seat belt warning and vehicle data recorder systems shall be provided by the cab/chassis manufacturer.

HELMET STORAGE

No helmet storage is required in the cab driving area.

HELMET STORAGE

No helmet storage is required in the cab crew area.

CAB CRASH TEST CERTIFICATION

A cab crash test certification from the fire apparatus manufacturer shall be provided with the equipment. A copy of this certification shall be included with the bid.

NOTE: There shall be no exception to any portion of the cab integrity certification requirements. Nonconformance shall lead to immediate rejection of bid.

The certification shall state that the cab does meet or exceed the requirements below:

2. European Occupant Protection Standard ECE Regulation No. 29.
 - 1) SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks.

CAB MIRRORS, DRIVER ADJUSTABLE

Section 14.3.5 of the NFPA 1901 Standards, 2009 edition, requires all primary rear view mirrors used by the driver to be adjustable from the driver's position.

MUDFLAPS

There shall be 1/4" rubber mudflaps provided and installed behind each set of tires to prevent throwing road debris and lower road spray.

AIR BRAKE SYSTEM QUICK BUILD-UP

The air brake quick build-up system shall be supplied from the cab/chassis manufacturer.

The quick buildup system shall provide sufficient air pressure so that the apparatus has no brake drag and is able to stop under the intended operating conditions following the 60-second buildup time.

City of Jasper Fire Department

Production Specification

ROAD EMERGENCY SAFETY KIT

One (1) set of three (3) dual faced triangular warning flares with fold away base complete with storage case per DOT requirements shall be provided with the completed apparatus.

One (1) 2.5 lb. ABC type vehicle fire extinguisher with bracket per DOT requirements shall be provided and mounted inside cab area.

CAB INTERIOR CABINET - CENTER REAR WALL

There shall be one (1) storage cabinet located in rear cab area. The cabinet shall be fabricated from 1/8" smooth aluminum and finished with a dark gray hammer tone powder coat paint for a hard and durable finish. The cabinet shall be approximately 40" wide x 40" high x 16" deep. Specified four (4) Streamlight Litebox flashlights shall be mounted to top of cabinet surface. Two (2) built-in medical glove box holders shall be provided on driver side and two (2) 6" plastic tubes on passenger side for storage of size "D" O2 cylinders. Final design to be determined at pre-construction meeting.

- 2) There shall be one (1) 100 amp Blue Sea Systems ST Series blade type fuse block with screw type terminals for both positive and negative buss with cover provided for distribution of up to six (6) 30 amp, 12 VDC circuits. Fuse block shall be located per required circuits and be protected from damage.

There shall be two (2) OnScene Solutions 36" Access LED light(s) mounted inside the cabinet.

- Cabinet shall be provided with vertically mounted shallow aluminum Shelf-Trac for specified component installation.
- There shall be one (1) adjustable shelf/shelves in the above cabinet(s). Each shelf shall have a 1.25" vertical lip at front to contain items while vehicle is in motion.
- Cargo netting of 2" nylon webbing shall be provided over cabinet opening with easy release automotive style latches at top and/or sides.

CAB MISCELLANEOUS EQUIPMENT

The following items shall be provided in cab as follows;

- There shall be one (1) 120 VAC outlet(s) located under desk against the back edge.
 - The outlet receptacle(s) shall be 20 amp, straight-blade (NEMA 5-20R).
 - Outlet(s) shall be powered by both the on-board generator and shore power system through a relay system.

FUEL FILL

There shall be one (1) fuel fill door located in the streetside exterior wheel well panel, behind the rear axle. The fill door shall be fabricated from brushed stainless steel. There shall be a permanent label with the text "DIESEL FUEL ONLY" located adjacent to the fuel fill access.

BODY DESIGN

City of Jasper Fire Department

Production Specification

The importance of public safety associated with emergency vehicles requires that the construction of this vehicle meet the following specifications. These specifications are written to establish the minimum level of quality and design. All Bidders shall be required to meet these minimum requirements.

It is the intent of these specifications to fully describe the requirements for a custom built emergency type vehicle. In order to extend the expected service life of this vehicle, the body module shall be removable from the chassis frame and be capable of being installed on a new chassis.

The sheet metal material requirements, including alloy and material thickness, throughout the specifications are considered to be a minimum. Since such materials are available to all Manufacturers, the material specifications shall be strictly adhered to.

The fabrication of the body shall be formed sheet metal. Formed components shall allow the City of Jasper Fire Department to have the body repaired locally in the case where any object has struck the body and caused damage. The use of proprietary extrusions will prevent the City of Jasper Fire Department from such repair and shall NOT be used.

Following construction of the subframe, which supports the apparatus body, the sheet metal portion of the body shall be built directly on the subframe. The joining of the subframe and body shall be of a welded integral construction.

The sheet metal fabrication of the body shall be performed using inert gas continuous feed welders only. The entire body shall be welded construction. The use of pop rivets in any portion of structural construction may allow premature failure of the body structure. Therefore, pop rivets shall NOT be used in the construction of the structural portions of the body. This includes side body sheets, inner panels of compartment doors, and any other structural portions of the body.

EXTERIOR ALUMINUM BODY

The fabrication of the body shall be constructed from aluminum 3003H-14 alloy smooth plate. This shall include compartment front panel, vertical side sheets, side upper rollover panels, rear panels and compartment door frames.

The body compartment floors and exterior panels shall be constructed with not less than 3/16" (.187) aluminum 3003H-14 smooth plate. Interior compartment dividing walls shall be constructed with not less than 1/8" (.125) aluminum 3003H-14 smooth plate. Lighter gauge sheet metal will not be acceptable in these areas, No Exceptions.

The front and rear corners of body shall be formed as part of the front or rear body panels. This provides a stronger body corner and finished appearance. The use of extruded corners, or caps will not be acceptable, No Exceptions.

The door side frame openings shall be formed "C" channel design. An electrical wiring conduit raceway running the full length of exterior compartments shall be provided. This raceway shall contain all 12 volt wiring running to the rear of the apparatus, permitting easy accessibility to wiring.

Individual compartment modules, with dead air space voids between compartments, will not be an acceptable method of compartment construction.

City of Jasper Fire Department

Production Specification

The compartments shall be an integral part of the body construction. Compartment floors from front of body to ahead of rear axle, also from rear axle to rear of body shall be single one-piece sections. Compartment floors shall be preformed, then positioned in body and welded into final position.

Compartment floors shall have a "sweep-out" design with door opening threshold positioned lower than compartment floor, permitting easy cleaning of compartments. Angles, lips, or door moldings are not acceptable in the base of compartment door opening. One-way rubber drain valves shall be provided in compartment floors so that a water hose may be used to flush-out compartment area.

All exterior seams in sheet metal below frame, and around the rear wheel well area shall be welded and caulked to prevent moisture from entering the compartments. All other interior seams and corners shall be sealed with silicone based caulk prior to painting.

Only stainless steel bolts, nuts, and sheet metal screws shall be used in mounting exterior trim, hardware and equipment.

DRIP RAILS

The body shall have drip rails over the side full height compartments. The drip rails shall be formed into the upper body panels providing a ridged lower panel and a flat upper body panel surface. The use of mechanically fastened, taped or glued on drip rails will not be acceptable, No Exceptions.

ROOF CONSTRUCTION WITH COMPARTMENTS

The roof structure shall be integral with the body sheet metal construction and shall be an all welded assembly. All seams in roof material shall be fully and continuously welded to prevent entry of moisture.

There shall be a total of four (4) 2" x 2" x 1/4" 6061-T6 alloy aluminum "C" channels running the length of body, two (2) on each outboard side. These "C" channels shall be used for roof support and in addition shall be used for mounting of any specified reels. This open "C" channel design along with special reel mounting clips allows for a universal location of any specified reels within each compartment.

In between the two (2) center "C" channels running the length of body shall be 2" x 2" x 1/4" 6061-T6 alloy aluminum tubing running in between and welded in place on approximate 16" centers to support roof and/or walkway structure if specified.

A 2" formed radius shall be provided along the body sides and utilized as a wiring trough. The use of aluminum extrusions in this area shall not be acceptable, .

BODY SUBFRAME

The chassis frame rails shall be fitted with 1/4" custom extruded UHMW polyethylene rail cap to isolate the body frame members from direct contact with chassis frame rails.

The body subframe shall be constructed from 6061T6 aluminum alloy tubing. Subframe shall consist of two (2) 2" x 6" x 1/4" aluminum tubes, the same width as the chassis frame rails, NO EXCEPTION. Welded to this tubing shall be cross members of 2" x 6" x 1/4" aluminum. These cross members shall extend the full width of the body to support the compartments. Cross members shall be located at front and rear of the body, below compartment divider walls, and in front and rear of wheel well opening. Additional aluminum cross members shall be located on 16" centers, or as necessary to support walkway or heavy equipment.

City of Jasper Fire Department

Production Specification

To form the frame, the tubing shall be beveled and welded at each joint using 5356 aluminum alloy welding wire.

BODY MOUNTING

The body subframe shall be fastened to the chassis frame with a minimum of six (6) spring loaded body mounts. Each mount shall be configured using a two-piece encapsulated slide bracket. The two (2) brackets shall be fabricated of heavy duty 1/4" thick steel and shall have a powder coat finish to prevent any corrosion. Each mounting assembly shall utilize two (2) 3/4" diameter x 6" long grade 8 bolts and two (2) heavy duty springs. The assembly design shall allow the body and subframe to act as one (1) component, separate from the chassis. As the chassis frame twists under driving conditions, the spring mounting system shall eliminate any stress from being transferred into the body. The spring loaded body mounts shall also prevent frame side rail or body damage caused by unevenly distributed stress and strains due to load and chassis movement.

Body mountings that do not allow relief from chassis movement will not be acceptable.

10" REAR STEP BUMPER

The full width rear bumper shall be constructed from 2" x 2" x 1/4" aluminum tubing frame and covered with 3/16" NFPA compliant aluminum tread plate. The bumper shall extend from the rear vertical body panel 10" and provide a rear step with a minimum of 1/2" space at body for water drainage.

REAR TOW EYES

There shall be two (2) heavy duty rear mounted tow eyes securely attached to the chassis frame and mounted above the rear bumper. The tow eyes shall be fabricated from 1" thick steel plate and shall have a black powder coat finish.

GROUND LIGHTS

There shall be two (2) OnScene 8" Access LED lights installed below bumper capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting shall be switchable but activated automatically when the vehicle park brake is set.

WHEEL WELL EXTERIOR PANEL

The exterior panel of the body wheel well enclosure shall be constructed from 3/16" smooth aluminum panels.

STAINLESS STEEL BODY FENDERS

The body wheel well openings shall be provided with round radius, polished stainless steel fenderettes. The fenderettes shall be bolted and easily replaceable if damaged. The fenderettes shall be installed using a rubber gasket to reduce buildup of moisture and/or debris.

WHEEL WELL LINERS

The wheel wells shall be provided with an easily removable polymer, circular inner fender liner. The inner liner shall be bolted to the wheel well with stainless steel bolts and spaced away from the wheel well so the liner will

City of Jasper Fiire Department

Production Specification

not accumulate dirt or water.

BODY PAINT SPECIFICATIONS

BODY PAINT PREPARATION

After the body and components have been fabricated they shall be disassembled so when vehicle is complete there shall be finish paint beneath the removable components. The body shall be removed from chassis during the paint process to insure proper paint coverage. The body and components shall be metal finished as follows to provide a superior substrate for painting.

The exterior (and interior, if painted) body shall undergo a thorough cleaning process starting with a biodegradable phosphoric acid solution to begin the etching process followed by a complete clear water rinse. The next step shall consist of a chemical conversion coating applied to seal the metal substrate and become part of the metal surface for greater film adhesion.

All bright metal fittings, if unavailable in stainless steel or polished aluminum, shall be chrome plated. Iron fittings shall be copper under plated prior to chrome plating.

PAINT PROCESS

The paint process shall follow the strict standards set forth by PPG Industries guidelines. Painters applying PPG products will be PPG Certified Commercial Technicians, and re-certified every two (2) years. The body shall go through the following paint process;

- Clean bare metal with a wax and grease remover using low lint rags.
- 1) Inspect, straighten, and hammer high points, grind all seams, sharp edges, and welds. DA sand entire paintable surfaces using 24-180 grit dry paper. Plastic fill all low spots and DA sand fill areas using 36-180 grit dry paper. Apply pinhole filler and DA sand areas using 80-180 grit dry paper.
- 2) Re-clean bare metal using a wax and grease remover and low lint rags.
- 3) Within 24 hours, a PPG Delfleet® epoxy color primer with proper hardener for corrosion resistance using a pressure pot spray gun and applying 2-5 full wet coats or 1.5-8.0 dry mils max. achieving full hiding and allow to air dry 60 minutes @ 70°F or bake for 45 minutes @ 140°F degree.
- 4) Inspect, putty fill, and dry guild coat entire body surface and DA sand using 180-400 grit dry paper.
- 5) Re-clean bare metal using a wax and grease remover using low lint rags.
- 6) A PPG Delfleet® primer sealer with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 1 full wet coat or 1.0-2.0 dry mils achieving full hiding and allow to flash off in spray booth for minimum of 60 minutes @ 70°F.
- 7) A PPG Delfleet® FBCH basecoat (color) with proper hardener and dry additive shall then be sprayed using a pressure pot set @ 45-60 PSI and achieving full hiding or 1.5-2.0 wet mils and allow to flash off in spray booth 45-60 minutes before applying clearcoat.
- 8) A PPG Delfleet® clearcoat with proper hardener and thinner shall be sprayed using a pressure pot spray gun and applying 2-3 full wet coats or 5.0 wet mils for a uniform gloss and allow to flash off in spray booth 10 minutes and bake for 120-140 minutes @ 125°F (surface temp.).
- 9) After cooling, DA sand heavy orange peel or runs using 1000 grit dry sand paper and final DA sand using 1500-2000 grit dry sand paper. Wipe off all surfaces to remove dust and debris. Buff unit as needed using 3M rubbing compound and a white wool pad and inspect until all sand scratches are removed.
- 10) Polish as needed using 3M Perfect-It-Polish and a black foam pad, repeat as necessary and inspect until all sand scratches are removed.

PAINT - ENVIRONMENTAL IMPACT

City of Jasper Fiire Department

Production Specification

The contractor shall meet or exceed all current State (his) regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. PPG Delfleet® Evolution paint shall be free of all heavy metal (lead & chromate) components. Paint emissions from sanding and painting shall be filtered and collected. All paint wastes shall be disposed of in an environmentally safe manner. Solvents used in cleanup operations shall be collected, sent off-site for distillation and returned for reuse.

FASTENERS

Prior to the assembly and reinstallation of exterior components; i.e. warning and DOT lights, handrails, steps, door hardware, and miscellaneous items, a Mylar isolation tape, or gasket shall be used to prevent damage to the finish painted surface. These components shall be fastened to body using either a plastic insert into body metal with stainless steel screws or zinc coated nut-serts into body surface using stainless steel bolts to prevent corrosion from dissimilar metals.

ELECTROLYSIS CORROSION CONTROL

The vehicle shall be assembled using ECK brand or similar corrosion control compound on all high corrosion potential areas.

ECK protects aluminum and stainless steel against electrolytic reaction, isolates dissimilar metals and gives bedding protection for hardware and fasteners. ECK contains anti-seizing lubricant for threads. ECK is dielectric and perfect for use with electrical connectors.

PAINT FINISH - SINGLE COLOR

The body shall be painted with a single color of PPG Delfleet® Evolution per City of Jasper Fiire Department approved paint spray out provided.

A small touch-up bottle of paint shall be provided with completed vehicle.

11) Paint Color: Match cab/chassis supplied paint color.

BODY UNDERCOATING

The entire underside of body shall be sprayed with black automotive undercoating. Undercoating shall cover all areas underside of body and wheel well area to help prevent corrosion under the vehicle.

UNDERCOAT WARRANTY

The body undercoating shall have a warranty provided by the manufacturer for the lifetime of the vehicle or twenty (20) years, whichever occurs first. The warranty shall be transferable between vehicle owners. Should the undercoating material applied to the underside of the body and wheel wells of the vehicle ever flake off, peel, chip or crack due to drying out, the damaged area shall be re-sprayed without charge to the vehicle owner.

PAINT WARRANTY

The vehicle shall be provided with a ten (10) year non-prorated warranty to the original owner. Warranty is provided by PPG Inc. A warranty sheet with all conditions and maintenance procedures shall be provided with the delivered vehicle. **Pro-rated warranties will not be acceptable.**

City of Jasper Fiire Department

Production Specification

COMPARTMENT INTERIOR FINISH

The interior of all exterior body compartments shall be a "Maintenance Free" smooth unpainted finish. All body seams shall be finished with a caulk sealant for both appearance and moisture protection.

REFLECTIVE STRIPE REQUIREMENTS

Material

All retroreflective materials shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

All retroreflective materials used that are colors not listed in ASTM D 4956, Section 6.1.1, shall have a minimum coefficient of retroreflection of 10 with observation angle of 0.2 degrees and entrance angle of -4 degrees.

Any printed or processed retroreflective film construction used shall conform to the standards required of an integral colored film as specified in ASTM D 4956, Section 6.1.1.

Minimum Requirements

A retroreflective stripe(s) shall be affixed to at least 50 percent of the cab and body length on each side, excluding the pump panel areas, and at least 25 percent of the width of the front of the apparatus.

The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The 4 in. (100 mm) wide stripe or combination of stripes shall be permitted to be interrupted by objects (i.e., receptacles, cracks between slats in roll up doors) provided the full stripe is seen as conspicuous when approaching the apparatus.

GRAPHICS PROOF

A color graphics proof of the reflective striping layout shall be provided for approval by City of Jasper Fiire Department prior to installation. The graphics proof shall be submitted to City of Jasper Fiire Department on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

REFLECTIVE STRIPE - CAB SIDE

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color with top and bottom 1/8" black edge.

There shall be a 1/2" Super Gold with engine turned finish stripe located approx. 1" below top of the main stripe and 1" above bottom of main stripe.

REFLECTIVE STRIPE - CAB FRONT

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color with top and bottom 1/8" black edge.

City of Jasper Fire Department

Production Specification

There shall be a 1/2" Super Gold with engine turned finish stripe located approx. 1" below top of the main stripe and 1" above bottom of main stripe.

- This reflective stripe shall be white in color.

CHEVRON STRIPE - CAB BUMPER

A reflective stripe shall be affixed to the front of cab. The stripe or combination of stripes shall be a minimum of 4 in. (100 mm) in total width.

The approximate 10" wide Chevron retroreflective stripe shall be affixed to at least 25 percent of the width of the front of the apparatus with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width. Chevron panels shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panels shall have a minimum 10 year warranty for material failure, and colorfastness.

- The stripe material shall be 3M Scotchlite Diamond Grade.

All retroreflective materials required shall conform to the requirements of ASTM D 4956, *Standard Specification for Retroreflective Sheeting for Traffic Control*, Section 6.1.1 for Type I Sheeting.

This reflective chevron stripe shall alternate red and fluorescent yellow-green in color.

REFLECTIVE STRIPE - BODY SIDES

The reflective stripe material shall be 6" wide, 3M Scotchcal 680 series.

- This reflective stripe shall be white in color with top and bottom 1/8" black edge.

There shall be a 1/2" Super Gold with engine turned finish stripe located approx. 1" below top of the main stripe and 1" above bottom of main stripe.

The stripe shall extend from the front of cab in a straight line, then just ahead of the rear wheels the stripe shall angle up and extend straight back to the rear of the body.

CHEVRON REFLECTIVE STRIPE - REAR SIDES PANELS

At least 50 percent of the rear-facing vertical surfaces, visible from the rear of the apparatus, excluding any pump panel areas not covered by a door, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" width.

The rear side panels of the body on each side of a rear stairway or compartment shall have a chevron style reflective stripe, extending from bumper height up to side compartment drip rail height. Each chevron panel shall be a full sheet and shall have a 3M UV over laminate to protect from UV rays, scene damage, and everyday use. Chevron panel shall have a minimum 10 year warranty for material failure, and colorfastness.

The stripe material shall be 3M Diamond Grade.

This reflective chevron stripe shall alternate red and fluorescent yellow-green in color.

City of Jasper Fire Department

Production Specification

LETTERING

GRAPHICS PROOF

A color graphics proof of the lettering layout shall be provided for approval by City of Jasper Fire Department prior to installation. The graphics proof shall be submitted to City of Jasper Fire Department on 8.5" x 11" sheets with front, sides, rear and plan views, each on one (1) sheet. In addition if there is any special art work an additional sheet shall be provided showing all details.

The following lettering shall be provided and installed on the completed unit as follows;

SIDE CAB DOOR LETTERING

There shall be twenty six (26) 6" high SuperGold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

"JASPER" - Arched on front cab doors.
"RESCUE 1" - Straight

UPPER BODY SIDE LETTERING

There shall be thirty two (32) 10" high SuperGold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

"JASPER FIRE RESCUE" - On upper body sides.

REAR BODY LETTERING

FRONT OF CAB LETTERING

There shall be six (6) 4" high SuperGold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

"JASPER" - Above windshield.

There shall be seven (7) 3" high SuperGold letters furnished and installed on the vehicle. Lettering shall have a clear 3M UV Protective Over Laminate applied before installation.

"RESCUE 1" - Below windshield.

DIAL 911

Two (2) "Dial 911" decals shall be provided one (1) on each side of vehicle rear doors, centered on main reflective stripe. Letters shall be Scotchcal retroreflective type material, and match main stripe color.

Reflective Color: _____

Options: White, Red, Blue, Forrest, Black. (call factory for more options)

LETTERING ALLOWANCE

City of Jasper Fire Department

Production Specification

In addition to the indicated striping, there shall be a lettering allowance totaling \$3,000.00 included in the price of the apparatus. Any additional lettering over the allowance shall be paid for by the City of Jasper Fire Department.

EXTERIOR COMPARTMENT DOORS

ROLL-UP DOOR CONSTRUCTION - AMDOR

The apparatus shall be equipped with Amdor brand exterior roll-up compartment doors. Amdor roll-up doors shall be complete with the following features;

- 1" aluminum double wall slats with continuous ball & socket hinge joint and recessed dual durometer slat seal
- Double wall reinforced bottom panel with stainless steel lift bar latching system
- Bottom panel flange with cut-outs for ease of access with gloved hands
- Reusable slat shoes with positive snap-in securement
- Smooth interior door curtain to prevent equipment hang-ups
- One-piece aluminum door track / side frame, top gutter with non-marring seal
- Non-marring recessed side seals with UV stabilizers to prevent warping
- Dual leg bottom seal, with all wear component material to be Type 6 Nylon
- The door shall be warranted for a period of 36 months from the date of delivery. AMDOR Inc. liability covers the replacement or repair of any component that fails due to defects in material and / or workmanship during the coverage period.

Each shutter door shall decrease the compartment door frame opening approximately 2.00" in width and approximately 5.50" in height for the bottom section of door assembly.

The specified retroreflective stripe material shall be applied on the roll-up compartment doors. The stripe shall be precision machine cut for each door slat of the roll-up doors. Under no circumstance will the stripe material be cut on roll-up door surface.

BODY HEIGHT MEASUREMENTS

The vertical body dimensions shall be as follows:

AHEAD OF REAR AXLE

	<u>Description</u>	<u>Dimension</u>
A	Bottom of Subframe to Top of Body	74.0"
B	Bottom of Subframe to Bottom of Body	22.5"
C	Vertical Door Opening	
	-with roll-up door	67.5"
	-with hinged door	71.5"

ABOVE REAR AXLE

	<u>Description</u>	<u>Dimension</u>
D	Vertical Door Opening - Above Rear Wheel	
	-with roll-up door	34.0"
	-with hinged door	37.0"

BEHIND REAR AXLE

	<u>Description</u>	<u>Dimension</u>
E	Bottom of Subframe to Bottom of Body	20.0"
F	Vertical Door Opening	

City of Jasper Fire Department

Production Specification

-with roll-up door	62.0"
-with hinged door	66.0"

GENERAL

	<u>Description</u>	<u>Dimension</u>
G	Bottom of Drip Rail to Top of Body	23.5"

(Dimensions are approximate and subject to change during construction or design process.)

FIVE (5) UPPER BODY COMPARTMENTS (OPEN)

The forward transverse compartment shall be 90.0" long x 27.0" wide x 18.5" deep. There shall be four (4) compartments parallel to the sides of the body, two (2) on each side. Each of these compartments shall be 63.0" long x 28.0" wide x 18.5" deep. The side compartments shall be open under each door sill to allow for long equipment. Each compartment shall be integral with the body construction, and will not be bolted or add-on modules. The outside walls of each compartment will be double walled to prevent equipment from denting the outside painted surface.

Each compartment shall have a lift-up type compartment door hinged on the outboard side. Each door shall be fabricated from 3/16" aluminum tread plate. Each door shall have two (2) pneumatic type cylinders, one (1) at each end, attached to cast aluminum brackets mounted to the interior surface of the door to hold the door in both the opened and closed positions. Each door shall be mounted using multiple 16" long, equally spaced, 14 gauge stainless steel hinges, with 1/4" stainless steel pin. A polyester barrier film gasket shall be placed between stainless steel hinge and the body mounting surface as necessary to prevent corrosion caused by dissimilar metals.

Each compartment door shall overlap a 2" vertical lip on the body roof to prevent entry of moisture and sealed with automotive type rubber molding to provide a weather resistant seal.

Each roof compartment door shall have a chrome 7" handle bolted to center of each door.

Each compartment shall have a 13/16" drain hole located in floor of compartment with a 1" flexible drain tube that terminates below body.

Each compartment shall have a horizontally mounted OnScene Solutions LED light on the underside of the door. The light and NFPA door ajar system shall be automatically activated by an individual switch per compartment.

UPPER BODY WALKWAY

A 34" wide, upper body walkway shall be provided at the center of body and recessed into the roof structure. The walkway shall be fabricated from NFPA compliant 3/16" aluminum tread plate with continuously welded cross seams to prevent moisture penetration into apparatus body, No Exceptions. The walkway shall be supported with 2" x 2" tubing on 14" - 22" centers.

13/16" drains shall be installed at front of walkway connected to 1" flexible drain tubes that will terminate below the body.

WALKWAY/STEP LIGHTS

There shall be four (4) OnScene Solutions Rough-Service 9" LED lights provided to illuminate the walkway or step area. The lights shall be activated when the parking brake is set.

City of Jasper Fire Department

Production Specification

Each light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

Lighting shall provide illumination at a minimum level of 2 fc (20 lx) on all work surfaces, steps, and walkways. Lighting shall be switchable but activated automatically when the vehicle park brake is set.

ROOF ACCESS STAIRWAY

The rear of the body shall be provided with a minimum 34" wide roof access stairway recessed into the side rear compartments. Stairs treads shall be 9 1/2" minimum depth and formed from 3/16" NFPA compliant aluminum tread plate with uniformed riser height design. Stair treads will be continuously welded into side walls. Bolt-in tread design will not be acceptable.

Roll-out ladder design requiring set-up time and 8 plus feet behind apparatus or vertical ladders that do not allow firefighter to safely ascend or descend with equipment will not be acceptable.

STAIRWAY HANDRAILS

There shall be two (2) handrails provided, one (1) on each side wall of recessed center stairway providing three-points of contact at all times for safer access to roof compartments. The handrails shall be angled for optimum use during ingress or egress of the upper walkway area.

Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

WALKWAY/STEP LIGHTS

There shall be two (2) OnScene Solutions Rough-Service 9" LED lights provided to illuminate the walkway or step area. The lights shall be activated when the parking brake is set.

Each light shall be mounted in an extruded aluminum housing to protect against damage from personnel or equipment.

Lighting shall provide illumination at a minimum level of 2 fc (20 lx) on all work surfaces, steps, and walkways. Lighting shall be switchable but activated automatically when the vehicle park brake is set.

STEP COMPARTMENT(S) - LOWER

There shall be one (1) compartment(s) located in the roof access stairway area below frame level. Each compartment shall have a horizontally hinged brushed stainless steel door with a D-ring handle. Each compartment shall be manufactured to prevent road debris, dirt and moisture from entering the enclosure. Each compartment(s) shall be 33" wide x 12" high x maximum depth based on chassis mounted components and requirements for structural integrity of the body.

Each compartment shall have an OnScene LED light that shall automatically activate when the door is opened and wired to the NFPA required hazard warning light provided in the cab.

- The hinged door(s) shall have a stainless steel 6" offset bent D-ring locking handle. A gasket shall be placed between handle and door. Door latch shall be a single point latch flush mounted to exterior door panel.

STEP COMPARTMENT - UPPER

City of Jasper Fire Department

Production Specification

There shall be one (1) upper compartment located directly below walkway area. The compartment shall have a horizontally hinged brushed stainless steel door with a D-ring handle. The compartment shall be manufactured to prevent road debris, dirt and moisture from entering the enclosure. The compartment shall be approximately 26" wide x 8" high x maximum depth available

Each Compartment shall have an OnScene LED light that shall be automatically activated when the door is opened and wired to the NFPA required hazard warning light provided in the cab.

Devices to secure equipment, compartment dividers, or UHMW plastic angles, or sheeting will be used for storage of specified equipment as required to prevent damage to equipment.

- The hinged door(s) shall have a stainless steel 6" offset bent D-ring locking handle. A gasket shall be placed between handle and door. Door latch shall be a single point latch flush mounted to exterior door panel.
- One (1) 6' folding ladder(s). Manufacturer, model number of the ladder shall be provided in equipment section of specification, or at pre-construction meeting when provided by City of Jasper Fire Department.

FOLD-DOWN STEP

There shall be one (1) fold-down step located at the bottom of the roof access stairway mounted on top of bumper to reduce the distance from the ground to the first step. The step surface shall be NFPA compliant aluminum treadplate and shall manually fold up into the stairway with an over-center gas shock to hold step in position during travel. The step shall activate the "Hazard Warning Light" in the cab when not in the stowed position.

REAR BODY HANDRAILS

There shall be two (2) 24" vertical handrails on the rear of the body. Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless steel with welded end stanchions.

BODY WIDTH DIMENSIONS

The body shall be 100.0" wide, not including drip rail or non-permanent fixtures. Interior compartment depth dimensions shall be approximately:

<u>Area Description</u>	<u>Dimension</u>
Transverse Area above Subframe	95.0"

Compartment Depth below Subframe	24.5"
----------------------------------	-------

STREETSIDE COMPARTMENT - FRONT (S1)

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block

City of Jasper Fire Department

Production Specification

to signal open door.

- There shall be NO keyed lock on this roll-up compartment door.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) OnScene Solutions 83 series aluminum tray base with 70% extension, and rating of 1,000 lbs. Slide-out tray(s) base shall be approximately 94" deep and as wide as the compartment layout or door opening permits, capable of extending out either side of the body located above the level of the chassis frame rails. Each slide base shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed, 40% extended and 70% extended positions. Each tray top shall be fabricated from 3/16" 3003 aluminum sheet shall have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".
 - Vertical partition(s) shall be provided on slide-out tray base dividing the tray into left and right sides. Each vertical partition shall be horizontally adjustable; mounted on aluminum Shelf Trac on tray floor. The vertical partition(s) shall be 3/16" (.188) 3003H-14 alloy smooth aluminum sheet.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
 - The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- One (1) Hannay ECR1618-17-18 electric cable reel(s) capable of storing 200' of 10/3 electric cable. Reel(s) shall be designed to hold 110% of the capacity of cord length, with fully enclosed 45 amp, three (3) conductor collector rings. Reel(s) shall be mounted to channel structure that allows for side-to-side adjustment of reel position.
 - Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and not be more than 72 in. (1830 mm) above the operator's standing position, and shall be marked with a label indicating its function.
 - A label shall be provided in a visible location adjacent to reel with following information: Current rating, Current type, Phase, Voltage, and Total cord length.
 - The cable reel shall equipped with 200' of 10/3 SEOW yellow cable, a molded plastic ball clamp, and a single heavy duty L5-30 twist-lock female plug at the end.

City of Jasper Fire Department

Production Specification

- One (1) Akron model EJB series, cast aluminum electrical power distribution box with yellow powder coat painted finish shall be provided. The power distribution box shall meet all requirements described in NFPA 1901. The power distribution box shall include the following outlets mounted on a backlit face plate;
 - A 12" pigtail that terminates in an L5-30 configuration to match the cable on the cord reel. The outlet configuration shall include:
 - One (1) 120 VAC, L5-15 dual twist lock receptacles
 - One (1) 120 VAC, L5-15 dual twist lock receptacles
 - One (1) 120 VAC, L5-15 dual twist lock receptacles
 - One (1) 120 VAC, L5-15 dual twist lock receptacles
- One (1) Akron formed aluminum treadplate vertical mounting bracket shall be provided for specified power distribution box.
- The reel shall be supplied with OnScene Solutions fairlead extension with a 6" - 10" extension (depending on compartment depth). The fairlead extension shall allow hoses or cords to be extended out and away from compartment door edges, slide trays, or shelving that may result in wear damage.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- The controls for the specified light tower(s).
- The 12 volt electrical distribution panel shall be located in the front lower compartment.

STREETSIDE COMPARTMENT - AHEAD OF REAR WHEELS (S2)

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

City of Jasper Fire Department

Production Specification

COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) adjustable shelf/shelves approximately 46" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the shelf. The striping shall be red/white in color.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) OnScene Solutions 81 series aluminum tray base with 100% extension, and rating of 1,000 lbs. Slide-out tray(s) base shall be approximately 46" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails. Each slide base shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

STREETSIDE COMPARTMENT - ABOVE REAR WHEELS (S3)

The interior useable compartment width shall be approximately 59.0" wide.

The compartment door opening shall be approximately 52.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior

City of Jasper Fire Department

Production Specification

color.

- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 30" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) OnScene Solutions 84 series aluminum tray base with 90% extension, and rating of 150 lbs. Slide-out tray(s) base shall be approximately 46" deep and as wide as the compartment layout or door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will hold the tray in the closed position. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- Two (2) OnScene 36" Access LED compartment lights, vertically mounted.
- Air storage consisting of two (2) UN/ISO DOT 510 SCF @ 6,000 PSI, (requires hydrostatic test every 10 years) air storage cylinders with gauges and valves. Each cylinder shall be 9.4" dia. x 52" long and weigh 202 lbs.

A label shall be placed on or near the operator's panel that provides the following:

- The original cylinder test date stamped on the cylinders
- The recommended testing interval

City of Jasper Fire Department

Production Specification

- 1) Five additional open spaces, appropriately labeled, for the user to enter actual retesting dates

The manufacturer's test date (month and year) on each air tank shall be current within 12 months of the apparatus delivery date.

Air tanks shall be marked with a label that reads;

"High Pressure ____ PSI Breathing Air" or "High Pressure ____ kPa Breathing Air."

- 2) There will be a welded reinforcement above the body frame to carry specified DOT or ASME cylinders. The mounting of the cylinders will be with adjustable track and powder coated steel band straps to securely hold all cylinders in place.

STREETSIDE COMPARTMENT - REAR (S4)

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have an Amdor roll-up door.

- 3) The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
 - The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
 - There shall be NO keyed lock on this roll-up compartment door.
 - One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
 - A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) bolt-in vertical compartment partition(s) provided dividing the compartment into left and right sides. The vertical partition(s) shall be 3/16" (.188) 3003H-14 alloy smooth aluminum sheet.
- There shall be one (1) SCBA cylinder storage module for 8" OD (maximum) SCBA bottles. The maximum length of the SCBA cylinder shall be 24.75". The module shall have an exterior shell fabricated from 1/8" (.125) 3003H-14 aluminum alloy sheet. The module shall have a 2" slope, front to back to prevent cylinders from sliding out. The SCBA cylinder storage tubing shall be fabricated from PVC pipe to prevent damage or abrasion to cylinders. In addition there shall be rubber matting provided in the base of each storage tube for bottle protection and to prevent slipping.

Brand: _____

City of Jasper Fire Department

Production Specification

Diameter: _____ " (Must be less than 7.625")

Length: _____ " (with valve)

- The SCBA cylinder module shall be capable of storing eight (8) SCBA cylinders up to 7.5" diameter.
- A clay absorbent (or similar weight material) storage hopper shall be provided in this compartment for approximately 150 pounds of material. The storage hopper shall be filled from an upper body compartment and funneled to a manual 3" PVC 1/4-turn ball valve with flexible hose in lower compartment. Bottom of absorbent hopper will allow for a 5 gallon pail to be stored under valve.
- The floor of the compartment above the frame rails shall cover the area directly above the frame rails ONLY (non-extended floor).
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- One (1) Resolve Specialty Space Saver model 100A mobile filling station(s) designed for SCBA and SCUBA cylinders shall be provided. Fill station shall be capable of simultaneously filling (2) cylinders. The unit comes complete with safety interlocks, safety gauges, charge and bleed valves and pressure regulator for automatic SCBA filling. The fill enclosure shall meet NFPA 1901 testing certification, and shall be approx. 43.00" high (53" with door open) x 13.00" wide x 23.00" deep and weigh 405 lbs. The cascade air fill control panel will attach to top of fill station.
 - The Resolve Space Saver fill station shall be provided with a four (4) bank, manual control cascade air fill control panel with black non-glare control panel with shielded LED light, and refill port with female fitting S252P with S44-2 dust cap.
 - The fill station fill whip(s) shall terminate in a low pressure CGA-346 threaded connectors for 2,216 - 3,000 PSI air pack cylinders.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

CURBSIDE COMPARTMENT - FRONT (C1)

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.

City of Jasper Fire Department

Production Specification

- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) OnScene Solutions 83 series aluminum tray base with 70% extension, and rating of 1,000 lbs. Slide-out tray(s) base shall be approximately 94" deep; capable of extending out either side of the body located above the level of the chassis frame rails. (Specified in opposite side compartment.)
 - Vertical partition(s) shall be provided on slide-out tray base dividing the tray into left and right sides. Each vertical partition shall be horizontally adjustable; mounted on aluminum Shelf Trac on tray floor. The vertical partition(s) shall be 3/16" (.188) 3003H-14 alloy smooth aluminum sheet.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- One (1) Hannay ECR1618-17-18 electric cable reel(s) capable of storing 200' of 10/3 electric cable. Reel(s) shall be designed to hold 110% of the capacity of cord length, with fully enclosed 45 amp, three (3) conductor collector rings. Reel(s) shall be mounted to channel structure that allows for side-to-side adjustment of reel position.
 - Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and not be more than 72 in. (1830 mm) above the operator's standing position, and shall be marked with a label indicating its function.
 - A label shall be provided in a visible location adjacent to reel with following information: Current rating, Current type, Phase, Voltage, and Total cord length.
 - The cable reel shall be equipped with 200' of 10/3 SEOW yellow cable, a molded plastic ball clamp, and a single heavy duty L5-30 twist-lock female plug at the end.
- One (1) Akron model EJB series, cast aluminum electrical power distribution box with yellow powder coat painted finish shall be provided. The power distribution box shall meet all requirements described in NFPA 1901. The power distribution box shall include the following outlets mounted on a backlit face plate;
 - A 12" pigtail that terminates in an L5-30 configuration to match the cable on the cord reel. The outlet configuration shall include:
 - One (1) 120 VAC, L5-15 dual twist lock receptacles

City of Jasper Fire Department

Production Specification

- One (1) 120 VAC, L5-15 dual twist lock receptacles
- One (1) 120 VAC, L5-15 dual twist lock receptacles
- One (1) 120 VAC, L5-15 dual twist lock receptacles
- One (1) Akron formed aluminum treadplate vertical mounting bracket shall be provided for specified power distribution box.
- The reel shall be supplied with OnScene Solutions fairlead extension with a 6" - 10" extension (depending on compartment depth). The fairlead extension shall allow hoses or cords to be extended out and away from compartment door edges, slide trays, or shelving that may result in wear damage.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- One (1) 120/240 VAC load center.
- The generator gauge panel.
- One (1) Genesis Mach III Outlaw (ART.593.508.1E) high pressure 10,500 psi hydraulic power unit(s) complete with OSC couplings shall be provided capable of operating two (2) hydraulic rescue tools simultaneously. One (1) 240 VAC twist lock receptacle(s) shall be provided adjacent to the hydraulic power unit. Location to be confirmed at pre-construction meeting.

CURBSIDE COMPARTMENT - AHEAD OF REAR WHEEL (C2)

The interior useable compartment width shall be approximately 49.0" wide.

The compartment door opening shall be approximately 42.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.

City of Jasper Fire Department

Production Specification

- There shall be one (1) adjustable shelf/shelves approximately 46" deep. Each shelf shall be fabricated from 3/16" 3003 aluminum sheet with a 2" vertical flange along the front and rear edges.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front face of the shelf. The striping shall be red/white in color.
- There shall be one (1) OnScene Solutions 81 series aluminum tray base with 100% extension, and rating of 1,000 lbs. Slide-out tray(s) base shall be approximately 46" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails. Each slide base shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 ½".
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- One (1) Lista drawer cabinet, model HS-0900-0603FA-NB-RG-IDL shall be provided in compartment. The Lista cabinet(s) shall be 40-1/4" wide x 39-3/8" high x 22-1/2" deep. Cabinet shall have six (6) individual locking drawers as follows as follows; one (1) 2", one (1) 3", one (1) 4", one (1) 5", one (1) 7", and one (1) 9". The cabinet shall be Light Gray in color.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- One (1) Hannay EF1514-17-18 low pressure air hose reel(s) shall be provided in this compartment. Reel shall be designed to hold 110% of the capacity needed.
 - Power rewind control(s) shall be in a position where the operator can observe the rewinding operation and shall be marked with a label indicating its function and shall be guarded to prevent accidental operation.
 - A label shall be provided in a visible location adjacent to reel with following information: (1) Utility air or breathing air, (2) Operating pressure, (3) Total hose length, (4) Hose size (ID).
 - The hose reel shall equipped with 100' of 3/8" Parker Series 7092 GST II low pressure air hose rated for 300 PSI maximum pressure. A molded plastic ball clamp shall be provided on the hose to stop it at the 4-way roller. The hose shall be Red in color.
- The air supply shall be from the utility air compressor.
- A reel shut-off valve, pressure regulator, and 0-150 psi gauge shall be provided on an aluminum control panel near the air reel, not exceeding 72" from ground.
- The reel shall be supplied with OnScene Solutions fairlead extension with a 6" - 10" extension (depending on compartment depth). The fairlead extension shall allow hoses or cords to be extended out and away from compartment door edges, slide trays, or shelving that may result in wear damage.

City of Jasper Fire Department

Production Specification

- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- One (1) Grainger model 1NNF7 or equal, 240 VAC, 3.1 HP electric powered air compressor with 20 gallon storage tank shall be located in upper front transverse roof compartment. Compressor shall be rated at 15.0 free air CFM @ 90 PSI, 10.20 free air CFM @ 135 PSI max. pressure. One (1) 240 VAC twist lock receptacle with switch shall be provided on wall within easy reach of operator for turning the compressor ON/OFF.

Results of the NFPA required utility air system test shall be provided with delivered vehicle.

- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

CURBSIDE COMPARTMENT - ABOVE REAR WHEEL (C3)

The interior useable compartment width shall be approximately 59.0" wide.

The compartment door opening shall be approximately 52.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 30" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
 - 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- There shall be one (1) OnScene Solutions 84 series aluminum tray base with 90% extension, and rating of 150 lbs. Slide-out tray(s) base shall be approximately 46" deep and as wide as the compartment layout or

City of Jasper Fire Department

Production Specification

door opening permits. It shall be located above the level of the chassis frame rails and shall be vertically adjustable in height. Each slide shall have a cable operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will hold the tray in the closed position. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".

- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- Two (2) OnScene 36" Access LED compartment lights, vertically mounted.
- Air storage cylinder location in center of compartment for specified air system.

CURBSIDE COMPARTMENT - REAR (C4)

The interior useable compartment width shall be approximately 56.0" wide.

The compartment door opening shall be approximately 49.0" wide.

This compartment shall have an Amdor roll-up door.

- The roll-up door slats and the door trim components shall be painted to match the single tone exterior color.
- The Amdor door shall be equipped with a door ajar switch integrated into the lower door handle retainer block to signal open door.
- There shall be NO keyed lock on this roll-up compartment door.
- One (1) aluminum drip pan/door finish guard shall be provided with the rollup door.
- A compartment threshold protection plate shall be installed on the bottom edge of the compartment door opening. The threshold protection shall be fabricated from an aluminum extrusion with an anodized exterior finish.

COMPARTMENT LAYOUT

- There shall be vertically mounted aluminum Shelf-Trac for specified component installation. Shelf-Trac extrusion shall have side extruded channels for use in mounting or securing special ancillary items, without need for drilling into body.
- There shall be one (1) 400 lbs. slide-out tray(s) approximately 24" deep and as wide as the compartment layout or door opening permits. The tray top shall be fabricated from 3/16" 3003 aluminum sheet with a 3" vertical lip and welded corners to form a box type tray surface. The sliding tracks shall extend 100% of the slide length. The tray assembly shall utilize a pneumatic cylinder mounted on underside to hold the tray in both the extended and closed positions.
- There shall be one (1) OnScene Solutions 81 series aluminum tray base with 100% extension, and rating of 1,000 lbs. Slide-out tray(s) base shall be approximately 70" deep and as wide as the compartment layout or door opening permits located above the level of the chassis frame rails. Each slide base shall have a cable

City of Jasper Fire Department

Production Specification

operated, spring loaded latch complimented by a large hand opening and red pull handle (Pull to Release) which will lock the tray in the closed and full extension positions. Each tray shall be fabricated from 3/16" 3003 aluminum sheet and shall have welded corners to form a box type tray surface with an internal depth of approximately 3 1/2".

- Vertical partition(s) shall be provided on slide-out tray base dividing the tray into left and right sides. Each vertical partition shall be horizontally adjustable; mounted on aluminum Shelf Trac on tray floor. The vertical partition(s) shall be 3/16" (.188) 3003H-14 alloy smooth aluminum sheet.
- 3M™ Diamond Grade™ Conspicuity striping shall be provided on the front and side faces of the tray. The striping shall be 2" wide and red/white in color.
- The floor of the compartment above the frame rails shall be extended to the interior edge of the door. The floor shall have a 2" vertical lip and a 1" return to increase strength.
- Two (2) OnScene 64" Access LED compartment lights, vertically mounted.
- Two (2) 3-1/2" x 3-1/2" black plastic louvered vents shall be provided in the lower compartment.

ROOF ACCESS STAIRWAY

The rear of the body shall be provided with a recessed center stairway with minimum 34" width. Stairs treads shall be 9.5" minimum depth and formed from 3/16" NFPA compliant aluminum tread plate with uniformed maximum riser height of 12". Roll-out ladder design requiring set-up time and 8 plus feet behind apparatus or vertical ladders that do not allow firefighter to safely ascend or descend with equipment will not be acceptable.

STAIRWAY HANDRAILS

There shall be two (2) handrails provided, one (1) on each side wall of recessed center stairway providing three-points of contact at all times for safer access to roof compartments. The handrails shall be angled for optimum use during ingress or egress of the upper walkway area.

Handrails shall be NFPA compliant 1-1/4" knurled 304 stainless tubing with welded end stanchions.

TOOL MOUNTING ALLOWENCE

There shall be an allowance of \$5,000 to allow for proper mounts and mounting of loose equipment.

PLASTIC FLOOR AND SHELF TILE

All compartment floors, shelves, and trays shall be covered with Dri-Dek plastic interlocking grating.

- The plastic floor tile shall be black.
- The plastic edge trim shall be black.

ROPE ANCHOR OR PORTABLE WINCH RECEIVERS

The completed unit shall have an integrated receiver or anchor system for use with removable rope anchor point and/or a portable electric winch, when specified.

City of Jasper Fire Department

Production Specification

Receivers or anchors installed at any location on the apparatus for use as removable winch anchors shall be designed and affixed to provide at least a 2.0 to 1 straight line pull no-yield safety factor over the load rating of the removable winch.

Receivers or anchors installed at any location on the apparatus for use with rope operations shall be designed and affixed to the apparatus to provide at least a 9,000 lbf (40,000 N) no-yield condition with a straight line pull.

A safety sign FAMA28 shall be located on or near each receiver or anchor stating the maximum straight line pull rating.

Side receiver(s) (if specified) shall have the following load rating:

	<u>STRAIGHT PULL</u>	<u>SAFETY FACTOR</u>
Rope Tie Off:	600 Lbs.	15:1
Winch:	5,000 Lbs.	2:1

Front and/or rear receiver(s) (if specified) shall have the following load rating:

	<u>STRAIGHT PULL</u>	<u>SAFETY FACTOR</u>
Rope Tie Off:	600 Lbs.	15:1
Winch:	Winch Load Rating (9,000 Lbs. Max)	2:1

The following items shall be provided to accomplish rope rescue and/or portable winch operation;

- Two (2) removable rope anchor(s) shall be provided with completed vehicle. Each rope anchor shall be fabricated from 3/4" steel, 2" high x 11.5" long with a 3" OD/2" ID eyelet. Eyelet end shall have radiused edge to prevent damage to rope or carabiner. Each rope anchor shall have a powder coat paint finish and a steel 5/8" hitch pin to lock it in place. An aluminum mounting bracket shall be provided to store rope anchor(s) inside a body compartment as close to receiver location as possible.
- One (1) Ramsey model QM9000, 9,000 lb. 12 volt electric winch shall be furnished with the completed unit. It shall be capable of being stored in a compartment and mounted to the apparatus by inserting the mounting point into a properly rated receiver. A minimum of 105' of 5/16" stranded galvanized steel cable with pinned utility hook shall be installed on the drum. A 25' remote control shall be provided with the assembly that permits the operator to stand at a safe operating distance from the cable and winch.
- There shall be one (1) 2" x 2" x 1/4" wall steel receiver tube(s) with powder coat paint finish located at the front bumper for use with removable rope anchor point and/or a portable electric winch (if specified).
 - There shall be one (1) 12 VDC plug(s) with quick connect provided to power a Ramsey portable winch. All 12 VDC cables to be sized according to Ramsey and installation for intended use.
 - The receiver(s) shall have one (1) rubber cover(s) provided.
- There shall be one (1) 2" x 2" x 1/4" wall steel receiver tube(s) with powder coat paint finish located on the streetside of the body in the forward wheel well panel area for use with removable rope anchor and/or a portable electric winch (when specified).

City of Jasper Fire Department

Production Specification

- There shall be one (1) 12 VDC plug(s) with quick connect provided to power a Ramsey portable winch. All 12 VDC cables to be sized according to Ramsey and installation for intended use.
- The receiver(s) shall have one (1) rubber cover(s) provided.
- There shall be one (1) 2" x 2" x 1/4" wall steel receiver tube(s) with powder coat paint finish located on the curbside of the body in the forward wheel well panel area for use with removable rope anchor and/or a portable electric winch (when specified).
 - There shall be one (1) 12 VDC plug(s) with quick connect provided to power a Ramsey portable winch. All 12 VDC cables to be sized according to Ramsey and installation for intended use.
 - The receiver(s) shall have one (1) rubber cover(s) provided.
- There shall be one (1) 2" x 2" x 1/4" wall steel receiver tube(s) located at the rear bumper for use with removable rope anchor point and/or a portable electric winch (when specified).
 - There shall be one (1) 12 VDC plug(s) with quick connect provided to power a Ramsey portable winch. All 12 VDC cables to be sized according to Ramsey and installation for intended use.
 - The receiver(s) shall have one (1) rubber cover(s) provided.

LOWER SIDE BODY PROTECTION - RUB RAIL

OnScene Solutions rub rails shall be provided below the compartment door openings on both the streetside and curbside.

The rub rail shall be fabricated from 6063 extruded aluminum, measuring approximately 2-3/4" high x 1-3/8" thick with tapered aluminum end caps. The rub rail shall be bolted to the body using stainless steel bolts and 1-1/2" diameter x 5/8" thick rubber mount isolators to prevent damage to the body.

The rails shall incorporate LED clearance marker lighting recessed into the rail fascia to avoid damage to the light in case of impact. The rub rail shall have an accessory mounting track integrated into the backside of the rail to allow mounting of accessories such as ground lighting.

FRONT GRAVEL GUARDS

Gravel guards shall be provided on front lower body corners. Guards shall be 12" high, extend from behind cab or step and wrap around to the front compartment door opening fabricated from 20 gauge brushed stainless steel.

LOW VOLTAGE ELECTRICAL SYSTEM- 12 VDC

General

Any low voltage electrical systems or warning devices installed on the fire apparatus shall be appropriate for the mounting location and intended electrical load.

Where wire passes through sheet metal, grommets shall be used to protect wire and wire looms. Electrical connections shall be with double crimp water-tight heat shrink connectors.

City of Jasper Fire Department

Production Specification

All 12 VDC wiring running from front to back of vehicle body shall be run in full length electrical wiring raceway down each side of body.

Wiring

All electrical circuit feeder wiring supplied and installed by the fire apparatus manufacturer shall meet the requirements of NFPA Chapter 13.

The circuit feeder wire shall be stranded copper or copper alloy conductors of a gauge rated to carry 125% of the maximum current for which the circuit is protected. Voltage drops in all wiring from the power source to the using device shall not exceed 10%. The use of star washers for circuit ground connections shall not be permitted.

All circuits shall otherwise be wired in conformance with SAE J1292, *Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Wiring*.

Wiring and Wire Harness Construction

All insulated wire and cable shall conform to SAE J1127, *Low Voltage Battery Cable*, or SAE J1128, *Low Voltage Primary Cable*, type SXL, GXL, or TXL.

All conductors shall be constructed in accordance with SAE J1127 or SAE J1128, except where good engineering practice dictates special strand construction. Conductor materials and stranding, other than copper, shall be permitted if all applicable requirements for physical, electrical, and environmental conditions are met as dictated by the end application. Physical and dimensional values of conductor insulation shall be in conformance with the requirements of SAE J1127 or SAE J1128, except where good engineering practice dictates special conductor insulation. The overall covering of conductors shall be moisture-resistant loom or braid that has a minimum continuous rating of 194°F (90°C) except where good engineering practice dictates special consideration for loom installations exposed to higher temperatures. The overall covering of jacketed cables shall be moisture resistant and have a minimum continuous temperature rating of 194°F (90°C), except where good engineering practice dictates special consideration for cable installations exposed to higher temperatures.

All wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection. The wiring connections and terminations shall be installed in accordance with the device manufacturer's instructions. All ungrounded electrical terminals shall have protective covers or be in enclosures. Wire nut, insulation displacement, and insulation piercing connections shall not be used.

Wiring shall be restrained to prevent damage caused by chafing or ice buildup and protected against heat, liquid contaminants, or other environmental factors.

Wiring shall be uniquely identified at least every 2 ft (0.6 m) by color coding or permanent marking with a circuit function code. The identification shall reference a wiring diagram.

Circuits shall be provided with properly rated low voltage overcurrent protective devices. Such devices shall be readily accessible and protected against heat in excess of the overcurrent device's design range, mechanical damage, and water spray. Circuit protection shall be accomplished by utilizing fuses, circuit breakers, fusible links, or solid state equivalent devices.

If a mechanical-type device is used, it shall conform to one of the following SAE standards:

- SAE J156, *Fusible Links*
- SAE J553, *Circuit Breakers*
- SAE J554, *Electric Fuses (Cartridge Type)*

City of Jasper Fire Department

Production Specification

- 1) SAE J1888, *High Current Time Lag Electric Fuses*
- 2) SAE J2077, *Miniature Blade Type Electrical Fuses*

Switches, relays, terminals, and connectors shall have a direct current (dc) rating of 125% of maximum current for which the circuit is protected.

Power Supply

A 12 V or greater electrical alternator shall be provided. The alternator shall have a minimum output at idle to meet the minimum continuous electrical load of the vehicle, at 200°F (93°C) ambient temperature within the engine compartment, and shall be provided with full automatic regulation.

Minimum Continuous Electrical Load

The minimum continuous electrical load shall consist of the total amperage required to simultaneously operate the following in a stationary mode during emergency operations:

- 3) The propulsion engine and transmission
- 4) All legally required clearance and marker lights, headlights, and other electrical devices except windshield wipers and four-way hazard flashers
- 5) The radio(s) at a duty cycle of 10 percent transmit and 90 % receive (for calculation and testing purposes, a default value of 5 A continuous)
- 1) The lighting necessary to produce 2 fc (20 lx) of illumination on all walking surfaces on the apparatus and on the ground at all egress points onto and off the apparatus, 5 fc (50 lx) of illumination on all control and instrument panels, and 50 percent of the total compartment lighting loads
- 2) The minimum optical warning system, where the apparatus is blocking the right-of way
- 3) The continuous electrical current required to simultaneously operate any fire pumps, aerial devices, and hydraulic pumps
- 4) Other warning devices and electrical loads defined by the purchaser as critical to the mission of the apparatus

If the apparatus is equipped to tow a trailer, an additional 45 A shall be added to the minimum continuous electrical load to provide electrical power for the federally required clearance and marker lighting and the optical warning devices mounted on the trailer.

The condition of the low voltage electrical system shall be monitored by a warning system that provides both an audible and a visual signal to persons on, in, or near the apparatus of an impending electrical system failure caused by the excessive discharge of the battery set.

The charge status of the battery shall be determined either by direct measurement of the battery charge or indirectly by monitoring the electrical system voltage.

If electrical system voltage is monitored, the alarm shall sound if the system voltage at the battery or at the master load disconnect switch drops below 11.8 V for 12 V nominal systems, 23.6 V for 24 V nominal systems, or 35.4 V for 42 V nominal systems for more than 120 seconds.

A voltmeter shall be mounted on the driver's instrument panel to allow direct observation of the system voltage.

Electromagnetic Interference

Electromagnetic interference suppression shall be provided, as required, to satisfy the radiation limits specified in SAE J551/1, *Performance Levels and Methods of Measurement of Electromagnetic Compatibility of Vehicles, Boats (up to 15 m), and Machines (16.6 Hz to 18 GHz)*.

City of Jasper Fire Department

Production Specification

Wiring Diagram

A complete electrical wiring schematic of actual system shall be provided with finished apparatus. Similar or generic type electrical schematics shall NOT BE ACCEPTABLE.

Low Voltage Electrical System Performance Test

A low voltage electrical system test certification shall be provided with delivered apparatus.

12 VOLT DIAGNOSTIC RELAY CONTROL CENTER

The 12 volt power distribution shall be conveniently located with easy access for service. All relays and circuit breakers shall be plug-in type allowing for removal for repairs without necessitating soldering or tools. The sockets mounts for both the relays and circuit breakers shall be of a design that permits the use of standard automotive type components.

The 12 volt distribution panel shall utilize printed circuit boards mounted in high strength enclosure. Each printed circuit board shall be provided with twelve (12) heavy duty independent switching relays. Each relay shall have the ability to be configured either normally open or normally closed and be protected by a 20 amp automatic reset breaker. Each circuit will be provided with a LED for visual diagnostic.

Power distribution panel shall be located in apparatus body within a protected enclosure with removable or hinged cover.

ROCKER SWITCH PANEL

The 12 volt control switch panel shall be supplied and installed by the cab/chassis manufacturer.

ELECTRICAL SYSTEM MANAGER

The chassis shall contain an electrical system manager for:

- 5) Monitoring chassis battery voltage
- 6) Shedding pre-determined electrical circuits
- 7) Sequencing pre-determined electrical circuits
 - Automatically controlling chassis engine fast-idle
 - Monitor master switch and parking brake applications
 - Automatically control warning light modes ("Calling-For" and "Blocking Right of Way")
 - Provide low voltage alarm
 - Programmable control circuits
 - Remote system status indicator panel

System manager shall perform all electrical functions required by current NFPA 1901 Standards.

The electrical system manager shall be supplied and installed by the cab/chassis manufacturer.

BATTERY SYSTEM

City of Jasper Fire Department

Production Specification

The battery connectors shall be heavy duty type with cables terminating in heat shrink loom. Heavy duty battery cables shall provide maximum power to the electrical system. Where required, the cables shall be shielded from exhaust tubing and the muffler. Large rubber grommets shall be provided where cables enter the battery compartment.

Batteries shall be of the high-cycle type. With the engine off, the battery system shall be able to provide the minimum continuous electrical load for 10 minutes without discharging more than 50 percent of the reserve capacity and then to restart the engine. The battery system cold cranking amps (CCA) rating shall meet or exceed the minimum CCA recommendations of the engine manufacturer. The batteries shall be mounted to prevent movement during fire apparatus operation and shall be protected against accumulations of road spray, snow, and road debris. The batteries shall be readily accessible for examination, testing, and maintenance.

A means shall be provided for jump-starting the engine if the batteries are not accessible without lifting the cab of a tilt-cab apparatus.

Where an enclosed battery compartment is provided, it shall be ventilated to the exterior to prevent the buildup of heat and explosive fumes. The batteries shall be protected against vibration and temperatures that exceed the battery manufacturer's recommendation.

An onboard battery conditioner or charger or a polarized inlet shall be provided for charging all batteries. Where an onboard conditioner or charger is supplied, the associated line voltage electrical power system shall be installed in accordance with Chapter 22.

One of the following master disconnect switches shall be provided:

- A master body disconnect switch that disconnects all electrical loads not provided by the chassis manufacturer
- A master load disconnect switch that disconnects all electrical loads on the apparatus except the starter

Electronic control systems and similar devices shall be permitted to be otherwise connected if so specified by their manufacturer.

The alternator shall be wired directly to the batteries through the ammeter shunt(s), if one is provided, and not through the master load disconnect switch.

A green "battery disconnect on" indicator light that is visible from the driver's position shall be provided.

Rechargeable hand lights, radios, and other similar devices shall be permitted to be connected to the electrical system ahead of the master disconnect switch.

A sequential switching device shall be permitted to energize the optical warning devices and other high current devices required in minimum continuous electrical load, provided the switching device shall first energize the electrical devices required in minimum continuous electrical load within 5 seconds.

BATTERY SWITCH

One (1) "battery disconnect on" switch in cab located within easy reach of Driver with indicator light that is visible from the driver's position shall be provided. The switch and indicator light shall be supplied and installed by the cab/chassis manufacturer.

BATTERY SOLENOID

City of Jasper Fire Department

Production Specification

Battery switch shall consist of a minimum 200 ampere, constant duty solenoid to feed from positive side of battery.

BATTERY CONDITIONER

The battery conditioner shall be supplied and installed by the cab chassis manufacturer.

ENGINE COMPARTMENT LIGHT

Engine compartment light(s) shall be supplied and installed by the cab chassis manufacturer.

CAB HAZARD WARNING LIGHT

A red flashing or rotating light, located in the driving compartment. The light shall be furnished by the cab/chassis manufacturer. The light shall be illuminated automatically whenever the vehicles parking brake is not fully engaged and any of the following conditions exist:

- Any passenger or equipment compartment door is not closed.
 - 1) Any ladder or equipment rack is not in the stowed position.
 - 2) Stabilizer system is not in its stowed position.
- Powered light tower is not stowed.
- Any other device permanently attached to the apparatus is open, extended, or deployed in a manner that is likely to cause damage to the apparatus if the apparatus is moved.

Compartments and equipment meeting all of the following conditions shall be permitted to be exempt from being wired to the hazard light:

- The volume is less than or equal to 4 ft³ (0.1 m³).
- The compartment has an opening less than or equal to 144 in.² (92,900 mm²).
- The open door does not extend sideways beyond the mirrors or up above the top of the fire apparatus.
- All equipment in the compartment is restrained so that nothing can fall out if the door is open while the apparatus is moving.
- Manually raised pole lights with an extension of less than 5 ft (1.5 m).

The hazard light shall be labeled "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

BACK-UP ALARM

An electronic back-up alarm shall be supplied and installed by the cab/chassis manufacturer. The back-up alarm shall actuate automatically when the transmission gear selector is placed in reverse.

REAR VIEW CAMERA

There shall be one (1) ASA Voyager rear observation camera system provided and installed on completed unit. The system shall include one (1) model VCC150 high resolution CCD color camera installed on the rear body.

The camera image shall be displayed on a model AOM713, 7" color flat panel display (up to 3 camera inputs) located within the driver's range of view.

TAIL LIGHTS

City of Jasper Fire Department

Production Specification

Rear body tail lights shall be vertically mounted and located per Federal Motor Vehicle Safety Standards, FMVSS and Canadian Motor Vehicle Safety Standards CMVSS. The following lights shall be furnished;

- Two (2) Whelen specified lower Zone "C" warning lights
- Two (2) Whelen amber LED 600 Series 60A00TAR turn signal lights
- Two (2) Whelen red LED 600 Series 60BTT stop/tail lights
- Two (2) Whelen LED 600 Series 60C00WCR maximum intensity back-up lights with clear lens

Two (2) Whelen CAST-4V, 4-light polished aluminum bezels shall be provided, one (1) each side vertically mounted on the rear of the apparatus body for the above tail lights.

MIDSHIP MARKER/TURN SIGNAL

Two (2) Whelen model T0A00MAR 2" round amber LED midship body clearance marker/turn signal lights shall be provided and installed, one (1) light on each side of the body, in forward wheel well of rear axle. Midship marker/turn lights shall be wired to the headlight circuit of the chassis.

MARKER LIGHTS

The body shall be equipped with all necessary clearance lights and reflectors in accordance with Federal Motor Vehicle Safety Standards (FMVSS) and Canadian Motor Vehicle Safety Standards (CMVSS) regulations. All body clearance lights shall be Truck-Lite Model 18 LED to reduce the need for maintenance and lower the amp draw. Clearance lights shall be wired to the headlight circuit of the chassis.

REAR BUMPER MARKER LIGHTS

Two (2) Britax style dual face flexible mounted rear bumper markers shall be located, one (1) each side lower rear corner of body visible from driver mirrors.

CAB STEP LIGHTS / GROUND LIGHTS

The step lights and/or ground lights shall be supplied and installed by the cab/chassis manufacturer. Light(s) shall be capable of providing illumination at a minimum level of 2 fc (20 lx) on ground areas within 30 in. (800 mm) of the edge of the vehicle in areas designed for personnel to climb onto or descend from the vehicle to the ground level.

Lighting designed to provide illumination on areas under the driver and crew riding area exits shall be switchable but activated automatically when the exit doors are opened.

LICENSE PLATE LIGHT

One (1) Arrow #437 chrome plated LED license plate light shall be installed on the rear of the body. License plate light shall be wired to the headlight circuit of chassis. A fastener system shall be provided for license plate installation.

ELECTRONIC SIREN

The siren control head shall be supplied and installed by the cab/chassis manufacturer. Siren power shall be wired through the master warning light switch.

City of Jasper Fire Department

Production Specification

SIREN SPEAKER

The siren speaker(s) shall be supplied and installed by the cab/chassis manufacturer.

FRONT CAB MOUNTED SCENE LIGHT(S)

Floodlight(s) shall be provided on the front of the cab by the cab/chassis manufacturer. Scene lights shall be provided with a lens or a means for preventing damage from water spray and shall be listed for wet location usage.

Each light shall be wired directly to the 12 VDC electrical system with stranded copper wire. The floodlights shall be protected with circuit breakers rated at the proper amperage and wire size.

One (1) switch shall be provided for front scene lights.

The lights shall be switched at the 12 volt control panel in the cab.

REAR SCENE LIGHTS

Two (2) Fire Research Spectra model SPA900-Q70 LED lights shall be provided on the upper rear body to light the work area immediately behind the vehicle to a level of at least 3 fc (30 lx) within a 10 ft x 10 ft (3 m x 3 m) square. The lights shall be mounted with four (4) screws to a flat surface. It shall be 6 3/4" high by 9" wide and have a profile of less than 1 3/4" beyond the mounting surface. Wiring shall extend from a weatherproof strain relief at the rear of the lamphead.

Each light shall have twenty-four (24) white LEDs. It shall operate at 12/24 volts DC, draw 6/3 amps and generate 7000 lumens of light. The lens shall redirect the light along the vehicle and out onto the working area. The lamphead housing shall be aluminum with a chrome colored bezel.

The above scene lights shall light to a level of at least 3 fc (30 lx), measured at 25 equally spaced points on a 2.5 ft (750 mm) grid within a 10 ft x 10 ft (3 m x 3m) square to the rear of vehicle.

The lights shall be switched at the 12 volt control panel in the cab.

The rear scene lights shall also be activated when the apparatus is in reverse.

TRAFFIC DIRECTIONAL LIGHT

One (1) Whelen TA4437M Super LED eight (8) lights, split two-piece housing, traffic directional warning device with 50' control cable shall be located on upper rear body. The control head shall be located in the cab within easy reach of Driver.

The traffic directional light shall be surface mounted on upper rear body.

WARNING LIGHT PACKAGE

Each apparatus shall have a system of optical warning devices that meets or exceeds the requirements of this section.

City of Jasper Fire Department

Production Specification

The optical warning system shall consist of an upper and a lower warning level. The requirements for each level shall be met by the warning devices in that particular level without consideration of the warning devices in the other level.

For the purposes of defining and measuring the required optical performance, the upper and lower warning levels shall be divided into four (4) warning zones. The four zones shall be determined by lines drawn through the geometric center of the apparatus at 45 degrees to a line drawn lengthwise through the geometric center of the apparatus. The four (4) zones shall be designated A, B, C, and D in a clockwise direction, with zone A to the front of the apparatus.

Each optical warning device shall be installed on the apparatus and connected to the apparatus's electrical system in accordance with the requirements of this standard and the requirements of the manufacturer of the device.

A master optical warning system switch that energizes all the optical warning devices shall be provided.

The optical warning system on the fire apparatus shall be capable of two (2) separate signaling modes during emergency operations. One (1) mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right-of-way. One (1) mode shall signal that the apparatus is stopped and is blocking the right-of-way. The use of some or all of the same warning lights shall be permitted for both modes provided the other requirements of this chapter are met.

A switching system shall be provided that senses the position of the parking brake or the park position of an automatic transmission. When the master optical warning system switch is closed and the parking brake is released or the automatic transmission is not in park, the warning devices signaling the call for the right-of-way shall be energized. When the master optical warning system switch is closed and the parking brake is on or the automatic transmission is in park, the warning devices signaling the blockage of the right-of-way shall be energized. The system shall be permitted to have a method of modifying the two (2) signaling modes.

The optical warning devices shall be constructed or arranged so as to avoid the projection of light, either directly or through mirrors, into any driving or crew compartment(s). The front optical warning devices shall be placed so as to maintain the maximum possible separation from the headlights.

Steadily burning, non flashing optical sources shall be permitted to be used.

UPPER LEVEL OPTICAL WARNING DEVICES

The upper-level optical warning devices shall be mounted as high and as close to the corner points of the apparatus as is practical to define the clearance lines of the apparatus. The upper-level optical warning devices shall not be mounted above the maximum height, specified by the device manufacturer.

ZONE A - FRONT WARNING LIGHTS

The light bar shall be supplied and installed by the cab/chassis manufacturer.

The lightbar shall be separately switched at the 12 volt control panel in the cab.

ZONES B AND D - SIDE WARNING LIGHTS

UPPER REAR CORNER WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FRR) provided, one (1)

City of Jasper Fire Department

Production Specification

each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

UPPER FORWARD CORNER WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

ZONE C - REAR WARNING LIGHTS

There shall be two (2) Whelen 900 series (9" x 7") Red Linear Super-LED lights (90RR5FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

LOWER LEVEL OPTICAL WARNING DEVICES

To define the clearance lines of the apparatus, the optical center of the lower-level optical warning devices in the front of the vehicle shall be mounted on or forward of the front axle centerline and as close to the front corner points of the apparatus as is practical.

The optical center of the lower-level optical warning devices at the rear of the vehicle shall be mounted on or behind the rear axle centerline and as close to the rear corners of the apparatus as is practical. The optical center of any lower-level device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground for large apparatus, and 18 in. and 48 in. (460 mm and 1600 mm) above level ground.

A midship optical warning device shall be mounted right and the left sides of the apparatus if the distance between the front and rear lower-level optical devices exceeds 25 ft (7.6 m) at the optical center. Additional midship optical warning devices shall be required, where necessary, to maintain a horizontal distance between the centers of adjacent lower-level optical warning devices of 25 ft (7.6 m) or less. The optical center of any midship mounted optical warning device shall be between 18 in. and 62 in. (460 mm and 1600 mm) above level ground.

ZONE A - FRONT WARNING LIGHTS

The warning lights shall be supplied and installed by the cab/chassis manufacturer. They shall be Whelen lights to complete an NFPA compliant lower level warning light system.

The lights shall be switched at the 12 volt control panel in the cab.

ZONES B AND D - CAB INTERSECTOR LIGHT (CAB FRONT CORNERS)

The warning lights shall be supplied and installed by the cab/chassis manufacturer. They shall be Whelen lights to complete an NFPA compliant lower level warning light system.

The lights shall be switched at the 12 volt control panel in the cab.

ZONES B AND D - BODY INTERSECTOR LIGHT (BODY WHEELWELL AREA)

City of Jasper Fire Department

Production Specification

There shall be two (2) Whelen 500 series (5" x 2") TIR6 Super-LED lights (50R03ZRR) provided, one (1) each side. Each light shall have a red lens and chrome finished flange.

The lights shall be switched at the 12 volt control panel in the cab.

ZONES B AND D - BODY INTERSECTOR LIGHT (BODY REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

ZONE C - REAR WARNING LIGHTS (LOWER REAR CORNERS)

There shall be two (2) Whelen 600 series (6" x 4") red Linear Super-LED lights (60R02FRR) provided, one (1) each side. Each light shall have a red lens and chrome flange.

The lights shall be switched at the 12 volt control panel in the cab.

LINE VOLTAGE ELECTRICAL SYSTEM

ONAN PTO GENERATOR

The vehicle shall be equipped with an Onan Protec PTO generator system with a capacity of 30,000 watts at 120/240 VAC, 250/125 amps, single phase. Current frequency shall be stable at 60 hertz.

The transmission's PTO port and PTO, or the split shaft PTO, and all associated drive shaft components shall be rated to support the continuous duty torque requirements of the generator's continuous duty rating as stated on the power source nameplate.

Where the generator is driven by the chassis engine and transmission through a split shaft PTO, the driving compartment speedometer shall register when the generator drive system is engaged.

Where the generator is driven by the chassis engine and transmission through a split shaft PTO and a chassis transmission retarder is furnished, it shall be automatically disengaged for generator operations.

The direct drive generator shall be mounted so that it does not change the ramp breakover angle, angle of departure, or angle of approach as defined by other components, and it shall not extend into the ground clearance area.

The direct drive generator shall be mounted away from exhaust and muffler areas or provided with a heat shield to reduce operating temperatures in the generator area.

GENERATOR BONDING

A minimum of four (4) 16" x 2 gauge copper ground straps shall be bolted to body sub-frame and chassis sub-frame for proper bonding of high voltage system. The conductor shall have a minimum amperage rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated amperage on the power source specification label.

City of Jasper Fire Department

Production Specification

GENERATOR ENGAGEMENT

A "Generator Engaged" indicator shall be provided in the driving compartment to indicate that the generator shift has been successfully completed.

An "OK to Operate Generator" indicator shall be provided in the driving compartment to indicate that the generator is engaged (if not always engaged), the transmission is in the proper gear (if required, automatic transmissions only), and the parking brake is engaged (if applicable).

An interlock system shall be provided to prevent advancement of the engine speed in the driving compartment or at any operator's panel unless the parking brake is engaged, and the transmission is in neutral or the output of the transmission is correctly connected to a pump or generator instead of the drive wheels.

WARRANTY PERIOD

Provided such goods are operated and maintained in accordance with Onan's written instructions, Onan warrants that the Protec YDCR series PTO generators shall be free from defects in material and workmanship for a period of five (5) years or one thousand (1,000) hours, whichever comes first, from the date of delivery to the first purchaser.

GENERATOR SPLASH GUARD

A powder coat painted splash cover shall be installed to reduce the amount of road spray on the frame mounted PTO generator. A V-ring seal shall also be installed in the cover to provide additional protection against contaminants reaching the generator front seals.

The generator shall be engaged at the 12 volt control panel in the cab.

GENERATOR MOUNTING

The generator shall be mounted between the chassis frame rails. The generator mounting brackets shall be fabricated using heavy duty steel tubing, or structural channel. The generator mounting shall be bolted and removable so that the generator can be lowered from under apparatus for service, if necessary. The generator case shall not extend below the bottom edge of the apparatus body.

MANUALS AND SCHEMATICS

Two (2) complete manuals on parts list, maintenance, wiring schematics, hydraulic schematics, circuit boards, voltage regulator board and other components shall be provided on delivery.

POWER-TAKE-OFF GENERATOR DRIVE

There shall be a "Hot Shift" power-take-off (PTO) installed on the transmission PTO opening of the chassis. The "Hot Shift" PTO is provided to allow the engagement of the PTO at higher engine RPM speeds. The PTO output shall be connected to the generator through hollow tube type driveline with heavy duty universals.

The engagement of the PTO shall be in the chassis cab with a rocker switch and red pilot light to note engagement of the PTO or via the V-Mux screen if so equipped.

City of Jasper Fire Department

Production Specification

The power supply to the PTO engagement control shall be wired to the parking brake and a neutral position transmission switch to prevent engagement unless the vehicle is stopped and transmission has been placed in neutral.

The installation of the engine, transmission, driven accessories (power takeoffs (PTO), etc.) shall meet the engine and transmission manufacturers' installation recommendations for the service intended.

Model part number shall be Chelsea 280GKFJP-B5XV, 164% Ratio.

Double check the model number and ratio with engineering before ordering the PTO on the chassis.

ENGINE SPEED CONTROL

An engine speed auxiliary control device (high idle switch or throttle) shall be installed to maintain a stable cycle output from generator when the apparatus is parked.

An interlock shall prevent the operation of the engine speed auxiliary control device unless the parking brake is engaged and the transmission is in neutral or park, or the parking brake is engaged and the engine is disengaged from the drive wheels.

The engine shall be prevented from regulating its own engine speed during times when engine rpm control is critical for consistent apparatus functions such as generator, water pump, or aerial operation.

LOADCENTER

The loadcenter shall be a Cutler Hammer, BR Series, specifically designed for protection and distribution of 120/240 volt AC, such as lighting and small motor branch circuits. The loadcenter enclosure shall be made of 16 gauge galvanized sheet steel. The galvanized coating provides corrosion protection and as such does not require paint. All trims used on the BR Loadcenter shall be chromate sealed and finished with electro disposition epoxy paint (ASA61) which exceeds requirements for outdoor and indoor applications. A combination surface/flush cover with integral door shall be supplied.

The loadcenter shall be UL / CSA listed, **NO EXCEPTIONS** will be allowed.

GENERATOR MONITORING PANEL

To properly monitor the generator performance and load demand during operation, the generator installation shall be equipped with a full instrument monitor panel.

- Generator frequency in hertz
- Line 1 current in amperes
- Line 2 current in amperes
- Generator voltage in volts

The program shall support the accumulation of elapsed generator hours. Generator hours shall be displayed.

SHORE POWER INLET - BATTERY CHARGER

The above mentioned shore power inlet, and battery conditioner shall be specified in the 12 volt section.

City of Jasper Fire Department

Production Specification

OUTLETS AND CIRCUITS

The generator and or shore power shall supply the 120/240 volt electrical equipment and outlets outlined below. Proper circuit protection shall be installed as noted:

- Two (2) 120 volt exterior outlets, one (1) each side near rear wheel well area.
 - The outlet receptacle(s) shall be 15 amp, twist-lock (NEMA L5-15R).

LINE VOLTAGE ELECTRICAL SYSTEM

GENERAL REQUIREMENTS

Stability

Any fixed line voltage power source producing alternating current (ac) shall produce electric power at 60 Hz, ± 3 Hz when producing power at all levels between no load and full rated power. Any fixed line voltage power source shall produce electric power at the rated voltage ± 10 percent when producing power at all levels between no load and full rated power.

The maximum voltage supplied to portable equipment shall not exceed 275 volts to ground. Higher voltage shall be permitted only when used to operate fixed wired, permanently mounted equipment on the apparatus.

Conformance with National Electrical Code

All components, equipment, and installation procedures shall conform to *NFPA 70, National Electrical Code*, except where superseded by the requirements of this chapter. Where the requirements of this chapter differ from those in *NFPA 70*, the requirements in this chapter shall apply.

Where available, line voltage electrical system equipment and materials included on the apparatus shall be listed and used only in the manner for which they have been listed. All equipment and materials shall be installed in accordance with the manufacturer's instructions.

Location Ratings

Any equipment used in a dry location shall be listed for dry locations. Any equipment used in a wet location shall be listed for wet locations.

Any equipment, except a PTO-driven generator, used in an underbody or under chassis location that is subject to road spray shall be either listed as Type 4 or mounted in an enclosure that is listed as Type 4.

If a PTO-driven generator is located in an underbody or under chassis location, the installation shall include a shield to prevent road spray from splashing directly on the generator.

Grounding

Grounding shall be in accordance with 250.34(A) and 250.34(B) of *NFPA 70*. Ungrounded systems shall not be used.

Only stranded or braided copper conductors shall be used for grounding and bonding.

City of Jasper Fire Department

Production Specification

The grounded current-carrying conductor (neutral) shall be insulated from the equipment-grounding conductors and from the equipment enclosures and other grounded parts.

The neutral conductor shall be colored white or gray in accordance with 200.6, "Means of Identifying Grounded Conductors," of *NFPA 70*.

Any bonding screws, straps, or buses in the distribution panel board or in other system components between the neutral and equipment-grounding conductor shall be removed and discarded.

City of Jasper Fire Department

Production Specification

Bonding

The neutral conductor of the power source shall be bonded to the vehicle frame. The neutral bonding connection shall occur only at the power source. In addition to the bonding required for the low voltage return current, each body and each driving or crew compartment enclosure shall be bonded to the vehicle frame by a copper conductor.

The conductor shall have a minimum ampere rating, as defined in 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*, of 115 percent of the rated ampere on the power source specification label.

A single conductor that is sized to meet the low voltage and line voltage requirements shall be permitted to be used.

Ground Fault Circuit Interrupters

In special service vehicles incorporating a lavatory, sink, toilet, shower, or tub, 120 V, 15 or 20 A receptacles within 6 ft (1.8 m) of these fixtures shall have ground fault circuit interrupter (GFCI) protection. GFCIs integrated into outlets or circuit breakers or as stand-alone devices shall be permitted to be used in situations.

Power Source General Requirements

All power source system mechanical and electrical components shall be sized to support the continuous duty nameplate rating of the power source.

The power source shall be shielded from contamination that would prevent the power source from operating within its design specifications.

Power Source Rating

For power sources of 8 kW or larger, the power source manufacturer shall declare the continuous duty rating that the power source can provide when installed on fire apparatus according to the manufacturer's instructions and run at 120°F (49°C) air intake temperature at 2000 ft (600 m) above sea level.

The rating on the power source specification label shall not exceed the declared rating from the power source manufacturer.

Access shall be provided to permit both routine maintenance and removal of the power source for major servicing. The power source shall be located such that neither it nor its mounting brackets interfere with the routine maintenance of the fire apparatus.

City of Jasper Fire Department

Production Specification

Instrumentation

If the power source is rated at less than 3 kW, a "Power On" indicator shall be provided. If the power source is rated at 3 kW or more but less than 8 kW, a voltmeter shall be provided.

If the power source is rated at 8 kW or more, the following instrumentation shall be provided at an operator's panel:

- Voltmeter
- Current meters for each ungrounded leg
 - Frequency (Hz) meter
 - 1) Power source hour meter

The instrumentation shall be permanently mounted at an operator's panel. The instruments shall be located in a plane facing the operator. Gauges, switches, or other instruments on this panel shall each have a label to indicate their function.

The instruments and other line voltage equipment and controls shall be protected from mechanical damage and not obstructed by tool mounting or equipment storage.

An instruction plate(s) that provides the operator with the essential power source operating instructions, including the power-up and power-down sequence, shall be permanently attached to the apparatus at any point where such operations can take place.

Operation

Provisions shall be made for placing the generator drive system in operation using controls and switches that are identified and within convenient reach of the operator.

Where the generator is driven by the chassis engine and engine compression brakes or engine exhaust brakes are furnished, they shall be automatically disengaged for generator operations.

Any control device used in the generator system power train between the engine and the generator shall be equipped with a means to prevent unintentional movement of the control device from its set position in the power generation mode.

If there is permanent wiring on the apparatus that is designed to be connected to the power source, a power source specification label that is permanently attached to the apparatus at the operator's control station shall provide the operator with the information required.

The power source, at any load, shall not produce a noise level that exceeds 90 dBA in any driving compartment, crew compartment, or onboard command area with windows and doors closed or at any operator's station on the apparatus.

Power Supply Assembly

The conductors used in the power supply assembly between the output terminals of the power source and the main over current protection device shall not exceed 12 ft (4 m) in length.

All power supply assembly conductors, including neutral and grounding conductors, shall have an equivalent amperage rating and shall be sized to carry not less than 115 percent of the amperage of the nameplate current rating of the power source.

City of Jasper Fire Department

Production Specification

If the power supply assembly connects to the vibrating part of a generator (not a connection on the base), the conductors shall be flexible cord or other fine-stranded conductors enclosed in metallic or nonmetallic liquid tight flexible conduit rated for wet locations and temperatures not less than 194°F (90°C).

City of Jasper Fire Department

Production Specification

Overcurrent Protection

Manually resettable over current devices shall be installed to protect the line voltage electrical system components.

Power Source Protection

A main over current protection device shall be provided that is either incorporated in the power source or connected to the power source by a power supply assembly.

The size of the main over current protection device shall not exceed 100 percent of the rated amperage stated on the power source specification label or the rating of the next larger available size over current protection device, where so recommended by the power source manufacturer.

If the main over current protection device is subject to road spray, the unit shall be housed in a Type 4-rated enclosure.

Branch Circuit Overcurrent Protection

Over current protection devices shall be provided for each individual circuit and shall be sized at not less than 15 amps in accordance with 240.4, "Protection of Conductors," of *NFPA 70*.

Any panel board shall have a main breaker where the panel has six or more individual branch circuits or the power source is rated 8 kW or larger.

Each over current protection device shall be marked with a label to identify the function of the circuit it protects.

Dedicated circuits shall be provided for any large appliance or device (air conditioning units, large motors, etc.) that requires 60 percent or more of the rated capacity of the circuit to which it is connected, and that circuit shall serve no other purpose.

Panelboards

All fixed power sources shall be hardwired to a permanently mounted panel board unless one of the following conditions exists:

- 2) All line voltage power connections are made through receptacles on the power source and the receptacles are protected by integrated over current devices.
- 3) Only one circuit is hardwired to the power source, which is protected by an integrated over current device.

The panel shall be visible and located so that there is unimpeded access to the panel board controls. All panel boards shall be designed for use in their intended location. The panel(s) shall be protected from mechanical damage, tool mounting, and equipment storage.

Where the power source is 120/240 V and 120 V loads are connected, the apparatus manufacturer or line voltage system installer shall consider load balancing to the extent that it is possible.

City of Jasper Fire Department

Production Specification

Wiring Methods

Fixed wiring systems shall be limited to the following:

- 4) Metallic or nonmetallic liquid tight flexible conduit rated at temperatures not less than 194°F (90°C) with stranded copper wire rated for wet locations and temperatures not less than 194°F (90°C)
- 1) Type SOW, SOOW, SEOW, or SEOOW flexible cord rated at 600 V and at temperatures not less than 194°F (90°C)

Electrical cord or conduit shall not be attached to chassis suspension components, water or fuel lines, air or air brake lines, fire pump piping, hydraulic lines, exhaust system components, or low voltage wiring and shall be arranged as follows:

- 2) Separated by a minimum distance of 12 in. (300 mm) from exhaust piping or shielded from such piping
- 1) Separated from fuel lines by a minimum distance of 6 in. (150 mm)

A means shall be provided to allow “flexing” between the driving and crew compartment, the body, and other areas or equipment whose movement would stress the wiring.

Electrical cord or conduit shall be supported within 6 in. (150 mm) of any junction box and at a minimum of every 24 in. (600 mm) of run.

Supports shall be made of nonmetallic materials or of corrosion-resistant or corrosion-protected metal. All supports shall be of a design that does not cut or abrade the conduit or cord and shall be mechanically fastened to the apparatus.

Only fittings and components listed for the type of cord or conduit being installed shall be used.

Splices shall be made only in a listed junction box.

Additional Requirements for Flexible Cord Installations

Where flexible cord is used in any location where it could be damaged, it shall be protected by installation in conduit, enclosures, or guards.

Where flexible cord penetrates a metal surface, rubber or plastic grommets or bushings shall be installed.

Wiring Identification

Each line voltage circuit originating from the main panel board shall be identified.

The wire or circuit identification either shall reference a wiring diagram or wire list or shall indicate the final termination point of the circuit.

Where pre-wiring for future power sources or devices exists, the un-terminated ends shall be marked with a label showing their wire size and intended function.

City of Jasper Fire Department

Production Specification

Wiring System Components

Only stranded copper conductors with an insulation rated for temperatures of at least 194°F (90°C) and wet locations shall be used. Conductors in flexible cord shall be sized in accordance with Table 400.5(A) of *NFPA 70*. Conductors used in conduit shall be sized in accordance with 310.15, "Ampacities for Conductors Rated 0–2000 Volts," of *NFPA 70*. Aluminum or copper-clad aluminum conductors shall not be used.

All boxes shall conform to and be mounted in accordance with Article 314, "Outlet, Device, Pull, and Junction Boxes; Conduit Bodies; Fittings; and Manholes," of *NFPA 70*. All boxes shall be accessible using ordinary hand tools. Boxes shall not be permitted behind welded or pop-riveted panels.

The maximum number of conductors permitted in any box shall be in accordance with 314.16, "Number of Conductors in Outlet, Device, and Junction Boxes, and Conduit Bodies," of *NFPA 70*.

All wiring connections and terminations shall provide a positive mechanical and electrical connection. Connectors shall be installed in accordance with the manufacturer's instructions. Wire nuts or insulation displacement and insulation piercing connectors shall not be used.

Each switch shall indicate the position of its contact points (i.e., open or closed) and shall be rated for the continuous operation of the load being controlled. All switches shall be marked with a label indicating the function of the switch. Circuit breakers used as switches shall be "switch rated" (SWD) or better. Switches shall simultaneously open all associated line voltage conductors. Switching of the neutral conductor alone shall not be permitted.

Line voltage circuits controlled by low voltage circuits shall be wired through properly rated relays in listed enclosures that control all non-grounded current-carrying conductors.

Receptacles and Inlet Devices

Wet and Dry Locations

All wet location receptacle outlets and inlet devices, including those on hardwired, remote power distribution boxes, shall be of the grounding type, provided with a wet location cover, and installed in accordance with Section 406.8, "Receptacles in Damp or Wet Locations," of *NFPA 70*.

All receptacles located in a wet location shall be not less than 24 in. (600 mm) from the ground. Receptacles on off road fire apparatus shall be a minimum of 30 in. (750 mm) from the ground. All receptacles located in a dry location shall be of the grounding type and shall be at least 12 in. (300 mm) above the interior floor height. No receptacle shall be installed in a face-up position.

The face of any wet location receptacle shall be installed in a plane from vertical to not more than 45 degrees off vertical.

Receptacle Label

Each receptacle shall be marked with a label indicating the nominal line voltage (120 volts or 240 volts) and the current rating in amps of the circuit. If the receptacle is DC or other than single phase, that information shall also be marked on the label.

All receptacles and electrical inlet devices shall be listed to UL 498, *Standard for Safety Attachment Plugs and Receptacles*, or other recognized performance standards.

City of Jasper Fire Department

Production Specification

Receptacles used for DC voltages shall be rated for DC service.

Wiring Schematics

An "As-Built" Wiring diagrams for line voltage systems shall be provided to include the following information;

- 2) Pictorial representations of circuit logic for all electrical components and wiring
- 1) Circuit identification
- 2) Connector pin identification
- (a) Zone location of electrical components
- (b) Safety interlocks
- (c) Alternator–battery power distribution circuits
- (d) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems

120/240 VAC SCENE LIGHTING

SIDE UPPER RECESSED SCENE LIGHTS

Four (4) Fire Research Spectra Max LED Scene Light model SPA260-J20 surface mount light(s) shall be installed. They shall be equally divided between the curbside and streetside. The light(s) shall be mounted with four (4) screws to a flat surface and require a cutout for the electronics box. It shall be no more than 6" high by 14 1/2" wide and have a profile of less than 1 3/4" beyond the mounting surface. Wiring shall extend from the electronics box at the rear of the lamphead.

The lamp head shall sixty (60) ultra-bright white LEDs, 48 for flood lighting and 12 to provide a spot light beam pattern. It shall operate at 240 volts AC, draw 0.7 amp, and generate 20,000 lumens of light. The lamphead shall have a unique lens that directs flood lighting onto the work area and focuses the spot light beam into the distance. The lamphead shall be powder coated. The LED scene light shall be for fire service use.

Scene lights shall be provided with a lens or a means for preventing damage from water spray and listed for wet location usage.

Make: Fire Research
Model: Spectra
PN: SPA260-J15

- (e) The above lights shall be controlled by two (2) switch(es) in the lower portion of compartment S1.

LIGHT TOWER

One (1) Command Light, CL Series light tower(s) shall be provided and installed on the completed unit. A flashing warning light shall be provided in cab, indicating when a light tower is not in nested position as required by NFPA 1901.

The Command Light shall be covered by a five (5) year limited warranty from defects in materials and workmanship. An operation, maintenance, and parts manual shall be provided with the completed unit.

The light tower shall extend 131" above the mounting surface and shall extend to full upright position in less than 15 seconds. The overall size of nested light tower shall be approximately 42" wide x 74" long x 12" high and weigh approximately 300 pounds.

City of Jasper Fire Department

Production Specification

Light Tower Construction and Design

The Command Light assembly shall be of aluminum construction, with stainless steel shafts and bronze bushings for long life and low maintenance.

The electrically controlled unit shall not require usage of the vehicle's air supply for operation, thereby eliminating the chance for air leaks in the vehicle braking system. Hydraulic or pneumatic type floodlights are not acceptable alternatives to the specified all electric light tower.

The light tower shall be tested to in wind conditions of 90 mph (150 kph) minimum. Light towers that have not been tested to these conditions are not acceptable.

The light tower shall be capable of overhanging the side or back of the vehicle to provide maximum illumination to the vicinity adjacent to the vehicle for the safety of emergency personnel in high traffic conditions. Light towers that are only capable of rotation at the top of a pole are not acceptable to the specified light tower.

Light Tower Electrical System

The light tower shall be a two-stage articulating device with a lighting bank on top of the second stage capable of continuous 360 degree rotation. The light shall be elevated by electric linear actuators, one (1) actuator shall elevate the light bank and one (1) actuator shall adjust the light bank angle from 0 to 110 degrees. Power for the light bank shall be supplied through power collecting rings thus allowing continuous 360 degree rotation in either direction.

The tower base shall have a light that illuminates the envelope of motion during any movement of the light tower mast as required by NFPA 1901.

Light Tower Floodlights

The Command Light model CL615A-HQ shall be equipped with the following bank of floodlights:

Floodlight manufacturer:	Hubbell Quartzlizer
Number of lamp heads:	Six (6)
Voltage:	240 volts
Watts of each lamp head:	1,500 watt
Total watts of light tower:	9,000 watts
Total lumens of light tower:	214,000 lumens
Configuration:	The light heads shall be mounted with three (3) on each side of the light tower, giving two (2) vertical lines of three (3) when the lights are in the upright position.

Light Tower Strobe Indicator

The floodlight tower shall have a strobe indicator located on the top of the upper section.

The lens color for the strobe light shall be green.

Light Tower Paint

The light tower shall be electrostatically powder coated with a hammer tone gray color.

Light Tower Controls

City of Jasper Fire Department

Production Specification

The light tower(s) shall be operated with a hand-held 15-foot umbilical line remote control. The storage station for the remote control unit shall be equipped with a button to activate the "Auto-Park" automatic nesting feature. The remote control shall be located per the itemized compartment list and include;

Three (3) switches; one (1) for each pair of lights.

One (1) switch for light bank rotation.

One (1) switch for elevating lower stage.

One (1) switch for elevating upper stage.

One (1) switch for optional light bank rotation.

One (1) switch for the optional strobe.

One (1) indicator light to indicate when light bank is out of the roof nesting position.

One (1) indicator light to indicate when light bank is rotated to proper nesting position.

Light Tower Mounting

The specified light tower(s) shall be recessed into the roof of body to allow light tower(s) to be stowed below roof level. The floor and side walls of recessed area shall be fabricated as a separate module from 3/16" aluminum treadplate with an overlapping 3" flange around perimeter roof line. The recessed area shall be completely water tight. All electrical connections made to light tower shall be located on sidewalls for a water tight connection.

The recessed area shall have two (2) water drain holes (in opposite corners) with flexible 1" diameter hose routed to the area below the body.

EQUIPMENT PAYLOAD WEIGHT ALLOWANCE

In compliance with NFPA 1901 standards, the special service vehicle shall be designed for an equipment loading allowance of 6,000 lbs. of City of Jasper Fire Department provided equipment based on a 40,001 - 50,000 pound gross vehicle weight rating.

EQUIPMENT

The following equipment shall be furnished with the completed special service vehicle;

- (f) One (1) container of assorted stainless steel nuts, bolts, screws and washers used in the construction of the apparatus shall be provided with the completed apparatus.
- (g) There shall be two (2) Zico SAC-44-E NFPA approved folding aluminum wheel chocks provided for 44" diameter tires that together will hold the vehicle when loaded to its GVWR or GCWR, on a hard surface with a 20 % grade, with the transmission in neutral, and the parking brake released.
 - The wheel chock(s) shall be mounted behind rear wheels, below body on streetside.
- One (1) Genesis 17 C Vario Combi Tool with OSC coupler and removeable tips shall be provided and located on on completed unit per City of Jasper Fire Department.
- One (1) Res-Q-Jack SPX-4PTX, 4-Point Deluxe Kit 19,300 lbs. shall be provided and located on completed vehicle per City of Jasper Fire Department with following kit items;
 - (2) / REMOVABLE Jacks USEABLE on ALL STRUT STANDS
 - (4) / Adjustable XSTRUT Stand, includes attached ratchet straps
 - (4) / Multi Purpose Heads

City of Jasper Fire Department

Production Specification

- (2) / RSTRAP15W) 15' Ratchet Strap w/Wire Hooks
 - (4) / SLING 8) 4' chains w/8" J Hook
 - (4) / CLUSTER) Clusters
 - (3) / RS15SNAP) 15' Ratchet Straps w/Snap Hooks
 - (2) / RSTRAP27C) 27' Ratchet StrapS w/Chain Ends
 - (2) / WEDGE 1) Wedges
 - (1) / CHAIN8016) 16' 3/8" grade 80 chain w/grab hooks
 - (1) / CHAIN8016) 16' 3/8" grade 80 chain w/grab hooks
 - (2) / STAKE 1) 1" Dim. Stake/Picket w/Collar 4' Long
 - (2 / STAKE 2) 3/4" Dim. Stake w/Head-20" Long
- One (1) Barska 200 Key Safe with key lock shall be provided and located on completed vehicle per City of Jasper Fire Department.
- The following Turtle Plastics shall be provided and located on completed vehicle per City of Jasper Fire Department.
- Thirty (30) 4"x 4" x 18" Pyramid Crib
 - Twelve (12) 2"x 4" x 18" Pyramid Crib
 - Four (4) medium step chock
 - Four (4) giant step chock
- Two (2) CMC 1/2" STATIC-PRO™ LIFELINE 200' ropes with rope storage bags #430205.
- Two (2) CMC steel anchor plates, #300615.
- Four (4) CMC Petzl VERTEX® VENT HELMET white in color, #345110.
- Two (2) Fol-Da-Tank, 12'x18' salvage covers 18 oz shall be provided on completed unit, location per City of Jasper Fire Department.
 - One (1) Kidde 15 LB. CO2 fire extinguisher(s) shall be provided with the completed unit.
 - The above specified fire extinguisher(s) shall be installed on the completed unit, location to be determined by the City of Jasper Fire Department.
 - One (1) Kidde 20 lb. ABC dry chemical aluminum fire extinguisher(s) shall be provided with the completed unit.
 - The above specified fire extinguisher(s) shall be installed on the completed unit, location to be determined by the City of Jasper Fire Department.
- One (1) Kidde 2-1/2 gallon pressurized water (Class A) fire extinguisher(s) shall be provided with the completed unit.
- The above specified fire extinguisher(s) shall be installed on the completed unit, location to be determined by the City of Jasper Fire Department.
- One (1) Super Vac 718VR3, 18" electric variable speed ventilation fan(s) shall be provided with the completed unit.
- The above specified ventilation fan(s) shall be installed on completed unit using mounting brackets and/or straps, location to be determined by the City of Jasper Fire Department.

City of Jasper Fiire Department

Production Specification

- Two (2) Streamlight FireBox halogen flashlight(s) with shoulder strap shall be provided. Each flashlight shall be orange in color and have a 12 volt DC charger and vehicle mount kit. Each flashlight shall have an 8 watt, 150 lumen halogen spotlight style bulb and reflector with 2 ultra-bright LED taillights. The flashlight(s) shall be wired to battery direct unless otherwise specified by City of Jasper Fiire Department.
 - The flashlight(s) shall be mounted on the completed unit in the lower area of compartment S1.
- Two (2) Streamlight FireBox LED flashlight(s) with shoulder strap shall be provided be provided with 540/330 lumen output and 7/15 hour run time.. Each flashlight shall be orange in color and have a 12 volt DC charger and vehicle mount kit. Each flashlight shall have a LED E-Spot spotlight style bulbs and reflectors with 2 ultra-bright LED taillights. The flashlight(s) shall be wired to battery direct unless otherwise specified by City of Jasper Fiire Department.
 - The flashlight(s) shall be mounted on the completed unit in the lower area of compartment S1.

REMAINING NFPA MINOR EQUIPMENT BY PURCHASER

All other minor equipment not specified above, but required by NFPA 1901 for special service vehicles, section 10.9.3 shall be supplied and mounted by City of Jasper Fiire Department before the unit is placed in emergency service.